

# SAFETY DATA SHEET



Date of issue/Date of revision

: 5 May 2024

Version

: 1.01

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : HARDENER 008 5617  
**Product code** : SDS-320TR00015-seria  
**Other means of identification**  
SKU-710015072

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications, Professional applications, Used by spraying.  
**Use of the substance/mixture** : Hardener.  
**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

Tikkurila Oyj  
P.O. Box 53  
FI-01301 VANTAA  
FINLAND  
Tel. +358 20 191 2000

**e-mail address of person responsible for this SDS** : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

#### Supplier

Tikkurila Oyj  
+358 20 191 2000 (GMT +2) Mon-Fri 8-16

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225  
Skin Irrit. 2, H315  
Eye Dam. 1, H318  
Skin Sens. 1, H317  
STOT SE 2, H371

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Code : SDS-320TR00015-seria  
HARDENER 008 5617

Date of issue/Date of revision : 5 May 2024

## SECTION 2: Hazards identification

### 2.2 Label elements

**Hazard pictograms**



**Signal word**

: Danger

**Hazard statements**

: Highly flammable liquid and vapour.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye damage.  
May cause damage to organs.

**Prevention**

: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapour.

**Response**

: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

**Storage**

: Not applicable.

**Disposal**

: Dispose of contents and container in accordance with all local, regional, national and international regulations.  
P280, P210, P260, P305 + P351 + P338, P310, P501

**Hazardous ingredients**

: resorcinol  
2,4,6-tris(dimethylaminomethyl)phenol

**Supplemental label elements**

: Not applicable.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

: Not applicable.

**Special packaging requirements**

**Containers to be fitted with child-resistant fastenings** : Not applicable.

**Tactile warning of danger** : Not applicable.

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB**

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification**

: Prolonged or repeated contact may dry skin and cause irritation.

Code : SDS-320TR00015-seria Date of issue/Date of revision : 5 May 2024  
 HARDENER 008 5617

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Type
propan-2-ol	REACH #: 01-2119457558-25 EC: 200-661-7 CAS: 67-63-0 Index: 603-117-00-0	≥10 - <20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	-	[1] [2]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7	≥10 - ≤15	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
resorcinol	REACH #: 01-2119480136-40 EC: 203-585-2 CAS: 108-46-3 Index: 604-010-00-1	≥1.0 - ≤5.0	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT SE 1, H370 (blood, central nervous system (CNS)) (oral) STOT SE 2, H371 (respiratory system) (oral) Aquatic Acute 1, H400 Aquatic Chronic 3, H412	ATE [Oral] = 510 mg/kg M [Acute] = 1	[1] [2]
2,4,6-tris (dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2 Index: 603-069-00-0	≥1.0 - <5.0	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318	ATE [Oral] = 1200 mg/kg ATE [Dermal] = 1280 mg/kg	[1]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥0.30 - ≤2.7	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412 <b>See Section 16 for the full text of the H statements declared above.</b>	ATE [Inhalation (vapours)] = 17.8 mg/l	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Code : SDS-320TR00015-seria Date of issue/Date of revision : 5 May 2024  
HARDENER 008 5617

## SECTION 3: Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May cause damage to organs following a single exposure in contact with skin. Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
- Ingestion** : May cause damage to organs following a single exposure if swallowed.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
dryness  
cracking  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

Code : SDS-320TR00015-seria Date of issue/Date of revision : 5 May 2024  
HARDENER 008 5617

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides

### 5.3 Advice for firefighters

**Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Code : SDS-320TR00015-seria  
HARDENER 008 5617

Date of issue/Date of revision : 5 May 2024

## SECTION 6: Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

- : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Code : SDS-320TR00015-seria  
HARDENER 008 5617

Date of issue/Date of revision

: 5 May 2024

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
propan-2-ol	<b>ACGIH TLV (United States, 7/2023).</b> STEL: 400 ppm 15 minutes. TWA: 200 ppm 8 hours.
xylene	<b>EU OEL (Europe, 1/2022). [xylene, mixed isomers] Absorbed through skin.</b> STEL: 442 mg/m <sup>3</sup> 15 minutes. STEL: 100 ppm 15 minutes. TWA: 221 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.
resorcinol	<b>EU OEL (Europe, 1/2022). Absorbed through skin.</b> TWA: 45 mg/m <sup>3</sup> 8 hours. TWA: 10 ppm 8 hours.
ethylbenzene	<b>EU OEL (Europe, 1/2022). Absorbed through skin.</b> STEL: 884 mg/m <sup>3</sup> 15 minutes. STEL: 200 ppm 15 minutes. TWA: 442 mg/m <sup>3</sup> 8 hours. TWA: 100 ppm 8 hours.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs

Product/ingredient name	Type	Exposure	Value	Population	Effects	
propan-2-ol	DNEL	Long term Inhalation	500 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Dermal	888 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Oral	26 mg/kg bw/day	General population	Systemic	
	DNEL	Short term Oral	51 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	89 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Short term Inhalation	178 mg/m <sup>3</sup>	General population	Systemic	
	xylene	DNEL	Long term Dermal	319 mg/kg bw/day	General population	Systemic
		DNEL	Short term Inhalation	1000 mg/m <sup>3</sup>	Workers	Systemic
		DNEL	Long term Oral	5 mg/kg bw/day	General population	Systemic
		DNEL	Long term Inhalation	65.3 mg/m <sup>3</sup>	General population	Local
		DNEL	Long term Inhalation	65.3 mg/m <sup>3</sup>	General population	Systemic
		DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic
		DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic
		DNEL	Long term Inhalation	221 mg/m <sup>3</sup>	Workers	Local
DNEL		Long term Inhalation	221 mg/m <sup>3</sup>	Workers	Systemic	
DNEL		Short term Inhalation	260 mg/m <sup>3</sup>	General population	Local	
DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	General population	Systemic		
DNEL	Short term Inhalation	442 mg/m <sup>3</sup>	Workers	Local		
DNEL	Short term Inhalation	442 mg/m <sup>3</sup>	Workers	Systemic		



Code : SDS-320TR00015-seria  
HARDENER 008 5617

Date of issue/Date of revision

: 5 May 2024

## SECTION 8: Exposure controls/personal protection

resorcinol	DNEL	Long term Oral	0.4 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	1.39 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Inhalation	5.6 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Dermal	20 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	33 mg/m <sup>3</sup>	General population	Local	
	DNEL	Long term Dermal	40 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	132.8 mg/m <sup>3</sup>	Workers	Local	
	DNEL	Long term Oral	0.075 mg/kg bw/day	General population	Systemic	
	2,4,6-tris (dimethylaminomethyl)phenol	DNEL	Short term Dermal	0.075 mg/kg bw/day	General population	Systemic
		DNEL	Long term Dermal	0.075 mg/kg bw/day	General population	Systemic
		DNEL	Short term Inhalation	0.13 mg/m <sup>3</sup>	General population	Systemic
		DNEL	Long term Inhalation	0.13 mg/m <sup>3</sup>	General population	Systemic
DNEL		Long term Dermal	0.15 mg/kg bw/day	Workers	Systemic	
DNEL		Long term Inhalation	0.53 mg/m <sup>3</sup>	Workers	Systemic	
DNEL		Short term Dermal	0.6 mg/kg bw/day	Workers	Systemic	
DNEL		Short term Inhalation	2.1 mg/m <sup>3</sup>	Workers	Systemic	
ethylbenzene		DMEL	Long term Inhalation	442 mg/m <sup>3</sup>	Workers	Local
		DMEL	Short term Inhalation	884 mg/m <sup>3</sup>	Workers	Systemic
		DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic
		DNEL	Long term Inhalation	15 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	77 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic	
	DNEL	Short term Inhalation	293 mg/m <sup>3</sup>	Workers	Local	

### PNECs

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
propan-2-ol	-	Fresh water	140.9 mg/l	Assessment Factors
	-	Marine water	140.9 mg/l	Assessment Factors
	-	Secondary Poisoning	160 mg/kg	-
	-	Fresh water sediment	552 mg/kg dwt	-
	-	Marine water sediment	552 mg/kg dwt	-
	-	Sewage Treatment Plant	2251 mg/l	Assessment Factors
	-	Soil	28 mg/kg dwt	-
xylene	-	Fresh water	0.327 mg/l	-
	-	Marine water	0.327 mg/l	-
	-	Sewage Treatment Plant	6.58 mg/l	-
	-	Fresh water sediment	12.46 mg/kg dwt	-
	-	Marine water sediment	12.46 mg/kg dwt	-
	-	Soil	2.31 mg/kg	-
	ethylbenzene	-	Fresh water	0.1 mg/l
-		Marine water	0.01 mg/l	Assessment Factors
-		Sewage Treatment Plant	9.6 mg/l	Assessment Factors
-		Fresh water sediment	13.7 mg/kg dwt	Equilibrium Partitioning
-		Marine water sediment	1.37 mg/kg dwt	Equilibrium Partitioning
-		Soil	2.68 mg/kg dwt	Equilibrium Partitioning
-		Secondary Poisoning	20 mg/kg	-

### 8.2 Exposure controls

#### Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### Individual protection measures



Code : SDS-320TR00015-seria  
HARDENER 008 5617

Date of issue/Date of revision : 5 May 2024

## SECTION 8: Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Chemical splash goggles and face shield. Use eye protection according to EN 166.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Gloves** : butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Yellow.
- Odour** : Characteristic.
- Odour threshold** : Not available.

Code : SDS-320TR00015-seria Date of issue/Date of revision : 5 May 2024  
HARDENER 008 5617

## SECTION 9: Physical and chemical properties

**Melting point/freezing point** : May start to solidify at the following temperature:  $<-20.15^{\circ}\text{C}$  ( $<-4.3^{\circ}\text{F}$ ) This is based on data for the following ingredient: 2,4,6-tris(dimethylaminomethyl)phenol. Weighted average:  $-82.93^{\circ}\text{C}$  ( $-117.3^{\circ}\text{F}$ )

**Initial boiling point and boiling range** :  $>37.78^{\circ}\text{C}$

**Flammability** : Not available.

**Upper/lower flammability or explosive limits** : Greatest known range: Lower: 2% Upper: 12% (Isopropyl alcohol)

**Flash point** : Closed cup:  $20^{\circ}\text{C}$

**Auto-ignition temperature** :

Ingredient name	$^{\circ}\text{C}$	$^{\circ}\text{F}$	Method
2,4,6-tris(dimethylaminomethyl)phenol	382	719.6	EU A.15

**Decomposition temperature** : Stable under recommended storage and handling conditions (see Section 7).

**pH** : Not applicable.

**Viscosity** : Kinematic ( $40^{\circ}\text{C}$ ):  $>21\text{ mm}^2/\text{s}$

**Solubility(ies)** :

Media	Result
cold water	Not soluble

**Partition coefficient: n-octanol/ water** : Not applicable.

**Vapour pressure** :

Ingredient name	Vapour Pressure at $20^{\circ}\text{C}$			Vapour pressure at $50^{\circ}\text{C}$		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Isopropyl alcohol	33.00268	4.4				

**Evaporation rate** : Highest known value: 1.7 (Isopropyl alcohol) Weighted average: 1.22 compared with butyl acetate

**Relative density** : 1

**Vapour density** : Highest known value: 3.7 (Air = 1) (xylene). Weighted average: 2.93 (Air = 1)

**Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

**Oxidising properties** : Product does not present an oxidizing hazard.

### Particle characteristics

**Median particle size** : Not applicable.

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

Code : SDS-320TR00015-seria Date of issue/Date of revision : 5 May 2024  
 HARDENER 008 5617

## SECTION 10: Stability and reactivity

**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

**10.6 Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Propan-2-ol	LC50 Inhalation Vapour	Rat	72600 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5045 mg/kg	-
xylene	LD50 Dermal	Rabbit	1.7 g/kg	-
	LD50 Oral	Rat	4.3 g/kg	-
resorcinol	LD50 Dermal	Rabbit	3360 mg/kg	-
	LD50 Oral	Rat	510 mg/kg	-
2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal	Rabbit	1.28 g/kg	-
	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
ethylbenzene	LC50 Inhalation Vapour	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
	LD50 Oral	Rat	3.5 g/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Acute toxicity estimates

Route	ATE value
Oral	8361.1 mg/kg
Dermal	11434.25 mg/kg
Inhalation (vapours)	98.55 mg/l

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
2,4,6-tris(dimethylaminomethyl)phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

#### Sensitisation

Product/ingredient name	Route of exposure	Species	Result
resorcinol	skin	Guinea pig	Sensitising

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

Code : SDS-320TR00015-seria Date of issue/Date of revision : 5 May 2024  
 HARDENER 008 5617

## SECTION 11: Toxicological information

### Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

### Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

### Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

### Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
propan-2-ol	Category 3	-	Narcotic effects
xylene	Category 3	-	Respiratory tract irritation
resorcinol	Category 1	oral	blood, central nervous system (CNS)
	Category 2	oral	respiratory system
ethylbenzene	Category 2	-	hearing organs

Information on likely routes of exposure : Not available.

### Potential acute health effects

**Inhalation** : No known significant effects or critical hazards.

**Ingestion** : May cause damage to organs following a single exposure if swallowed.

**Skin contact** : May cause damage to organs following a single exposure in contact with skin. Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

**Eye contact** : Causes serious eye damage.

### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** : No specific data.

**Ingestion** : Adverse symptoms may include the following:  
stomach pains

**Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
dryness  
cracking  
blistering may occur

**Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

#### Long term exposure

Potential immediate effects : Not available.

Code : SDS-320TR00015-seria Date of issue/Date of revision : 5 May 2024  
 HARDENER 008 5617

## SECTION 11: Toxicological information

**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary** : Not available.

**General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

**Other information** : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing. Exposure to amine vapor has been reported to cause transient corneal edema described as blue haze, halo effect, foggy or blurred vision for several hours. This condition is typically temporary and does not cause permanent visual effects. When the proper eye protection specified in Section 8 is worn, exposure is significantly reduced and the condition has not been observed.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
propan-2-ol	Acute EC50 10100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
resorcinol	Acute EC50 1 mg/l Chronic NOEC 0.17 mg/l	Daphnia Daphnia	48 hours 21 days
2,4,6-tris(dimethylaminomethyl)phenol	Acute LC50 175 mg/l	Fish	96 hours
ethylbenzene	Acute EC50 1.8 mg/l Fresh water Chronic NOEC 1 mg/l Fresh water	Daphnia  Daphnia - <i>Ceriodaphnia dubia</i>	48 hours  -

**Conclusion/Summary** : There are no data available on the mixture itself.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
resorcinol	OECD 302B	97 % - Readily - 4 days	-	-
ethylbenzene	-	79 % - Readily - 10 days	-	-

**Conclusion/Summary** : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
xylene	-	-	Readily
resorcinol	-	-	Readily
ethylbenzene	-	-	Readily

Code : SDS-320TR00015-seria Date of issue/Date of revision : 5 May 2024  
HARDENER 008 5617

## SECTION 12: Ecological information

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
propan-2-ol	0.05	-	Low
xylene	3.12	7.4 to 18.5	Low
resorcinol	0.8	-	Low
2,4,6-tris(dimethylaminomethyl)phenol	0.219	-	Low
ethylbenzene	3.6	79.43	Low

### 12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Mobility : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

#### European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 04 metallic packaging

Code : SDS-320TR00015-seria Date of issue/Date of revision : 5 May 2024  
HARDENER 008 5617

## SECTION 13: Disposal considerations

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## 14. Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	No.	Yes.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

### Additional information

ADR/RID : None identified.

Tunnel code : (D/E)

ADN : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.

IMDG : None identified.

IATA : None identified.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorisation

##### Annex XIV

None of the components are listed.

#### Substances of very high concern

None of the components are listed.



Code : SDS-320TR00015-seria

Date of issue/Date of revision

: 5 May 2024

HARDENER 008 5617

## SECTION 15: Regulatory information

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

**Explosive precursors** : Not applicable.

### Ozone depleting substances (1005/2009/EU)

Not listed.

### Seveso Directive

This product is controlled under the Seveso Directive.

### Danger criteria

Category

P5c

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

### Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.
H371	May cause damage to organs.
H373	May cause damage to organs through prolonged or repeated

**Code** : SDS-320TR00015-seria **Date of issue/Date of revision** : 5 May 2024  
**HARDENER 008 5617**

## SECTION 16: Other information

H400 H412	exposure. Very toxic to aquatic life. Harmful to aquatic life with long lasting effects.
--------------	--

### Full text of classifications [CLP/GHS]

Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 3 Asp. Tox. 1 Eye Dam. 1 Eye Irrit. 2 Flam. Liq. 2 Flam. Liq. 3 Skin Corr. 1C Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1B STOT RE 2  STOT SE 1  STOT SE 2  STOT SE 3	ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 2 FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 1C SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
--	--

### History

**Date of issue/ Date of revision** : 5 May 2024  
**Date of previous issue** : 12 January 2024  
**Prepared by** : EHS  
**Version** : 1.01

### Disclaimer

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*