

# SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 3 September 2023

Version 13

## Section 1. Identification

**Product name** : PPG1040 PPG TIMELESS STAIN & SEALANT IN ONE TRANSPARENT PENETRATING WOOD OIL - OXFORD BROWN

**Product code** : 00387502

**Other means of identification** : Not available.

**Product type** : Liquid.

### Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Consumer applications, Professional applications, Used by spraying.

**Use of the substance/ mixture** : Coating.

**Uses advised against** : Not applicable.


**Supplier** : PPG Architectural Coatings Canada, Inc.  
1550, rue Ampère, bureau 500  
Boucherville (Québec) J4B 7L4  
Canada  
+1 450-655-3121

PPG Industries, Inc.  
One PPG Place  
Pittsburgh, PA 15272

**Emergency telephone number** : (412) 434-4515 (U.S.)  
(514) 645-1320 (Canada)  
SETIQ Interior de la República: 800-00-214-00 (México)  
SETIQ Ciudad de México: (55) 5559-1588 (México)

**Technical Phone Number** : 1-800-441-9695 (8:00 am to 5:00 pm EST)

## Section 2. Hazard identification

**Classification of the substance or mixture** :  FLAMMABLE LIQUIDS - Category 3  
EYE IRRITATION - Category 2A  
CARCINOGENICITY - Category 2  
TOXIC TO REPRODUCTION - Category 1  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1  
ASPIRATION HAZARD - Category 1  
Health Hazards Not Otherwise Classified - Category 1

### GHS label elements


**Product name PPG1040 PPG TIMELESS STAIN & SEALANT IN ONE TRANSPARENT  
PENETRATING WOOD OIL - OXFORD BROWN****Section 2. Hazard identification****Hazard pictograms**

:

**Signal word**

: Danger

**Hazard statements**

:  Flammable liquid and vapor.  
May be fatal if swallowed and enters airways.  
Causes serious eye irritation.  
May cause respiratory irritation.  
Suspected of causing cancer.  
May damage fertility or the unborn child.  
Causes damage to organs through prolonged or repeated exposure. (central nervous system (CNS))  
Prolonged or repeated contact may dry skin and cause irritation.

**Precautionary statements****General**

: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

**Prevention**

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

**Response**

: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

**Storage**

: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

**Disposal**

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Supplemental label elements**

: Contains isothiazolinones. May cause allergic reaction. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated. DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity:  
36.2% (oral), 41.1% (dermal), 92.5% (inhalation)

**Product code** 00387502**Date of issue** 3 September 2023 **Version** 13**Product name** PPG1040 PPG TIMELESS STAIN & SEALANT IN ONE TRANSPARENT  
PENETRATING WOOD OIL - OXFORD BROWN

### Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture  
**Product name** : PPG1040 PPG TIMELESS STAIN & SEALANT IN ONE TRANSPARENT  
PENETRATING WOOD OIL - OXFORD BROWN  
**Other means of identification** : Not available.

#### CAS number/other identifiers

| Ingredient name                             | Synonyms  | % (w/w)    | CAS number |
|---|---|------------|------------|
| Naphtha (petroleum), hydrotreated heavy     | Low boiling point hydrogen treated naphtha; Hydrotreated heavy naphtha (petroleum); Hydrotreated light steam cracked naphtha residuum (petroleum); Naphtha, petroleum, hydrotreated heavy; Hydrotreated light, steam cracked naphtha residuum, petroleum; Hydrotreated heavy naphtha; Naphtha, (petroleum), heavy, hydrotreated; NAPHTHA  | 30 - 60*   | 64742-48-9 |
| Solvent naphtha (petroleum), medium aliph.  | Straight run kerosine; Solvent naphtha, petroleum, medium aliphatic; Medium aliphatic solvent naphtha, petroleum; Solvent naphtha medium aliphatic; Solvent naphtha, medium aliph.; Stoddard Solvent; Solvent naphtha (petroleum), medium aliphatic; MEDIUM ALIPHATIC SOLVENT NAPHTHA (PETROLEUM); Straight run white spirit; White spirit type 0, regular flash point; Medium aliphatic solvent naphtha (petroleum) C9-C12 | 5 - 10*    | 64742-88-7 |
| Paraffin waxes and Hydrocarbon waxes        | MALAM; Fischer-Tropsch wax; Paraffin wax; Paraffin wax, petroleum; Poly (methylene) wax; Synthetic paraffin wax, Fischer-Tropsch; SYNTHETIC WAX; Wax, extract; Paraffin wax fume; E 905; microcrystalline wax; Paraffin   | 1 - 5*     | 8002-74-2  |
| Distillates (petroleum), hydrotreated light | Distillates (petroleum), hydro- treated light; Kerosine - unspecified; Distillates, petroleum, hydrotreated light; Hydrotreated light distillate; Jet fuels; lamp oil; Kerosene (petroleum), hydrotreated; Hydrotreated light distillates (petroleum); DISTILLATES; Deodorized kerosene; Dearomatized kerosine  | 1 - 5*     | 64742-47-8 |
| iron hydroxide oxide yellow                 | C.I. Pigment Yellow 42; CI 77492; iron hydroxide oxide yellow; E 172; iron oxide yellow; C.I. 77492; iron hydroxide oxide yellow; C.I. 77492; E 172; iron oxide yellow; Iron oxide; Iron Oxide Yellow; Transparent iron oxide yellow; C.I. pigment yellow 042; FERRIC OXIDE,  | 0.5 - 1.5* | 51274-00-1 |

**Product name PPG1040 PPG TIMELESS STAIN & SEALANT IN ONE TRANSPARENT  
PENETRATING WOOD OIL - OXFORD BROWN**

### Section 3. Composition/information on ingredients

|   |   |          |            |
|---|---|----------|------------|
|   | FERRIC HYDROXIDE, CALCIUM CARBONATE; C.I. PIGMENT YELLOW 42, (IRON OXIDE (YELLOW)); SYNTHETIC YELLOW IRON OXIDE   |          |            |
| carbon black                                    | Lampblack; Acetylene black; C.I. 77266; C.I. Pigment Black 6; C.I. Pigment Black 7; Charcoal  | 0.1 - 1* | 1333-86-4  |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | Decanedioic acid, 1,10-bis (1,2,2,6,6-pentamethyl-4-piperidiny) ester; Decanedioic acid, bis (1,2,2,6,6-pentamethyl-4-piperidiny) ester; bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate; Bis(1,2,2,6,6-pentamethyl-4-piperidiny) decanedioate; Bis (1,2,2,6,6-pentamethyl-4-piperidyl) decanedioate; Decanedioic acid bis (1,2,2,6,6-pentamethyl-4-piperidiny) ester; DECANEDIOATE, BIS (1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) (PICCS); Bis(N-methyl-2,2,6,6-tetramethyl-4-piperidiny) sebacate; Bis(1,2,2,6,6-pentamethyl-4-piperidyl) 1,8-octanedicarboxylate; Bis (1,2,2,6,6-pentamethyl-4-piperidiny) sebacate; DECANEDIOATE, BIS (1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) | 0.1 - 1* | 41556-26-7 |
| 2-butanone oxime                                | butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime; 2-Butanone, oxime; METHYL ETHYL KETOXIME; METHYL ETHYL KETONE OXIME; ethyl methyl ketoxime; ethyl methyl ketone oxime; MEKO; syn-O,O'-di(butan-2-one oxime)diethoxysilane; Methyl alkyl (C2-4) ketoxime; Butan-2-one oxime  | 0.1 - 1* | 96-29-7    |
| 2-ethylhexanoic acid, zirconium salt            | Hexanoic acid, 2-ethyl-, zirconium salt (1:?) ; Hexanoic acid, 2-ethyl-, zirconium salt; Zirconium 2-ethylhexanoate; Zirconium salt of 2-ethylhexanoic acid; Aliphatic monocarboxylic acid (C6-28) salt (Pb, Cu, Mn, Zn, Zr, Ce, Cd, Sn, Sr, Co); 2-Ethylhexanoic acid zirconium salt; HEXANOATE, 2-ETHYL-, ZIRCONIUM; ZIRCONIUM OCTOATE; Zirconium 2-ethylhexanoate (component unspecified)  | 0.1 - 1* | 22464-99-9 |
| 2-ethylhexanoic acid, manganese salt            | Hexanoic acid, 2-ethyl-, manganese salt (1:?) ; Hexanoic acid, 2-ethyl-, manganese salt; Manganese 2-ethyl hexanoate; manganese 2-ethylhexoate; Manganese soap of 2-ethylhexoic acid; Aliphatic   | 0.1 - 1* | 15956-58-8 |

**Product name PPG1040 PPG TIMELESS STAIN & SEALANT IN ONE TRANSPARENT  
PENETRATING WOOD OIL - OXFORD BROWN**

### Section 3. Composition/information on ingredients

|  |   |  |  |
|--|---|--|--|
|  | monocarboxylic acid (C6-28) salt (Pb, Cu, Mn, Zn, Zr, Ce, Cd, Sn, Sr, Co);<br>2-Ethylhexanoic acid, manganese salt (1:?)<br>); 2-Ethylhexanoic acid manganese salt;<br>HEXANOATE, 2-ETHYL-, MANGANESE;<br>MANGANESE OCTOATE |  |  |
|--|---|--|--|

\*Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

**Occupational exposure limits, if available, are listed in Section 8.**

### Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

#### Description of necessary first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

##### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : May be fatal if swallowed and enters airways.


##### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

**Product name PPG1040 PPG TIMELESS STAIN & SEALANT IN ONE TRANSPARENT  
PENETRATING WOOD OIL - OXFORD BROWN****Section 4. First-aid measures**

- Skin contact** : Adverse symptoms may include the following:  
irritation  
dryness  
cracking  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
nausea or vomiting  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

**Indication of immediate medical attention and special treatment needed, if necessary**

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** :  No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

**Section 5. Fire-fighting measures****Extinguishing media**

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.
- Specific hazards arising from the chemical** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon oxides  
metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.



**Product name PPG1040 PPG TIMELESS STAIN & SEALANT IN ONE TRANSPARENT  
PENETRATING WOOD OIL - OXFORD BROWN**

## Section 7. Handling and storage

- Special precautions** : Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name   | Exposure limits  |
|---|--|
| Naphtha (petroleum), hydrotreated heavy<br>Solvent naphtha (petroleum), medium aliph. | None.<br><b>CA Ontario Provincial (Canada, 6/2019). [Mineral Spirits]</b><br>TWA: 525 mg/m <sup>3</sup> 8 hours.   |
| Paraffin waxes and Hydrocarbon waxes  | <b>CA Alberta Provincial (Canada, 6/2018).</b><br>8 hrs OEL: 2 mg/m <sup>3</sup> 8 hours. Form: Fume<br><b>CA British Columbia Provincial (Canada, 6/2022).</b><br>TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Fume<br><b>CA Ontario Provincial (Canada, 6/2019).</b><br>TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Fume<br><b>CA Saskatchewan Provincial (Canada, 7/2013).</b><br>STEL: 4 mg/m <sup>3</sup> 15 minutes. Form: Fume<br>TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Fume |
| Distillates (petroleum), hydrotreated light   | <b>CA Quebec Provincial (Canada, 6/2022).</b><br>TWA/EV: 2 mg/m <sup>3</sup> 8 hours. Form: fume<br><b>CA British Columbia Provincial (Canada, 6/2022). [Kerosene/Jet fuels as total hydrocarbon vapour] Absorbed through skin.</b><br>TWA: 200 mg/m <sup>3</sup> , (as total hydrocarbon  |



## Section 8. Exposure controls/personal protection

iron hydroxide oxide yellow

vapour) 8 hours.

**CA Alberta Provincial (Canada, 6/2018).****[Kerosene/Jet fuels as total hydrocarbon vapour] Absorbed through skin.**8 hrs OEL: 200 mg/m<sup>3</sup>, (as total hydrocarbon vapour) 8 hours.**CA Ontario Provincial (Canada, 6/2019).****Absorbed through skin.**TWA: 200 mg/m<sup>3</sup>, (as total hydrocarbon vapour) 8 hours.**CA British Columbia Provincial (Canada, 6/2022). [Iron oxide dust as Fe]**TWA: 5 mg/m<sup>3</sup>, (as Fe) 8 hours. Form: Dust**CA British Columbia Provincial (Canada, 6/2022). [Iron oxide Fume, as Fe]**TWA: 5 mg/m<sup>3</sup>, (as Fe) 8 hours. Form: FumeSTEL: 10 mg/m<sup>3</sup>, (as Fe) 15 minutes. Form: Fume

carbon black

**CA British Columbia Provincial (Canada, 6/2022).**TWA: 3 mg/m<sup>3</sup> 8 hours. Form: Inhalable**CA Ontario Provincial (Canada, 6/2019).**TWA: 3 mg/m<sup>3</sup> 8 hours. Form: Inhalable particulate matter.**CA Quebec Provincial (Canada, 6/2022).**TWA/EV: 3 mg/m<sup>3</sup> 8 hours. Form: inhalable dust**CA Alberta Provincial (Canada, 6/2018).**8 hrs OEL: 3.5 mg/m<sup>3</sup> 8 hours.**CA Saskatchewan Provincial (Canada, 7/2013).**STEL: 7 mg/m<sup>3</sup> 15 minutes.TWA: 3.5 mg/m<sup>3</sup> 8 hours.bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate  
2-butanone oxime

None.

**IPEL (-).**

TWA: 3 ppm

STEL: 9 ppm

2-ethylhexanoic acid, zirconium salt

**CA Alberta Provincial (Canada, 6/2018).****[Zirconium and compounds as Zr]**15 min OEL: 10 mg/m<sup>3</sup>, (as Zr) 15 minutes.8 hrs OEL: 5 mg/m<sup>3</sup>, (as Zr) 8 hours.**CA British Columbia Provincial (Canada, 6/2022). [Zirconium and compounds as Zr]**STEL: 10 mg/m<sup>3</sup>, (as Zr) 15 minutes.TWA: 5 mg/m<sup>3</sup>, (as Zr) 8 hours.**CA Quebec Provincial (Canada, 6/2022).****[Zirconium and compounds]**STEV: 10 mg/m<sup>3</sup>, (as Zr) 15 minutes.TWA/EV: 5 mg/m<sup>3</sup>, (as Zr) 8 hours.**CA Ontario Provincial (Canada, 6/2019).****[Zirconium and compounds as Zr]**STEL: 10 mg/m<sup>3</sup>, (as Zr) 15 minutes.TWA: 5 mg/m<sup>3</sup>, (as Zr) 8 hours.

**Section 8. Exposure controls/personal protection**

2-ethylhexanoic acid, manganese salt

**CA British Columbia Provincial (Canada, 6/2022). [manganese - Elemental & inorganic compounds as Mn]**TWA: 0.02 mg/m<sup>3</sup>, (as Mn) 8 hours. Form: RespirableTWA: 0.2 mg/m<sup>3</sup>, (as Mn, Total) 8 hours.**CA Quebec Provincial (Canada, 6/2022). [Manganese- fumes, dusts and compounds]**TWA-EV: 0.2 mg/m<sup>3</sup>, (as Mn) 8 hours. Form: Total dust.**CA Alberta Provincial (Canada, 6/2018). [Manganese, elemental & inorganic compounds as Mn]**8 hrs OEL: 0.2 mg/m<sup>3</sup>, (as Mn) 8 hours.**CA Ontario Provincial (Canada, 6/2019). [Manganese elemental and inorganic compounds as Mn]**TWA: 0.2 mg/m<sup>3</sup>, (as Mn) 8 hours.**CA Saskatchewan Provincial (Canada, 7/2013). [Manganese and inorganic compounds as Mn]**STEL: 0.6 mg/m<sup>3</sup>, (measured as Mn) 15 minutes.TWA: 0.2 mg/m<sup>3</sup>, (measured as Mn) 8 hours.**Consult local authorities for acceptable exposure limits.****Recommended monitoring procedures** : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.**Individual protection measures****Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.**Eye/face protection** : Chemical splash goggles.**Skin protection**

## Section 8. Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Gloves** : For prolonged or repeated handling, use the following type of gloves:  
Recommended: nitrile rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Characteristic.
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting point** : Not available.
- Boiling point** : >37.78°C (>100°F)
- Flash point** : Closed cup: 42.22°C (108°F)
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Flammability** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Evaporation rate** : Not available.
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Relative density** : 0.87
- Density ( lbs / gal )** : 7.26

**Product code** 00387502**Date of issue** 3 September 2023 **Version** 13**Product name** PPG1040 PPG TIMELESS STAIN & SEALANT IN ONE TRANSPARENT  
PENETRATING WOOD OIL - OXFORD BROWN

## Section 9. Physical and chemical properties

|   |   | Media  | Result      |
|---|---|--|-------------|
|   |   | Cold water   | Not soluble |
| <b>Solubility(ies)</b>                        | : |  |             |
| <b>Partition coefficient: n-octanol/water</b> | : | Not applicable.  |             |
| <b>Viscosity</b>                              | : | Kinematic (40°C (104°F)): <14 mm <sup>2</sup> /s (<14 cSt) |             |
| <b>Volatility</b>                             | : | 64% (v/v), 57.115% (w/w)                                   |             |
| <b>% Solid. (w/w)</b>                         | : | 42.885   |             |

## Section 10. Stability and reactivity

|   |   |   |
|---|---|---|
| <b>Reactivity</b>                         | : | No specific test data related to reactivity available for this product or its ingredients.  |
| <b>Chemical stability</b>                 | : | The product is stable.  |
| <b>Possibility of hazardous reactions</b> | : | Under normal conditions of storage and use, hazardous reactions will not occur.   |
| <b>Conditions to avoid</b>                | : | When exposed to high temperatures may produce hazardous decomposition products.<br>Refer to protective measures listed in sections 7 and 8. |
| <b>Incompatible materials</b>             | : | Keep away from the following materials to prevent strong exothermic reactions:<br>oxidizing agents, strong alkalis, strong acids.           |
| <b>Hazardous decomposition products</b>   | : | Depending on conditions, decomposition products may include the following materials:<br>carbon oxides metal oxide/oxides                    |

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name                         | Result                          | Species | Dose        | Exposure |
|---|---------------------------------|---------|-------------|----------|
| Naphtha (petroleum), hydrotreated heavy         | LD50 Dermal                     | Rabbit  | >5000 mg/kg | -        |
|   | LD50 Oral                       | Rat     | >6 g/kg     | -        |
| Solvent naphtha (petroleum), medium aliph.      | LD50 Dermal                     | Rabbit  | >3000 mg/kg | -        |
|   | LD50 Oral                       | Rat     | >5000 mg/kg | -        |
| Paraffin waxes and Hydrocarbon waxes            | LD50 Oral                       | Rat     | >5000 mg/kg | -        |
|   | LD50 Oral                       | Rat     | >5000 mg/kg | -        |
| iron hydroxide oxide yellow                     | LC50 Inhalation Dusts and mists | Rat     | >5.05 mg/l  | 4 hours  |
|   | LD50 Oral                       | Rat     | >10 g/kg    | -        |
| carbon black                                    | LD50 Oral                       | Rat     | >10 g/kg    | -        |
|   | LD50 Oral                       | Rat     | 3.125 g/kg  | -        |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate | LD50 Dermal                     | Rabbit  | 1100 mg/kg  | -        |
|   | LD50 Oral                       | Rat     | 100 mg/kg   | -        |
| 2-butanone oxime                                | LD50 Dermal                     | Rabbit  | >5 g/kg     | -        |
|   |                                 |         |             |          |
| 2-ethylhexanoic acid, zirconium salt            |                                 |         |             |          |
|   |                                 |         |             |          |

**Product code** 00387502**Date of issue** 3 September 2023 **Version** 13**Product name** PPG1040 PPG TIMELESS STAIN & SEALANT IN ONE TRANSPARENT  
PENETRATING WOOD OIL - OXFORD BROWN

## Section 11. Toxicological information

|  |           |     |         |   |
|--|-----------|-----|---------|---|
|  | LD50 Oral | Rat | >5 g/kg | - |
|--|-----------|-----|---------|---|

**Conclusion/Summary** : There are no data available on the mixture itself.

### Irritation/Corrosion

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Sensitization

**Skin** : There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| carbon black            | -    | 2B   | -   |

**Carcinogen Classification code:**

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

| Name                                       | Category   | Route of exposure | Target organs                |
|--|------------|-------------------|------------------------------|
| Naphtha (petroleum), hydrotreated heavy    | Category 3 | -                 | Respiratory tract irritation |
| Solvent naphtha (petroleum), medium aliph. | Category 3 | -                 | Narcotic effects             |

### Specific target organ toxicity (repeated exposure)

| Name                                       | Category   | Route of exposure | Target organs                |
|--|------------|-------------------|------------------------------|
| Solvent naphtha (petroleum), medium aliph. | Category 1 | -                 | central nervous system (CNS) |
| 2-ethylhexanoic acid, manganese salt       | Category 2 | inhalation        | -                            |

**Target organs** : Contains material which causes damage to the following organs: brain, skin, central nervous system (CNS).  
Contains material which may cause damage to the following organs: kidneys, upper respiratory tract, eyes.

### Aspiration hazard

**Section 11. Toxicological information**

| Name  | Result                         |
|---|--------------------------------|
| Naphtha (petroleum), hydrotreated heavy     | ASPIRATION HAZARD - Category 1 |
| Solvent naphtha (petroleum), medium aliph.  | ASPIRATION HAZARD - Category 1 |
| Distillates (petroleum), hydrotreated light | ASPIRATION HAZARD - Category 1 |

**Information on the likely routes of exposure****Potential acute health effects**

|                     |   |
|---------------------|---|
| <b>Eye contact</b>  | : Causes serious eye irritation.                                |
| <b>Inhalation</b>   | : May cause respiratory irritation.                             |
| <b>Skin contact</b> | : Defatting to the skin. May cause skin dryness and irritation. |
| <b>Ingestion</b>    | : May be fatal if swallowed and enters airways.                 |

**Over-exposure signs/symptoms**

|                     |   |
|---------------------|---|
| <b>Eye contact</b>  | : Adverse symptoms may include the following:<br>pain or irritation<br>watering<br>redness  |
| <b>Inhalation</b>   | : Adverse symptoms may include the following:<br>respiratory tract irritation<br>coughing<br>reduced fetal weight<br>increase in fetal deaths<br>skeletal malformations |
| <b>Skin contact</b> | : Adverse symptoms may include the following:<br>irritation<br>dryness<br>cracking<br>reduced fetal weight<br>increase in fetal deaths<br>skeletal malformations        |
| <b>Ingestion</b>    | : Adverse symptoms may include the following:<br>nausea or vomiting<br>reduced fetal weight<br>increase in fetal deaths<br>skeletal malformations                       |

**Delayed and immediate effects and also chronic effects from short and long term exposure**

|                           |  |
|---------------------------|--|
| <b>Conclusion/Summary</b> | : There are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and |
|---------------------------|--|

**Section 11. Toxicological information**

immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**Short term exposure**

**Potential immediate effects** : There are no data available on the mixture itself.

**Potential delayed effects** : There are no data available on the mixture itself.

**Long term exposure**

**Potential immediate effects** : There are no data available on the mixture itself.

**Potential delayed effects** : There are no data available on the mixture itself.

**Potential chronic health effects**

**General** : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

**Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : May damage fertility or the unborn child.

**Numerical measures of toxicity****Acute toxicity estimates**

| Product/ingredient name   | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| PPG1040 PPG TIMELESS STAIN & SEALANT IN ONE TRANSPARENT PENETRATING WOOD OIL - OXFORD BROWN | N/A          | 19147.0        | N/A                      | N/A                        | N/A                                 |
| Solvent naphtha (petroleum), medium aliph.  | N/A          | 2500           | N/A                      | N/A                        | N/A                                 |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate   | 3125         | N/A            | N/A                      | N/A                        | N/A                                 |
| 2-butanone oxime  | 500          | 1100           | N/A                      | N/A                        | N/A                                 |

**Section 12. Ecological information****Toxicity**

| Product/ingredient name              | Result                  | Species | Exposure |
|--------------------------------------|-------------------------|---------|----------|
| Iron hydroxide oxide yellow          | Acute LC50 >100000 mg/l | Fish    | 96 hours |
| 2-ethylhexanoic acid, zirconium salt | Acute LC50 >100 mg/l    | Fish    | 96 hours |

**Persistence and degradability**

| Product/ingredient name                     | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| Distillates (petroleum), hydrotreated light | -                 | -          | Readily          |

**Bioaccumulative potential**



Product code 00387502

Date of issue 3 September 2023 Version 13

Product name PPG1040 PPG TIMELESS STAIN & SEALANT IN ONE TRANSPARENT  
PENETRATING WOOD OIL - OXFORD BROWN

## Section 12. Ecological information

| Product/ingredient name                     | LogP <sub>ow</sub> | BCF  | Potential |
|---|--------------------|------|-----------|
| Distillates (petroleum), hydrotreated light | -                  | 159  | Low       |
| 2-butanone oxime                            | 0.63               | 5.01 | Low       |

### Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

## Section 14. Transport information

|                             | TDG  | IMDG   | IATA   |
|-----------------------------|--|--|--|
| UN number                   | UN1263                                       | UN1263                                       | UN1263   |
| UN proper shipping name     | PAINT  | PAINT  | PAINT  |
| Transport hazard class (es) | 3  | 3  | 3  |
| Packing group               | III  | III  | III  |
| Environmental hazards       | Yes.   | Yes.   | Yes. The environmentally hazardous substance mark is not required. |
| Marine pollutant substances | (Solvent naphtha (petroleum), medium aliph.) | (Solvent naphtha (petroleum), medium aliph.) | Not applicable.  |

### Additional information

**Product code** 00387502

**Date of issue** 3 September 2023 **Version** 13

**Product name** PPG1040 PPG TIMELESS STAIN & SEALANT IN ONE TRANSPARENT  
PENETRATING WOOD OIL - OXFORD BROWN

## Section 14. Transport information

- TDG** : The marine pollutant mark is not required when transported by road or rail.  
**IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.  
**IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not applicable.

**Proof of classification statement** : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3), 2.7 (Marine pollutant mark).

## Section 15. Regulatory information

### National Inventory List

**Canada inventory (DSL)** : All components are listed or exempted.

## Section 16. Other information

### **Hazardous Material Information System (U.S.A.)**

**Health** : 2 \* **Flammability** : 2 **Physical hazards** : 0

(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

### **National Fire Protection Association (U.S.A.)**

**Health** : 2 **Flammability** : 2 **Instability** : 0

**Date of issue/Date of revision** 3 September 2023

**Organization that prepared the SDS** : EHS

**Key to abbreviations** : ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
N/A = Not available  
SGG = Segregation Group  
UN = United Nations

Indicates information that has changed from previously issued version.

**Product code** 00387502

**Date of issue** 3 September 2023 **Version** 13

**Product name** PPG1040 PPG TIMELESS STAIN & SEALANT IN ONE TRANSPARENT  
PENETRATING WOOD OIL - OXFORD BROWN

## Section 16. Other information

### Disclaimer

*The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.*