SAFETY DATA SHEET



Date of issue/Date of revision6 September 2024Version 12.02

Section 1. Identification		
Product name	: 12-510XIC PITTSBURGH PAINTS SPEEDHIDE PRO EV ZERO SEMI-GLOSS WHITE & PASTEL BASE	
Product code	: 00391120	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	Consumer applications, Professional applications, Used by spraying.	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Not applicable.	
Manufacturer <u>Emergency telephone</u> <u>number</u>	 PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272 (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México) 	
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)	

Section 2. Hazards identification

OSHA/HCS status	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 21.8% (oral), 23.8% (dermal), 21.8% (inhalation)
	This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8).
GHS label elements	

United States

Page: 1/13

Product name 12-510XIC PITTSBURGH PAINTS SPEEDHIDE PRO EV ZERO SEMI-GLOSS WHITE & PASTEL BASE

Section 2. Hazards identification

Hazard pictograms



	•
Signal word	: Warning
Hazard statements	 Suspected of causing cancer. Suspected of damaging fertility or the unborn child.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.
Response	: IF exposed or concerned: Get medical advice or attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Contains isothiazolinones. May cause allergic reaction. Emits toxic fumes when heated.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: 12-510XIC PITTSBURGH PAINTS SPEEDHIDE PRO EV ZERO SEMI-GLOSS WHITE & PASTEL BASE

Ingredient name	%	CAS number
titanium dioxide	≥10 - ≤20	13463-67-7
Kaolin	≥1.0 - ≤5.0	1332-58-7
propylidynetrimethanol	≤1.0	77-99-6

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Product name 12-510XIC PITTSBURGH PAINTS SPEEDHIDE PRO EV ZERO SEMI-GLOSS WHITE & PASTEL BASE

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact :	No known significant effects or critical hazards.
Inhalation :	No known significant effects or critical hazards.
Skin contact :	No known significant effects or critical hazards.
Ingestion :	No known significant effects or critical hazards.
Over-exposure signs/symptor	<u>ns</u>
Eye contact :	No specific data.
Inhalation :	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact :	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion :	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary	
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Date of issue 6 September 2024 Version 12.02

Product name 12-510XIC PITTSBURGH PAINTS SPEEDHIDE PRO EV ZERO SEMI-GLOSS WHITE & PASTEL BASE

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

g. from
or or mist.
ormation in For non-
, drains mental
nd mop up aterial and ⁄aste
from eas. Wash collect e or ulations minated see al.
ra fro e ul un se

Date of issue 6 September 2024 Version 12.02

Product name 12-510XIC PITTSBURGH PAINTS SPEEDHIDE PRO EV ZERO SEMI-GLOSS WHITE & PASTEL BASE

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
titanium dioxide	OSHA PEL (United States, 5/2018).
	TWA: 15 mg/m ³ 8 hours. Form: Total dust
	ACGIH TLV (United States, 7/2023).
	TWA: 2.5 mg/m ³ 8 hours. Form: respirable
	fraction, finescale particles
Kaolin	ACGIH TLV (United States, 7/2023).
	TWA: 2 mg/m ³ 8 hours. Form: Respirable
	fraction
	OSHA PEL (United States, 5/2018).
	TWA: 5 mg/m ³ 8 hours. Form: Respirable
	fraction
	TWA: 15 mg/m³ 8 hours. Form: Total dust
propylidynetrimethanol	None.
Key to abbreviatio	ns
A = Acceptable Maximum Peak	S = Potential skin absorption
CGIH = American Conference of Governmental Industrial Hygienists.	SR = Respiratory sensitization SS = Skin sensitization
C = Ceiling Limit F = Fume	SS = Skin sensitization STEL = Short term Exposure limit values
	United States Page: 5/13

Date of issue 6 September 2024 Version 12.02

Product name 12-510XIC PITTSBURGH PAINTS SPEEDHIDE PRO EV ZERO SEMI-GLOSS WHITE & PASTEL BASE

Section 8. Exposure controls/personal protection

IPEL = Internal Permissible Exp OSHA = Occupational Safety and R = Respirable Z = OSHA 29 CFR 1910.120		
Consult local authorities for	otable exposure limits.	
Recommended monitoring procedures	eference should be made to appropriate monitoring standards. Reference to national uidance documents for methods for the determination of hazardous substances we so be required.	
Appropriate engineering controls	user operations generate dust, fumes, gas, vapor or mist, use process enclosures cal exhaust ventilation or other engineering controls to keep worker exposure to rborne contaminants below any recommended or statutory limits.	S,
Environmental exposure controls	missions from ventilation or work process equipment should be checked to ensure ey comply with the requirements of environmental protection legislation. In some ases, fume scrubbers, filters or engineering modifications to the process equipment ill be necessary to reduce emissions to acceptable levels.	•
Individual protection measur		
Hygiene measures	ash hands, forearms and face thoroughly after handling chemical products, befor ating, smoking and using the lavatory and at the end of the working period. ppropriate techniques should be used to remove potentially contaminated clothing ash contaminated clothing before reusing. Ensure that eyewash stations and saf nowers are close to the workstation location.] .
Eye/face protection	afety glasses with side shields.	
Skin protection		
Hand protection	hemical-resistant, impervious gloves complying with an approved standard should orn at all times when handling chemical products if a risk assessment indicates th ecessary. Considering the parameters specified by the glove manufacturer, check uring use that the gloves are still retaining their protective properties. It should be oted that the time to breakthrough for any glove material may be different for differ ove manufacturers. In the case of mixtures, consisting of several substances, the rotection time of the gloves cannot be accurately estimated.	nis is k rent
Body protection	ersonal protective equipment for the body should be selected based on the task b erformed and the risks involved and should be approved by a specialist before andling this product.	eing
Other skin protection	ppropriate footwear and any additional skin protection measures should be selected ased on the task being performed and the risks involved and should be approved becialist before handling this product.	
Respiratory protection	espirator selection must be based on known or anticipated exposure levels, the azards of the product and the safe working limits of the selected respirator. If wor re exposed to concentrations above the exposure limit, they must use appropriate ertified respirators. Use a properly fitted, air-purifying or air-fed respirator complyin ith an approved standard if a risk assessment indicates this is necessary. he respiratory protection shall be in accordance to 29 CFR 1910.134.	; ,

Date of issue 6 September 2024 Version 12.02

Product name 12-510XIC PITTSBURGH PAINTS SPEEDHIDE PRO EV ZERO SEMI-GLOSS WHITE & PASTEL BASE

Section 9. Physical and chemical properties

Appearance

Physical state	:	Liquid.	
Color	:	Various	
Odor	:	Characteristic.	
Odor threshold	:	Not available.	
рН	1	8.5	
Melting point	1	Not available.	
Boiling point	1	100°C (212°F)	
Flash point	1	Closed cup: Not applica	able. [Product does not sustain combustion.]
Auto-ignition temperature	:	Not available.	
Decomposition temperature	:	Not available.	
Flammability	:	Not available.	
Lower and upper explosive (flammable) limits	:	Not available.	
Evaporation rate	:	0.05 (butyl acetate = 1)	
Vapor pressure	:	3.3 kPa (25 mm Hg)	
Vapor density	:	Not available.	
Relative density	:	1.15	
Density(lbs / gal)	:	9.6	
		Media	Result
Solubility(ies)	1	cold water	Soluble
Partition coefficient: n- octanol/water	:	Not applicable.	
Viscosity		Kinematic (40°C (104°F	⁻)): >21 mm²/s (>21 cSt)
Volatility	:	69% (v/v), 60.196% (w/	/w)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
	United States Page: 7/13

Date of issue 6 September 2024 Version 12.02

Product name 12-510XIC PITTSBURGH PAINTS SPEEDHIDE PRO EV ZERO SEMI-GLOSS WHITE & PASTEL BASE

Section 10. Stability and reactivity

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result		Species	Dose	Exposure
titanium dioxide	LC50 Inhal	ation Dusts and mis	sts Rat	>6.82 mg/l	4 hours
	LD50 Dern	nal	Rabbit	>5000 mg/kg	-
	LD50 Oral		Rat	>5000 mg/kg	-
Kaolin		ation Dusts and mis		>5.07 mg/l	4 hours
propylidy (potrimothopol	LD50 Oral LD50 Dern		Rat Rabbit	>5000 mg/kg	-
propylidynetrimethanol	LD50 Dem LD50 Oral	lai	Rabbit	10 g/kg 14000 mg/kg	-
	LD50 Oral		Mai	14000 mg/kg	-
Conclusion/Summary	: There are	e no data available c	on the mixture itse	lf.	
Irritation/Corrosion					
Conclusion/Summary					
Skin	: There are	e no data available c	on the mixture itse	lf.	
Eyes	: There are	e no data available c	on the mixture itse	lf.	
Respiratory	: There are	e no data available c	on the mixture itse	lf.	
Sensitization					
Conclusion/Summary					
Skin	: There are	e no data available c	on the mixture itse	lf.	
Respiratory	: There are	e no data available c	on the mixture itse	lf.	
Mutagenicity					
Conclusion/Summary	: There are	e no data available c	on the mixture itse	lf.	
Carcinogenicity					
Conclusion/Summary	: There are	e no data available c	on the mixture itse	lf.	
<u>Classification</u>					
Product/ingredient name	OSHA	IARC NTP			
titanium dioxide	-	2B -			
		I I			

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

Reproductive toxicity

Conclusion/Summary	: There are no data available on the mixture itself.
<u>Teratogenicity</u> Conclusion/Summary	: There are no data available on the mixture itself.

Date of issue 6 September 2024 Version 12.02

Product name 12-510XIC PITTSBURGH PAINTS SPEEDHIDE PRO EV ZERO SEMI-GLOSS WHITE & PASTEL BASE

Section 11. Toxicological information

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Target organs

: Contains material which causes damage to the following organs: eyes. Contains material which may cause damage to the following organs: lungs, upper respiratory tract, stomach.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sympt	<u>oms</u>
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary
 There are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/ or engineering controls (see Section 8). If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

Date of issue 6 September 2024 Version 12.02

Product name 12-510XIC PITTSBURGH PAINTS SPEEDHIDE PRO EV ZERO SEMI-GLOSS WHITE & PASTEL BASE

Section 11. Toxicological information

	•
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Long term exposure	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health eff	lects
General	: No known significant effects or critical hazards.
Carcinogenicity	 Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Numerical measures of toxic	<u>city</u>

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)			(vapors)	Inhalation (dusts and mists) (mg/ I)
propylidynetrimethanol	14000	10000	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
	3	Daphnia - <i>Daphnia magna</i> Fish	48 hours 96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
propylidynetrimethanol	-0.47	-	Low

Mobility in soil

Soil/water partition : N coefficient (Koc)

: Not available.

United States Page: 10/13

Date of issue 6 September 2024 Version 12.02

Product name 12-510XIC PITTSBURGH PAINTS SPEEDHIDE PRO EV ZERO SEMI-GLOSS WHITE & PASTEL BASE

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards Marine pollutant substances	No. Not applicable.	No. Not applicable.	No. Not applicable.

Additional information

DOT: None identified.IMDG: None identified.IATA: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Date of issue 6 September 2024 Version 12.02

Product name 12-510XIC PITTSBURGH PAINTS SPEEDHIDE PRO EV ZERO SEMI-GLOSS WHITE & PASTEL BASE

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : At least one component is inactive.

United States - TSC	A 5(a)2 - Proposed significant new use	rules:	
3(2H)-Isothiazolone,	2-methyl-	Listed	P-96-1250
5-chloro-2-methyl-2H-isothiazol-3-one		Listed	P-96-1251
<u>SARA 302/304</u>			
SARA 304 RQ	: Not applicable.		

Composition/information on ingredients

No products were found.

SARA 311/312

Classification

: CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2

Composition/information on ingredients

Name	%	Classification
titanium dioxide propylidynetrimethanol		CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 1 * Flammability : 0 Physical hazards : 0 (*) - Chronic effects

Continue energy of the energy

preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)Health : 1Flammability : 0Instability : 0Instability : 0Date of previous issue: 7/30/2024Organization that prepared: EHSthe SDS

Date of issue 6 September 2024 Version 12.02

Product name 12-510XIC PITTSBURGH PAINTS SPEEDHIDE PRO EV ZERO SEMI-GLOSS WHITE & PASTEL BASE

Section 16. Other information

Kow to obbrowistions	· ATE - Aguta Taviaity Estimate
Key to abbreviations	: ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973
	as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	SGG = Segregation Group
	UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.