SAFETY DATA SHEET



Date of issue/Date of revision 23 January 2024 Version 11

Section 1. Identification	
Product name	: PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE
Product code	: 00392818
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Product use	: Consumer applications, Professional applications.
Use of the substance/ mixture	: Coating.
Uses advised against	: Not applicable.
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)

Section 2. Hazards identification

OSHA/HCS status	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 23.1% (oral), 23.1% (dermal), 23.1% (inhalation)
	This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8).
GHS label elements	

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 2. Hazards identification

Hazard pictograms



	•	
Signal word	: Warning	
Hazard statements	: Suspected of causing cancer. Suspected of damaging fertility or the unborn child.	
Precautionary statements		
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.	
Response	: IF exposed or concerned: Get medical advice or attention.	
Storage	: Store locked up.	
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.	
Supplemental label elements	: Contains isothiazolinones. May cause allergic reaction. Emits toxic fumes when heated	•
Hazards not otherwise classified	: None known.	

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Ingredient name	%	CAS number
	≥10 - ≤20	13463-67-7
	≥1.0 - ≤5.0	61790-53-2
propylidynetrimethanol	≤1.0	77-99-6

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person. **Description of necessary first aid measures**

Eye contact

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

United States	Page: 2/12
---------------	------------

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 4. First aid measures

Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effe	<u>cts</u>	
Eye contact	1	No known significant effects or critical hazards.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	1	No known significant effects or critical hazards.
Ingestion	1	No known significant effects or critical hazards.
Over-exposure signs/symp	otom	<u>15</u>
Eye contact	1	No specific data.
Inhalation	:	Adverse symptoms may include the following: reduced fetal weight
		increase in fetal deaths
		skeletal malformations
Skin contact	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths
		skeletal malformations
Ingestion	1	Adverse symptoms may include the following: reduced fetal weight
		increase in fetal deaths
		skeletal malformations
Indication of immediate med	dica	l attention and special treatment needed, if necessary
Notes to physician	- :	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	1	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

United States

Page: 3/12

Date of issue 23 January 2024 Version 11

United States

Page: 4/12

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 5. Fire-fighting measures

Hazardous thermal decomposition products	: Decomposition products may include the following materials: metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protec	tive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	ng
Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Date of issue 23 January 2024 Version 11

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 7. Handling and storage

Special precautions	: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits		
Manium dioxide	OSHA PEL (United States, 5/2018).		
	TWA: 15 mg/m ³ 8 hours. Form: Total dust		
	ACGIH TLV (United States, 1/2023).		
	TWA: 2.5 mg/m ³ 8 hours. Form: respirable		
	fraction, finescale particles		
Diatomaceous earth	OSHA PEL Z3 (United States, 6/2016).		
	TWA: 20 mppcf 8 hours.		
	TWA: 80 mg/m³ / (%SiO2) 8 hours.		
propylidynetrimethanol	None.		
Key to abbreviatio	ns		
A = Acceptable Maximum Peak	S = Potential skin absorption		
CGIH = American Conference of Governmental Industrial Hygienists.	SR = Respiratory sensitization		
C = Ceiling Limit	SS = Skin sensitization		
F = Fume	STEL = Short term Exposure limit values		
IPEL = Internal Permissible Exposure Limit	TD = Total dust		
DSHA = Occupational Safety and Health Administration.	TLV = Threshold Limit Value		
R = Respirable	TWA = Time Weighted Average		

Z = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

Consult local authorities for acceptable exposure limits.

Recommended monitoring	: Reference should be made to appropriate monitoring standards. Reference to national
procedures	guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Date of issue 23 January 2024 Version 11

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 8. Exposure controls/personal protection

Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection meas	res
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety glasses with side shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134.

Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	Liquid.
Color	Various
Odor	Alcohol-like.
Odor threshold	Not available.
рН	: 9
Melting point	Not available.
Boiling point	: 100°C (212°F)
Flash point	Closed cup: Not applicable. [Product does not sustain combustion.]
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Flammability	Not available.

United States Page: 6/12

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 9. Physical and chemical properties

Lower and upper explosive (flammable) limits	: Not available.		
Evaporation rate	: 0.05 (butyl acetate :	= 1)	
Vapor pressure	: 3.3 kPa (25 mm Hg	(1	
Vapor density	: Not available.		
Relative density	: 1.28		
Density(lbs / gal)	: 10.68		
Solubility(ies)	Media	Result	
	cold water	Soluble	
Partition coefficient: n- octanol/water	: Not applicable.		
Viscosity	: Kinematic (40°C (10	04°F)): >21 mm²/s (>21 cSt)	
Volatility	: 60% (v/v), 47.21% ((w/w)	
% Solid. (w/w)	: 52.79		

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure	
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours	
	LD50 Dermal	Rabbit	>5000 mg/kg	-	
	LD50 Oral	Rat	>5000 mg/kg	-	
propylidynetrimethanol	LD50 Dermal	Rabbit	10 g/kg	-	
	LD50 Oral	Rat	14000 mg/kg	-	
Conclusion/Summary : There are no data available on the mixture itself.					

United States Page: 7/12

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 11. Toxicological information

	•		
Irritation/Corrosion			
Conclusion/Summary			
Skin	: There ar	e no data	available on the mixture itself.
Eyes	: There ar	e no data	available on the mixture itself.
Respiratory	: There ar	e no data	available on the mixture itself.
Sensitization			
Conclusion/Summary			
Skin	: There ar	e no data	available on the mixture itself.
Respiratory	: There ar	e no data	available on the mixture itself.
<u>Mutagenicity</u>			
Conclusion/Summary	: There ar	e no data	available on the mixture itself.
Carcinogenicity			
Conclusion/Summary	: There ar	e no data	available on the mixture itself.
Classification			
Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-
Diatomaceous earth	-	3	-
Carcinogen Classification	code:		
IARC: 1, 2A, 2B, 3, 4 NTP: Known to be OSHA: + Not listed/not regul	a human car	cinogen; Re	asonably anticipated to be a human carcinogen
Reproductive toxicity			
Conclusion/Summary :	There are	e no data a	available on the mixture itself.
Toratogonicity			

Teratogenicity

Conclusion/Summary	: There are no data available on the mixture itself.
---------------------------	--

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Target organs

: Contains material which may cause damage to the following organs: lungs, upper respiratory tract, eyes.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effectsEye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 11. Toxicological information

Eye contact	: No specific data.
Inhalation	: 🗚 dverse symptoms may include the following:
	reduced fetal weight
	increase in fetal deaths
	skeletal malformations
Skin contact	: Adverse symptoms may include the following:
	reduced fetal weight increase in fetal deaths
	skeletal malformations
Ingestion	: Adverse symptoms may include the following:
3	reduced fetal weight
	increase in fetal deaths
	skeletal malformations
	<u>ets and also chronic effects from short and long term exposure</u>
Conclusion/Summary	Phere are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/ or engineering controls (see Section 8). If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
Short term exposure	
Potential immediate	: There are no data available on the mixture itself.
effects	
Potential delayed effects	: There are no data available on the mixture itself.
Long term exposure	
Potential immediate	: There are no data available on the mixture itself.
effects	
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health eff	ects
General	No known significant effects or critical hazards.
Carcinogenicity	Suspected of causing cancer. Risk of cancer depends on duration and level of
Carolinogonicity	exposure.
Mutagenicity	. No known significant effects or critical hazards.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Numerical measures of toxic	ity
Acute toxicity estimates	

Date of issue 23 January 2024 Version 11

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 11. Toxicological information

Product/ingredient name				(vapors)	Inhalation (dusts and mists) (mg/ I)
propylidynetrimethanol	14000	10000	N/A	N/A	N/A

Section 12. Ecological information

Т	oxi	C	ity	
			_	

Product/ingredient name	Result	Species	Exposure
Manium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
propylidynetrimethanol	Acute LC50 >1000 mg/l	Fish	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
propylidynetrimethanol	-0.47	-	Low

Mobility in soil

Soil/water partition coefficient (K_{oc})

: Not available.

Section 13. Disposal considerations

requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable pro- via a licensed waste disposal contractor. Waste should not be disposed of untre- the sewer unless fully compliant with the requirements of all authorities with jurisc Waste packaging should be recycled. Incineration or landfill should only be cons when recycling is not feasible. This material and its container must be disposed safe way. Care should be taken when handling emptied containers that have not cleaned or rinsed out. Empty containers or liners may retain some product residu Avoid dispersal of spilled material and runoff and contact with soil, waterways, dra and sewers.	via a licensed waste disposal contractor. Waste should not the sewer unless fully compliant with the requirements of all Waste packaging should be recycled. Incineration or landfi when recycling is not feasible. This material and its contain safe way. Care should be taken when handling emptied co	times comply with the al legislation and any nd non-recyclable products be disposed of untreated I authorities with jurisdiction Il should only be considered for must be disposed of in ntainers that have not been	to n. d
---	---	---	---------------

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

14. Transport information

	DOT	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

DOT: None identified.IMDG: None identified.IATA: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are active or exempted.

United States	- TSCA 5(a)2 -	- Proposed significant new use rules:
•••••••		

3(2H)-Isothiazolone, 2-methyl-	Listed	P-96-1250
SARA 302/304		

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification

: CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2

Composition/information on ingredients

Name	%	Classification
intanium dioxide propylidynetrimethanol		CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2

		United States	Page: 11/12
--	--	---------------	-------------

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 15. Regulatory information

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 1 * Flammability : 0 Physical hazards : 0 (*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.) Health : 1 Flammability : 0 Instability : 0 Date of previous issue : 5/9/2022 Organization that prepared : EHS the SDS Key to abbreviations : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not availableSGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.