SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision

6 September 2024

Version 11.01

Section 1. Identification

Product name : PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Product code : 00392818

Other means of : Not available.

identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Consumer applications, Professional applications.

Use of the substance/

mixture

: Coating.

Uses advised against

: Not applicable.

Supplier : PPG Architectural Coatings Canada, Inc.

1550, rue Ampère, bureau 500 Boucherville (Québec) J4B 7L4

Canada

+1 450-655-3121

PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272 : (412) 434-4515 (U.S.)

Emergency telephone : (412 number : (514

(514) 645-1320 (Canada) SETIQ Interior de la República: 8

SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)

Technical Phone Number: 1-800-441-9695 (8:00 am to 5:00 pm EST)

Section 2. Hazard identification

Classification of the substance or mixture

: CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2

This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8).

GHS label elements

Canada Page: 1/13

Section 2. Hazard identification

Hazard pictograms

Signal word

: Warning

Hazard statements

: Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

Precautionary statements

General

: Read label before use. Keep out of reach of children. If medical advice is needed,

have product container or label at hand.

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions

have been read and understood. Wear protective gloves, protective clothing and

eye or face protection.

Response

: IF exposed or concerned: Get medical advice or attention.

Storage

: Store locked up.

Disposal

: Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Supplemental label

elements

: Contains isothiazolinones. May cause allergic reaction. Emits toxic fumes when

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity:

23.1% (oral), 23.1% (dermal), 23.1% (inhalation)

Other hazards which do not : None known.

result in classification

Section 3. Composition/information on ingredients

Substance/mixture

Product name

: PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Other means of identification

: Not available.

CAS number/other identifiers

Ingredient name	Synonyms	% (w/w)	CAS number
Nepheline syenite	potassium, sodium, oxido-oxo- oxoalumanyloxysilane	10 - 30*	37244-96-5
titanium dioxide	Titanium oxide; Titanium oxide (TiO2); CI 77891; Titanium peroxide; Rutile; C.I. Pigment White 6; titanium dioxide coated with isopropoxytitanium triisostearate, containing by weight 1,5 % or more but not more than 2,5 % of isopropoxytitanium triisostearate; glass flakes (CAS RN 65997-17-3): — of a thickness of 0,3 µm or more but not more than 10 µm, and — coated with titanium dioxide (CAS RN 13463-67-7) or iron oxide (CAS RN 18282- 10-5); titanium dioxide, other than those of heading 3206 11 00; C.I. 77891; E 171; titanium(IV) oxide, other than those of heading 3206	7 - 13*	13463-67-7

Canada Page: 2/13 Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 3. Composition/information on ingredients

	11 00		
Diatomaceous earth	Celite, Diatomaceous earth; Diatomaceous earth (< 1% crystalline silica); Silica, amorphous, diatomaceous earth; Silica, Amorphous; Silica - Amorphous, Diatomaceous earth; Diatomaceous Earth; Silica, Amorphous - Diatomaceous earth (uncalcined); Silica - Amorphous: Diatomaceous earth; diatomaceous earth; diatomite; Silica, amorphous - diatomaceous earth; diatomaceous earth, natural	1 - 5*	61790-53-2
propylidynetrimethanol	1,3-Propanediol, 2-ethyl-2-(hydroxymethyl) -; 1,1,1-Trimethylolpropane; Propane, 1,1,1-tris(hydroxymethyl)-; trimethylolpropane; 2-ethyl- 2-hydroxymethyl-1,3-propanediol; 2-hydroxymethyl-1,3-propanediol; 1,1,1-TRIS(HYDROXYMETHYL) PROPANE; Hexaglycerine; Hexaglycerol; 2-Ethyl-2-(hydroxymethyl) -1,3-propanediol; Tris(hydroxymethyl) propane	0.1 - 1*	77-99-6

^{*}Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion

: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Canada Page: 3/13

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 4. First-aid measures

Skin contact

: No known significant effects or critical hazards.

Ingestion

: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact

: No specific data.

Inhalation

: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact

: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion

: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

: In a fire or if heated, a pressure increase will occur and the container may burst.

: Decomposition products may include the following materials: metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Canada Page: 4/13

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Special precautions

: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

> Canada Page: 5/13

Date of issue 6 September 2024 Version 11.01

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Nepheline syenite	CA Ontario Provincial (Canada, 6/2019).
	TWA: 10 mg/m³ 8 hours. Form: Total dust
titanium dioxide	CA British Columbia Provincial (Canada,
	8/2023).
	TWA: 10 mg/m³ 8 hours. Form: Total dust
	TWA: 3 mg/m³ 8 hours. Form: respirable
	fraction
	CA Quebec Provincial (Canada, 7/2023).
	TWAEV: 10 mg/m³ 8 hours. Form: Total
	dust.
	CA Alberta Provincial (Canada, 3/2023).
	Skin sensitizer.
	OEL: 10 mg/m³ 8 hours.
	CA Saskatchewan Provincial (Canada,
	7/2013).
	STEL: 20 mg/m³ 15 minutes.
	TWA: 10 mg/m ³ 8 hours.
	CA Ontario Provincial (Canada, 6/2019).
	TWA: 10 mg/m³ 8 hours. Form: total dust
Diatomaceous earth	CA Saskatchewan Provincial (Canada, 7/2013).
	STEL: 20 mg/m³ 15 minutes. Form:
	Inhalable fraction
	TWA: 10 mg/m ³ 8 hours. Form: Inhalable
	fraction
	STEL: 6 mg/m³ 15 minutes. Form:
	respirable fraction
	TWA: 3 mg/m³ 8 hours. Form: respirable
	fraction
	CA British Columbia Provincial (Canada,
	8/2023).
	TWA: 1.5 mg/m ³ 8 hours. Form: Respirable
	TWA: 4 mg/m³ 8 hours. Form: Total
	CA Quebec Provincial (Canada, 7/2023).
	TWAEV: 6 mg/m³ 8 hours. Form: Total
	dust.
propylidynetrimethanol	None.

Consult local authorities for acceptable exposure limits.

Canada Page: 6/13

Date of issue 6 September 2024 Version 11.01

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 8. Exposure controls/personal protection

procedures

Recommended monitoring: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection **Skin protection Hand protection**

: Safety glasses with side shields.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid. Color : Various : Alcohol-like. Odor : Not available. **Odor threshold**

pН

Melting point : Not available. **Boiling point** : 100°C (212°F)

Flash point : Closed cup: Not applicable. [Product does not sustain combustion.]

Canada Page: 7/13

Date of issue 6 September 2024 Version 11.01

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 9. Physical and chemical properties

Auto-ignition temperature : Not available.

Decomposition temperature : Not available. : Not available. **Flammability** Lower and upper explosive : Not available.

(flammable) limits

: 0.05 (butyl acetate = 1) **Evaporation rate** : 3.3 kPa (25 mm Hg) Vapor pressure Vapor density : Not available.

Relative density : 1.28

Density (lbs/gal) : 10.68

Media Result Solubility(ies) cold water Soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Viscosity : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

: 60% (v/v), 47.21% (w/w) **Volatility**

% Solid. (w/w) 52.79

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

: When exposed to high temperatures may produce hazardous decomposition **Conditions to avoid**

products.

Refer to protective measures listed in sections 7 and 8.

: Keep away from the following materials to prevent strong exothermic reactions: **Incompatible materials**

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition

products

: Depending on conditions, decomposition products may include the following materials:

metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Canada Page: 8/13

Date of issue 6 September 2024 Version 11.01

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
Nepheline syenite	LC50 Inhalation Dusts and mists	Rat	>5.07 mg/l	4 hours
·	LD50 Dermal	Rat	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
propylidynetrimethanol	LD50 Dermal	Rabbit	10 g/kg	-
	LD50 Oral	Rat	14000 mg/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

Sensitization

Skin: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Classification

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-
Diatomaceous earth		3	-

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

<u>Target organs</u>: Contains material which may cause damage to the following organs: lungs, upper

respiratory tract, eyes.

Aspiration hazard

Not available.

Canada Page: 9/13

Product code 00392818 Date of issue 6 September 2024 Version 11.01

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 11. Toxicological information

Information on the likely routes of exposure

Potential acute health effects

: No known significant effects or critical hazards. **Eye contact** Inhalation : No known significant effects or critical hazards. **Skin contact** : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

: Adverse symptoms may include the following: **Skin contact**

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary

: There are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

Potential immediate

effects

effects

: There are no data available on the mixture itself.

Potential delayed effects

: There are no data available on the mixture itself.

Long term exposure

Potential immediate

: There are no data available on the mixture itself.

Potential delayed effects

: There are no data available on the mixture itself.

Potential chronic health effects

General : No known significant effects or critical hazards.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Canada Page: 10/13

Date of issue 6 September 2024 Version 11.01

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 11. Toxicological information

Mutagenicity

: No known significant effects or critical hazards.

Reproductive toxicity

: Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

	- 1 th (111 g)	Dermal (mg/kg)	(gases)	(mg/l)	Inhalation (dusts and mists) (mg/l)	
propylidynetrimethanol	14000	10000	N/A	N/A	N/A	l

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
	Acute LC50 >100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 >1000 mg/l	Fish	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
propylidynetrimethanol	-0.47	-	Low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Canada Page: 11/13

Date of issue 6 September 2024 Version 11.01

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 14. Transport information

	TDG	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

TDG : None identified. **IMDG** : None identified. **IATA** : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not applicable.

to IMO instruments

Section 15. Regulatory information

National Inventory List

Canada inventory (DSL) : All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health: Flammability: 0 Physical hazards:

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health: Flammability: 0 Instability: 0

Date of issue/Date of 6 September 2024

revision

Organization that prepared : EHS

the SDS

Canada Page: 12/13

Date of issue 6 September 2024 Version 11.01

Product name PPG83-120 PPG TIMELESS INTERIOR PAINT + PRIMER FLAT MIDTONE BASE

Section 16. Other information

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group

UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Canada Page: 13/13