SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 3 September 2023 Version 8.05

| Section 1. Identification | | | |
|---|--|--|--|
| Product name | : 9-340 PURE PERFORMANCE PAINT/PRIMER IN ONE INTERIOR EGGSHELL- ULTRA DEEP BASE | | |
| Product code | : 00402772 | | |
| Other means of identification | : Not available. | | |
| Product type | : Liquid. | | |
| Relevant identified uses of the substance or mixture and uses advised against | | | |
| Product use | : Consumer applications, Professional applications, Used by spraying. | | |
| Use of the substance/ mixture | : Coating. | | |
| Uses advised against | : Not applicable. | | |
| Supplier | PPG Architectural Coatings Canada, Inc. 1550, rue Ampère, bureau 500 Boucherville (Québec) J4B 7L4 Canada +1 450-655-3121 | | |
| <u>Emergency telephone</u> <u>number</u> | PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272 : (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México) | | |
| Technical Phone Number | : 1-800-441-9695 (8:00 am to 5:00 pm EST) | | |

Section 2. Hazard identification

| Classification of the substance or mixture <u>GHS label elements</u> | : Not classified. |
|--|---|
| Signal word | : No signal word. |
| Hazard statements | : No known significant effects or critical hazards. |
| Precautionary statements | |
| General | : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. |
| Prevention | : Not applicable. |
| Response | : Not applicable. |

Date of issue 3 September 2023 Version 8.05

Product name 9-340 PURE PERFORMANCE PAINT/PRIMER IN ONE INTERIOR EGGSHELL-ULTRA DEEP BASE

Section 2. Hazard identification

| Storage | : Not applicable. |
|-----------------------------|---|
| Disposal | : Not applicable. |
| Supplemental label elements | : Contains isothiazolinones. May cause allergic reaction. Emits toxic fumes when heated. |
| | Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 18.1% (oral), 26.4% (dermal), 18.1% (inhalation) |

Section 3. Composition/information on ingredients

| Substance/mixture | : Mixture |
|----------------------------------|--|
| Product name | : 9-340 PURE PERFORMANCE PAINT/PRIMER IN ONE INTERIOR EGGSHELL- ULTRA DEEP BASE |
| Other means of identification | : Not available. |

CAS number/other identifiers

| Ingredient name | Synonyms | % (w/w) | CAS number |
|-------------------|---|---------|------------|
| Nepheline syenite | potassium, sodium, oxido-oxo- oxoalumanyloxysilane | 5 - 10* | 37244-96-5 |
| Limestone | Calcium carbonate; Marble; calcite; MARBLE DUST; VALERITE; GROUND LIMESTONE; LIMESTONE FLOUR; LIMESTONE, GROUND; Agstone; CALCIUM CARBONATE (MARBLE) | 3 - 7* | 1317-65-3 |
| Kaolin | Argilla; Porcelain clay; Hydrite; Hydrated aluminum silicate; Clay; China clay; μ- [1,3-dioxodisiloxane-1,3-diolato(2-)-κO1: κO3](dioxo)dialuminum dihydrate; E 559; kaolin; China clay; aluminium silicate, hydrated; oxo-oxoalumanyloxy-[oxo (oxoalumanyloxy)silyl]oxysilane dihydrate; Clay (kaolin); KAOLIN DUST | 1 - 5* | 1332-58-7 |

*Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Date of issue 3 September 2023 Version 8.05

Product name 9-340 PURE PERFORMANCE PAINT/PRIMER IN ONE INTERIOR EGGSHELL-ULTRA **DEEP BASE**

Section 4. First-aid measures

| Inhalation | : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. |
|--------------|--|
| Skin contact | Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. |
| Ingestion | : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting. |

Most important symptoms/effects, acute and delayed

| Potential acute health effect | :ts | |
|--|--|--|
| Eye contact | : No known significant effects or critical hazards. | |
| Inhalation | : No known significant effects or critical hazards. | |
| Skin contact | : No known significant effects or critical hazards. | |
| Ingestion | : No known significant effects or critical hazards. | |
| Over-exposure signs/symp | <u>toms</u> | |
| Eye contact | : No specific data. | |
| Inhalation | : No specific data. | |
| Skin contact | : No specific data. | |
| Ingestion | : No specific data. | |
| Indication of immediate medical attention and special treatment needed, if necessary | | |
| Notes to physician | : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. | |
| Specific treatments | No specific treatment. | |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. | |

See toxicological information (Section 11)

Section 5. Fire-fighting measures

| Extinguishing media | | | |
|--|---|---|--|
| Suitable extinguishing media | : | Use an extinguishing agent suitable for the surrounding fire. | |
| Unsuitable extinguishing media | : | None known. | |
| Specific hazards arising from the chemical | : | In a fire or if heated, a pressure increase will occur and the container may burst. | |
| Hazardous thermal decomposition products | : | Decomposition products may include the following materials: carbon oxides metal oxide/oxides | |
| Special protective actions for fire-fighters | : | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. | |
| Special protective equipment for fire-fighters | : | Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. | |
| | | Canada Page: 3/11 | |

Product name 9-340 PURE PERFORMANCE PAINT/PRIMER IN ONE INTERIOR EGGSHELL-ULTRA DEEP BASE

Section 6. Accidental release measures

| tiv | <u>e equipment and emergency procedures</u> |
|-----|--|
| : | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. |
| : | If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| : | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). |
| nt | ainment and cleaning up |
| : | Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
| : | Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |
| | : : : : |

Section 7. Handling and storage

| Precautions for safe handling | 1 | |
|--|---|--|
| Protective measures | 1 | Put on appropriate personal protective equipment (see Section 8). |
| Special precautions | : | If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts. |
| Advice on general occupational hygiene | : | Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
| Conditions for safe storage, including any incompatibilities | : | Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. |

Product name 9-340 PURE PERFORMANCE PAINT/PRIMER IN ONE INTERIOR EGGSHELL-ULTRA DEEP BASE

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|-------------------|---|
| Nepheline syenite | CA Ontario Provincial (Canada, 6/2019). TWA: 10 mg/m ³ 8 hours. Form: Total dust |
| Limestone | CA British Columbia Provincial (Canada, 6/2022). |
| | TWA: 10 mg/m³ 8 hours. Form: Total dust STEL: 20 mg/m³ 15 minutes. |
| | TWA: 3 mg/m ³ 8 hours. Form: respirable fraction |
| | CA Quebec Provincial (Canada, 6/2022). TWAEV: 10 mg/m ³ 8 hours. Form: Total |
| | dust. CA Alberta Provincial (Canada, 6/2018). [Calcium carbonate] Skin sensitizer. 8 hrs OEL: 10 mg/m³ 8 hours. |
| | CA Saskatchewan Provincial (Canada, 7/2013). [Limestone] STEL: 20 mg/m³ 15 minutes. |
| Kaolin | TWA: 10 mg/m ³ 8 hours. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 2 mg/m ³ 8 hours. Form: Respirable |
| | CA British Columbia Provincial (Canada, 6/2022). |
| | TWA: 2 mg/m³ 8 hours. Form: Respirable CA Quebec Provincial (Canada, 6/2022). TWAEV: 2 mg/m³ 8 hours. Form: |
| | Respirable dust. CA Ontario Provincial (Canada, 6/2019). TWA: 2 mg/m³ 8 hours. Form: Respirable |
| | particulate matter. CA Saskatchewan Provincial (Canada, 7/2013). |
| | STEL: 4 mg/m ³ 15 minutes. Form: respirable fraction |
| | TWA: 2 mg/m ³ 8 hours. Form: respirable fraction |

Consult local authorities for acceptable exposure limits.

| Recommended monitoring procedures | : | Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required. |
|-----------------------------------|---|---|
| Appropriate engineering controls | : | Good general ventilation should be sufficient to control worker exposure to airborne contaminants. |
| Environmental exposure controls | : | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. |

Canada Page: 5/11

Product name 9-340 PURE PERFORMANCE PAINT/PRIMER IN ONE INTERIOR EGGSHELL-ULTRA DEEP BASE

Section 8. Exposure controls/personal protection

Individual protection measures

| Hygiene measures | : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
|------------------------|--|
| Eye/face protection | : Safety glasses with side shields. |
| Skin protection | |
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. |
| Body protection | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. |

Section 9. Physical and chemical properties

| <u>Appearance</u> | |
|---------------------------|--|
| Physical state | : Liquid. |
| Color | : Various |
| Odor | : Characteristic. |
| Odor threshold | : Not available. |
| рН | : 9 |
| Melting point | : Not available. |
| Boiling point | : 100°C (212°F) |
| Flash point | : Closed cup: Not applicable. [Product does not sustain combustion.] |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| Flammability | : Not available. |
| Lower and upper explosive | : Not available. |
| (flammable) limits | |
| Evaporation rate | : 0.05 (butyl acetate = 1) |
| Vapor pressure | : 3.3 kPa (25 mm Hg) |
| Vapor density | : Not available. |
| Relative density | : 1.16 |
| Density(lbs / gal) | : 9.68 |
| | |

Product name 9-340 PURE PERFORMANCE PAINT/PRIMER IN ONE INTERIOR EGGSHELL-ULTRA DEEP BASE

Section 9. Physical and chemical properties

| Solubility(ies) | | Media | Result | _ |
|--|---|--------------------|-------------------------------|---|
| | • | old water | Soluble | |
| Partition coefficient: n- octanol/water | : | Not applicable. | | |
| Viscosity | : | Kinematic (40°C (7 | (104°F)): >21 mm²/s (>21 cSt) | |
| Volatility | | 70% (v/v), 60.4889 | % (w/w) | |
| % Solid. (w/w) | : | 39.512 | | |

Section 10. Stability and reactivity

| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
|------------------------------------|---|
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8. |
| Incompatible materials | : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids. |
| Hazardous decomposition products | : Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides |

Section 11. Toxicological information

Information on toxicological effects

| Acute | tox | icity |
|-------|-----|-------|
| | | _ |

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|--|---------|-------------|----------|
| Nepheline syenite | LC50 Inhalation Dusts and mists | Rat | >5.07 mg/l | 4 hours |
| | LD50 Dermal | Rat | >5000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| Limestone | LD50 Oral | Rat | 6450 mg/kg | - |
| Kaolin | LC50 Inhalation Dusts and mists | Rat | >5.07 mg/l | 4 hours |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| Conclusion/Summary | : There are no data available on the mixture itself. | | | |
| Irritation/Corrosion | | | | |

| Irritation/Corrosion | |
|----------------------|--|
| Conclusion/Summary | |
| Skin | : There are no data available on the mixture itself. |
| Eyes | : There are no data available on the mixture itself. |
| Respiratory | : There are no data available on the mixture itself. |
| Sensitization | |
| Skin | : There are no data available on the mixture itself. |
| | |

Product name 9-340 PURE PERFORMANCE PAINT/PRIMER IN ONE INTERIOR EGGSHELL-ULTRA DEEP BASE

Section 11. Toxicological information

| Respiratory | : There are no data available on the mixture itself. |
|----------------------------|--|
| Mutagenicity | |
| Conclusion/Summary | : There are no data available on the mixture itself. |
| Carcinogenicity | |
| Conclusion/Summary | : There are no data available on the mixture itself. |
| Reproductive toxicity | |
| Conclusion/Summary | : There are no data available on the mixture itself. |
| Teratogenicity | |
| Conclusion/Summary | : There are no data available on the mixture itself. |
| Specific target organ toxi | <u>city (single exposure)</u> |
| Not available. | |

Specific target organ toxicity (repeated exposure)

Not available.

Target organs

: Contains material which causes damage to the following organs: eyes. Contains material which may cause damage to the following organs: lungs, upper respiratory tract, skin, stomach.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effectsEye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

| Eye contact | : No specific data. |
|--------------|---------------------|
| Inhalation | : No specific data. |
| Skin contact | : No specific data. |
| Ingestion | : No specific data. |

Delayed and immediate effects and also chronic effects from short and long term exposure

| : There are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. |
|--|
| : There are no data available on the mixture itself. |
| |

Product name 9-340 PURE PERFORMANCE PAINT/PRIMER IN ONE INTERIOR EGGSHELL-ULTRA DEEP BASE

Section 11. Toxicological information

| Potential delayed effects | : There are no data available on the mixture itself. |
|-------------------------------|--|
| Long term exposure | |
| Potential immediate effects | : There are no data available on the mixture itself. |
| Potential delayed effects | : There are no data available on the mixture itself. |
| Potential chronic health effe | ects |
| General | : No known significant effects or critical hazards. |
| Carcinogenicity | : No known significant effects or critical hazards. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Reproductive toxicity | : No known significant effects or critical hazards. |

Numerical measures of toxicity

Acute toxicity estimates

| Product/ingredient name | Oral (mg/ kg) | (mg/kg) | Inhalation (gases) (ppm) | (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|-------------------------|------------------|---------|--------------------------------|--------------------|--|
| Limestone | 6450 | N/A | N/A | N/A | N/A |

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|------------------------|---------|----------|
| Limestone | Acute LC50 >56000 mg/l | Fish | 96 hours |

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or

Canada Page: 9/11

Date of issue 3 September 2023 Version 8.05

Product name 9-340 PURE PERFORMANCE PAINT/PRIMER IN ONE INTERIOR EGGSHELL-ULTRA DEEP BASE

Section 13. Disposal considerations

landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Section 14. Transport information

| | TDG | IMDG | ΙΑΤΑ |
|--------------------------------|-----------------|-----------------|-----------------|
| UN number | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - |
| Transport hazard class (es) | - | - | - |
| Packing group | - | - | - |
| Environmental hazards | No. | No. | No. |
| Marine pollutant substances | Not applicable. | Not applicable. | Not applicable. |

Additional information

- **TDG** : None identified.
- IMDG : None identified.
- IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

National Inventory List

Canada inventory (DSL)

: All components are listed or exempted.

Canada Page: 10/11

Date of issue 3 September 2023 Version 8.05

Product name 9-340 PURE PERFORMANCE PAINT/PRIMER IN ONE INTERIOR EGGSHELL-ULTRA DEEP BASE

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 1 Flammability : 0 Physical hazards : 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

| National Fire Protection Asso | ociation (U.S.A.) | |
|------------------------------------|---|--|
| Health : 1 Flamma | bility : 0 Instability : 0 | |
| Date of issue/Date of revision | 3 September 2023 | |
| Organization that prepared the SDS | : EHS | |
| Key to abbreviations | : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 19 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations | |

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.