SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 3 September 2023

Version 9.01

Section 1. Identification

Product name : 56404 OLYMPIC MAXIMUM STAIN/SEALANT IN ONE TONER-REDWOOD

NATURALTONE

Product code : 00408200

Other means of : Not available.

identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Consumer applications, Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

Uses advised against

: Not applicable.

Supplier : PPG Architectural Coatings Canada, Inc.

1550, rue Ampère, bureau 500 Boucherville (Québec) J4B 7L4

Canada

+1 450-655-3121

PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272 : (412) 434-4515 (U.S.)

Emergency telephone

<u>number</u>

(514) 645-1320 (Canada)

SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)

Technical Phone Number : 1-800-441-9695 (8:00 am to 5:00 pm EST)

Section 2. Hazard identification

Classification of the substance or mixture GHS label elements

: CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 1

Hazard pictograms



Signal word : Danger

Hazard statements : Suspected of causing cancer.

May damage fertility or the unborn child.

Canada Page: 1/12

Product name 56404 OLYMPIC MAXIMUM STAIN/SEALANT IN ONE TONER-REDWOOD

NATURALTONE

Section 2. Hazard identification

Precautionary statements

: Read label before use. Keep out of reach of children. If medical advice is needed, General

have product container or label at hand.

Prevention : Obtain special instructions before use. Do not handle until all safety precautions

have been read and understood. Wear protective gloves, protective clothing and

eye or face protection.

: IF exposed or concerned: Get medical advice or attention. Response

: Store locked up. **Storage**

: Dispose of contents and container in accordance with all local, regional, national **Disposal**

and international regulations.

Supplemental label

elements

: Contains isothiazolinones. May cause allergic reaction. Sanding and grinding dusts

may be harmful if inhaled. Emits toxic fumes when heated.

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity:

13.2% (oral), 13.2% (dermal), 13.2% (inhalation)

Section 3. Composition/information on ingredients

Substance/mixture

Mixture **Product name**

56404 OLYMPIC MAXIMUM STAIN/SEALANT IN ONE TONER-REDWOOD

NATURALTONE

Other means of identification

: Not available.

CAS number/other identifiers

Ingredient name	Synonyms	% (w/w)	CAS number
2-butanone oxime	butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime; 2-Butanone, oxime; METHYL ETHYL KETOXIME; METHYL ETHYL KETONE OXIME; ethyl methyl ketoxime; ethyl methyl ketone oxime; MEKO; syn-O,O'-di(butan-2-one oxime)diethoxysilane; Methyl alkyl (C2-4) ketoxime; Butan-2-one oxime	0.1 - 1*	96-29-7
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Decanedioic acid, 1,10-bis (1,2,2,6,6-pentamethyl-4-piperidinyl) ester; Decanedioic acid, bis (1,2,2,6,6-pentamethyl-4-piperidinyl) ester; bis(1,2,2,6,6-pentamethyl-4-piperidin-4-yl) decanedioate; Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) decanedioate; Bis (1,2,2,6,6-pentamethyl-4-piperidyl) decanedioate; Decanedioic acid bis (1,2,2,6,6-pentamethyl-4-piperidinyl) ester; DECANEDIOATE, BIS (1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) (PICCS); Bis(N-methyl-2,2,6,6-tetramethyl-4-piperidinyl) sebacate; Bis(1,2,2,6,6-pentamethyl-4-piperidyl) 1,8-octanedicarboxylate; Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate; DECANEDIOATE, BIS	0.1 - 1*	41556-26-7

Canada Page: 2/12 Product code 00408200

Date of issue 3 September 2023 Version 9.01

Product name 56404 OLYMPIC MAXIMUM STAIN/SEALANT IN ONE TONER-REDWOOD

NATURALTONE

Section 3. Composition/information on ingredients

	•	•		
		(1,2,2,6,6-PENTAMETHYL-4- PIPERIDINYL)		
2-ethylhexanoic ac	id, zirconium salt	Hexanoic acid, 2-ethyl-, zirconium salt (1:?); Hexanoic acid, 2-ethyl-, zirconium salt; Zirconium 2-ethylhexanoate; Zirconium salt of 2-ethylhexanoic acid; Aliphatic monocarboxylic acid (C6-28) salt (Pb, Cu, Mn, Zn, Zr, Ce, Cd, Sn, Sr, Co); 2-Ethylhexanoic acid zirconium salt; HEXANOATE, 2-ETHYL-, ZIRCONIUM; ZIRCONIUM OCTOATE; Zirconium 2-ethylhexanoate (component unspecified)	0.1 - 1*	22464-99-9

^{*}Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion

: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact

: No specific data.

Inhalation

: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Canada Page: 3/12

Product name 56404 OLYMPIC MAXIMUM STAIN/SEALANT IN ONE TONER-REDWOOD

NATURALTONE

Section 4. First-aid measures

Skin contact: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

: In a fire or if heated, a pressure increase will occur and the container may burst.

: No specific data.

Special protective actions

for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters

 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Canada Page: 4/12

Product code 00408200

Date of issue 3 September 2023 Version 9.01

Product name 56404 OLYMPIC MAXIMUM STAIN/SEALANT IN ONE TONER-REDWOOD

NATURALTONE

Section 6. Accidental release measures

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Special precautions

: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

> Canada Page: 5/12

Product code 00408200

Date of issue 3 September 2023 Version 9.01

Product name 56404 OLYMPIC MAXIMUM STAIN/SEALANT IN ONE TONER-REDWOOD **NATURALTONE**

Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage. : Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	
2-butanone oxime	IPEL (-).	
	TWA: 3 ppm	
	STEL: 9 ppm	
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	None.	
2-ethylhexanoic acid, zirconium salt	CA Alberta Provincial (Canada, 6/2018).	
	[Zirconium and compounds as Zr]	
	15 min OEL: 10 mg/m³, (as Zr) 15 minutes.	
	8 hrs OEL: 5 mg/m³, (as Zr) 8 hours.	
	CA British Columbia Provincial (Canada,	
	6/2022). [Zirconium and compounds as Zr]	
	STEL: 10 mg/m³, (as Zr) 15 minutes.	
	TWA: 5 mg/m³, (as Zr) 8 hours.	
	CA Quebec Provincial (Canada, 6/2022).	
	[Zirconium and compounds]	
	STEV: 10 mg/m³, (as Zr) 15 minutes.	
	TWAEV: 5 mg/m³, (as Zr) 8 hours.	
	CA Ontario Provincial (Canada, 6/2019).	
	[Zirconium and compounds as Z]	
	STEL: 10 mg/m³, (as Zr) 15 minutes.	
	TWA: 5 mg/m³, (as Zr) 8 hours.	

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Canada Page: 6/12

Product name 56404 OLYMPIC MAXIMUM STAIN/SEALANT IN ONE TONER-REDWOOD

NATURALTONE

Section 8. Exposure controls/personal protection

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing.

Wash contaminated clothing before reusing. Ensure that eyewash stations and

safety showers are close to the workstation location.

Eye/face protection

Skin protection

Hand protection

kin protection

: Safety glasses with side shields.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of

estimated.

Body protection : Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

several substances, the protection time of the gloves cannot be accurately

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

Section 9. Physical and chemical properties

<u>Appearance</u>

Physical state : Liquid.

Color : Not available.

Odor : Characteristic.

Odor threshold : Not available.

pH : Not available.

Melting point : Not available.

Boiling point : >37.78°C (>100°F)

Flash point : Closed cup: 93.33°C (200°F) [Product does not sustain combustion.]

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Flammability : Not available.

Lower and upper explosive

(flammable) limits

: Not available.

Evaporation rateVapor pressureVapor densityNot available.Not available.

Relative density : 1.01 Density (lbs / gal) : 8.43

Canada Page: 7/12

Product name 56404 OLYMPIC MAXIMUM STAIN/SEALANT IN ONE TONER-REDWOOD

NATURALTONE

Section 9. Physical and chemical properties

Solubility(ies) : Media Result

cold water Soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Viscosity : Kinematic (40°C (104°F)): <14 mm²/s (<14 cSt)

Volatility : 84% (v/v), 82.414% (w/w)

% Solid. (w/w) : 17.586

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

Refer to protective measures listed in sections 7 and 8.

Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-butanone oxime	LD50 Dermal LD50 Oral	Rabbit Rat	1100 mg/kg 100 mg/kg	-
bis(1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate	LD50 Oral	Rat	3.125 g/kg	-
2-ethylhexanoic acid, zirconium salt	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	>5 g/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

Sensitization

Skin: There are no data available on the mixture itself.

Canada Page: 8/12

Product name 56404 OLYMPIC MAXIMUM STAIN/SEALANT IN ONE TONER-REDWOOD

NATURALTONE

Section 11. Toxicological information

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary

: There are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Canada Page: 9/12

Product name 56404 OLYMPIC MAXIMUM STAIN/SEALANT IN ONE TONER-REDWOOD

NATURALTONE

Section 11. Toxicological information

Short term exposure

Potential immediate

effects

: There are no data available on the mixture itself.

Potential delayed effects

: There are no data available on the mixture itself.

Long term exposure

Potential immediate

effects

: There are no data available on the mixture itself.

Potential delayed effects

: There are no data available on the mixture itself.

Potential chronic health effects

General : No known significant effects or critical hazards.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity: No known significant effects or critical hazards.

Reproductive toxicity: May damage fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
2-butanone oxime bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	500	1100	N/A	N/A	N/A
	3125	N/A	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
2-ethylhexanoic acid, zirconium salt	Acute LC50 >100 mg/l	Fish	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-butanone oxime	0.63	5.01	Low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Canada Page: 10/12

Product name 56404 OLYMPIC MAXIMUM STAIN/SEALANT IN ONE TONER-REDWOOD **NATURALTONE**

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Section 14. Transport information

	TDG	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

TDG : None identified. : None identified. **IMDG IATA** : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Canada Page: 11/12

Product name 56404 OLYMPIC MAXIMUM STAIN/SEALANT IN ONE TONER-REDWOOD

NATURALTONE

Section 15. Regulatory information

National Inventory List

Canada inventory (DSL) : At least one component is not listed in DSL but all such components are listed in

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health: 2 Flammability: 1 Physical hazards:

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health: Flammability: 1 **Instability**: 0

Date of issue/Date of 3 September 2023

revision

Organization that prepared : EHS

the SDS

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group

UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

> Canada Page: 12/12