# **SAFETY DATA SHEET**



#### The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 3 September 2023 Version 11.01

Section 1 Identifi	Section 1. Identification		
Product name	: 70-320 MANOR HALL PAINT/PRIMER IN ONE EXTERIOR EGGSHELL-MIDTONE BASE		
Product code	: 00408370		
Other means of identification	: Not available.		
Product type	: Liquid.		
Relevant identified uses of t	the substance or mixture and uses advised against		
Product use	: Consumer applications, Professional applications, Used by spraying.		
Use of the substance/ mixture	: Coating.		
Uses advised against	: Not applicable.		
Supplier	<ul> <li>PPG Architectural Coatings Canada, Inc.</li> <li>1550, rue Ampère, bureau 500</li> <li>Boucherville (Québec) J4B 7L4</li> <li>Canada</li> <li>+1 450-655-3121</li> </ul>		
	PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272		
<u>Emergency telephone</u> <u>number</u>	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)		
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)		

### Section 2. Hazard identification

Classification of the substance or mixture	: CARCINOGENICITY - Category 1 TOXIC TO REPRODUCTION - Category 1
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
	Category 2 based on its IARC 2B classification. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8).
GHS label elements	

Canada Page: 1/14

Product code 00408370 Product name 70-320 MANOR HALL PAINT/PRIMER IN ONE EXTERIOR EGGSHELL-MIDTONE BASE

### Section 2. Hazard identification

#### Hazard pictograms



Signal word	Danger	
Hazard statements	May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.	
Precautionary statements		
General	Read label before use. Keep out of reach of children. If medical advice is need have product container or label at hand.	ded,
Prevention	Obtain special instructions before use. Do not handle until all safety precaution have been read and understood. Wear protective gloves, protective clothing ar eye or face protection. Do not breathe vapor. Do not eat, drink or smoke wher using this product. Wash thoroughly after handling.	nd
Response	IF exposed or concerned: Get medical advice or attention.	
Storage	Store locked up.	
Disposal	Dispose of contents and container in accordance with all local, regional, nationa and international regulations.	al
Supplemental label elements	Contains isothiazolinones. May cause allergic reaction. Sanding and grinding d may be harmful if inhaled. This product contains crystalline silica which can cau lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Emits fumes when heated. Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 34.2% (oral), 34.2% (dermal), 34.2% (inhalation)	use of toxic

### Section 3. Composition/information on ingredients

Substance/mixture	<ul> <li>Mixture</li> <li>70-320 MANOR HALL PAINT/PRIMER IN ONE EXTERIOR EGGSHELL-MIDTONE</li></ul>
Product name	BASE
Other means of identification	: Not available.

#### **CAS number/other identifiers**

Ingredient name	Synonyms	% (w/w)	CAS nu	umber
Manium dioxide	Titanium oxide; Titanium oxide (TiO2); CI 77891; Titanium peroxide; Rutile; C.I. Pigment White 6; titanium dioxide coated with isopropoxytitanium triisostearate, containing by weight 1,5 % or more but not more than 2,5 % of isopropoxytitanium triisostearate; glass flakes (CAS RN 65997-17-3): — of a thickness of 0,3 $\mu$ m or more but not more than 10 $\mu$ m, and — coated with titanium dioxide (CAS RN 13463-67-7) or iron oxide (CAS RN 18282- 10-5); titanium dioxide, other than those of heading 3206	5 - 10*	13463-	67-7
			Canada	Page: 2/14

## Product name 70-320 MANOR HALL PAINT/PRIMER IN ONE EXTERIOR EGGSHELL-MIDTONE BASE

### Section 3. Composition/information on ingredients

Section 3. Composition	intornation on ingredient	.5	
	11 00; C.I. 77891; E 171; titanium(IV) oxide, other than those of heading 3206 11 00		
crystalline silica, respirable powder (<10 microns)	alpha-quartz; Silica, crystalline (quartz); Silica, Crystalline Quartz; SILICA, CRYSTALLINE, QUARTZ; Silica- Crystalline, Quartz; Silica - Crystalline Quartz; Silica-Crystalline : Quartz; Silica, crystalline - quartz	1 - 5*	14808-60-7
crystalline silica, respirable powder (>10 microns)	alpha-quartz; Silica, crystalline (quartz); Silica, Crystalline Quartz; SILICA, CRYSTALLINE, QUARTZ; Silica- Crystalline, Quartz; Silica - Crystalline Quartz; Silica-Crystalline : Quartz; Silica, crystalline - quartz	1 - 5*	14808-60-7
Diatomaceous earth	Celite, Diatomaceous earth; Silica, amorphous, diatomaceous earth; Silica, Amorphous; Silica - Amorphous, Diatomaceous earth; Diatomaceous Earth; Silica, Amorphous - Diatomaceous earth (uncalcined); Silica - Amorphous: Diatomaceous earth; diatomaceous earth; diatomite; Silica, amorphous - diatomaceous earth; diatomaceous earth, natural; SILICA, AMORPHOUS DIATOMACEOUS EARTH	1 - 5*	61790-53-2
N-methyl-2-pyrrolidone	1-methyl-2-pyrrolidone; 2-Pyrrolidinone, 1-methyl-; n-Methylpyrrolidone; N-Methyl- 2-pyrrolidinone; Methylpyrrolidone; 1-methylpyrrolidin-2-one; 1-methyl- 2-pyrrolidinone; NMP; M-pyrol; Methyl- 2-Pyrrolidone, n-; n-methyl-2-pyrrolidine	0.1 - 1*	872-50-4

\*Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

#### Description of necessary first aid measures

Eye contact

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Date of issue 3 September 2023 Version 11.01

Product name 70-320 MANOR HALL PAINT/PRIMER IN ONE EXTERIOR EGGSHELL-MIDTONE BASE

#### Section 4. First-aid measures Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. **Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting. Most important symptoms/effects, acute and delayed Potential acute health effects Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards. **Over-exposure signs/symptoms** Eye contact : No specific data. : Adverse symptoms may include the following: Inhalation reduced fetal weight increase in fetal deaths skeletal malformations Skin contact : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations Ingestion : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations Indication of immediate medical attention and special treatment needed, if necessary Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. **Specific treatments** : No specific treatment.

# Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

Extinguishing media		
Suitable extinguishing media	1	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	1	None known.

Canada Page: 4/14

Date of issue 3 September 2023 Version 11.01

Product name 70-320 MANOR HALL PAINT/PRIMER IN ONE EXTERIOR EGGSHELL-MIDTONE BASE

### Section 5. Fire-fighting measures

Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>

### Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures			
:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.		
:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		
nta	ainment and cleaning up		
:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.		
:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.		
	: :		

Date of issue 3 September 2023 Version 11.01

Product name 70-320 MANOR HALL PAINT/PRIMER IN ONE EXTERIOR EGGSHELL-MIDTONE BASE

### Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	:	If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

**Occupational exposure limits** 

Ingredient name	Exposure limits
irtanium dioxide	<ul> <li>CA British Columbia Provincial (Canada, 6/2022). [Titanium dioxide]</li> <li>TWA: 10 mg/m<sup>3</sup> 8 hours. Form: Total dust TWA: 3 mg/m<sup>3</sup> 8 hours. Form: respirable fraction</li> <li>CA Quebec Provincial (Canada, 6/2022). TWAEV: 10 mg/m<sup>3</sup> 8 hours. Form: Total dust.</li> <li>CA Alberta Provincial (Canada, 6/2018).</li> <li>Skin sensitizer.</li> <li>8 hrs OEL: 10 mg/m<sup>3</sup> 8 hours.</li> <li>CA Ontario Provincial (Canada, 6/2019). TWA: 10 mg/m<sup>3</sup> 8 hours. Form: total dust</li> <li>CA Saskatchewan Provincial (Canada, 7/2013).</li> <li>STEL: 20 mg/m<sup>3</sup> 15 minutes. TWA: 10 mg/m<sup>3</sup> 8 hours.</li> </ul>
crystalline silica, respirable powder (<10 microns)	CA British Columbia Provincial (Canada, 6/2022). [Silica, Crystalline - alpha quartz and Cristobalite Respirable]
	Canada Page: 6/

Date of issue 3 September 2023 Version 11.01

Product name 70-320 MANOR HALL PAINT/PRIMER IN ONE EXTERIOR EGGSHELL-MIDTONE BASE

#### Section 8. Exposure controls/personal protection TWA: 0.025 mg/m<sup>3</sup> 8 hours. Form: Respirable CA Ontario Provincial (Canada, 6/2019). [Silica, Crystalline (Quartz/Tripoli)] TWA: 0.1 mg/m<sup>3</sup> 8 hours. Form: Respirable CA Quebec Provincial (Canada, 6/2022). [Silica Crystalline -Quartz] TWAEV: 0.1 mg/m<sup>3</sup> 8 hours. Form: Respirable dust. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 0.025 mg/m<sup>3</sup> 8 hours. Form: Respirable particulate CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.05 mg/m<sup>3</sup> 8 hours. Form: respirable fraction CA British Columbia Provincial (Canada, crystalline silica, respirable powder (>10 microns) 6/2022). [Silica, Crystalline - alpha quartz and Cristobalite Respirable] TWA: 0.025 mg/m<sup>3</sup> 8 hours. Form: Respirable CA Ontario Provincial (Canada, 6/2019). [Silica, Crystalline (Quartz/Tripoli)] TWA: 0.1 mg/m<sup>3</sup> 8 hours. Form: Respirable CA Quebec Provincial (Canada, 6/2022). [Silica Crystalline -Quartz] TWAEV: 0.1 mg/m<sup>3</sup> 8 hours. Form: Respirable dust. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 0.025 mg/m<sup>3</sup> 8 hours. Form: Respirable particulate CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.05 mg/m<sup>3</sup> 8 hours. Form: respirable fraction Diatomaceous earth CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m<sup>3</sup> 15 minutes. Form: Inhalable fraction TWA: 10 mg/m<sup>3</sup> 8 hours. Form: Inhalable fraction STEL: 6 mg/m<sup>3</sup> 15 minutes. Form: respirable fraction TWA: 3 mg/m<sup>3</sup> 8 hours. Form: respirable fraction CA British Columbia Provincial (Canada, 6/2022). TWA: 1.5 mg/m<sup>3</sup> 8 hours. Form: Respirable CA Quebec Provincial (Canada, 6/2022). TWAEV: 6 mg/m<sup>3</sup> 8 hours. Form: Total dust. N-methyl-2-pyrrolidone CA Ontario Provincial (Canada, 6/2019). TWA: 400 mg/m<sup>3</sup> 8 hours.

#### Product name 70-320 MANOR HALL PAINT/PRIMER IN ONE EXTERIOR EGGSHELL-MIDTONE BASE

### Section 8. Exposure controls/personal protection

#### Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measured	res	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	1	Safety glasses with side shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use

### Section 9. Physical and chemical properties

necessary.

		Canada	Page: 8/14
Melting point	: Not available.		
pH	: Not available.		
Odor threshold	: Not available.		
Odor	: Characteristic.		
Physical state Color	: Liquid. : Not available.		
<u>Appearance</u>			

appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

Date of issue 3 September 2023 Version 11.01

Product name 70-320 MANOR HALL PAINT/PRIMER IN ONE EXTERIOR EGGSHELL-MIDTONE BASE

### Section 9. Physical and chemical properties

-			
Boiling point	:	>37.78°C (>100°F)	
Flash point	1	Closed cup: 113.33	°C (236°F) [Product does not sustain combustion.]
Auto-ignition temperature	:	Not available.	
Decomposition temperature	1	Not available.	
Flammability	1	Not available.	
Lower and upper explosive (flammable) limits	:	Not available.	
Evaporation rate	:	Not available.	
Vapor pressure	:	Not available.	
Vapor density	:	Not available.	
Relative density	1	1.17	
Density(lbs / gal)	:	9.76	
Solubility(ies)		Media	Result
Solubility(les)	1	old water	Soluble
Partition coefficient: n- octanol/water	:	Not applicable.	
Viscosity	:	Kinematic (40°C (10	04°F)): >21 mm²/s (>21 cSt)
Volatility	:	64% (v/v), 54.616%	(w/w)
% Solid. (w/w)	1	45.384	

### Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	<ul> <li>When exposed to high temperatures may produce hazardous decomposition products.</li> <li>Refer to protective measures listed in sections 7 and 8.</li> </ul>
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

Product name 70-320 MANOR HALL PAINT/PRIMER IN ONE EXTERIOR EGGSHELL-MIDTONE BASE

### Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	:		Species	Dose	Exposure	
titanium dioxide	LC50 I	nhalation	Dusts and mist	s Rat	>6.82 mg/l	4 hours	
	LD50 I	Dermal		Rabbit	>5000 mg/kg	-	
	LD50 (			Rat	>5000 mg/kg	-	
N-methyl-2-pyrrolidone			Dusts and mist		>5100 mg/m <sup>3</sup>	4 hours	
		Dermal		Rabbit	8 g/kg	-	
	LD50 (	Jrai		Rat	3.914 g/kg	-	
Conclusion/Summary	: The	re are no o	data available o	on the mixture i	tself.		
Irritation/Corrosion							
Conclusion/Summary							
Skin	: The	re are no o	data available o	on the mixture i	tself.		
Eyes	: There are no data available on the mixture itself.						
Respiratory	: There are no data available on the mixture itself.						
Sensitization							
Skin	: There are no data available on the mixture itself.						
Respiratory	: There are no data available on the mixture itself.						
<u>Mutagenicity</u>							
Conclusion/Summary	: The	re are no o	data available o	on the mixture i	tself.		
Carcinogenicity							
<b>Conclusion/Summary</b> : There are no data available on the mixture itself.							
<b>Classification</b>							
Product/ingredient name		OSHA	IARC N	P			
titanium dioxide		-	2B -				
crystalline silica, respirable p (<10 microns)	owder	-	1 Kn	own to be a hu	man carcinogen.		
`' ·							

Known to be a human carcinogen.

Carcinogen	Classification code:

crystalline silica, respirable powder

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

1

3

#### **Reproductive toxicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

#### **Teratogenicity**

(>10 microns) Diatomaceous earth

**Conclusion/Summary** : There are no data available on the mixture itself.

#### <u>Specific target organ toxicity (single exposure)</u>

Name		Route of exposure	Target organs
N-methyl-2-pyrrolidone	Category 3		Respiratory tract irritation

Product name 70-320 MANOR HALL PAINT/PRIMER IN ONE EXTERIOR EGGSHELL-MIDTONE BASE

### Section 11. Toxicological information

#### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
crystalline silica, respirable powder (<10 microns)	Category 1	inhalation	-
N-methyl-2-pyrrolidone	Category 2	-	

Target organs

: Contains material which causes damage to the following organs: liver, spleen, bone marrow. Contains material which may cause damage to the following organs: kidneys, lungs, upper respiratory tract, immune system, eyes.

#### **Aspiration hazard**

Not available.

#### Information on the likely routes of exposure

#### Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Eye contact	No specific data.
Inhalation	<ul> <li>Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations</li> </ul>
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary	: There are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/
	or engineering controls (see Section 8). If splashed in the eyes, the liquid may

Canada Page: 11/14

#### Product name 70-320 MANOR HALL PAINT/PRIMER IN ONE EXTERIOR EGGSHELL-MIDTONE BASE

### Section 11. Toxicological information

		cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
<u>Short term exposure</u>		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
Long term exposure		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
Potential chronic health effe	ect	<u>S</u>
General	:	Causes damage to organs through prolonged or repeated exposure.
Carcinogenicity	:	May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	May damage fertility or the unborn child.
Numerical measures of toxic	<u>ity</u>	

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	(vapors)	Inhalation (dusts and mists) (mg/l)
✓-methyl-2-pyrrolidone	3914	8000	N/A	N/A	N/A

### Section 12. Ecological information

<u>Toxicity</u>			
Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
<b>⋈</b> -methyl-2-pyrrolidone	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
-methyl-2-pyrrolidone	-0.46	3.16	Low

#### Mobility in soil

Product name 70-320 MANOR HALL PAINT/PRIMER IN ONE EXTERIOR EGGSHELL-MIDTONE BASE

### Section 12. Ecological information

Soil/water partition coefficient (Koc)

: Not available.

### Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

### Section 14. Transport information

	TDG	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### Additional information

- : None identified. TDG
- : None identified. IMDG

ΙΑΤΑ : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Date of issue 3 September 2023 Version 11.01

#### Product name 70-320 MANOR HALL PAINT/PRIMER IN ONE EXTERIOR EGGSHELL-MIDTONE BASE

### Section 15. Regulatory information

#### National Inventory List

Canada inventory (DSL)

: All components are listed or exempted.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 2 \* Flammability : 1 Physical hazards : 0 (\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

### The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health : 2 Flammabili	lity : 1 Instability : 0
Date of issue/Date of revision	3 September 2023
Organization that prepared : the SDS	EHS
Key to abbreviations       : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemica IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations	

#### Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.