SAFETY DATA SHEET



Date of issue/Date of revision18 September 2023Version 23

Section 1. Identification		
Product name	: 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE	
Product code	: 00410925	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	: Consumer applications, Professional applications.	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Not applicable.	
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272	
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)	
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)	

Section 2. Hazards identification

OSHA/HCS status	: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
Classification of the substance or mixture	: Not classified.
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 20% (oral), 23.4% (dermal), 20% (inhalation)
GHS label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statement	<u>S</u>
Prevention	: Not applicable.
Response	: Not applicable.

Date of issue 18 September 2023Version 23

Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

Section 2. Hazards identification

	Photosensitive agents : In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact. In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact.
Storage	: Not applicable.
Disposal	: Not applicable.
Supplemental label elements	: Contains isothiazolinones. May cause allergic reaction. Emits toxic fumes when heated.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

Ingredient name	%	CAS number
Kaolin	≥1.0 - ≤5.0	1332-58-7

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person. Description of necessary first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. Case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact.

Date of issue 18 September 2023Version 23

Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

Section 4. First aid measures

Ingestion

: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects	
Eye contact :	No known significant effects or critical hazards.
Inhalation	No known significant effects or critical hazards.
Skin contact :	No known significant effects or critical hazards.
Ingestion :	No known significant effects or critical hazards.
Over-exposure signs/sympton	<u>ns</u>
Eye contact :	No specific data.
Inhalation	No specific data.
Skin contact :	No specific data.
Ingestion :	No specific data.

Indication of immediate med	ical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing mediaSuitable extinguishing media: Use an extinguishing agent suitable for the surrounding fire.Unsuitable extinguishing media: None known.Specific hazards arising from the chemical: In a fire or if heated, a pressure increase will occur and the container may burst.Hazardous thermal decomposition products: Decomposition products may include the following materials: carbon oxidesSpecial protective actions for fire-fighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.Special protective equipment for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathir apparatus (SCBA) with a full face-piece operated in positive pressure mode.		
media Unsuitable extinguishing media: None known.Specific hazards arising from the chemical Hazardous thermal decomposition products: In a fire or if heated, a pressure increase will occur and the container may burst.Hazardous thermal decomposition products: Decomposition products may include the following materials: carbon oxidesSpecial protective actions for fire-fighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.Special protective: Fire-fighters should wear appropriate protective equipment and self-contained breathing	Extinguishing media	
mediaSpecific hazards arising from the chemical Hazardous thermal decomposition products: In a fire or if heated, a pressure increase will occur and the container may burst.Hazardous thermal decomposition products: Decomposition products may include the following materials: carbon oxidesSpecial protective actions for fire-fighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.Special protective: Fire-fighters should wear appropriate protective equipment and self-contained breathin	• •	: Use an extinguishing agent suitable for the surrounding fire.
from the chemical Hazardous thermal decomposition products: Decomposition products may include the following materials: carbon oxidesSpecial protective actions for fire-fighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.Special protective: Fire-fighters should wear appropriate protective equipment and self-contained breathin		: None known.
decomposition productscarbon oxidesSpecial protective actions for fire-fighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.Special protective: Fire-fighters should wear appropriate protective equipment and self-contained breathin	•	: In a fire or if heated, a pressure increase will occur and the container may burst.
for fire-fightersthere is a fire. No action shall be taken involving any personal risk or without suitable training.Special protective: Fire-fighters should wear appropriate protective equipment and self-contained breathir		
		there is a fire. No action shall be taken involving any personal risk or without suitable
		: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

Section 6. Accidental release measures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling		
Protective measures Special precautions	Put on appropriate personal protective equipment (see Section 8). If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.	
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.	
Conditions for safe storage, including any incompatibilities	Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.	

Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	E	posure limits	
Raolin		ACGIH TLV (United States, 1/2022). TWA: 2 mg/m ³ 8 hours. Form: Respirable fraction OSHA PEL (United States, 5/2018). TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction TWA: 15 mg/m ³ 8 hours. Form: Total dust	
	Key to abbreviations		
C = Ceiling Limit F = Fume IPEL = Internal Permissible Exp OSHA = Occupational Safety and R = Respirable	Governmental Industrial Hygienists. SR SS STE osure Limit TD Health Administration. TL\v 10 Subpart Z - Toxic and Hazardous Substances SI	 Skin sensitization Short term Exposure limit values Total dust Threshold Limit Value 	
		enitering standards. Defenses to notion.	
Recommended monitoring procedures	: Reference should be made to appropriate m guidance documents for methods for the def also be required.		
ppropriate engineering ontrols	: Good general ventilation should be sufficient contaminants.	to control worker exposure to airborne	
nvironmental exposure ontrols	: Emissions from ventilation or work process of they comply with the requirements of enviror cases, fume scrubbers, filters or engineering will be necessary to reduce emissions to acc	mental protection legislation. In some modifications to the process equipment	
dividual protection measur	<u>es</u>		
Hygiene measures	: Wash hands, forearms and face thoroughly eating, smoking and using the lavatory and a Appropriate techniques should be used to re Wash contaminated clothing before reusing. showers are close to the workstation location	at the end of the working period. move potentially contaminated clothing. Ensure that eyewash stations and safety	
Eye/face protection <u>Skin protection</u>	: Safety glasses with side shields.		
Hand protection	: Chemical-resistant, impervious gloves comp worn at all times when handling chemical pro necessary.		
Gloves Body protection	 polyethylene Personal protective equipment for the body s performed and the risks involved and should handling this product. 		

Date of issue 18 September 2023Version 23

Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

Section 8. Exposure controls/personal protection

Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134.

Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	: Liqu	uid.
Color	: Var	ious
Odor	: Cha	aracteristic.
Odor threshold	• • • • • •	t available.
рН	: 8.6	
Melting point		t available.
Boiling point	: 100)°C (212°F)
Flash point	: Clo	sed cup: Not applicable. [Product does not sustain combustion.]
Auto-ignition temperature	: Not	t available.
Decomposition temperature	: Not	t available.
Flammability	: Not	t available.
Lower and upper explosive (flammable) limits	: Not	t available.
Evaporation rate	: 0.0	5 (butyl acetate = 1)
Vapor pressure	: 3.3	kPa (25 mm Hg)
Vapor density	: Not	t available.
Relative density	: 1.06	6
Density(lbs / gal)	: 8.8	5
	_	edia Result
Solubility(ies)	col	d water Soluble
Partition coefficient: n- octanol/water	: Not	t applicable.
Viscosity	: Kine	ematic (40°C (104°F)): >21 mm²/s (>21 cSt)
Volatility	: 77%	% (v/v), 72.628% (w/w)
% Solid. (w/w)	: 27.3	372

Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Kaolin	LC50 Inhalation Dusts and mists LD50 Oral	Rat Rat	>5.07 mg/l >5000 mg/kg	4 hours -
Conclusion/Summary	: There are no data available on the	he mixture itself.		
Irritation/Corrosion				
Conclusion/Summary				
Skin	: There are no data available on the	he mixture itself.		
Eyes	: There are no data available on the	he mixture itself.		
Respiratory	: There are no data available on the	he mixture itself.		
Sensitization				
Conclusion/Summary				
Skin	: There are no data available on the	he mixture itself.		
Respiratory	: There are no data available on the	he mixture itself.		
<u>Mutagenicity</u>				
Conclusion/Summary	: There are no data available on the	he mixture itself.		
Carcinogenicity				
Conclusion/Summary	: There are no data available on the	he mixture itself.		
Reproductive toxicity				
Conclusion/Summary	: There are no data available on th	e mixture itself.		
<u>Feratogenicity</u>				
Conclusion/Summary	: There are no data available on th	e mixture itself.		
Specific target organ toxicit	ty (single exposure)			
Not available.				

Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

Section 11. Toxicological information

Specific target organ toxic	ity (repeated exposure)
Not available.	
<u>Target organs</u>	: Contains material which causes damage to the following organs: eyes. Contains material which may cause damage to the following organs: lungs, upper respiratory tract, stomach.
Aspiration hazard	
Not available.	
Information on the likely rou	ites of exposure
Potential acute health effect	<u>ets</u>
Eye contact Inhalation Skin contact Ingestion	 No known significant effects or critical hazards.
Over-exposure signs/symp	<u>itoms</u>
Eye contact Inhalation Skin contact Ingestion <u>Delayed and immediate effer</u> Conclusion/Summary	 No specific data. Cts and also chronic effects from short and long term exposure There are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure
<u>Short term exposure</u> Potential immediate	by oral, inhalation and dermal routes of exposure and eye contact. There are no data available on the mixture itself.
effects Potential delayed effects	: There are no data available on the mixture itself.
Long term exposure Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects Potential chronic health eff	: There are no data available on the mixture itself. fects
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Date of issue 18 September 2023Version 23

Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

Section 11. Toxicological information

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

	DOT	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
	<u>.</u>		United States Page: 9/11

14. Transport information

Date of issue 18 September 2023Version 23

Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

14. Transport information

Marine pollutant No	ot applicable.	Not applicable.	Not applicable.
substances			

Additional information

DOT	: None identified.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are active or exempted.

: Not applicable.

United States - TSCA 5(a)2 - Proposed significant new use rules:		
2(2H)-Isothiazolone, 2-methyl-	Listed	P-96-1250
5-chloro-2-methyl-2H-isothiazol-3-one	Listed	P-96-1251
0.4.5.4.000/00.4		

<u>SARA 302/304</u>

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification

Composition/information on ingredients

No products were found.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 2 Flammability : 0 Physical hazards : 0 (*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

United States Page: 10/11

Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

Section 16. Other information

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health : 🔽 Flammab	pility : 0 Instability : 0
Date of previous issue	: 8/21/2023
Organization that prepared the SDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.