# **SAFETY DATA SHEET**



### The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 24 April 2024 Version 16

Section 1. Identification		
Product name	: 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE	
Product code	: 00410925	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	: Consumer applications, Professional applications.	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Not applicable.	
Supplier	<ul> <li>PPG Architectural Coatings Canada, Inc. 1550, rue Ampère, bureau 500 Boucherville (Québec) J4B 7L4 Canada +1 450-655-3121</li> </ul>	
	PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272	
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)	
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)	

# Section 2. Hazard identification

l word. n significant effects or critical hazards.
n significant effects or critical hazards.
el before use. Keep out of reach of children. If medical advice is needed, duct container or label at hand.
cable.
cable.
i

### Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

### Section 2. Hazard identification

	Photosensitive agents : In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact. In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact.
Storage	: Not applicable.
Disposal	: Not applicable.
Supplemental label elements	<ul> <li>Contains isothiazolinones. May cause allergic reaction. Emits toxic fumes when heated.</li> </ul>
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 20% (oral), 23.4% (dermal), 20% (inhalation)

### Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE
Other means of identification	: Not available.

### **CAS number/other identifiers**

Ingredient name	Synonyms	% (w/w)	CAS number
Kaolin	Argilla; Porcelain clay; Hydrite; Hydrated aluminum silicate; Clay; China clay; μ- [1,3-dioxodisiloxane-1,3-diolato(2-)-κO1: κO3](dioxo)dialuminum dihydrate; E 559; kaolin; China clay; aluminium silicate, hydrated; oxo-oxoalumanyloxy-[oxo (oxoalumanyloxy)silyl]oxysilane dihydrate; Clay (kaolin); KAOLIN DUST	1 - 5*	1332-58-7

\*Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

### Description of necessary first aid measures

Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> <li>In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact.</li> </ul>
-------------	---

Version 16

### Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

# Section 4. First-aid measures

Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after</li> </ul>
Ingestion	<ul> <li>contact.</li> <li>If swallowed, seek medical advice immediately and show this container or label.</li> <li>Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>
Most important symptoms/e	ffects, acute and delayed
Potential acute health effect	<u>ets</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symp	i <u>toms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate med	lical attention and special treatment needed, if necessary

indication of infinediate medical attention and special freatment needed, in necessary	
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

### Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

# Section 5. Fire-fighting measures

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

Personal precautions, protect	<u>tiv</u>	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Special precautions	<ul> <li>If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.</li> </ul>
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

# Section 7. Handling and storage

Conditions for safe storage,	: Do not store below the following temperature: 5°C (41°F). Store in accordance with
including any	local regulations. Store in original container protected from direct sunlight in a dry,
incompatibilities	cool and well-ventilated area, away from incompatible materials (see Section 10)
	and food and drink. Keep container tightly closed and sealed until ready for use.
	Containers that have been opened must be carefully resealed and kept upright to
	prevent leakage. Do not store in unlabeled containers. Use appropriate
	containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

### **Control parameters**

<b>Occu</b>	pationa	l exposure	<u>limits</u>

Ingredient name	Exposure limits
Kaolin	CA Alberta Provincial (Canada, 6/2018).
	OEL: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable
	CA British Columbia Provincial (Canada,
	6/2022).
	TWA: 2 mg/m³ 8 hours. Form: Respirable
	CA Quebec Provincial (Canada, 6/2022).
	TWAEV: 2 mg/m <sup>3</sup> 8 hours. Form:
	Respirable dust.
	CA Ontario Provincial (Canada, 6/2019).
	TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable
	particulate matter.
	CA Saskatchewan Provincial (Canada,
	7/2013).
	STEL: 4 mg/m <sup>3</sup> 15 minutes. Form:
	respirable fraction
	TWA: 2 mg/m³ 8 hours. Form: respirable
	fraction

### Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures		Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	es	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	1	Safety glasses with side shields.
Skin protection		

# Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

# Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Gloves	: polyethylene
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# Section 9. Physical and chemical properties

<u>Appearance</u>			
Physical state		Liquid.	
Color	4	Various	
Odor	:	Characteristic.	
Odor threshold	1	Not available.	
рН	÷	8.6	
Melting point	4	Not available.	
Boiling point	1	100°C (212°F)	
Flash point	1	Closed cup: Not applicable. [Produc	t does not sustain combustion.]
Auto-ignition temperature	:	Not available.	
Decomposition temperature	1	Not available.	
Flammability	:	Not available.	
Lower and upper explosive (flammable) limits	:	Not available.	
Evaporation rate	1	0.05 (butyl acetate = 1)	
Vapor pressure	:	3.3 kPa (25 mm Hg)	
Vapor density	:	Not available.	
Relative density	:	1.06	
Density(lbs / gal)	:	8.85	
Solubility(ies)		Media Result	
	1	cold water Soluble	
Partition coefficient: n- octanol/water	:	Not applicable.	
Viscosity	:	Kinematic (40°C (104°F)): >21 mm <sup>2</sup>	/s (>21 cSt)
Volatility	:	7% (v/v), 72.556% (w/w)	
% Solid. (w/w)	:	27.444	

Version 16

Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

# Section 10. Stability and reactivity

	5
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides

# Section 11. Toxicological information

### Information on toxicological effects

Acute toxicity				
Product/ingredient name	Result	Species	Dose	Exposure
Kaolin	LC50 Inhalation Dusts and mists LD50 Oral	Rat Rat	>5.07 mg/l >5000 mg/kg	4 hours -
Conclusion/Summary	: There are no data available on	the mixture i	tself.	
rritation/Corrosion				
Conclusion/Summary				
Skin	: There are no data available on	the mixture i	tself.	
Eyes	: There are no data available on	the mixture in	tself.	
Respiratory	: There are no data available on	the mixture i	tself.	
Sensitization				
Skin	: There are no data available on	the mixture i	tself.	
Respiratory	: There are no data available on	the mixture it	tself.	
<u>Mutagenicity</u>				
Conclusion/Summary	: There are no data available on	the mixture i	tself.	
Carcinogenicity				
Conclusion/Summary	: There are no data available on	the mixture in	tself.	
Reproductive toxicity				
Conclusion/Summary	: There are no data available on	the mixture in	tself.	
Teratogenicity				
Conclusion/Summary	: There are no data available on	the mixture i	tself.	
Specific target organ toxici	<u>ty (single exposure)</u>			
Not available.				
On a sifin town at a way to sign				
Specific target organ toxici	ity (repeated exposure)			
Not available.				

### Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

# Section 11. Toxicological information

### Target organs

: Contains material which causes damage to the following organs: eyes. Contains material which may cause damage to the following organs: lungs, upper respiratory tract, stomach.

#### **Aspiration hazard**

Not available.

#### Information on the likely routes of exposure

#### Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Over-exposure signs/symp	<u>toms</u>	
Eve contact	: No specific data	

	• • • • • • • • • • • • • • • • • • • •
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary	:	There are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
<u>Short term exposure</u>		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
Long term exposure		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
Potential chronic health effe	ect	<u>S</u>

General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Version 16

Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

### Section 11. Toxicological information

# Section 12. Ecological information

**Toxicity** 

Not available.

### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

# Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

# Section 14. Transport information

	TDG	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
I		I	Canada Page: 9/11

Date of issue 24 April 2024

Version 16

Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

### Section 14. Transport information

Marine pollutant	Not applicable.	Not applicable.	Not applicable.
substances			

### **Additional information**

- **TDG** : None identified.
- **IMDG** : None identified.
- IATA : None identified.

**Special precautions for user : Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

# Section 15. Regulatory information

### National Inventory List

Canada inventory (DSL)

: At least one component is not listed.

### Section 16. Other information

#### Hazardous Material Information System (U.S.A.)

Health : 2 Flammability : 0 Physical hazards : 0

(\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Asso Health : 2 Flammab	ciation (U.S.A.) vility : 0 Instability : 0
Date of issue/Date of revision	24 April 2024
Organization that prepared the SDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

#### Indicates information that has changed from previously issued version.

### Product name 6-8527 SPEEDHIDE LATEX ENAMEL INT/EXT SEMI-GLOSS-NEUTRAL BASE

### Section 16. Other information

### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.