# **SAFETY DATA SHEET**



Date of issue/Date of revision15 August 2022Version 11

Section 1. Identification		
Product name	: 79070 OLYMPIC WOOD PROTECTOR WATERPROOFING SEALANT D/F/S-CLEAR	
Product code	: 00411938	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	: 🖉 onsumer applications, Professional applications, Used by spraying.	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Not applicable.	
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272	
<u>Emergency telephone</u> number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)	
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)	

# Section 2. Hazards identification

OSHA/HCS status	<ul> <li>This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).</li> </ul>
Classification of the substance or mixture	: CARCINOGENICITY - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 13.5% (oral), 13.5% (dermal), 13.5% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: Suspected of causing cancer.
Precautionary statements	

Product name 79070 OLYMPIC WOOD PROTECTOR WATERPROOFING SEALANT D/F/S-CLEAR

### Section 2. Hazards identification

Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.
Response	: IF exposed or concerned: Get medical advice or attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Contains isothiazolinones. May cause allergic reaction. Sanding and grinding dusts may be harmful if inhaled. Emits toxic fumes when heated. DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.
Hazards not otherwise classified	: None known.

### Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: 79070 OLYMPIC WOOD PROTECTOR WATERPROOFING SEALANT D/F/S-CLEAR

Ingredient name	%	CAS number
2-butanone oxime	<1.0	96-29-7

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

### Description of necessary first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	<ul> <li>If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>

#### Most important symptoms/effects, acute and delayed

Product name 79070 OLYMPIC WOOD PROTECTOR WATERPROOFING SEALANT D/F/S-CLEAR

# Section 4. First aid measures

### Potential acute health effects

Eye contact Inhalation Skin contact Ingestion Over-exposure signs/symp	<ul> <li>No known significant effects or critical hazards.</li> </ul>
Eye contact Inhalation Skin contact Ingestion	<ul> <li>No specific data.</li> <li>No specific data.</li> <li>No specific data.</li> <li>No specific data.</li> </ul>
Indication of immediate me	lical attention and special treatment needed, if necessary
Notes to physician Specific treatments	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> <li>No specific treatment.</li> </ul>
Protection of first-aiders	<ul> <li>No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.</li> </ul>

### See toxicological information (Section 11)

### Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: No specific data.
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency	: No action shall be taken involving any personal risk or without suitable training.
personnel	Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is
	inadequate. Put on appropriate personal protective equipment.

Product name 79070 OLYMPIC WOOD PROTECTOR WATERPROOFING SEALANT D/F/S-CLEAR

# Section 6. Accidental release measures

For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	: Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Product name 79070 OLYMPIC WOOD PROTECTOR WATERPROOFING SEALANT D/F/S-CLEAR

# Section 7. Handling and storage

Conditions for safe storage,	: Do not store below the following temperature: 5°C (41°F). Store in accordance with
including any	local regulations. Store in original container protected from direct sunlight in a dry, cool
incompatibilities	and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits	
₽-butanone oxime	IPEL (-). TWA: 3 ppm STEL: 9 ppm	
Key to abbreviations		

А	= Acceptable Maximum Peak	S	<ul> <li>Potential skin absorption</li> </ul>
ACGIH	<ul> <li>American Conference of Governmental Industrial Hygienists.</li> </ul>	SR	<ul> <li>Respiratory sensitization</li> </ul>
С	= Ceiling Limit	SS	<ul> <li>Skin sensitization</li> </ul>
F	= Fume	STEL	<ul> <li>Short term Exposure limit values</li> </ul>
IPEL	= Internal Permissible Exposure Limit	TD	= Total dust
OSHA	<ul> <li>Occupational Safety and Health Administration.</li> </ul>	TLV	= Threshold Limit Value
R	= Respirable	TWA	<ul> <li>Time Weighted Average</li> </ul>
-			

Z = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

#### Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	es	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety glasses with side shields.
Skin protection		

Product name 79070 OLYMPIC WOOD PROTECTOR WATERPROOFING SEALANT D/F/S-CLEAR

# Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134.

# Section 9. Physical and chemical properties

Physical state:Liquid.Color:Not available.Odor:Characteristic.Odor threshold:Not available.pH:Not available.Melting point:Not available.Boiling point:100°C (212°F)Flash point:Closed cup: Not applicable. [Product does not sustain combustion.]Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:1.01Density (1bs / gal):8.43Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not available.	Appearance		
Odor:Characteristic.Odor threshold:Not available.pH:Not available.Melting point:Not available.Boiling point:100°C (212°F)Flash point:Closed cup: Not applicable. [Product does not sustain combustion.]Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Flammability (solid, gas):Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:1.01Density (lbs / gal):8.43Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not applicable.	Physical state	1	Liquid.
Odor threshold: Not available.pH: Not available.Melting point: Not available.Boiling point: 100°C (212°F)Flash point: Closed cup: Not applicable. [Product does not sustain combustion.]Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive: Not available.(flammable) limits: Not available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.01Density (lbs / gal): 8.43Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.	Color	1	Not available.
pH:Not available.Melting point:Not available.Boiling point:100°C (212°F)Flash point:Closed cup: Not applicable. [Product does not sustain combustion.]Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Clower and upper explosive (flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:1.01Density (lbs / gal):Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not applicable.	Odor	1	Characteristic.
Melting point:Not available.Boiling point:100°C (212°F)Flash point:Closed cup: Not applicable. [Product does not sustain combustion.]Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability (solid, gas):Not available.Flammability (solid, gas):Not available.Lower and upper explosive (flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:1.01Density ( lbs / gal ):8.43Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not applicable.	Odor threshold	1	Not available.
Boiling point: 100°C (212°F)Flash point: Closed cup: Not applicable. [Product does not sustain combustion.]Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Not available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.01Density (lbs / gal): 8.43Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.	рН	4	Not available.
Flash point: Closed cup: Not applicable. [Product does not sustain combustion.]Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Not available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.01Density (lbs / gal): 8.43Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.	Melting point	1	Not available.
Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Not available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.01Density ( lbs / gal ): 8.43Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.	Boiling point	1	100°C (212°F)
Decomposition temperature: Not available.Flammability (solid, gas): Not available.Lower and upper explosive: Not available.(flammable) limits: Not available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.01Density ( lbs / gal ): 8.43Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.	Flash point	1	Closed cup: Not applicable. [Product does not sustain combustion.]
Flammability (solid, gas): Not available.Lower and upper explosive (flammable) limits: Not available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.01Density (lbs / gal): 8.43Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.	Auto-ignition temperature	1	Not available.
Lower and upper explosive (flammable) limits: Not available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.01Density ( lbs / gal ): 8.43Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.	Decomposition temperature	:	Not available.
(flammable) limitsEvaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.01Density ( lbs / gal ): 8.43Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.	Flammability (solid, gas)	:	Not available.
Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.01Density ( lbs / gal ): 8.43Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.		:	Not available.
Vapor density: Not available.Relative density: 1.01Density ( lbs / gal ): 8.43Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.	Evaporation rate	1	Not available.
Relative density: 1.01Density ( lbs / gal ): 8.43Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.	Vapor pressure	1	Not available.
Density ( lbs / gal ): 8.43Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.	Vapor density	:	Not available.
Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.	Relative density	:	1.01
Partition coefficient: n- : Not applicable. octanol/water	Density(Ibs / gal)	1	8.43
octanol/water	Solubility	1	Soluble in the following materials: cold water.
Viscosity : Kinematic $(40^{\circ}C, (104^{\circ}F))$ ; <14 mm <sup>2</sup> /s (<14 cSt)		:	Not applicable.
	Viscosity	:	Kinematic (40°C (104°F)): <14 mm²/s (<14 cSt)
Volatility : 85% (v/v), 84.131% (w/w)	Volatility	1	85% (v/v), 84.131% (w/w)

#### Date of issue 15 August 2022 Version 11

Product name 79070 OLYMPIC WOOD PROTECTOR WATERPROOFING SEALANT D/F/S-CLEAR

### Section 9. Physical and chemical properties

% Solid. (w/w)

: 15.869

Section 1	10.	Stability	and	reactivity
-----------	-----	-----------	-----	------------

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-butanone oxime	LD50 Dermal	Rabbit	1100 mg/kg	-
	LD50 Oral	Rat	100 mg/kg	-
Conclusion/Summary	: There are no data available of	on the mixture itse	lf.	
Irritation/Corrosion				
Conclusion/Summary				
Skin	: There are no data available of	on the mixture itse	lf.	
Eyes	: There are no data available of	on the mixture itse	lf.	
Respiratory	: There are no data available of	on the mixture itse	lf.	
Sensitization				
Conclusion/Summary				
Skin	: There are no data available of	on the mixture itse	lf.	
Respiratory	: There are no data available of	on the mixture itse	lf.	
<u>Mutagenicity</u>				
Conclusion/Summary	: There are no data available of	on the mixture itse	lf.	
Carcinogenicity				
Conclusion/Summary	: There are no data available of	on the mixture itse	lf.	
Reproductive toxicity				
Conclusion/Summary	: There are no data available o	n the mixture itself	F.	
<b>Feratogenicity</b>				

Product name 79070 OLYMPIC WOOD PROTECTOR WATERPROOFING SEALANT D/F/S-CLEAR

# Section 11. Toxicological information

Conclusion/Summary	: There are no data available on the mixture itself.
Specific target organ toxici	<u>ty (single exposure)</u>
Not available.	
Specific target organ toxici	t <u>y (repeated exposure)</u>
Not available.	
Aspiration hazard	
Not available.	
Information on the likely rou	tes of exposure
Potential acute health effect	<u>its</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symp	<u>toms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate effect	<u>cts and also chronic effects from short and long term exposure</u>
Conclusion/Summary	: There are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
<u>Short term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Long term exposure	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health eff	ects
General	No known significant effects or critical hazards.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of
ourchiogenicity	exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
Numerical measures of toxic	<u>sity</u>
Acute toxicity estimates	

Product name 79070 OLYMPIC WOOD PROTECTOR WATERPROOFING SEALANT D/F/S-CLEAR

# Section 11. Toxicological information

Product/ingredient name				(vapors)	Inhalation (dusts and mists) (mg/ I)
₽ butanone oxime	500	1100	N/A	N/A	N/A

# Section 12. Ecological information

### **Toxicity**

Not available.

### Persistence and degradability

Not available.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
-butanone oxime	0.63	5.01	low

### Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

# Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains
	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Product name 79070 OLYMPIC WOOD PROTECTOR WATERPROOFING SEALANT D/F/S-CLEAR

### 14. Transport information

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### Additional information

DOT: None identified.IMDG: None identified.IATA: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable.

### to IMO instruments

### Section 15. Regulatory information

#### United States

United States inventory (TSCA 8b) : All components are active or exempted.

United States - TSCA 5( ≸-chloro-2-methyl-2H-iso 3(2H)-Isothiazolone, 2-m		Listed Listed	P-96-1251 P-96-1250	
<u>SARA 302/304</u>				
SARA 304 RQ	: Not applicable.			
Composition/informatio	<u>n on ingredients</u>			
No products were found.				
<u>SARA 311/312</u>				
Classification	: CARCINOGENICITY - Category 2			
Composition/information on ingredients				

Date of issue 15 August 2022 Version 11

Product name 79070 OLYMPIC WOOD PROTECTOR WATERPROOFING SEALANT D/F/S-CLEAR

# Section 15. Regulatory information

Name	%	Classification
₽-butanone oxime		FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1B CARCINOGENICITY - Category 2

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

# Section 16. Other information

#### Hazardous Material Information System (U.S.A.)

Health : 2 \* Flammability : 0 Physical hazards : 0 (\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Ass	sociation (U.S.A.)		
Health : 2 Flamma	ability : 0 Instability : 0		
Date of previous issue	: 12/13/2021		
Organization that prepared the SDS	: EHS		
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations		

### Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.