SAFETY DATA SHEET

Europe



Date of issue/Date of revision

: 5 May 2024

Version : 1.01

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: PINJA COLOR OIL
Product code	: SDS-439-s

Other means of identification

SKU-43900000170T; SKU-43900700170

1.2 Relevant identified uses of the substance or mixture and uses advised against				
Product use	: Industrial applications, Used by spraying.			
Use of the substance/ mixture	: Coating.			
Uses advised against	: Product is not intended, labelled or packaged for consumer use.			

1.3 Details of the supplier of the safety data sheet

Tikkurila Ovj P.O. Box 53 FI-01301 VANTAA **FINLAND** Tel. +358 20 191 2000

e-mail address of person

: Product.Stewardship.EMEA@ppg.com

responsible for this SDS

1.4 Emergency telephone number

Supplier

Tikkurila Oyi +358 20 191 2000 (GMT +2) Mon-Fri 8-16

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word

: No signal word.

English (GB)

Code : SDS-439-s PINJA COLOR OIL	Date of issue/Date of revision : 5 May 2024
SECTION 2: Hazards	identification
Hazard statements	: Harmful to aquatic life with long lasting effects.
Prevention	: Avoid release to the environment.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations. P273, P501
Hazardous ingredients	: Not applicable.
Supplemental label elements	: Contains 3-iodo-2-propynyl butylcarbamate and 2-hydroxyethyl methacrylate. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirem	<u>ients</u>
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria	: This mixture does not contain any substances that are assessed to be a PBT or a vPy

Product meets the criteria : This mixture does not contain any substances that are assessed to be a PBT or a vPvB. for PBT or vPvB

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
ୈiodo-2-propynyl butylcarbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	<1.0	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 1470 mg/ kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10 M [Chronic] = 1	[1]
ammonium hydroxide	REACH #: 01-2119488876-14 EC: 215-647-6 CAS: 1336-21-6 Index: 007-001-01-2	≤0.30	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400	STOT SE 3, H335: C ≥ 5% M [Acute] = 1	[1] [2]
2-hydroxyethyl methacrylate	EC: 212-782-2	≤0.30	Skin Irrit. 2, H315	-	[1] [2]
English (GB)			Europe		2/14

Code : SDS-439-s PINJA COLOR OIL	Date of issue/Date of revision	:5 May 2024	
SECTION 3: Composition/informa	ation on ingredients		
CAS: 868-77-9 Index: 607-124-00->	K Eye Irrit. 2, H319 Skin Sens. 1, H317 See Section 16 for		

	the full text of the H statements declared above.		
	See Section 16 for		l

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. **Skin contact** : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards. Over-exposure signs/symptoms **Eve contact** : No specific data. Inhalation : No specific data. **Skin contact** : No specific data. Ingestion : No specific data. 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

- **Specific treatments**
- : No specific treatment.

Code	: SDS-439-s	Date of issue/Date of revision	: 5 May 2024	
PINJA CO	LOR OIL			

SECTION 5: Firefighting measures

•	
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising fi	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides
5.3 Advice for firefighters	
Special precautions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.

English (GB)	Europe	4/14
5 - (-)		

	Code : SDS	S-439-s	Date of issue/Date of revision	: 5 May 2024
PINJA COLOR OIL	PINJA COLOR OIL	L		

SECTION 6: Accidental release measures

6.4 Reference to other	: See Section 1 for emergency contact information.
sections	See Section 8 for information on appropriate personal protective equipment.
	See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
	Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
ammonium hydroxide	EU OEL (Europe, 1/2022). [ammonia, anhydrous] TWA: 20 ppm 8 hours. TWA: 14 mg/m ³ 8 hours. STEL: 50 ppm 15 minutes. STEL: 36 mg/m ³ 15 minutes.
2-hydroxyethyl methacrylate	IPEL (-, 10/2017). Absorbed through skin. TWA: 1 ppm STEL: 3 ppm

English (GB) Europe 5/14	Europe	5/14
--------------------------	--------	------

С	ode :	SDS-439-s	Date of issue/Date of revision	: 5 May 2024
Ρ	VINJA COLOR	ROIL		

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures	: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General
	requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
	DNEL	Long term Inhalation	0.023 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	0.07 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	1.16 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	1.16 mg/m ³	Workers	Local
	DNEL	Long term Dermal	2 mg/kg bw/day	Workers	Systemic
2-hydroxyethyl methacrylate	DNEL	Long term Oral	0.83 mg/kg bw/day	General population	
	DNEL	Long term Dermal	0.83 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1.39 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.45 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	4.9 mg/m ³	Workers	Systemic

PNECs

PNECs - Not available.

8.2 Exposure controls

Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection measured	es	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety glasses with side shields. Use eye protection according to EN 166.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Gloves	:	nitrile rubber, butyl rubber, PVC, Viton®

English (GB) Europe 0/14	English (GB)	Europe	6/14
--------------------------	--------------	--------	------

SECTION 8: Exposure contr	ale/nergenel protection	
PINJA COLOR OIL		
Code : SDS-439-s	Date of issue/Date of revision	: 5 May 2024

SECTION 8: Exposure controls/personal protection

Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection		Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance		
Physical state	Liquid.	
Colour	Clear.	
Odour	Chlorinated hydrocarbon odour.	
Odour threshold	Not available.	
Melting point/freezing point	May start to solidify at the following temperature: 0°C (32°F) This is based on for the following ingredient: water.	data
Initial boiling point and boiling range	>37.78°C	
Flammability	Not available.	
Upper/lower flammability or explosive limits	Not available.	
Flash point	Closed cup: Not applicable.	
Auto-ignition temperature	Not available.	
Decomposition temperature	Stable under recommended storage and handling conditions (see Section 7).	
рН	6 to 9	
Viscosity	Kinematic (40°C): >21 mm²/s	
Solubility(ies)		
Media	Result	
cold water	Partially soluble	
Partition coefficient: n-octano water	Not applicable.	
Vapour pressure		

Code	: SDS-439-s	Date of issue/Date of revision	: 5 May 2024
PINJA COLC	DR OIL		

SECTION 9: Physical and chemical properties

			Vapour Pressure at 20°C			Vap	Vapour pressure at 50°C	
		Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
		water	17.5	2.3				
Evaporation rate	:	Not available.						
Relative density	:	1						
Explosive properties	:	The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.						
Oxidising properties	:	Product does not pre	esent an o	oxidizing	hazard.			
Particle characteristics								
Median particle size	:	Not applicable.						
9.2 Other information								
No odditional information								

No additional information.

SECTION 10: Stability and reactivity					
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.				
10.2 Chemical stability	: The product is stable.				
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.				
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition product Refer to protective measures listed in sections 7 and 8.				
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.				
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials carbon oxides				

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
3-iodo-2-propynyl butylcarbamate	LC50 Inhalation Dusts and mists	Rat	0.67 mg/l	4 hours
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	1470 mg/kg	-
ammonium hydroxide	LD50 Oral	Rat	350 mg/kg	-
2-hydroxyethyl methacrylate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	5050 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

Route	ATE value
Inhalation (dusts and mists)	83.62 mg/l
	0/44

Code : SDS-439-s PINJA COLOR OIL Date of issue/Date of revision

: 5 May 2024

SECTION 11: Toxicological information

Irritation/Corrosion

Product/ingredien	it name	Result	Species	Score	Exposure	Observation
3-iodo-2-propynyl butylcarl		Eyes - Severe irritant	Rabbit			-
Conclusion/Summary		I				
Skin	: There are	no data available on the	mixture itself			
Eyes	: There are	no data available on the	mixture itself			
Respiratory	: There are	no data available on the	mixture itself			
Sensitisation						
Conclusion/Summary						
Skin	: There are	e no data available on the	e mixture itsel	f.		
Respiratory	: There are	e no data available on the	e mixture itsel	f.		
Mutagenicity						
Conclusion/Summary	: There are	e no data available on the	e mixture itsel	f.		
Carcinogenicity						
Conclusion/Summary	: There are	e no data available on the	e mixture itsel	f.		
Reproductive toxicity						
Conclusion/Summary	: There are	e no data available on the	e mixture itsel	f.		
Teratogenicity						
Conclusion/Summary	: There are	e no data available on the	e mixture itsel	f.		
Specific target organ toxi	i <mark>city (single exp</mark>	<u>oosure)</u>				

Product/ingredient name	Category	Route of exposure	Target organs
ammonium hydroxide	Category 3	-	Respiratory tract irritation
3-iodo-2-propynyl butylcarbamate	Category 1	-	larynx

Information on likely routes of exposure	:	Not available.
Potential acute health effect	s	
Inhalation	1	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Eye contact	:	No known significant effects or critical hazards.
Symptoms related to the ph	ys	ical, chemical and toxicological characteristics
Inhalation	:	No specific data.
Ingestion	:	No specific data.
Skin contact	:	No specific data.
Eye contact	:	No specific data.
Delayed and immediate effe	cts	s as well as chronic effects from short and long-term exposure
Short term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		

Code : SDS	S-439-s	Date of issue/Date of revision	: 5 May 2024
PINJA COLOR OIL			

SECTION 11: Toxicological information

Potential immediate	: Not available.
effects	

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General

: No known significant effects or critical hazards.

Carcinogenicity

Conclusion/Summary

- No known significant effects or critical hazards.No known significant effects or critical hazards.
- Mutagenicity Reproductive toxicity
 - : No known significant effects or critical hazards.
- Other information : Not available.

None known.

11.2 Information on other hazards

- 11.2.1 Endocrine disrupting properties
- Not available.
- **11.2.2 Other information**

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
3-iodo-2-propynyl butylcarbamate	Acute EC50 0.186 mg/l Fresh water Acute LC50 0.067 mg/l Chronic NOEC 0.049 mg/l	Daphnia - <i>Daphnia magna</i> Fish Fish	48 hours 96 hours 96 hours

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
3-iodo-2-propynyl butylcarbamate	-	25 % - Inherent - 28 days	-	-
Conclusion/Summary : There are no data available on the mixture itself				

Conclusion/Summary : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
3-iodo-2-propynyl butylcarbamate	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-hydroxyethyl methacrylate	0.42	-	Low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

English (GB) Europe 10/14

Code	: SDS-439-s	Date of issue/Date of revision	: 5 May 2024
PINJA COLO			

SECTION 12: Ecological information

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
Packaging	-

ackaging

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.		
Type of packaging		European waste catalogue (EWC)	
Container	15 01 04 metallic packaging		
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out		

Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
English (GB)				11/14

Code : SDS-439-s PINJA COLOR OIL	Date of issue/Date of revision	: 5 May 2024
14. Transport information		

14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional inf	ormation
ADR/RID	: None identified.
ADN	: The product is only regulated as a dangerous good when transported in tank vessels.
IMDG	: None identified.
ΙΑΤΑ	: None identified.
14.6 Special µ user	brecautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
447 Moritimo	fremenent in

 14.7 Maritime transport in
 : Not applicable.

 bulk according to IMO
 instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Explosive precursors	: Not applicable.
Ozone depleting substance Not listed.	<u>⊧s (1005/2009/EU)</u>
VOC for Ready-for-Use Mixture	 IIA/e. Interior/exterior trim varnishes and woodstains, including opaque woodstains. EU limit values: 130 g/l (2010.) This product contains a maximum of 130 g/l VOC.

Seveso Directive

This product is not controlled under the Seveso Directive.

Code	: SDS-439-s	Date of issue/Date of revision	: 5 May 2024	
PINJA C				

SECTION 15: Regulatory information

15.2 Chemical safety assessment

: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

Full text of abbreviated H statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE -
	Category 1
STOT SE 3	SPEČIFÍC TARGET ORGAN TOXICITY - SINGLE EXPOSURE -
	Category 3

<u>History</u>

Date of issue/ Date of revision	: 5 May 2024
Date of previous issue	: 12 January 2024
Prepared by	: EHS

English (GB)

Conforms to Regulation (EC) No. 1907/2006 (RE 2020/878	ACH), Annex II, as amended by Comr	nission Regulation (EU)
Code : SDS-439-s PINJA COLOR OIL	Date of issue/Date of revision	: 5 May 2024
SECTION 16: Other information		

Version

: 1.01

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.