

# SAFETY DATA SHEET



Date of issue/Date of revision : 28 March 2024 Version : 1.02

SECTION 1: Identification of the substance/mixture and of the company/  
undertaking

1.1 Product identifier

Product name : FONTECRYL SC-MR 10  
Product code : SDS-FI60010S  
Other means of identification  
SKU-710009737; SKU-710009737T; SKU-710009738; SKU-710013677; SKU-710013677T; SKU-710017632; SKU-710017683

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications, Professional applications, Used by spraying.  
Use of the substance/  
mixture : Coating.  
Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

Tikkurila Oyj  
P.O. Box 53  
FI-01301 VANTAA  
FINLAND  
Tel. +358 20 191 2000

e-mail address of person : Product.Stewardship.EMEA@ppg.com  
responsible for this SDS

1.4 Emergency telephone number

Supplier

Tikkurila Oyj  
+358 20 191 2000 (GMT +2) Mon-Fri 8-16

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture  
Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]  
Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.  
See Section 16 for the full text of the H statements declared above.  
See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

|                    |                |                                |                 |
|--------------------|----------------|--------------------------------|-----------------|
| Code               | : SDS-FI60010S | Date of issue/Date of revision | : 28 March 2024 |
| FONTECRYL SC-MR 10 |                |                                |                 |

SECTION 2: Hazards identification

|  |   |
|--|---|
| Signal word  | : No signal word.   |
| Hazard statements  | : Harmful to aquatic life with long lasting effects.  |
| Prevention   | : Avoid release to the environment.   |
| Response   | : Not applicable.   |
| Storage  | : Not applicable.   |
| Disposal   | : Dispose of contents and container in accordance with all local, regional, national and international regulations.<br>P273, P501   |
| Hazardous ingredients  | : Not applicable.   |
| Supplemental label elements  | : Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol, 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : Not applicable.   |
| Special packaging requirements   |   |
| Containers to be fitted with child-resistant fastenings  | : Not applicable.   |
| Tactile warning of danger  | : Not applicable.   |

2.3 Other hazards

|   |   |
|---|---|
| Product meets the criteria for PBT or vPvB          | : This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do not result in classification | : None known.   |

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name     | Identifiers  | % by weight  | Classification  | Specific Conc. Limits, M-factors and ATEs                      | Type    |
|-----------------------------|--|--------------|---|--|---------|
| 2-butoxyethanol             | REACH #:<br>01-2119475108-36<br>EC: 203-905-0<br>CAS: 111-76-2<br>Index: 603-014-00-0  | ≥5.0 - <10   | Acute Tox. 4, H302<br>Acute Tox. 3, H331<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319 | ATE [Oral] = 1200 mg/kg<br>ATE [Inhalation (vapours)] = 3 mg/l | [1] [2] |
| trizinc bis(orthophosphate) | REACH #:<br>01-2119485044-40<br>EC: 231-944-3<br>CAS: 7779-90-0<br>Index: 030-011-00-6 | ≥0.10 - ≤2.1 | Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                                      | M [Acute] = 1<br>M [Chronic] = 1                               | [1]     |
| zinc oxide                  | REACH #:   | ≤0.37        | Aquatic Acute 1, H400   | M [Acute] = 1  | [1]     |

|                    |                |                                |                 |
|--------------------|----------------|--------------------------------|-----------------|
| Code               | : SDS-FI60010S | Date of issue/Date of revision | : 28 March 2024 |
| FONTECRYL SC-MR 10 |                |                                |                 |

SECTION 3: Composition/information on ingredients

|   |  |         |  |  |         |
|---|--|---------|--|--|---------|
| ammonium hydroxide  | 01-2119463881-32<br>EC: 215-222-5<br>CAS: 1314-13-2<br>Index: 030-013-00-7<br><br>REACH #:<br>01-2119488876-14<br>EC: 215-647-6<br>CAS: 1336-21-6<br>Index: 007-001-01-2 | ≤0.30   | Aquatic Chronic 1, H410<br><br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>STOT SE 3, H335<br>Aquatic Acute 1, H400   | M [Chronic] = 1<br><br>STOT SE 3, H335: C ≥ 5%<br>M [Acute] = 1  | [1] [2] |
| 2,4,7,9-tetramethyldec-5-yne-4,7-diol   | REACH #:<br>01-2119954390-39<br>EC: 204-809-1<br>CAS: 126-86-3   | ≤0.30   | Eye Dam. 1, H318<br>Skin Sens. 1B, H317<br>Aquatic Chronic 3, H412   | -  | [1]     |
| 1,2-benzisothiazol-3(2H)-one  | EC: 220-120-9<br>CAS: 2634-33-5<br>Index: 613-088-00-6   | <0.050  | Acute Tox. 4, H302<br>Acute Tox. 2, H330<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 2, H411  | ATE [Oral] = 1020 mg/kg<br>ATE [Inhalation (dusts and mists)] = 0.4 mg/l<br>Skin Sens. 1, H317: C ≥ 0.05%<br>M [Acute] = 1   | [1]     |
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) | REACH #:<br>01-2120764691-48<br>EC: 911-418-6<br>CAS: 55965-84-9<br>Index: 613-167-00-5  | <0.0010 | Acute Tox. 3, H301<br>Acute Tox. 2, H310<br>Acute Tox. 2, H330<br>Skin Corr. 1C, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1A, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410<br>EUH071<br><br>See Section 16 for the full text of the H statements declared above. | ATE [Oral] = 53 mg/kg<br>ATE [Dermal] = 50 mg/kg<br>ATE [Inhalation (vapours)] = 0.5 mg/l<br>Skin Corr. 1C, H314: C ≥ 0.6%<br>Skin Irrit. 2, H315: 0.06% ≤ C < 0.6%<br>Eye Dam. 1, H318: C ≥ 0.6%<br>Eye Irrit. 2, H319: 0.06% ≤ C < 0.6%<br>Skin Sens. 1, H317: C ≥ 0.0015%<br>M [Acute] = 100<br>M [Chronic] = 100 | [1]     |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

|                    |                |                                |                 |
|--------------------|----------------|--------------------------------|-----------------|
| Code               | : SDS-FI60010S | Date of issue/Date of revision | : 28 March 2024 |
| FONTECRYL SC-MR 10 |                |                                |                 |

SECTION 4: First aid measures

4.1 Description of first aid measures

|                            |  |
|----------------------------|--|
| Eye contact                | : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.  |
| Inhalation                 | : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. |
| Skin contact               | : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.   |
| Ingestion                  | : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.   |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training.   |

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

|              |   |
|--------------|---|
| Eye contact  | : No known significant effects or critical hazards. |
| Inhalation   | : No known significant effects or critical hazards. |
| Skin contact | : No known significant effects or critical hazards. |
| Ingestion    | : No known significant effects or critical hazards. |

Over-exposure signs/symptoms

|              |                     |
|--------------|---------------------|
| Eye contact  | : No specific data. |
| Inhalation   | : No specific data. |
| Skin contact | : No specific data. |
| Ingestion    | : No specific data. |

4.3 Indication of any immediate medical attention and special treatment needed

|                     |   |
|---------------------|---|
| Notes to physician  | : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : No specific treatment.  |

SECTION 5: Firefighting measures

5.1 Extinguishing media

|                                |   |
|--------------------------------|---|
| Suitable extinguishing media   | : Use an extinguishing agent suitable for the surrounding fire. |
| Unsuitable extinguishing media | : None known.   |

5.2 Special hazards arising from the substance or mixture

|                                       |   |
|---------------------------------------|---|
| Hazards from the substance or mixture | : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |
| Hazardous combustion products         | : Decomposition products may include the following materials:<br>carbon oxides<br>phosphorus oxides<br>metal oxide/oxides   |

5.3 Advice for firefighters

|                    |                |                                |                 |
|--------------------|----------------|--------------------------------|-----------------|
| Code               | : SDS-FI60010S | Date of issue/Date of revision | : 28 March 2024 |
| FONTECRYL SC-MR 10 |                |                                |                 |

SECTION 5: Firefighting measures

|  |   |
|--|---|
| Special precautions for fire-fighters          | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.   |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents. |

SECTION 6: Accidental release measures

|  |   |
|--|---|
| 6.1 Personal precautions, protective equipment and emergency procedures  |   |
| For non-emergency personnel  | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.   |
| For emergency responders   | : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".   |
| 6.2 Environmental precautions  |   |
| : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. |   |
| 6.3 Methods and material for containment and cleaning up   |   |
| Small spill  | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.   |
| Large spill  | : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. |
| 6.4 Reference to other sections  | : See Section 1 for emergency contact information.<br>See Section 8 for information on appropriate personal protective equipment.<br>See Section 13 for additional waste treatment information.   |

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

|  |  |
|--|--|
| 7.1 Precautions for safe handling      |  |
| Protective measures                    | : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.  |

|                    |                |                                |                 |
|--------------------|----------------|--------------------------------|-----------------|
| Code               | : SDS-FI60010S | Date of issue/Date of revision | : 28 March 2024 |
| FONTECRYL SC-MR 10 |                |                                |                 |

SECTION 7: Handling and storage

**7.2 Conditions for safe storage, including any incompatibilities** : Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

**7.3 Specific end use(s)**  
See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**8.1 Control parameters**  
Occupational exposure limits

| Product/ingredient name | Exposure limit values   |
|-------------------------|---|
| 2-butoxyethanol         | <b>EU OEL (Europe, 1/2022). Absorbed through skin.</b><br>STEL: 246 mg/m³ 15 minutes.<br>STEL: 50 ppm 15 minutes.<br>TWA: 98 mg/m³ 8 hours.<br>TWA: 20 ppm 8 hours. |
| ammonium hydroxide      | <b>EU OEL (Europe, 1/2022). [ammonia, anhydrous]</b><br>TWA: 20 ppm 8 hours.<br>TWA: 14 mg/m³ 8 hours.<br>STEL: 50 ppm 15 minutes.<br>STEL: 36 mg/m³ 15 minutes.    |

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

| Product/ingredient name     | Type | Exposure              | Value             | Population         | Effects  |
|-----------------------------|------|-----------------------|-------------------|--------------------|----------|
| 2-butoxyethanol             | DNEL | Long term Oral        | 6.3 mg/kg bw/day  | General population | Systemic |
|                             | DNEL | Short term Oral       | 26.7 mg/kg bw/day | General population | Systemic |
|                             | DNEL | Long term Inhalation  | 59 mg/m³          | General population | Systemic |
|                             | DNEL | Long term Inhalation  | 98 mg/m³          | Workers            | Systemic |
|                             | DNEL | Short term Inhalation | 147 mg/m³         | General population | Local    |
|                             | DNEL | Short term Inhalation | 246 mg/m³         | Workers            | Local    |
|                             | DNEL | Short term Inhalation | 426 mg/m³         | General population | Systemic |
| trizinc bis(orthophosphate) | DNEL | Short term Inhalation | 1091 mg/m³        | Workers            | Systemic |
|                             | DNEL | Long term Oral        | 0.83 mg/kg bw/day | General population | Systemic |
|                             | DNEL | Long term Inhalation  | 2.5 mg/m³         | General population | Systemic |
|                             | DNEL | Long term Inhalation  | 5 mg/m³           | Workers            | Systemic |
| English (GB)                |      |                       | Europe            |                    | 6/16     |



|                    |                |                                |                 |
|--------------------|----------------|--------------------------------|-----------------|
| Code               | : SDS-FI60010S | Date of issue/Date of revision | : 28 March 2024 |
| FONTECRYL SC-MR 10 |                |                                |                 |

SECTION 8: Exposure controls/personal protection

|   |      |                       |                    |                    |          |
|---|------|-----------------------|--------------------|--------------------|----------|
| zinc oxide  | DNEL | Long term Dermal      | 83 mg/kg bw/day    | General population | Systemic |
|   | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers            | Systemic |
|   | DNEL | Long term Inhalation  | 0.5 mg/m³          | Workers            | Local    |
|   | DNEL | Long term Oral        | 0.83 mg/kg bw/day  | General population | Systemic |
|   | DNEL | Long term Inhalation  | 2.5 mg/m³          | General population | Systemic |
|   | DNEL | Long term Inhalation  | 5 mg/m³            | Workers            | Systemic |
|   | DNEL | Long term Dermal      | 83 mg/kg bw/day    | General population | Systemic |
|   | DNEL | Long term Dermal      | 83 mg/kg bw/day    | Workers            | Systemic |
| 2,4,7,9-tetramethyldec-5-yne-4,7-diol   | DNEL | Long term Oral        | 0.25 mg/kg bw/day  | General population | Systemic |
|   | DNEL | Long term Dermal      | 0.25 mg/kg bw/day  | General population | Systemic |
|   | DNEL | Long term Inhalation  | 0.43 mg/m³         | General population | Systemic |
|   | DNEL | Long term Dermal      | 0.5 mg/kg bw/day   | Workers            | Systemic |
|   | DNEL | Short term Oral       | 0.75 mg/kg bw/day  | General population | Systemic |
|   | DNEL | Short term Dermal     | 0.75 mg/kg bw/day  | General population | Systemic |
|   | DNEL | Short term Inhalation | 1.29 mg/m³         | General population | Systemic |
|   | DNEL | Short term Dermal     | 1.5 mg/kg bw/day   | Workers            | Systemic |
| 1,2-benzisothiazol-3(2H)-one  | DNEL | Long term Inhalation  | 1.76 mg/m³         | Workers            | Systemic |
|   | DNEL | Short term Inhalation | 5.28 mg/m³         | Workers            | Systemic |
|   | DNEL | Long term Dermal      | 0.345 mg/kg bw/day | General population | Systemic |
|   | DNEL | Long term Dermal      | 0.966 mg/kg bw/day | Workers            | Systemic |
|   | DNEL | Long term Inhalation  | 1.2 mg/m³          | General population | Systemic |
|   | DNEL | Long term Inhalation  | 6.81 mg/m³         | Workers            | Systemic |
|   | DNEL | Long term Inhalation  | 0.02 mg/m³         | General population | Local    |
|   | DNEL | Long term Inhalation  | 0.02 mg/m³         | Workers            | Local    |
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) | DNEL | Short term Inhalation | 0.04 mg/m³         | General population | Local    |
|   | DNEL | Short term Inhalation | 0.04 mg/m³         | Workers            | Local    |
|   | DNEL | Long term Oral        | 0.09 mg/kg bw/day  | General population | Systemic |
|   | DNEL | Short term Oral       | 0.11 mg/kg bw/day  | General population | Systemic |
|   | DNEL | Long term Inhalation  | 0.02 mg/m³         | Workers            | Local    |
|   | DNEL | Short term Inhalation | 0.04 mg/m³         | General population | Local    |
|   | DNEL | Short term Inhalation | 0.04 mg/m³         | Workers            | Local    |
|   | DNEL | Long term Oral        | 0.09 mg/kg bw/day  | General population | Systemic |

PNECs

| Product/ingredient name               | Type | Compartment Detail     | Value           | Method Detail            |
|---------------------------------------|------|------------------------|-----------------|--------------------------|
| 2-butoxyethanol                       | -    | Fresh water            | 8.8 mg/l        | Assessment Factors       |
|                                       | -    | Marine water           | 0.88 mg/l       | Assessment Factors       |
|                                       | -    | Fresh water sediment   | 34.6 mg/kg      | Equilibrium Partitioning |
|                                       | -    | Marine water sediment  | 3.46 mg/kg      | Equilibrium Partitioning |
|                                       | -    | Soil                   | 3.13 mg/kg      | Equilibrium Partitioning |
| trizinc bis(orthophosphate)           | -    | Sewage Treatment Plant | 463 mg/l        | Assessment Factors       |
|                                       | -    | Fresh water            | 20.6 µg/l       | Sensitivity Distribution |
|                                       | -    | Marine water           | 6.1 µg/l        | Sensitivity Distribution |
|                                       | -    | Sewage Treatment Plant | 100 µg/l        | Assessment Factors       |
|                                       | -    | Fresh water sediment   | 117.8 mg/kg dwt | Sensitivity Distribution |
| zinc oxide                            | -    | Marine water sediment  | 56.5 mg/kg dwt  | Equilibrium Partitioning |
|                                       | -    | Soil                   | 35.6 mg/kg dwt  | Sensitivity Distribution |
|                                       | -    | Fresh water            | 20.6 µg/l       | Sensitivity Distribution |
|                                       | -    | Marine water           | 6.1 µg/l        | Sensitivity Distribution |
|                                       | -    | Fresh water sediment   | 117 mg/kg dwt   | Sensitivity Distribution |
| 2,4,7,9-tetramethyldec-5-yne-4,7-diol | -    | Sewage Treatment Plant | 52 µg/l         | Assessment Factors       |
|                                       | -    | Marine water sediment  | 56.5 mg/kg dwt  | Assessment Factors       |
|                                       | -    | Soil                   | 35.6 mg/kg dwt  | Sensitivity Distribution |
|                                       | -    | Fresh water            | 0.04 mg/l       | Assessment Factors       |
|                                       | -    | Marine water           | 0.004 mg/l      | Assessment Factors       |
|                                       | -    | Sewage Treatment Plant | 7 mg/l          | Assessment Factors       |
|                                       | -    | Fresh water sediment   | 0.32 mg/kg dwt  | Equilibrium Partitioning |

|                    |                |                                |                 |
|--------------------|----------------|--------------------------------|-----------------|
| Code               | : SDS-FI60010S | Date of issue/Date of revision | : 28 March 2024 |
| FONTECRYL SC-MR 10 |                |                                |                 |

SECTION 8: Exposure controls/personal protection

|  |   |                       |                |                          |
|--|---|-----------------------|----------------|--------------------------|
|  | - | Marine water sediment | 0.032 mg/kg dw | Equilibrium Partitioning |
|  | - | Soil                  | 0.028 mg/kg dw | Equilibrium Partitioning |

8.2 Exposure controls

|                                  |   |
|----------------------------------|---|
| Appropriate engineering controls | : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.  |
| Individual protection measures   |   |
| Hygiene measures                 | : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.   |
| Eye/face protection              | : Safety glasses with side shields. Use eye protection according to EN 166.   |
| Skin protection                  |   |
| Hand protection                  | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. |
| Gloves                           | : For prolonged or repeated handling, use the following type of gloves:<br><br>Recommended: nitrile rubber, Chloroprene, butyl rubber   |
| Body protection                  | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.   |
| Other skin protection            | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.   |
| Respiratory protection           | : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3  |
| Environmental exposure controls  | : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.  |



|                    |                |                                |                 |
|--------------------|----------------|--------------------------------|-----------------|
| Code               | : SDS-FI60010S | Date of issue/Date of revision | : 28 March 2024 |
| FONTECRYL SC-MR 10 |                |                                |                 |

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state

Colour

Odour

Odour threshold

Melting point/freezing point

Initial boiling point and boiling range

Flammability

Upper/lower flammability or explosive limits

Flash point

Auto-ignition temperature

Decomposition temperature

pH

Viscosity

Solubility(ies)

Partition coefficient: n-octanol/ water

Vapour pressure

Evaporation rate

Relative density

Vapour density

Explosive properties

Oxidising properties

Particle characteristics

Median particle size

: Liquid.

: Various

: Characteristic.

: Not available.

: May start to solidify at the following temperature: 0°C (32°F) This is based on data for the following ingredient: water. Weighted average: -9.06°C (15.7°F)

: >37.78°C

: Not available.

: Not available.

: Closed cup: Not applicable.

:

| Ingredient name | °C  | °F  | Method    |
|-----------------|-----|-----|-----------|
| 2-butoxyethanol | 230 | 446 | DIN 51794 |

: Stable under recommended storage and handling conditions (see Section 7).

: 6 to 9

: Kinematic (40°C): >21 mm²/s

:

| Media      | Result            |
|------------|-------------------|
| cold water | Partially soluble |

: Not applicable.

:

| Ingredient name | Vapour Pressure at 20°C |     |        | Vapour pressure at 50°C |     |        |
|-----------------|-------------------------|-----|--------|-------------------------|-----|--------|
|                 | mm Hg                   | kPa | Method | mm Hg                   | kPa | Method |
| water           | 17.5                    | 2.3 |        |                         |     |        |

: 0.072 (2-butoxyethanol) compared with butyl acetate

: 1.2

: Highest known value: 4.1 (Air = 1) (2-butoxyethanol).

: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

: Product does not present an oxidizing hazard.

:

: Not applicable.

9.2 Other information

No additional information.

|                    |                |                                |                 |
|--------------------|----------------|--------------------------------|-----------------|
| Code               | : SDS-FI60010S | Date of issue/Date of revision | : 28 March 2024 |
| FONTECRYL SC-MR 10 |                |                                |                 |

SECTION 10: Stability and reactivity

|   |   |
|---|---|
| 10.1 Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients.  |
| 10.2 Chemical stability                 | : The product is stable.  |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.   |
| 10.4 Conditions to avoid                | : When exposed to high temperatures may produce hazardous decomposition products.<br>Refer to protective measures listed in sections 7 and 8. |
| 10.5 Incompatible materials             | : Keep away from the following materials to prevent strong exothermic reactions:<br>oxidising agents, strong alkalis, strong acids.           |
| 10.6 Hazardous decomposition products   | : Depending on conditions, decomposition products may include the following materials:<br>carbon oxides phosphorus oxides metal oxide/oxides  |

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

| Product/ingredient name   | Result                          | Species | Dose        | Exposure |
|---|---------------------------------|---------|-------------|----------|
| 2-butoxyethanol   | LC50 Inhalation Vapour          | Rat     | 3 mg/l      | 4 hours  |
|   | LD50 Dermal                     | Rat     | >2000 mg/kg | -        |
|   | LD50 Oral                       | Rat     | 1200 mg/kg  | -        |
| trizinc bis(orthophosphate)   | LC50 Inhalation Dusts and mists | Rat     | >5.7 mg/l   | 4 hours  |
|   | LD50 Oral                       | Rat     | >5000 mg/kg | -        |
| zinc oxide  | LC50 Inhalation Dusts and mists | Rat     | >5700 mg/m³ | 4 hours  |
|   | LD50 Dermal                     | Rat     | >2000 mg/kg | -        |
|   | LD50 Oral                       | Rat     | >5000 mg/kg | -        |
| ammonium hydroxide  | LD50 Oral                       | Rat     | 350 mg/kg   | -        |
| 2,4,7,9-tetramethyldec-5-yne-4,7-diol   | LC50 Inhalation Dusts and mists | Rat     | >20 mg/l    | 1 hours  |
|   | LD50 Dermal                     | Rabbit  | >2000 mg/kg | -        |
|   | LD50 Oral                       | Rat     | 4.6 g/kg    | -        |
| 1,2-benzisothiazol-3(2H)-one  | LC50 Inhalation Dusts and mists | Rat     | 0.4 mg/l    | 4 hours  |
|   | LD50 Oral                       | Rat     | 1020 mg/kg  | -        |
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) | LD50 Oral                       | Rat     | 53 mg/kg    | -        |

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

| Route                | ATE value      |
|----------------------|----------------|
| Oral                 | 23509.95 mg/kg |
| Inhalation (vapours) | 58.77 mg/l     |

Irritation/Corrosion

|                    |                |                                |                 |
|--------------------|----------------|--------------------------------|-----------------|
| Code               | : SDS-FI60010S | Date of issue/Date of revision | : 28 March 2024 |
| FONTECRYL SC-MR 10 |                |                                |                 |

SECTION 11: Toxicological information

| Product/ingredient name                                  | Result                   | Species | Score | Exposure        | Observation |
|--|--------------------------|---------|-------|-----------------|-------------|
| 2-butoxyethanol<br>2,4,7,9-tetramethyldec-5-yne-4,7-diol | Eyes - Irritant          | Rabbit  | -     | 24 hours        | 21 days     |
|  | Skin - Moderate irritant | Rabbit  | -     | 4 hours         | 28 days     |
|  | Eyes - Severe irritant   | Rabbit  | -     | 0.1 Milliliters | -           |
|  | Skin - Mild irritant     | Rabbit  | -     | 0.5 Grams       | -           |

Conclusion/Summary

- Skin : There are no data available on the mixture itself.
- Eyes : There are no data available on the mixture itself.
- Respiratory : There are no data available on the mixture itself.

Sensitisation

| Product/ingredient name    | Route of exposure | Species    | Result      |
|----------------------------|-------------------|------------|-------------|
| 2-benzisothiazol-3(2H)-one | skin              | Guinea pig | Sensitising |

Conclusion/Summary

- Skin : There are no data available on the mixture itself.
- Respiratory : There are no data available on the mixture itself.

Mutagenicity

- Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

- Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

- Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

- Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs                |
|-------------------------|------------|-------------------|------------------------------|
| ammonium hydroxide      | Category 3 | -                 | Respiratory tract irritation |

Not available.

- Information on likely routes of exposure : Not available.

Potential acute health effects

- Inhalation : No known significant effects or critical hazards.
- Ingestion : No known significant effects or critical hazards.
- Skin contact : No known significant effects or critical hazards.
- Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation : No specific data.
- Ingestion : No specific data.
- Skin contact : No specific data.
- Eye contact : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

|                    |                |                                |                 |
|--------------------|----------------|--------------------------------|-----------------|
| Code               | : SDS-FI60010S | Date of issue/Date of revision | : 28 March 2024 |
| FONTECRYL SC-MR 10 |                |                                |                 |

SECTION 11: Toxicological information

|  |   |
|--|---|
| Potential immediate effects  | : Not available.                                    |
| Potential delayed effects  | : Not available.                                    |
| Long term exposure   |   |
| Potential immediate effects  | : Not available.                                    |
| Potential delayed effects  | : Not available.                                    |
| Potential chronic health effects   |   |
| Not available.   |   |
| Conclusion/Summary   | : Not available.                                    |
| General  | : No known significant effects or critical hazards. |
| Carcinogenicity  | : No known significant effects or critical hazards. |
| Mutagenicity   | : No known significant effects or critical hazards. |
| Reproductive toxicity  | : No known significant effects or critical hazards. |
| Other information  | : Not available.                                    |
| Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains isothiazolinones. May cause allergic reaction. |   |
| 11.2 Information on other hazards  |   |
| 11.2.1 Endocrine disrupting properties   |   |
| Not available.   |   |
| 11.2.2 Other information   |   |
| Not available.   |   |

SECTION 12: Ecological information

## 12.1 Toxicity

| Product/ingredient name      | Result                   | Species                                  | Exposure |
|------------------------------|--------------------------|--|----------|
| 2-butoxyethanol              | Acute LC50 1474 mg/l     | Fish                                     | 96 hours |
|                              | Chronic NOEC >100 mg/l   | Fish                                     | 21 days  |
| trizinc bis(orthophosphate)  | Acute LC50 0.112 mg/l    | Fish                                     | 96 hours |
|                              | Chronic NOEC 0.026 mg/l  | Fish                                     | 30 days  |
| zinc oxide                   | Acute EC50 0.17 mg/l     | Algae                                    | 72 hours |
|                              | Acute EC50 0.481 mg/l    | Daphnia - <i>Daphnia magna</i> - Neonate | 48 hours |
|                              | Fresh water              |  |          |
|                              | Chronic NOEC 0.017 mg/l  | Algae                                    | 72 hours |
|                              | Fresh water              |  |          |
| 1,2-benzisothiazol-3(2H)-one | Acute EC50 0.11 mg/l     | Algae                                    | 72 hours |
|                              | Acute EC50 2.9 mg/l      | Daphnia                                  | 48 hours |
|                              | Acute LC50 2.15 mg/l     | Fish                                     | 96 hours |
|                              | Chronic NOEC 0.0403 mg/l | Algae                                    | 72 hours |

|                                    |  |
|------------------------------------|--|
| Conclusion/Summary                 | : There are no data available on the mixture itself. |
| 12.2 Persistence and degradability |  |
| Conclusion/Summary                 | : There are no data available on the mixture itself. |

|                    |                |                                |                 |
|--------------------|----------------|--------------------------------|-----------------|
| Code               | : SDS-FI60010S | Date of issue/Date of revision | : 28 March 2024 |
| FONTECRYL SC-MR 10 |                |                                |                 |

SECTION 12: Ecological information

| Product/ingredient name      | Aquatic half-life | Photolysis | Biodegradability |
|------------------------------|-------------------|------------|------------------|
| 2-butoxyethanol              | -                 | -          | Readily          |
| 1,2-benzisothiazol-3(2H)-one | -                 | -          | Readily          |

12.3 Bioaccumulative potential

| Product/ingredient name      | LogP <sub>ow</sub> | BCF | Potential |
|------------------------------|--------------------|-----|-----------|
| 2-butoxyethanol              | 0.81               | -   | Low       |
| 1,2-benzisothiazol-3(2H)-one | 0.7                | -   | Low       |

12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

| Waste code | Waste designation   |
|------------|---|
| 08 01 11*  | waste paint and varnish containing organic solvents or other hazardous substances |

Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container         | 15 01 06 mixed packaging       |

|                    |                |                                |                 |
|--------------------|----------------|--------------------------------|-----------------|
| Code               | : SDS-FI60010S | Date of issue/Date of revision | : 28 March 2024 |
| FONTECRYL SC-MR 10 |                |                                |                 |

SECTION 13: Disposal considerations

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

|                                 | ADR/RID         | ADN   | IMDG            | IATA            |
|---------------------------------|-----------------|---|-----------------|-----------------|
| 14.1 UN number or ID number     | Not regulated.  | 9006  | Not regulated.  | Not regulated.  |
| 14.2 UN proper shipping name    | -               | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. | -               | -               |
| 14.3 Transport hazard class(es) | -               | 9   | -               | -               |
| 14.4 Packing group              | -               | -   | -               | -               |
| 14.5 Environmental hazards      | No.             | Yes.  | No.             | No.             |
| Marine pollutant substances     | Not applicable. | Not applicable.                                     | Not applicable. | Not applicable. |

Additional information

**ADR/RID** : None identified.  
**ADN** : The product is only regulated as a dangerous good when transported in tank vessels.  
**IMDG** : None identified.  
**IATA** : None identified.

**14.6 Special precautions for user** : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not applicable.

SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
EU Regulation (EC) No. 1907/2006 (REACH)  
Annex XIV - List of substances subject to authorisation  
Annex XIV  
None of the components are listed.  
Substances of very high concern  
None of the components are listed.



|                    |                |                                |                 |
|--------------------|----------------|--------------------------------|-----------------|
| Code               | : SDS-FI60010S | Date of issue/Date of revision | : 28 March 2024 |
| FONTECRYL SC-MR 10 |                |                                |                 |

SECTION 15: Regulatory information

|  |   |
|--|---|
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : Not applicable.   |
| Explosive precursors   | : Not applicable.   |
| Ozone depleting substances (1005/2009/EU)  | Not listed.   |
| VOC for Ready-for-Use Mixture  | : IIA/i. One-pack performance coatings. EU limit values: 140 g/l (2010.)<br>This product contains a maximum of 140 g/l VOC. |
| Seveso Directive   | This product is not controlled under the Seveso Directive.  |
| Biocidal products regulation   | : Contains a biocidal product; C(M)IT/MIT (3:1)   |

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

|   |
|---|
| Indicates information that has changed from previously issued version.                                |
| Abbreviations and acronyms  |
| ATE = Acute Toxicity Estimate   |
| CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]              |
| DNEL = Derived No Effect Level  |
| EUH statement = CLP-specific Hazard statement   |
| PNEC = Predicted No Effect Concentration  |
| RRN = REACH Registration Number   |
| PBT = Persistent, Bioaccumulative and Toxic   |
| vPvB = Very Persistent and Very Bioaccumulative   |
| ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road         |
| ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway |
| IMDG = International Maritime Dangerous Goods   |
| IATA = International Air Transport Association  |

Full text of abbreviated H statements

|        |   |
|--------|---|
| H301   | Toxic if swallowed.                                   |
| H302   | Harmful if swallowed.                                 |
| H310   | Fatal in contact with skin.                           |
| H314   | Causes severe skin burns and eye damage.              |
| H315   | Causes skin irritation.                               |
| H317   | May cause an allergic skin reaction.                  |
| H318   | Causes serious eye damage.                            |
| H319   | Causes serious eye irritation.                        |
| H330   | Fatal if inhaled.                                     |
| H331   | Toxic if inhaled.                                     |
| H335   | May cause respiratory irritation.                     |
| H400   | Very toxic to aquatic life.                           |
| H410   | Very toxic to aquatic life with long lasting effects. |
| H411   | Toxic to aquatic life with long lasting effects.      |
| H412   | Harmful to aquatic life with long lasting effects.    |
| EUH071 | Corrosive to the respiratory tract.                   |

Full text of classifications [CLP/GHS]

|                    |                |                                |                 |
|--------------------|----------------|--------------------------------|-----------------|
| Code               | : SDS-FI60010S | Date of issue/Date of revision | : 28 March 2024 |
| FONTECRYL SC-MR 10 |                |                                |                 |

SECTION 16: Other information

|                   |   |
|-------------------|---|
| Acute Tox. 2      | ACUTE TOXICITY - Category 2                                   |
| Acute Tox. 3      | ACUTE TOXICITY - Category 3                                   |
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                                   |
| Aquatic Acute 1   | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1                |
| Aquatic Chronic 1 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1               |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2               |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3               |
| Eye Dam. 1        | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1                |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2                |
| Skin Corr. 1B     | SKIN CORROSION/IRRITATION - Category 1B                       |
| Skin Corr. 1C     | SKIN CORROSION/IRRITATION - Category 1C                       |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2                        |
| Skin Sens. 1      | SKIN SENSITISATION - Category 1                               |
| Skin Sens. 1A     | SKIN SENSITISATION - Category 1A                              |
| Skin Sens. 1B     | SKIN SENSITISATION - Category 1B                              |
| STOT SE 3         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |

History

|                                 |                 |
|---------------------------------|-----------------|
| Date of issue/ Date of revision | : 28 March 2024 |
| Date of previous issue          | : 27 March 2024 |
| Prepared by                     | : EHS           |
| Version                         | : 1.02          |

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.