

*PPG Metallic Tones Interior Specialty Finish***GENERAL DESCRIPTION**

PPG *Metallic Tones* Interior Specialty Finish provides a sleek, luminous finish that lends a shimmering richness to classic colors and introduces a timeless luxury to walls, trim and architectural elements throughout the home.

RECOMMENDED SUBSTRATES

Gypsum Wallboard - Drywall
Wood Trim

FEATURES / BENEFITS

Interior Specialty Finish
Available in Any One of 42 Curated Colors
Bring a Touch of Luxury to Walls, Trim and Accents
Provides a Beautiful Hammered Metal Finish

PRODUCT INFORMATION

PPG3000	Gold Base (May Be Tinted)
PPG4000	Silver Base (Must Be Tinted)

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

PACKAGING

Quart (946 mL)
1-Gallon (3.78 L)

PRODUCT DATA

PRODUCT TYPE:	100% Acrylic
SHEEN:	Semi-Gloss, 25-40 @ 60°
VOLUME SOLIDS*:	28% +/- 2%
WEIGHT SOLIDS*:	36% +/- 2%
VOC:	<350 g/L (2.9 lbs./gal.)
WEIGHT/GALLON*:	9.3 lbs. (4.2 kg) +/- 0.2 lbs. (91 g)

*Product data calculated on product PPG3000

COVERAGE: One gallon (3.78 L) will cover approximately 200 sq. ft. (18.6 sq. meters) with two coats. Do not thin. It will take two coats to achieve the look of METALLIC.

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Dry time @ 77°F (25°C); 50% relative humidity.
To Touch: 30-60 minutes
To Recoat: 2 hours

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

CLEANUP: Clean brushes and tools with warm, soapy water.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

LIMITATIONS OF USE

FOR INTERIOR USE ONLY. PROTECT FROM FREEZING.

Do not apply when the surface or air temperature is below 50°F (10°C).

Not recommended for application on ceilings or textured walls. Touch-up may be difficult due to the appearance of this finish.

PPG Metallic Tones Interior Specialty Finish

GENERAL SURFACE PREPARATION

All surfaces must be sound, dry, clean and free of oil, grease, dirt, mildew, rust, form release agents, curing compounds, loose and flaking paint and other foreign substances. Wash walls before painting and rinse well. Glossy surfaces must be dulled by sanding to ensure proper adhesion. Remove sanding dust. Fill all cracks and nail holes with crack filler and spot prime with the appropriate primer. For best results, prime heavily stained areas or watermarks with a stain blocking primer.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

GYPSUM WALLBOARD-DRYWALL: Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust, then prime prior to painting the substrate.

WOOD TRIM: Unpainted wood or wood in poor condition should be sanded smooth, wiped clean, then primed. Any knots or resinous areas must be primed before painting. Countersink all nails, putty flush with surface, then prime.

APPLICATION INFORMATION

Tape off all areas to be painted. Stir paint thoroughly before use. New and previously painted surfaces should be primed with the appropriate latex primer prior to applying paint. See primer label directions for specific instructions. Do not apply when the surface or air temperature is below 50°F (10°C).

HELPFUL HINT: For best results, it is recommended that one person apply the *METALLIC TONES* Specialty Finish to all walls.

Step 1: Apply one coat using a premium quality 3/8" nap roller. Follow with a final downward sweep from top to bottom across the entire area. Use the small sponge insert to dab any areas around the edges. Allow first basecoat to dry for at least two hours.

HELPFUL HINT: Lap marks and appearance inconsistencies are expected in the first coat. For lighter colors, two coats may be required.

Step 2: Specialty faux finish sponge roller should be rinsed with warm water prior to use. Remove excess water by squeezing the roller. Apply final coat with a specialty faux finish sponge roller. Start application in one corner and apply from top to bottom. Use slightly overlapping strokes until the paint is spread to an even consistency. Follow with a final downward sweep from top to bottom across the entire area. Use the small sponge insert to dab any areas around the edges.

HELPFUL HINT: For a more irregular or random pattern, follow the above instructions and apply paint in a small V pattern until wall is covered.

BRUSHING (TRIM WORK): Apply evenly in a single direction (horizontal or vertical) with a premium quality nylon/polyester brush. Do not feather the end of the brush stroke; leave a wet edge so that it may be blended with the next brush stroke for an even finish. For complete coverage, apply two coats or more, allowing two hours dry time between coats.

THINNING: DO NOT THIN.

PRECAUTIONS

WARNING! HARMFUL IF SWALLOWED. Sanding and grinding dusts may be harmful if inhaled. Do not swallow. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

© 2017 PPG Industries, Inc. All Rights Reserved. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. *Metallic Tones* is a trademark of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.ppg.com
www.ppgmetallictones.com

Technical Services
1-800-441-9695

Architect/Specifier
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.
2505, rue de la Métropole,
Longueuil (Québec) Canada J4G 1E5

PPG3000 3/2018