

LOW-VOC UNDERCOAT SELECTIONS

DIRECT-TO-METAL/CORROSION PROTECTION

JP390 Epoxy Primer

- Excellent corrosion resistance
- Can be used as sealer
- Quart pack size



PRIMER SEALER

JP36X Series 2.1 VOC Urethane Sealer

- Easy application, smooth appearance
- Available in white, gray and dark gray



PRIMER SURFACER

JP35X Series 2.1 VOC Multi-Purpose Primer

- High build and easy to sand
- Can be converted to sealer
- Available in gray, dark gray and white



POLYESTER

JP209 Polyester Primer

- High build
- Quick dry, easy to sand
- Hardener tube included



LOW-VOC CLEARCOAT SELECTIONS

PRODUCTION—PANEL/MULTI-PANEL

JC830 2.1 VOC Production Clear

- Short, low-bake option, 20 minutes/120°F
- Excellent productivity with impressive air dry times
- Easy 4:1 mix ratio



JC7200 2.1 VOC HS European Clearcoat

- Short bake cycle, 20 minutes/140°F
- Excellent appearance
- Easy 2:1 mix ratio with European packaging



OVERALL—MULTI-PANEL

JC7100 2.1 VOC European Multi-Panel Clearcoat

- Excellent gloss and appearance
- Ideal for large and overall jobs
- Easy 2:1 mix ratio with European packaging



SPEED—SPOT/PANEL

JC780 2.1 VOC Polyurethane Speed Clear

- Short bake time, 15 minutes/140°F
- Fast air dry times
- Good buffability, 4:1 mix ratio



JC815 Low VOC Speed Clear

- Fast 20-minute bake
- Suitable for air dry
- 10 minutes out of dust
- Excellent gloss and appearance

