

**PDS N1.6C**

May 2005

**P562-100*****WATERBASED SANDING PASTE*****PRODUCT DESCRIPTION**

Nexa Autocolor Waterbased Sanding Paste, P562-100 is an abrasive paste for use in preparing surfaces for blending or fad-out. This product used in conjunction with an abrasive pad, provides a fast and effective method of evenly de-glossing and abrading topcoats in preparation for blending.

This product is silicone and wax free, and residue can easily be washed off with water for maximum adhesion.

## ***WATERBASED SANDING PASTE***

### **PRODUCTS**

***P562-100***

***WATERBASED SANDING PASTE***

**THESE PRODUCTS ARE FOR THE PROFESSIONAL PAINTING OF AUTOMOTIVE VEHICLES ONLY**

## PROCESS

### APPLICATION



**NOTE:** Ensure the whole area to be repaired has been thoroughly cleaned using Body Cleaner, P273-901 or Waterborne Pre-Cleaner P980-251.

1. Apply Waterbased Sanding Paste directly onto an abrasive scuff pad (ultrafine grey or equivalent). Use the pad and paste with water to abrade the area to be painted.
2. Wash off all residue with clean water and dry thoroughly. The painted surface should have a uniformly matt appearance.  
**Note:** Failure to remove all residue could result in adhesion failure.
3. Clean the surface thoroughly with P980-251, Waterborne Pre-Cleaner prior to topcoating.

## 2K PERFORMANCE SPECIFICATIONS

**Product:** P562-100  
**Category:** Surface Cleaner  
**VOC:** 0.0 lbs per gal./0 gm/l  
**VOC RTU:** Packaged ready for use

For further information please contact:

**Nexa Autocolor-USA**  
19699 Progress Drive  
Strongsville, OH 44149

**Nexa Autocolor-Canada**  
2301 Royal Windsor Drive  
Mississauga, Ontario L5J 1K5