

PDS N1.6
July 2005

P562-100 WATERBASED SANDING PASTE

PRODUCT DESCRIPTION

Nexa Autocolor Waterbased Sanding Paste (**P562-100**) is an abrasive paste for use in preparing surfaces for blending or fade-out. This product, used in conjunction with an abrasive pad, provides a fast and effective method of evenly de-glossing and abrading topcoats in preparation for blending. The product is silicone and wax free, and residue can easily be washed off with water for maximum adhesion.

• Fast Surface Preparation = reduced process times

• Fast Quality Repair = customer satisfaction



WATERBASED SANDING PASTE

PRODUCTS

P562-100

Waterbased Sanding Paste

THESE PRODUCTS ARE FOR THE PROFESSIONAL PAINTING OF AUTOMOTIVE VEHICLES ONLY

PROCESS

APPLICATION





Note: Ensure the whole area to be repaired has been thoroughly cleaned using either Spirit Wipe (P850-1402) or Body Cleaner (P273-901).

- 1. Apply Waterbased Sanding paste directly onto an scuff pad (ultrafine Grey or equivalent). Use the pad and paste with water to abrade the area to be painted.
- 2. Wash off all residue with clean water and dry thoroughly. The painted surface should have a uniformly matt appearance.

Note: Failure to remove all residue could result in adhesion failure.

3. Clean the surface thoroughly with either Spirit Wipe (P850-14 or P850-1402) or Waterborne Precleaner (P980-251) prior to overcoating.

2K™ PERFORMANCE SPECIFICATIONS

Product: P562-100

Category: Surface Cleaner VOC As Packaged: 0.0 lbs. per gal

VOC RFU: Packaged Ready-for-Use

For further information please contact:

Nexa Autocolor-USA 19699 Progress Drive Strongsville, OH 44149 **Nexa Autocolor**-Canada 2301 Royal Windsor Drive Mississauga, Ontario L5J 1K5