

2.9 VOC Bug and Tar

SX1009

ONECHOICE® SX1009 2.9 VOC Bug and Tar Remover is specifically designed to remove bugs, road tar, wax, grease, silicone, engine oil, and other contaminants. It can also be used on bare metal, plastics, primers, or cured automotive finishes.

SX1009 is packaged ready-to-use.

It is compliant in many markets with a VOC of 2.9 lbs. per gallon.



Features & Benefits

- Packaged ready for use
- Convenient
- Low VOC
- Simple to Use
- Reduced Emissions

Compatible Surfaces

- OEM Surfaces
- Cured and Dried Automotive Surfaces
- Ferrous and non-ferrous metals
- Automotive Plastics

Compatible Products

- SX1009 2.9 VOC Bug and Tar Remover is for use with PPG and NEXA AUTOCOLOR® brand refinish products.

Directions for Use

Application



- Wash surface with soap and water before cleaning.
- Clean surface before and after sanding.
- Apply a generous amount of SX1009 to a clean white disposable cloth or apply with a hand held spray bottle.
- Initial application floats contaminants to the surface where the second wipe with a clean, dry white cloth will remove the contaminants.
- For best results, wiping dry with clean white cloth in one direction while the surface is still wet will aid in eliminating instead of smearing of the contaminants.
- Tack the entire surface with a SX1070 tack rag prior to being painted.
- **Note: Test surface for sensitive substrates.**

Technical Data:

Properties:

RTS Combinations:

SX1009

Volume Ratio	As is
Applicable Use Category	Solvent (Substrate Cleaner)
VOC Content (g/L)	346
VOC Content (lbs./US Gal.)	2.89
Wt. % VOC	31.8%

Important:

Before opening the package, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all of its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

See Material Safety Data Sheet and Labels for additional safety information and handling instructions.

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION (412) 434-4515; IN CANADA (514) 645-1320

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to PPG Industries. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does PPG Industries warrant freedom from patent infringement in the use of any formula or process set forth herein.

PPG Industries

Bringing innovation to the surface.™

PPG Industries
19699 Progress Drive
Strongsville, OH 44149

PPG Canada Inc.
2301 Royal Windsor Drive Unit #6
Mississauga, Ontario Canada L5J 1K5

The PPG Logo, *Bringing innovation to the surface*, *OneChoice*, and *Nexa Autocolor* are trademarks of PPG Industries Ohio, Inc.