

MULTI-PREP™

SX103/SXA103

ONECHOICE® SX103 and SXA103 MULTI-PREP™ is a product developed for use as an anti-static agent, a plastic parts cleaning wipe, or as a cleaning agent for mold release. SX103 and SXA103 are packaged ready-to-use.



Features & Benefits

- Packaged ready for use
- Minimizes attraction of dust and dirt
- Reduces static electricity
- Produces consistent results
- Increased productivity
- Aerosol available

Compatible Products

- SX103 *Multi-Prep* is for use with all PPG and NEXA AUTOCOLOR® systems.

Direction For Use**Application:**

- SX103 and SXA103 *Multi-Prep* is packaged ready for use.
- **As an anti-static agent:**
 - Using a spray gun, apply a mist coat of SX103 on the surface to be painted both before and after tacking.
 - Using the SXA103 aerosol can, apply a mist coat of SXA103 on the surface to be painted both before and after tacking.
 - This will help reduce static electricity on all treated surfaces, minimizing the attraction of dust & dirt.
 - Coverage is approximately one (1) quart per car.
- **As a cleaner for Plastics and Flexible parts:**
 - Saturate a clean white cloth with SX103/SXA103, wipe in one direction only, and immediately dry with a clean cloth.
 - Use SX103/SXA103 before and after sanding.

NOTE: Do not apply over painted or sensitive substrates such as fresh topcoats and/or primers as softening may occur.

Can disposal:

When the material in the aerosol can is spent, turn can upside down and depress the nozzle until all propellant is exhausted. Place empty can or cans that are no longer to be used into properly labeled metal containers. The waste containers should be managed as a hazardous waste pursuant to local, state and federal regulations.

Important:

Improper spray technique may result in a hazardous condition. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

Technical Data:**Properties:****RTS Combinations:****SX103****SXA103**

Volume Ratio	As is	As in
Intended Use	Plastic Substrate Cleaner	Plastic Substrate Cleaner
VOC Content (g/L)	777	705
VOC Content (lbs./ US Gal.)	6.48	5.88
Density (g/L)	787	706
Density (lbs./ US Gal)	6.57	5.90

Important:

Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all of its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

See Safety Data Sheet and Labels for additional safety information and handling instructions.

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION (412) 434-4515; IN CANADA (514) 645-1320

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to PPG Industries. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does PPG Industries warrant freedom from patent infringement in the use of any formula or process set forth herein.



PPG Industries
19699 Progress Drive
Strongsville, OH 44149

PPG Canada Inc.
2301 Royal Windsor Drive Unit #6
Mississauga, Ontario Canada L5J 1K5

The PPG Logo, *We protect and beautify the world*, *Multi-Prep*, *Nexa Autocolor*, and *OneChoice* are trademarks of PPG Industries Ohio, Inc.