

Sanding Paste

# SX1002

ONECHOICE® SX1002 is designed to assist the refinish technician to thoroughly and quickly prepare painted automotive surfaces for re-painting or blending.



## Features & Benefits

- Packaged ready for use
- Easy to squeeze tubes - 16 fl. oz.
- Fast abrasion, cutting action
- Approximately 1000 - 1200 grit scratch
- Works well for refinishing or blending.

## Compatible Surfaces

- OEM Surfaces
- Cured and Dried Automotive Surfaces
- Ferrous and non-ferrous metals
- Automotive Plastics

*Note: When applying PPG topcoats and undercoats over plastic substrates, please refer to the products' specific technical bulletin for proper application*

## Compatible Products

- SX1002 Sanding Paste is for use with all PPG and NEXA AUTOCOLOR® systems.

---

**Direction For Use**

---

**Application:**

- SX1002 is packaged ready for use.
- Wash surface with soap and water.
- Clean surface with appropriate PPG Cleaner
- Dampen a fine abrasive scuff pad with water.
- Apply a small amount of SX1002 Sanding Paste to the abrasive pad.
- Abrade the surface completely. Re-apply water and appropriate PPG Cleaner as needed.
- Clean entire surface with appropriate PPG Cleaner, wiping off in one direction.

---

**Technical Data:**

---

**Properties:****RTS Combinations:****SX1002**

Volume Ratio	As is
Intended Use	Sanding Paste
VOC Actual (g/L)	41
VOC Actual (lbs./ US Gal.)	0.34
Volume Solids	27.0
Weight Solids	46.8

---

**Important:**

Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all of its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

---

**See Safety Data Sheet and Labels for additional safety information and handling instructions.**

---

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION (412) 434-4515; IN CANADA (514) 645-1320

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to PPG Industries. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does PPG Industries warrant freedom from patent infringement in the use of any formula or process set forth herein.

## PPG Industries

Bringing innovation to the surface.™

PPG Industries  
19699 Progress Drive  
Strongsville, OH 44149

PPG Canada Inc.  
2301 Royal Windsor Drive Unit #6  
Mississauga, Ontario Canada L5J 1K5

The PPG Logo, *Bringing innovation to the surface*, *OneChoice*, and *Nexa Autocolor*, are trademarks of PPG Industries Ohio, Inc.