

DEFT® WOOD STAIN INTERIOR – WATER-BASED

WATER-BASED FORMULA TO ENHANCE THE NATURAL BEAUTY OF WOOD AND CLEAN UP WITH SOAP AND WATER



Deft Interior Water-Based Wood Stain is a unique oil modified formula that penetrates deeply into wood pores for a rich, even color that enhances the natural beauty of wood. This easy to use product cleans up with soap and water, and dries fast to enable stain and finishing in one day. The low odor formula is ideal for use in enclosed spaces. Excellent for use on furniture, doors, cabinets, trim and molding.



PRODUCT FEATURES

Quick & Easy

- Dries fast
- Top coat in 2 hours
- Stain and top coat in just 1 day
- Easy touch-up
- Extended open time for ease of application

Beautiful and Versatile

- Oil modified formula
- Minimal grain raise
- Excellent penetration
- Use Tint Base (Natural) for a natural color finish, to create custom colors, or as a wood conditioner and stain controller
- Oil enriched formula enhances the natural beauty of wood

For Interior Wood Projects

- Furniture
- Floors
- Doors
- Molding
- Cabinets
- Paneling

CONFORMANCE STANDARD

VOC compliant in all regulated areas

PRODUCT DATA

*PRODUCT DATA CALCULATED ON DFT300

PRODUCT TYPE: Waterborne Alkyd

VOLUME SOLIDS: 14%

WEIGHT SOLIDS: 16%

VOC*: <250 g/L

WEIGHT/GALLON: 8.5 lb/Gal.

VISCOSITY* @77°F (25°C): 48-58 KU (Kreb's Units)

FLASH POINT: >200°F (>99.3°C)

COVERAGE: Up to 400 sq.ft. (46.5 sq meters) per US gallon (3.78 L) on properly prepared surfaces. Coverage figures will vary with wood type, preparation and application.

DRYING TIME: Allow a minimum of 2 hours before application of a topcoat.

Dry times vary with temperature, humidity, color and wood type.

CLEANUP: Clean all brushes and applicators with warm, soapy water.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

PRODUCT AVAILABILITY

DFT300	Tint Base (Natural)	Quarts, Gallons
DFT301	Golden Oak	Quarts
DFT302	Early American	Quarts
DFT303	Cherry	Quarts
DFT304	Red Mahogany	Quarts
DFT305	Dark Walnut	Quarts
DFT306	Spanish Oak	Quarts
DFT307	Dark Mahogany	Quarts



APPLICATION INFORMATION

Provide adequate ventilation. Stir well before and during use. When working with multiple cans, mix together for color consistency.

APPLICATION EQUIPMENT: Apply with a clean cloth, brush, sponge, pad, roller or by spray equipment.

APPLICATION METHOD: Allow stain to penetrate no longer than 5 minutes. Wipe off the excess stain with a clean cloth. Do not allow stain to dry before wiping. To further increase color intensity, allow the stain to dry for 1 hour, and then apply a second coat.

THINNING: No thinning is needed.

GENERAL SURFACE PREPARATION

Surface must be clean and dry.

BARE WOOD: Prepare bare wood for staining by sanding in the direction of the grain with sandpaper until smooth.

REFINISHING OLD WOOD: Previous finishes will inhibit penetration of the stain. Remove all old finishes down to bare wood prior to application.

FINAL SURFACE PREPARATION: Wood must be free of dust, dirt, grease and oils. Use a tack cloth or vacuum cleaner to remove any dust or dirt from the wood. Surfaces must be dry before staining.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

LIMITATIONS OF USE

FOR INTERIOR USE ONLY. Do not apply when the air, coating or surface temperature is below 50°F (10°C).

WARNING! HARMFUL IF SWALLOWED. CAUSES EYE AND SKIN IRRITATION. MAY BE HARMFUL IF INHALED. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains material that can cause target organ damage. Do not breathe vapor or mist. Do not swallow. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. Keep container tightly closed and sealed until ready for use. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER. FIRST AID If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Contains water (7732-18-5), proprietary alkyd resin (Not available.), proprietary low molecular weight polyols (Not available.), 1-propoxypropan-2-ol (1569-01-3), Limestone (1317-65-3) Not photochemically reactive pursuant to SCAQMD Rule 102. Keep out of the reach of children. SEE MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.)(514) 645-1320 (Canada)01-800-00-21-400 (Mexico)