



FLOOD RESURFACER 100% Acrylic Stain

GENERAL DESCRIPTION

Provides a barefoot friendly texture\* that enhances the look of worn or weather wood and concrete. Designed for application on aged, rough concrete and structurally sound weathered wood (decks, stairs, posts, railings, and more); retaining walls; as well as, new concrete surfaces cured for 30 days and new wood. It is formulated to fill cracks up to 1/4". DO NOT APPLY TO: Wood that is rotted or loose, garage floors, driveways or any other area with vehicular traffic; submerged surfaces such as ponds, fountains or swimming pools; interior concrete surfaces. Not recommended for whole-house vertical surfaces such as stucco or wood siding.

\*WARNING – Darker colors may result in higher surface temperatures from direct sun exposure than light colors.

RECOMMENDED SUBSTRATES

Wood
Concrete

TINTING AND BASE INFORMATION

FLD922 Deep Base\*

\*Must be tinted. Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

PACKAGING

1 - Gallon (3.78 L)
3 - Gallon (11.34 L)

PRODUCT DATA

PRODUCT TYPE: 100% Acrylic
VOLUME SOLIDS: 47% +/- 2%
WEIGHT SOLIDS: 62% +/- 2%
VOC: <50 g/L (0.4 lbs./gal.)
WEIGHT/GALLON: 11.4 lbs. (4.8 kg) +/- 0.2 lbs. (91 g)

COVERAGE: Up to 75 sq. ft. (13.9 sq. meters) per gallon (3.78 Liters) in two coats depending on application technique, wood texture and porosity. Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Allow minimum of 6 hours for the first coat to dry. To apply the second coat, cut in around the edges of the entire surface again and roll out as for the first coat. Allow the final coat to dry 48 hours before foot traffic and 72 hours before replacing furniture or heavy objects. Cool or humid conditions require longer drying time. If surface remains tacky, allow more time to dry. Premature use will cause coating to fail. Avoid heavy use for 30 days to allow full cure to a hard finish.

To Recoat: 6 hours
For Pedestrian Service: 48 hours

Drying times listed may vary depending on temperature, humidity, film build, color and air movement.

CLEANUP: Clean brushes and tools with warm, soapy water.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

PERMISSIBLE TEMPERATURES DURING APPLICATION:

Material: 50 to 90°F (10 to 32°C)
Ambient: 50 to 90°F (10 to 32°C)
Substrate: 50 to 90°F (10 to 32°C)

FLASH POINT: Over 200°F (93°C)

FEATURES / BENEFITS

Features

100% Acrylic high performance coating

Great on wood and concrete decks, porches, sidewalks and more

Finely textured finish

Added Mildewcide and Algaecide package

Water repellent coating

Benefits

Locks down splinters, fills and bridges cracks up to 1/4"; Easy soap and water clean-up

Versatile coating suitable for multiple projects

Barefoot friendly texture and slip-resistant

Provides a mildew resistant finish

Protects wood from water damage

Read Label and Material Safety Data Sheet prior to use. See other cautions on last page.

## FLOOD RESURFACER 100% Acrylic Stain

## GENERAL SURFACE PREPARATION

**Failure to clean surface of dirt and contaminants will cause loss of adhesion (blistering and peeling).**

**Wood:** Surface must be clean, dry and free of loose wood/wood fibers, dirt, grease, mildew and algae. Complete ALL of the following steps: 1. Scrape to remove peeling paint/stain. 2. Replace rotting or severely damaged boards, remove all loose splinters. 3. Secure loose deck screws, raised nail heads or loose decking boards. 4. Clean with **FLOOD Wood Cleaner** and rinse well to remove cleaning product residue and contaminants. Repeat cleaning steps as many times as necessary to remove ALL dirt, mildew, grease and algae. 5. Pressure-wash using LOW to MODERATE pressure. (High pressure may damage wood surface and cause product to fail.) Allow wood to dry completely (minimum 24 hours). 6. Use coarse sandpaper to remove any loose wood fibers and then remove all sanding dust that will interfere with bonding. 7. Fill larger than hairline cracks and depressions with an exterior paintable sealant caulk.

**Concrete:** Complete ALL of the following steps: 1. Scrape away all loose/peeling previous coatings. 2. Clean with **FLOOD Wood Cleaner** and rinse. Repeat cleaning step until ALL surface contaminants (dirt, grease, mildew and algae) are completely removed. 3. Rinse well to remove cleaner residue or perform final rinse with a power washer. 4. Patch larger than hairline cracks and depressions with a polymeric concrete patching compound (follow manufacturer's instructions). Do not use caulks or other non-concrete patching compounds.

**WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.**

## APPLICATION INFORMATION

**BOTH WOOD AND CONCRETE SURFACES MUST BE COMPLETELY DRY.** Stir product thoroughly. DO NOT THIN. When using more than one can of the same color, intermix to ensure color uniformity. Apply with a high quality brush or 1/2" nap roller. **TWO COATS ARE REQUIRED.** Application of one coat or use of smaller nap roller will not build film thickness required to seal surface. Water will penetrate and peeling will result. DO NOT APPLY IF: Temperature is expected to fall below 50°F, or if rain is expected within 24 hours of each coat, as product will not cure properly and peeling will result. Do not apply above 90°F. Avoid staining in direct sunlight or on hot surfaces. Before applying first coat, dab a heavily loaded brush into cracks, gaps, nail/screw holes and knots until filled. Cut in around the edges of the deck or concrete surface with a brush using a short dabbing stroke. To apply the first coat, fully saturate the roller by rolling back and forth in the tray. A fully-loaded roller will cover an area of approximately 10-14 sq. ft. Using light and even pressure, apply product to a few boards or a few square feet at a time, keeping a wet edge to avoid lap marks. For cupped, cracked or warped boards, drive product into cracks by rolling across the narrow width as well as the length of the board. Lightly brush any product that drips between the boards. Back-brush after rolling for a smoother appearance. Please use caution when applying around aquatic habitats to avoid spills.

## LIMITATIONS OF USE

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight. **FOR EXTERIOR USE ONLY. PROTECT FROM FREEZING.**

## PRECAUTIONS

**WARNING! MAY CAUSE ALLERGIC RESPIRATORY REACTION.** Sanding and grinding dusts may be harmful if inhaled. Do not breathe vapor or mist. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information. FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. Call physician immediately. Keep out of the reach of children. For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. FLOOD and the FLOOD and Paintbrush Design are registered trademarks of PPG Industries, Inc. © 2015 PPG Industries, Inc. All Rights Reserved.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



PPG Industries, Inc.  
Architectural Coatings  
One PPG Place  
Pittsburgh, PA 15272  
[www.flood.com](http://www.flood.com)

Technical Services  
1-800-426-6306

Architect/Specifier  
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.  
2505, rue de la Métropole,  
Longueuil (Québec) Canada J4G 1E5

T.D. FLD922 12/2015

