



FLOOD®

FLD6C

FLOOD FLOETROL® Latex-Based Paint Additive

GENERAL DESCRIPTION

FLOETROL is a latex paint additive that makes interior and exterior latex or acrylic paint flow and level like oil-based paint while compensating for the adverse effects that weather and surface conditions have on paints and primers.

RECOMMENDED USES

Use in Latex or Water-Based Paints and Primers

PRODUCT INFORMATION

FLD6C

PACKAGING

946 mL- (Quart)
3.78 L- (Gallon)

PRODUCT DATA

PRODUCT TYPE: Latex
VOLUME SOLIDS: 10% +/- 2%
WEIGHT SOLIDS: 12% +/- 2%
VOC: <2% by wt. (<50 g/L)
WEIGHT/GALLON: 3.9 kg (8.5 lbs.) +/- 91 g (0.2 lbs.)

COVERAGE: Varies depending on use.

DRYING TIME: When added to paint, may increase the dry time of the paint. High humidity or temperatures below 10°C (50°F) may prolong drying and recoat time.

CLEANUP: Clean brushes and tools with warm, soapy water.

DISPOSAL: Consult your municipality about proper disposal procedure of residue in accordance with the laws and respect the environment. Do not pour down a drain or storm sewer.

PERMISSIBLE TEMPERATURES DURING APPLICATION:

Material: 10 to 32°C (50 to 90°F)
Ambient: 10 to 32°C (50 to 90°F)
Substrate: 10 to 32°C (50 to 90°F)

FLASH POINT: Over 93°C (200°F)

FEATURES

Eliminates brush and roller marks*.

Improves flow and levelling.

Improves the coverage and will not change the color or sheen of most paints.

Extends dry time.

Lubricates paint to reduce wear and tear on spray guns.

*Subject to the use of products in conformance to PPG's recommendations.

Before use, be sure to read and follow the instructions and warnings on the label and Safety Data Sheet. See other cautions on last page.

FLOOD FLOETROL Latex-Based Paint Additive

DIRECTIONS FOR INTERIOR AND EXTERIOR USE

DIRECTIONS FOR INTERIOR AND EXTERIOR USE: Shake container well. Always mix a small amount of Floetrol with paint to test compatibility. If compatible, add Floetrol to the latex or acrylic paint following these guidelines.

When Painting with a Brush or Roller: Add approximately 237 mL (8 oz.) per 3.78 L of paint. If paint is thick, or in extreme temperatures, more Floetrol may be gradually added, up to 473 mL (16 oz.) per 3.78 L. Stir Floetrol-paint mixture thoroughly. Paint as usual.

When Painting with a Cup Gun Sprayer: Floetrol acts as a stir-in lubricant. Helps cup guns work with latex or acrylic paints. Mix 118 to 237 mL (4 to 8 oz.) of Floetrol into each 946 mL of paint. The amount depends on the consistency and flow properties of the paint. Stir Floetrol-paint mixture thoroughly. Paint as usual.

NOTE: The amount of Floetrol added will not change the colour or sheen of most latex or acrylic paint. Floetrol may reduce the sheen in gloss paints.

Faux Finishing: Using an empty container or dispensable cup as a measuring device, mix 3 parts latex or acrylic paint to 1 part Floetrol. The more Floetrol you add to the mixture (glaze), the more open time you will have and the more translucent the finish will be. Do not add too much conditioner for vertical surfaces as technique may sag or vanish.

PRECAUTION: Dry sanding will give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. Wear suitable respiratory protective equipment when exposure cannot be avoided by adequate local ventilation. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact a regional Health Canada office for more information.

LIMITATIONS OF USE

Do not add too much conditioner for vertical surfaces as the technique may cause the paint to sag or vanish.

PROTECT FROM FREEZING.

PRECAUTIONS

MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE AND SKIN IRRITATION. Avoid breathing vapours, spray or mists. Avoid contact with skin and eyes. Wear protective gloves/clothing and eye/face protection. Keep out of reach of children. **Prior to use, read and follow product-specific SDS and label information.** **FIRST AID TREATMENT:** If swallowed, call a Poison Control Centre or doctor immediately. If in eyes or on skin, rinse well with water. If breathed in, move person to fresh air. Contains isothiazolinones. May cause allergic reaction. Keep container tightly closed and sealed until ready for use. For workplace use, an SDS is available from your retailer or by calling 1-800-463-7426 (Canada). **EMERGENCY SPILL INFORMATION:** (412) 434-4515 (U.S.), (514) 645-1320 (Canada).

LIMITED WARRANTY

PPG Architectural Coatings Canada, Inc. warrants performance of its products to its intended use if properly applied in accordance with the label directions and the specifications of the technical data sheet. Having no control over the application methods and conditions or the circumstances related to its use, no other warranty, expressed or implied, statutory or otherwise is given. This limited warranty extends only to the original purchaser of the product and is not transferable or assignable. If the product fails to conform to this limited warranty, we will, at your option, furnish replacement product or refund the purchase price. This limited warranty excludes (1) labour or costs of labour for the application or removal of any product and (2) all other direct, indirect, incidental, special, or consequential damages.

The *PPG Logo* is a registered trademark of PPG Industries Ohio, Inc. *Floetrol, Flood, and Flood and Paintbrush Design* are registered trademarks of PPG Architectural Finishes, Inc.

PPG Architectural Coatings Canada, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-866-660-2220.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.flood.com

Technical Services
1-866-660-2220

Architect/Specifier
1-888-PPG-IDEA

PPG Architectural Coatings Canada, Inc.
1550 rue Ampère, Suite 500
Boucherville (Quebec), J4B 7L4

FLD6C 6/2024