



Architectural Coatings

**GENERAL DESCRIPTION**

*Liquid Nails* Cove Base & Stair Tread Adhesive, CB-10, is a water-resistant, latex-based construction adhesive. It offers strong initial grab to minimize the need for bracing. CB-10 is designed specifically to bond vinyl or rubber cove base and stair treads.

**RECOMMENDED SUBSTRATES**

**Recommended for Bonding Vinyl or Rubber Cove Base & Stair Treads to:** Wood, Drywall, Plaster, Paneling, and Concrete

**FEATURES / BENEFITS**

Strong initial grab  
Minimizes need for bracing  
Water-resistant  
Easy water clean-up

**CONFORMANCE STANDARDS**

Compliant with all US VOC regulations for cove based adhesive category as of 04/2024

**PRODUCT INFORMATION / PACKAGING**

CB-10 10.0 FL OZ (295 mL) Tube (12 Tubes/Carton)

**LIMITATIONS OF USE**

Not recommended for uses other than cove base and stair tread installations, and bonding to nonporous surfaces.

Not for use on wood stair treads.

**FREEZE/THAW STABLE.** Store product at 40°F (4°C) to 100°F (38°C). **USE PRODUCT WITHIN ONE YEAR OF PURCHASE.**

*Liquid Nails* Cove Base & Stair Tread Interior Construction Adhesive**PRODUCT DATA****BASE:** Synthetic Rubber Latex**COLOR:** Tan**APPEARANCE:** Smooth paste**APPLICATION TEMPERATURE:** 60°F to 100°F (16°C to 38°C)**SERVICE TEMPERATURE:** -20°F to 140°F (-29°C to 60°C)**SAG:** None**SHEAR STRENGTH:** 24 hours – 100 psi  
48 hours – 130 psi  
7 days – 160 psi**WEIGHT PER GALLON:** 11.7 lbs. (5.31 kg)**VISCOSITY:** 550,000 cps**OPEN TIME:** 15 minutes at room temperature**MINIMUM CURE TIME:** 24 hours at room temperature**FREEZE/THAW STABILITY:** No effect after 5 cycles**FLAMMABILITY:** Non-flammable**FLASH POINT:** 205°F (96°C)**PERCENT VOLATILE:** 38% (includes water)**PERCENT SOLIDS:** 62%**COVERAGE:** 30 linear ft. (9 linear meters) using ¼" (6 mm) bead. Covers 16 linear ft. (4.5 linear meters) of 4" (10 cm) cove base using two ¼" (6 mm) beads.**SHELF LIFE:** One year from date of purchase**ODOR:** Mild Latex**MAX VOC:** < 7% by weight

## GENERAL SURFACE PREPARATION/APPLICATION

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**DIRECTIONS:** Surfaces must be clean, dry, and structurally sound. Lay cove strip flat for at least 24 hours prior to installation. Cut and prefit materials prior to installation. Do not apply at temperatures below 60°F (16°C). Cut nozzle, puncture inner seal, and insert tube into caulking gun. One surface must be porous. **Cove Base:** Apply two zigzag ¼" (6 mm) beads to cove base. Press or roll into place. Cove base may require bracing until adhesive sets. **Stair Treads:** Apply ¼" (6 mm) beads to stair treads 4" (10 cm) apart. Press into place.

**CLEANUP:** Use water for wet adhesive. Use mineral spirits or an adhesive remover for dry adhesive.

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product.

**PERMISSIBLE TEMPERATURES DURING APPLICATION:**

Material:	60 to 100°F	16 to 38°C
Ambient:	60 to 100°F	16 to 38°C
Substrate:	60 to 100°F	16 to 38°C

## PRECAUTIONS

**WARNING! HARMFUL IF INHALED. HARMFUL IF SWALLOWED.** Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces. Do not breathe vapor. Do not swallow. Do not get on skin or clothing. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust or particulates arising from the application of this preparation. Use personal protective equipment as required. **Prior to use, read and follow product-specific SDS and label information. FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. Call physician immediately. Contains isothiazolinones. May cause allergic reaction. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

© 2024 PPG Industries, Inc. All Rights Reserved. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc. Liquid Nails is a registered trademark of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.

