



OLYMPIC®

79002, 79003, 79004

**OLYMPIC WOOD PROTECTOR Waterproofing Sealant Toner****GENERAL DESCRIPTION**

OLYMPIC WOOD PROTECTOR Toner provides waterproofing protection with a slight hint of color that maintains or restores the natural beauty of weathered wood.

Recommended for use on properly prepared exterior wood, including decks, fences, siding, railings, outdoor furniture and other wood surfaces. May be used on new, dry, pressure-treated wood, uncoated new or weathered wood, or previously coated wood with a weathered, clear sealant or semi-transparent stain.

**RECOMMENDED USES**

Exterior wood surfaces	New wood
Decks	Pressure-treated wood
Fences	Weathered wood
Siding	Outdoor Furniture

**FEATURES / BENEFITS**

Waterproofing Protection  
SunBlock® UV Defense  
Exclusive Scuff Guard® Technology  
Provides Mildew Resistant Coating  
Easy Water Cleanup

**APPLICATION INFORMATION**

Stir thoroughly before and occasionally during use. When using more than one can of the same color, intermix to ensure color uniformity.

**Pretest:** Apply to a small area and allow to dry to ensure acceptable appearance and penetration. If the product is not absorbed into the surface and is still tacky after 12 hours, the surface is not suitable for a waterproofing sealant.

**Application Equipment:** Apply with a high quality brush, roller, paint pad or spray equipment.

**Application Method:** Apply one thin coat. When spraying or rolling, always back brush for best results. To help avoid lap-marks, apply to only a few boards at a time keeping a wet edge. Do not saturate or puddle on horizontal surfaces.

**Thinning:** Do not thin.

**Permissible temperatures during application:**

Material:	50 to 90°F	10 to 32°C
Ambient:	35 to 90°F	2 to 32°C
Substrate:	35 to 90°F	2 to 32°C

**PRODUCT INFORMATION**

79002	Honey Gold
79003	Cedar Naturaltone
79004	Redwood Naturaltone

DO NOT TINT.

**PRODUCT DATA**

<b>PRODUCT TYPE:</b>	Acrylic Oil
<b>VOLUME SOLIDS*:</b>	13% +/- 2%
<b>WEIGHT SOLIDS*:</b>	14% +/- 2%
<b>VOC*:</b>	83 g/L (0.7 lbs./gal.)
<b>WEIGHT/GALLON*:</b>	8.4 lbs. (3.8 kg) +/- 0.2 lbs. (91 g)

\*Product data calculated on 79003.

**COVERAGE:** Approximately 250 to 350 sq. ft. (23.2 to 32.5 sq. meters) per gallon (3.78 Liters) depending upon wood texture. One coat application is recommended.

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

**DRYING TIME:** Normally dries in 24 hours when applied in temperatures of 50°F (10°C) to 85°F (29°C). High humidity or low temperature application may prolong drying time. It is not recommended to apply product if rain is expected within 24 hours.

Drying times listed may vary depending on temperature, humidity, color and air movement.

**CLEANUP:** Clean brushes and tools with warm, soapy water.

**DANGER:** Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container. Refer to [www.ppgac.com](http://www.ppgac.com), Spontaneous Combustion Advisory for additional information.

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**FLASH POINT:** Over 200°F (93°C)

## OLYMPIC WOOD PROTECTOR Waterproofing Sealant Toner

## GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the *OLYMPIC* limited warranty to apply. All surfaces must be dry, clean, and free of dirt, dust, mildew, oil, loose wood fibers, and other contaminants. Previous coatings must be completely removed. Prior to sealant application, clean weathered, dirty, or mildewed surfaces with *OLYMPIC* Deck Cleaner. After rinsing, ensure surface is free to standing water. Remove grade stamps or pencil marks. by sanding.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**DECKS, FENCES OR SIDING:** Clean weathered, dirty or mildewed surfaces with *OLYMPIC* Deck Cleaner prior to applying product.

**PRETEST:** Test a small hidden area prior to application to ensure acceptable appearance and penetration.

**EXTRACTIVE BLEEDING:** Some woods, such as cedar and redwood, contain natural water-soluble colorings or extractives that tend to "bleed" or migrate to the surface. If extractive bleeding occurs, allow the coating to dry completely, then wash with a mild detergent solution and rinse with clear water.

## LIMITATIONS OF USE

Apply when air, and surface temperatures are 35°F to 90°F (2°C to 32°C and will remain above 35°F (2°C) for the next 24 hours. Avoid staining in direct sunlight or on hot surfaces. It is not recommended to apply product if rain is expected within 24 hours. FOR EXTERIOR USE ONLY.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

Not recommended for recently painted or sealed surfaces. Do not use on metallic, plastic, rubber, asphalt, tile, vinyl, concrete or any non-porous surface.

PROTECT FROM FREEZING.

## SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. High pressure injection of coatings into the skin by airless equipment may cause serious injury.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

## PACKAGING

1-Gallon (3.78 L)

5-Gallon (3.78L)

Not all products are available in all sizes.

The PPG logo is a registered trademark of PPG Industries Ohio, Inc. *OLYMPIC*, *OLYMPIC* design, *SunBlock* and *Scuff Guard* are registered trademarks of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate: however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



PPG Industries, Inc.  
Architectural Coatings  
One PPG Place  
Pittsburgh, PA 15272  
[www.olympic.com](http://www.olympic.com)

Technical Services  
1-800-426-6306

Architect/Specifier:  
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.  
4 Kenview Blvd  
Brampton, ON L6T 5E4

T.D. 79002 2/2014  
(Supersedes 10/2012)