

**OLYMPIC RESCUE IT!® Light Restoration Resurfacer + Sealant In One****GENERAL DESCRIPTION**

*OLYMPIC RESCUE IT!* Light Resurfacer + Sealant in One is designed for application on lightly worn concrete and structurally sound wood (decks, stairs, posts, railings, and more); retaining walls; as well as new concrete surfaces cured for 30 days and new wood. This 100% acrylic, high-performance coating conceals hairline cracks, helps prevent splinters and provides a safe, durable surface that resists fading and creates a mildew resistant coating. Ideal for decks, porches and sidewalks.

**RECOMMENDED SUBSTRATES**

Wood                                  Concrete

**APPLICATION INFORMATION**

**BOTH WOOD AND CONCRETE SURFACES MUST BE COMPLETELY DRY.** Stir product thoroughly. **TWO COATS ARE REQUIRED.** When using more than one can of the same color, intermix to ensure color uniformity.

**Application Equipment:** Apply two coats with a high quality brush or 1/2" nap roller.

**Application Method:** Application of one coat or use of smaller nap roller will not build film thickness required to seal surface. Water will penetrate and peeling will result. **DO NOT APPLY IF: Temperature is expected to fall below 50°F, or if rain is expected within 24 hours of each coat, as product will not cure properly and peeling will result. Do not apply above 90°F.** Before applying first coat, dab a heavily loaded brush into cracks, gaps, nail/screw holes and knots until filled. Cut in around the edges of the deck or concrete surface with a brush using a short dabbing stroke. To apply the first coat, fully saturate the roller by rolling back and forth in the tray. A fully-loaded roller will cover an area of approximately 10-14 sq. ft. Using light and even pressure, apply product to a few boards or a few square feet at a time, keeping a wet edge to avoid lap marks. **For cupped, cracked or warped boards, drive product into cracks by rolling across the narrow width as well as the length of the board.** Lightly brush any product that drips between the boards. Backbrush after rolling for a smoother appearance. Please use caution when applying around aquatic habitats to avoid spills.

**Thinning:** Do not thin.

**Permissible temperatures during application:**

Material:	50 to 90°F	10 to 32°C
Ambient:	50 to 90°F	10 to 32°C
Substrate:	50 to 90°F	10 to 32°C

**FEATURES / BENEFITS****Features**

High-performance coating based on 100% acrylic technology  
Conceals & Bridges hairline cracks & helps prevent splinters  
Great on wood and concrete decks, porches, sidewalks and more  
Slightly textured finish  
Resists cracking and peeling and provides a dual-action mildew resistant coating  
Water Resistant coating  
Premium latex formula

**Benefits**

Moves with natural expansion and contraction of the substrate  
Extends the life of time-worn wood and concrete  
Versatile coating suitable for multiple projects  
Barefoot friendly and slip-resistant  
Long-lasting finish  
Protects the substrate  
Easy soap and water cleanup

**TINTING AND BASE INFORMATION**

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

79704                                  Base 2\*

\*Must be tinted.

**PRODUCT DATA**

<b>PRODUCT TYPE:</b>	100% acrylic
<b>VOLUME SOLIDS:</b>	37% +/- 2%
<b>WEIGHT SOLIDS:</b>	51% +/- 2%
<b>VOC:</b>	<50 g/L (0.4 lbs./gal.)
<b>WEIGHT/GALLON:</b>	10.6 lbs. (4.8 kg) +/- 0.2 lbs. (91 g)

**COVERAGE:** Up to 100 sq. ft. (9.29 sq. meters) per U.S. gallon (3.78 Liters) in two coats.

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

**DRYING TIME: Allow minimum of 6 hours for the first coat to dry.** To apply the second coat, cut in around the edges of the entire surface again and roll out as for the first coat.

**Allow the final coat to dry 48 hours before foot traffic and 72 hours before replacing furniture or heavy objects.** Cool or humid conditions require longer drying time. **If surface remains tacky, allow more time to dry. Premature use will cause coating to fail. Avoid heavy use for 30 days to allow full cure to a hard finish.**

To Recoat:	6 hours
For Pedestrian Service:	48 hours

Drying times listed may vary depending on temperature, humidity, film build, color and air movement.

**CLEANUP:** Clean brushes and tools with warm soapy water.

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**FLASH POINT:** Over 200°F (93°C)

## OLYMPIC RESCUE IT! Light Restoration Resurfacer + Sealant In One

### GENERAL SURFACE PREPARATION

Failure to clean surface of dirt and contaminants will cause loss of adhesion (blistering and peeling).

**WOOD:** Surface must be clean, dry and free of loose wood/wood fibers, dirt, grease, mildew and algae. Complete ALL of the following steps: 1. Scrape to remove peeling paint/stain. 2. Replace rotting or severely damaged boards, remove all loose splinters. 3. Secure loose deck screws, raised nail heads or loose decking boards. 4. Clean with Olympic Premium Deck Cleaner and rinse well to remove cleaning product residue and contaminants. Repeat cleaning steps as many times as necessary to remove ALL dirt, mildew, grease and algae. 5. Pressure-wash using LOW to MODERATE pressure. (High pressure may damage wood surface and cause product to fail.) Allow wood to dry completely (minimum 24 hours). See "How to Prep" video on olympic.com for pressure-washing demonstration and details on drying time and dryness test.) 6. Use coarse sandpaper to remove any loose wood fibers and then remove all sanding dust that will interfere with bonding. (See "How to Prep" video on olympic.com for loose wood fiber test.) For more detailed instructions and "How to Prep" videos, please visit olympic.com 7. Fill larger than hairline cracks and depressions with an exterior paintable sealant caulk.

**CONCRETE:** Complete ALL of the following steps: 1. Scrape away all loose/peeling previous coatings. 2. Clean with Olympic Premium Deck Cleaner and rinse. Repeat cleaning step until ALL surface contaminants (dirt, grease, mildew and algae) are completely removed. 3. Rinse well to remove cleaner residue or perform final rinse with a power washer. 4. Patch larger than hairline cracks and depressions with a polymeric concrete patching compound (follow manufacturer's instructions). Do not use caulks or other non-concrete patching compounds. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

Both wood and concrete surfaces must be thoroughly dry before application and there should be no threat of rain for 24 hours. **Please use caution when applying around aquatic habitats to avoid spills.**

### LIMITATIONS OF USE

Apply when air temperatures are between 50°F (10°C) and 90°F (32°C). Do not apply if rain is expected within 24 hours of application. Both wood and concrete surfaces must be thoroughly dry before application.

**Do not apply to wood that is rotted or loose, garage floors, driveways, or any other areas with vehicular traffic. Do not use on submerged surfaces such as ponds, fountains, swimming pools or interior concrete surfaces.**

Rescue It! is not recommended for whole-house vertical surfaces such as stucco or wood siding.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

FOR EXTERIOR USE ONLY. PROTECT FROM FREEZING.

**WARNING! MAY CAUSE ALLERGIC RESPIRATORY REACTION.** Sanding and grinding dusts may be harmful if inhaled. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Do not breathe vapor or mist. Do not swallow. Do not get on skin or clothing. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. Call physician immediately. Keep out of the reach of children. For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. **EMERGENCY SPILL INFORMATION:** (412) 434-4515 (U.S.).

The PPG logo is a registered trademark of PPG Industries Ohio, Inc. OLYMPIC and OLYMPIC design, and RESCUE IT! are registered trademarks of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.

### SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

Please use caution when applying around aquatic habitats to avoid spills.

### PACKAGING

1-Gallon (3.78 L)

3-Gallon (11.3 L)



Olympic - US  
PPG Architectural Finishes, Inc.  
One PPG Place  
Pittsburgh, PA 15272  
[www.olympic.com](http://www.olympic.com)

Technical Services  
1-800-426-6306

Architect/Specifier  
1-888-PPG-IDEA

Olympic - Canada  
PPG Architectural Coatings Canada Inc.  
2505, rue de la Metropole  
Longueuil (Quebec) Canada J4G 1E5

T.D. 79704 3/2015