

**OLYMPIC ELITE Advanced Stain + Sealant In One Toner****GENERAL DESCRIPTION**

OLYMPIC ELITE Advanced Stain + Sealant in One is a super-premium stain formulated to unlock and protect wood's natural beauty with unrivaled richness and depth of color. OLYMPIC ELITE Toners are ready-mix colors that exclusively use transparent iron oxide pigments and deliver extreme clarity to enhance wood's natural grain with a slight hint of color.

Recommended for use on any properly prepared exterior wood, including decks, fences, siding, railings, outdoor furniture and other wood surfaces. Apply to new, dry, pressure-treated wood, uncoated new or weathered wood, or previously coated wood with a weathered, clear sealant, or semi-transparent stain.

**RECOMMENDED SUBSTRATES**

Wood

**APPLICATION INFORMATION**

**FOR EXTERIOR USE ONLY.** Stir thoroughly before and often during use. When using more than one can of the same color, intermix to ensure color uniformity.

Apply to new, dry, pressure-treated wood, uncoated new or weathered wood, or previously coated wood with a weathered, clear sealant or semi-transparent stain. Apply when air and surface temperatures are 35°F (2°C) to 90°F (32°C) and will remain above 35°F (2°C) for the next 24 hours.

**Pretest:** Apply to a small area and allow to dry to ensure acceptable appearance and penetration. If the product is not absorbed into the surface and is still tacky after 12 hours, the surface is not suitable for a waterproofing sealant.

**Application Method:** Apply one thin coat with a high quality brush, paint /stain pad, or by spray equipment. When applying by roller or spray, always back brush for best results. To help avoid lapmarks, apply to only a few boards at a time and maintain a wet edge.

**Thinning:** DO NOT THIN.

**Permissible temperatures during application:**

Material:	35 to 90°F	2 to 32°C
Ambient:	35 to 90°	2 to 32°C
Substrate:	35 to 90°	2 to 32°C

**FEATURES / BENEFITS****Features**

Advanced Stain + Sealant In One

Tinted with transparent iron oxides

Color Rich™ Technology

4-Season™ Protection Package

**Benefits**

Protect & Beautify in one step

Color & protection without sacrificing clarity

Color formulas that unlock the beauty of wood & maximize durability

Urethane-fortified resin combines strength & flexibility for toughness and resilience  
Enhanced waterproofing protection protects wood from water damage  
Exceptional UV resistance to slow color fade  
Provides our best mildew and algae resistant coating

**PRODUCT INFORMATION**

80013

Red Cedar

DO NOT TINT.

**PRODUCT DATA**

**VOLUME SOLIDS:** 17% +/- 2%

**WEIGHT SOLIDS:** 18% +/- 2%

**VOC:** <100 g/L (0.8 lbs./gal.)

**WEIGHT/GALLON:** 8.4 lbs. (3.8 kg) +/- 0.2 lbs. (91 g)

**COVERAGE:** Approximately 250 to 350 sq. ft. (23.2 to 32.5 sq. meters) per gallon (3.78 L) depending upon wood texture and porosity. Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

**DRYING TIME:** Normally dries in 24 hours when applied in optimal temperatures of 50°F (10°C) to 85°F (29°C). Application in high humidity or in temperatures below 50°F (10°C) may prolong drying and recoating times.

Allow 24 to 48 hours of drying time before light foot traffic or replacing furniture. It is not recommended to apply product if rain is expected within 24 hours.

Drying times listed may vary depending on temperature, humidity, film build, color and air movement.

**CLEANUP:** Clean brushes and tools with warm, soapy water

**DANGER:** Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container. Refer to [www.pittsburghpaints.com](http://www.pittsburghpaints.com), Spontaneous Combustion Advisory for additional information.

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**FLASH POINT:** Over 200°F (93°C)

**OLYMPIC ELITE Advanced Stain + Sealant In One Toner****GENERAL SURFACE PREPARATION**

Surface must be dry and clean. Remove all dust, dirt, mildew, oil, loose wood fibers, and other contaminants. Previous coatings must be completely removed. To ensure proper penetration, weathered, dirty or mildew stains should be cleaned with *OLYMPIC* Deck Cleaner prior to applying stain. After rinsing, allow wood to dry.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**DECKS:** Clean weathered, dirty or mildew stains with *OLYMPIC* Deck Cleaner prior to applying product.

**FENCES OR SIDING:** Remove mildew stains with *OLYMPIC* Deck Cleaner. Before use, be sure to read and follow the instructions and warnings on the label.

**PRETEST:** Test a small hidden area prior to application to ensure acceptable appearance and penetration.

**EXTRACTIVE BLEEDING:** Some woods, such as redwood and cedar contain natural water-soluble colorings or extractives that tend to "bleed" or migrate to the surface. If extractive bleeding occurs, allow the coating to dry completely, then wash with a mild detergent solution and rinse with clear water.

**LIMITATIONS OF USE**

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

Do not apply when air, material or surface temperatures are below 35°F (2°C). Avoid painting in direct sunlight or on hot surfaces. It is not recommended to apply product if rain is expected within 24 hours.

Not recommended for recently painted or sealed surfaces. Do not use on plastic, rubber, asphalt, tile, vinyl, concrete or any non-porous surface. **FOR EXTERIOR USE ONLY. PROTECT FROM FREEZING.**

**PACKAGING**

1-Gallon (3.78 L)

**SAFETY PRECAUTIONS**

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555. Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury. **USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.**

**PRECAUTIONS AND FIRST AID:** Sanding and grinding dusts may be harmful if inhaled. Inhalation of high concentrations of vapor may affect the central nervous system. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. Can enter lungs and cause damage. Keep away from heat and flame. Do not breathe vapor or mist. Do not swallow. Avoid contact with eyes. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH ELITE STAIN MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.** **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Keep out of the reach of children. For workplace use, an MSDS is available from your retailer or by calling (412) 492-5555. **EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).**

The PPG logo is a registered trademark of PPG Industries Ohio, Inc. *Olympic* and *Olympic Design* are registered trademarks and *Color Rich* and *4-Season* are trademarks of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



PPG Industries, Inc.  
Architectural Coatings  
One PPG Place  
Pittsburgh, PA 15272  
[www.olympic.com](http://www.olympic.com)

Technical Services  
1-800-426-6306

Architect/Specifier  
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.  
2505, rue de la Métropole,  
Longueuil (Québec) Canada J4G 1E5

T.D. 80013 6/2014

Made in the  
**USA**