



OLYMPIC ICON Interior Self Priming Semi-Gloss

GENERAL DESCRIPTION

OLYMPIC ICON Interior Self Priming paint applies with ease and delivers a highly durable finish that stands up to the daily wear and tear that happens inside a busy home. Ideal for use on properly prepared or previously painted interior walls or ceilings.

RECOMMENDED SUBSTRATES

Concrete/Masonry Block
Gypsum Wallboard-Drywall
Plaster
Wood

CONFORMANCE STANDARDS

AIM Architectural Industrial Maintenance
CARB California Air Resources Board
LADCO Lake Michigan Air Directors Consortium
OTC Ozone Transport Commission
SCQAMD South Coast Air Quality Management District
Meets MPI® approval in category #54, Latex, Interior, Semi-Gloss
(MPI Gloss Level 5)
Meets MPI Green Performance Standard (GPS-1 & GPS-2)

APPLICATION INFORMATION

Stir thoroughly before and occasionally during use. When using more than one can of the same color, intermix to ensure color uniformity.

Application Method: Apply with a high quality brush, roller, paint pad, or by spray equipment. Where necessary, apply a second coat. Allow each coat to dry before applying the next coat.

Application Equipment: For smooth surfaces, use a polyester nylon brush or 3/16" - 3/8" nap roller cover. For textured surfaces, use a nylon brush or roller designed for this purpose. If applied by spray, back-brushing or back-rolling is recommended. For airless spray application, use tip size 0.015" - 0.021" and pressure range of 1500 - 2000 psi.

Thinning: No thinning is usually required. If necessary, thin with up to 1/4 pint (118 mL) of water per U.S. gallon (3.78L) of paint.

Permissible temperatures during application:

Material:	50 to 90°F	10 to 32°C
Ambient:	50 to 90°F	10 to 32°C
Substrate:	50 to 90°F	10 to 32°C

FEATURES / BENEFITS

Features

Self priming
Scrubable and washable finish
Stain resistant
Zero VOC
Lifetime warranty
Provides mildew resistant coating
Excellent hide & coverage
Smooth finish
Resists sticking
Easy application & cleanup
100% acrylic latex

TINTING AND BASE INFORMATION

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

74901	Ultra White (Also Base 1)
72201C	Ultra White (Also Base 1)
74902	Base 2*
72202C	Base 2*
74903	Base 3*
72203C	Base 3*
74905	Base 5*
72205C	Base 5*

*Must be tinted before use.

Some colors, drastic color changes, or porous substrates may require more than one coat to achieve a uniform finish.

PRODUCT DATA

PRODUCT TYPE:	100% Acrylic Latex
SHEEN:	Semi-Gloss: 35 to 45 (60° Gloss Meter)
VOLUME SOLIDS*:	32% +/- 2%
WEIGHT SOLIDS*:	43% +/- 2%
VOC*:	0 g/L (0 lbs./gal.)
WEIGHT/GALLON*:	9.9 lbs. (4.5 kg) +/- 0.2 lbs. (91 g)

*Product data calculated on 74901, 72201C.

COVERAGE: One gallon (3.78 Liters) covers approximately 400 sq. ft. (37.2 sq. meters) on primed, smooth non-porous surfaces.

Wet Film Thickness:	4.0 mils
Wet Microns:	102
Dry Film Thickness:	1.3 mils
Dry Microns:	33

Coverage does not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Dry time @ 77°F (25°C); 50% relative humidity.

To Touch	1 hour
To Recoat:	4 hours
To Full Cure:	30 days

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

WASHING INSTRUCTIONS: Wait at least 14 days after painting before cleaning the surface with a non-abrasive mild cleaner.

CLEANUP: Wipe up spills immediately with a damp cloth or sponge. Wash brushes, rollers and other painting tools with soap and water immediately after use.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

Benefits

Combines the protection of paint with primer-like hide
Withstands repeated cleaning
Resistance to soiling from common household stains
Low odor
Customer satisfaction guarantee
Resists mold and mildew on the paint film
Covers most colors in two coats
Uniform even appearance
Resists sticking
Easy to apply and clean-up hands and tools
Excellent durability and washable finish

OLYMPIC ICON Interior Self Priming Semi-Gloss

GENERAL SURFACE PREPARATION

Surfaces to be coated must be dry, clean, sound, and free from all contamination including loose and peeling paint, dirt, grease, oil, wax, concrete curing agents and bond breakers, chalk, efflorescence, mildew, rust, product fines, and dust. Remove loose paint, chalk, and efflorescence by wire brushing, scraping, sanding, and/or pressure washing. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces. Feather back all rough edges to sound surface by sanding. Masonry and plaster surfaces must be allowed to cure for 30 days prior to painting. Uncoated substrates, repaired surfaces or lightly stained areas may require more than one coat. For severe stains, water marks, and other challenging conditions use the appropriate high-quality primer.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

CONCRETE/MASONRY BLOCK: Mortar should cure for at least 30 days and preferably 90 days prior to painting. Fill block with an appropriate block filler. Surfaces previously coated with water thinned cement-based paint must be prepared with extra care. If the material appears to be adhering tightly, a masonry sealer may be applied to seal the surface. Check adhesion by applying a piece of masking tape. If the sealer peels off and has loose particles, remove all chalking or crumbling material, re-seal and re-check adhesion.

GYPSUM WALLBOARD-DRYWALL: Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust prior to painting the substrate.

PLASTER: Plaster, hardcoat, skim coat, or other alkaline surfaces should be allowed to cure for at least 30 days prior to painting.

WOOD: Unpainted wood or wood in poor condition should be sanded smooth, wiped clean, then primed. Any knots or resinous areas must be primed before painting. Countersink all nails, putty flush with surface before painting.

LIMITATIONS OF USE

FOR INTERIOR USE ONLY. Apply when air, product, and surface temperatures are between 50°F (10°C) and 90°F (32°C).

Not recommended for use on floors. When *OLYMPIC ICON* is applied to an uncoated substrate, two coats are required, with the first coat acting as the primer. For stains, water marks, and challenging conditions use an appropriate high-quality primer.

PROTECT FROM FREEZING.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae.

SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. High pressure injection of coatings into the skin by airless equipment may cause serious injury.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

PACKAGING

Quart (946 mL)
1-Gallon (3.78 L)
5-Gallon (18.9L)

Not all products available in all sizes.

The PPG logo is a registered trademark of PPG Industries Ohio, Inc. *OLYMPIC* and *OLYMPIC* design are registered trademarks and *ICON* is a trademark of PPG Architectural Finishes, Inc. The *Master Painters Institute* and *MPI* are registered trademarks of Master Painters Institute, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



Olympic® - US
PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.olympic.com

Technical Services
1-800-426-6306

Architect/Specifier
1-888-PPG-IDEA

Olympic - Canada
PPG Canada, Inc.
Architectural Coatings
4 Kenview Blvd
Brampton, ON L6T 5E4

T.D. 74901, 72201C
4/2013