



## OLYMPIC® WOOD PROTECTOR Waterproofing Sealant Clear

## GENERAL DESCRIPTION

OLYMPIC® WOOD PROTECTOR Clear Sealant provides a clear finish to protect the natural beauty of your wood while allowing it to weather gray naturally. It's unique formula penetrates deep, enhancing the natural look of wood while it strengthens, protects, and conditions wood fibers. Recommended for use on exterior wood decks, fences, siding, railings, outdoor furniture and other wood surfaces. May be used on new wood, pressure-treated wood, weathered wood, and wood with a weathered solvent-based clear or semi-transparent stain.

## RECOMMENDED USES

Wood	Wood Shingles
Pressure-treated Wood	Railings
Decks	Plywood
Fences	Outdoor Furniture
Siding	

## FEATURES / BENEFITS

WaterGuard® Protection  
SunBlock® U.V. Protection  
Exclusive Scuff Guard® Formula  
Creates Mildew Resistant Coating

## DIRECTIONS FOR USE

FOR EXTERIOR USE ONLY Stir thoroughly before and often during use.

**Pretest:** Apply to a small area and allow to dry to ensure applicable appearance and penetration. If the product is not absorbed into the surface and is still tacky after 12 hours, the surface is not suitable for a waterproofing sealant.

## APPLICATION INFORMATION

**Application Method:** Apply one thin coat. To help avoid lap-marks, apply to only a few boards at a time keeping a wet edge. Do not saturate or puddle on horizontal surfaces.

**Application Equipment:** Apply with a high quality polyester brush, roller, or paint pad. When rolling, always back brush for best results.

**Thinning:** DO NOT THIN.

## PRODUCT INFORMATION

79030 Waterproofing Sealant Clear

DO NOT TINT.

## PRODUCT DATA

<b>PRODUCT TYPE:</b>	Alkyd / Linseed Oil Resin
<b>VOLUME SOLIDS:</b>	26% +/- 2%
<b>WEIGHT SOLIDS:</b>	30% +/- 2%
<b>VOC:</b>	574 g/L (4.8 lbs./gal.)
<b>WEIGHT/GALLON:</b>	6.9 lbs. (3.1 kg) +/- 0.2 lbs. (91 g)
<b>FLASH POINT:</b>	108°F (42°C)

**COVERAGE:** Approximately 250 to 350 sq. ft. (23.2 to 32.5 sq. meters) per gallon (3.78 Liters) depending upon wood texture. One coat application is recommended.

Coverage does not include variation due to application methods, surface porosity, and/or mixing.

**DRYING TIME:** Normally dries in 24 hours when applied in temperatures of 50°F (10°C) to 85°F (29°C). High humidity or low temperature application may prolong drying time.

Drying times listed may vary depending on temperature, humidity and air movement.

**CLEAN UP:** Clean brushes and equipment immediately with mineral spirits.

**DANGER:** RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER. REFER TO WWW.PITTSBURGHPAINTS.COM, SPONTANEOUS COMBUSTION ADVISORY FOR ADDITIONAL INFORMATION.

## OLYMPIC® WOOD PROTECTOR Waterproofing Sealant Clear

## GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the OLYMPIC limited warranty to apply. All surfaces must be dry, clean, and free of dirt, dust, oil, mildew, and other contaminants. Remove grade stamps, pencil marks, etc. by sanding. Remove loose, peeling stain and loose wood fibers by sanding, scraping or wire brushing.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**DECKS, FENCES OR SIDING:** Clean weathered, dirty or mildewed surfaces prior to applying product.

**PRETEST:** Test a small hidden area prior to application to ensure acceptable appearance and penetration.

**EXTRACTIVE BLEEDING:** Some woods, such as cedar and redwood, contain natural water-soluble colorings or extractives that tend to "bleed" or migrate to the surface. If extractive bleeding occurs, allow the coating to dry completely, then wash with a mild detergent solution and rinse with clear water.

## LIMITATIONS OF USE

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

Do not apply when air, coating or surface temperatures are below 50°F (10°C). Avoid application in direct sunlight or on hot surfaces. It is not recommended to apply product if rain is expected within 24 hours.

Not recommended for recently painted or sealed surfaces. Do not use on metallic, plastic, rubber, asphalt, tile, vinyl, concrete or any non-porous surface. FOR EXTERIOR USE ONLY.

## SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

Keep containers closed and away from heat, sparks, and flames when not in use.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

## PACKAGING

1-Gallon (3.78 L)  
5-Gallon (18.9 L)

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



Olympic - US  
PPG Industries, Inc.  
Architectural Coatings  
One PPG Place  
Pittsburgh, PA 15272  
[www.olympic.com](http://www.olympic.com)

Technical Services  
1-800-426-6306

Architect/Specifier:  
1-888-PPG-IDEA

Olympic - Canada  
PPG Canada, Inc.  
Architectural Coatings  
4 Kenview Blvd  
Brampton, ON L6T 5E4

T.D. 3541 1/2008  
(Supersedes 11/2007)