



Architectural Coatings

PPG Deck Cleaner

GENERAL DESCRIPTION

PPG Deck Cleaner, with its S-74 deep cleaning formula, is a unique, premium quality product for restoring the clean, natural look to exterior wood and other surfaces. It cleans stains caused by mildew, dirt, algae and mold without scrubbing. Unlike bleach alone, PPG Deck Cleaner penetrates deep into the wood and lifts dirt to the surface to be rinsed away. This product contains no phosphates, acids, solvents or petroleum distillates. Recommended for use on exterior decks, wood siding, shakes, shingles and fences. Also recommended for use on concrete, brick, stucco, tile and vinyl.

RECOMMENDED SUBSTRATES / USES

Brick	Concrete
Decks	Fences
Stucco	Wood Siding
Shingles	Shakes
Tile	Vinyl

FEATURES / BENEFITS

Fast and easy to use - no scrubbing
Penetrates deep and lifts dirt to the surface to be rinsed away.
Cleans stains caused by mildew, dirt, algae and mold.
Ready to use - no mixing
Biodegradable
Test in a small, inconspicuous area before application. May cause redwood and cedar to darken or develop a hazy appearance.

LIMITATIONS OF USE

Application of this product may cause a fuzzy appearance to wood previously damaged by pressure washing or excessive weathering. Application to new wood or newly sealed wood may cause spotting and discoloration. May cause redwood to darken. Test in a small, inconspicuous area before application. Do not allow PPG Deck Cleaner to come into contact with metal, fabric, floor coverings, or lawn furniture. Do not mix with any other chemicals or cleaners as hazardous fumes may result.

DIRECTIONS FOR USE

Stir thoroughly. When using more than one can of the same color, mix together (box) before applying. **USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.** Read all label and Material Safety Data Sheet (MSDS) information prior to use. MSDS are available through our website or by calling 1-800-441-9695.

Permissible temperatures during application:

Material:	50 to 120°F	10 to 49°C
Ambient:	50 to 100°F	10 to 38°C
Substrate:	50 to 100°F	10 to 38°C

TINTING AND BASE INFORMATION

Not applicable

18-2 PPG Deck Cleaner

PRODUCT DATA

PRODUCT TYPE:	Water / Sodium Hypochlorite
SHEEN:	Not applicable for this product code
CLEAN UP:	Soap and Water
DFT:	0.10 minimum to 0.20 maximum mils
COVERAGE:	250 to 300 sq. ft./gal. (23 to 27 sq. m/3.78L)
Coverage does not include variation due to application methods, surface porosity, and/or mixing.	
WEIGHT/GALLON:	8.9 lbs. (4.1 kg) +/- 0.2 lbs. (91 g)
FLASH POINT:	212°F (100°C)

PPG Deck Cleaner

Architectural Coatings

GENERAL SURFACE PREPARATION

PREPARING THE SPRAY AREA: Spray all surrounding plants and vegetation liberally with water before and after application. Cover delicate vegetation to avoid damage. Do not allow PPG Deck Cleaner to come into contact with metal, fabric, floor coverings, or lawn furniture.

APPLICATION DIRECTIONS: Always test a small hidden area, rinse and let dry before using this product. Surfaces must be completely dry. Use a PPG Deck Care Sprayer or a plastic pump-style garden sprayer. Liberally apply PPG Deck Cleaner at full strength to the area you intend to clean. Wait 5 - 10 minutes. No scrubbing necessary. Thoroughly rinse treated surface and surrounding areas with large amounts of water to neutralize cleansing action.

PERIODIC CLEANING OF COMPOSITE DECKS: Liberally apply PPG Deck Cleaner and work into surface with a stiff brush. Rinse, let dry, apply a second application if needed. Slight yellowing of the deck is normal and will fade in a matter of days.

CLEANUP: Rinse spray equipment thoroughly with water.

STORAGE AND DISPOSAL: Store in a cool dry location. Avoid exposure to sunlight. Store in an upright position. Keep from freezing. Do not reuse container. Rinse container thoroughly before disposal.

RECOMMENDED PRIMERS

None. Refer to Surface Preparation Recommendations

APPLICATION INFORMATION

Application Equipment: Use a PPG Deck Care Sprayer or a plastic pump-style garden sprayer.

PACKAGING

2.5 Gallon (9.46L)

Not all products are available in all sizes.

PPGAF believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-441-9695.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.pittsburghpaints.com

Technical Services
1-800-441-9695
1-888-807-5123 fax

Architect/Specifier:
1-888-PPG-IDEA

PPG Architectural Finishes
400 S. 13th Street
Louisville, KY 40203

PPG Canada, Inc.
Architectural Coatings
4 Kenview Blvd
Brampton, ON L6T 5E4

B1.11 6/2006