

Architectural Coatings

SUN-PROOF® Composite Deck Stain Acrylic/Oil Semi-Transparent

GENERAL DESCRIPTION

SUN-PROOF® Composite Deck Stain Acrylic/Oil Semi-Transparent is formulated to add subtle color to restore the original look of composite decking. Recommended for use on exterior composite decks, railings, privacy panels, and other composite surfaces. For use on composite decking that has been weathered for at least 12 months.

RECOMMENDED SUBSTRATES

Composite Decks
Privacy Panels
Railings

FEATURES / BENEFITS

Restores the Look of Composite Decking and Railings
Enhanced Acrylic Formulation for Extended Durability
Superior Adhesion Properties
Provides a Mildew Resistant Coating
Soap & Water Cleanup
Application Down to 35°F (2°C)

LIMITATIONS OF USE

Apply only when air and surface temperatures are 35°F (2°C) or above and when the air and surface temperatures will remain above 35°F (2°C) for the next 24 hours. Avoid staining late in the day when dew and condensation are likely to form or if rain is expected within 24 hours. Avoid staining in direct sunlight or on hot surface. PROTECT FROM FREEZING. For use on composite decking that has been weathered for at least 12 months.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

DIRECTIONS FOR USE

Stir thoroughly before using and often during use. Test a small area to ensure acceptable appearance. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Material Safety Data Sheet (MSDS) information prior to use. MSDS are available through our website or by calling 1-800-441-9695.

Permissible temperatures during application:

Material:	50 to 85°F	10 to 29°C
Ambient:	35 to 85°F	2 to 29°C
Substrate:	35 to 85°F	2 to 29°C

TINTING AND BASE INFORMATION

Use PITTSBURGH® Paints Custom Colorants to achieve hundreds of colors. Refer to THE VOICE OF COLOR® formula book for tinting instructions.

77-2100 Neutral Base

Must be tinted before use.

PRODUCT DATA

PRODUCT TYPE:	Acrylic / Oil Resin
VOLUME SOLIDS:	23% +/- 2%
WEIGHT SOLIDS:	29% +/- 2%
VOC:	236 g/L (2.0 lbs./gal.)
WEIGHT/GALLON:	9.0 lbs. (4.1 kg) +/- 0.2 lbs. (91 g)
COVERAGE:	Approximately 250 to 350 sq. ft./gal. (23.2 to 32.5 sq. m/3.78L) depending upon surface texture and porosity.

Coverage does not include variation due to application methods, surface porosity, and/or mixing.

DRYING TIME: Normally dries in 24 hours when applied in temperatures of 50°F (10°C) to 85°F (29°C). High humidity, low temperature, or color may prolong drying time.

CLEAN UP: Clean brushes and tools with warm soapy water.

DANGER: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container. Refer to www.pittsburghpaints.com, Spontaneous Combustion Advisory for additional information.

FLASH POINT: 200°F (93°C)

GENERAL SURFACE PREPARATION

Surface must be clean, dry, and free of dust, dirt, mildew, oil, and other contaminants. Smooth surfaces must be sanded with coarse to medium sandpaper to aid in adhesion. Clean weathered, dirty or mildewed surfaces with PPG Deck Cleaner prior to applying product. Remove grade stamps, pencil marks, etc. by sanding.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

Test a small area to ensure acceptable appearance and adhesion. Intermit containers to ensure color uniformity. Apply one thin coat. To help avoid lapmarks, apply to only a few boards at a time keeping a wet edge.

RECOMMENDED PRIMERS

No primer required.
Refer to Surface Preparation Recommendations.

APPLICATION INFORMATION

Application Equipment: Apply one thin coat with a high quality polyester brush, roller, or paint pad. To help avoid lap marks, apply to only a few boards at a time keeping a wet edge.

Brush: Polyester / Nylon Brush

Thinning: No thinning is usually required.

PACKAGING

1-Gallon (3.78 L)
5-Gallon (18.9 L)

PPGAF believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-441-9695.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.pittsburghpaints.com

Technical Services
1-800-441-9695
1-888-807-5123 fax

Architect/Specifier:
1-888-PPG-IDEA

PPG Architectural Finishes
400 S. 13th Street
Louisville, KY 40203

PPG Canada, Inc.
Architectural Coatings
4 Kenview Blvd
Brampton, ON L6T 5E4

C2.23 1/2007