

MATERIAL SAFETY DATA SHEET

PPG PITTBULL BBQ STOVE BLACK 55-631

1. Product And Company Identification			
Supplier PPG Architectural Finishes, Inc One PPG Place Pittsburgh, PA 15272 Company Contact: Technical Service Telephone Number: 1-800-441-9695 FAX Number: 1-888-807-5123		Manufacturer Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA Company Contact: Aludia B. Hernandez Telephone Number: 708-865-1000 FAX Number: 708-865-0923 E-Mail: sales@chaseproducts.com Web Site: www.chaseproducts.com	
Supplier Emergency Contacts & Phone Number None Given		Manufacturer Emergency Contacts & Phone Number Chem-Tel: 1-800-255-3924	
Issue Date: 12/17/2001 Product Name: PPG PITTBULL BBQ STOVE BLACK 55-631 Chemical Name: 6-6065 CAS Number: Not Established MSDS Number: 1293 Product Code: 55-631 (429-1370) Product/Material Uses - Spray Paint			
2. Composition/Information On Ingredients			
Ingredient Name	CAS Number		Percent Of Total Weight
ACETONE	67-64-1		30 - 35
BONE BLACK	8021-99-6	<	1
BUTANE	106-97-8		10 - 15
PROPANE	74-98-6		15 - 20
MINERAL SPIRITS	8052-41-3		5 - 10
TOLUENE	108-88-3		15 - 20
The ingredients listed on this section are only the hazardous components of the product.			
3. Hazards Identification			
Primary Routes(s) Of Entry - Ingestion (possible, but considered unlikely), eye contact, skin contact, inhalation. Eye Hazards - Causes eye irritation. Skin Hazards - Causes skin irritation. Ingestion Hazards - This is an aerosol product, ingestion is unlikely to occur. Contains petroleum distillate, harmful if swallowed. If accidentally swallowed, do not induce vomiting. Call physician immediately. Inhalation Hazards - Deliberate inhalation of concentrate vapor or mist may cause headache, dizziness and nausea. May cause irritation of the respiratory tract. Irritant to skin on prolonged contact. Irritant to eyes on contact. Chronic/Carcinogenicity Effects - Toluene has been associated with kidney and liver disorders. Contains a small amount of carbon black (from bone black), IARC has classified carbon black as possible human carcinogen (group 2B). May contain ethylbenzene, IARC has evaluated and classified ethylbenzene as a possible human carcinogen (group 2B) based on sufficient evidence of carcinogenicity in animals, but inadequate evidence for cancer in exposed humans. Epidemiology - None known Teratogenicity (Birth Defects) - California's Proposition 65: "Warning: this product contains toluene, a chemical known to the State of California to cause birth defects or other reproductive harm". Reproductive Effects - Suspect reproductive hazard. Contains material which may cause birth defects, based on			

MATERIAL SAFETY DATA SHEET

PPG PITTBULL BBQ STOVE BLACK 55-631

3. Hazards Identification - Continued

animal data. This product contains toluene.

Neurotoxicity - None known


Mutagenicity (Genetic Effect) - None known

Signs And Symptoms - Acute: Prolonged inhalation of vapor or mist may cause headache, dizziness and nausea. May cause irritation of the respiratory tract. Prolonged contact with the skin causes irritation. Irritant to eyes.

Conditions Aggravated By Exposure - Pre-existing skin, respiratory, liver and kidney disorders.

Conditions Aggravated By Overexposure - Pre-existing skin, respiratory, liver and kidney disorders.

First Aid (Pictograms)



4. First Aid Measures

Eye - Flush from eyes with plenty of water. If irritation develops, consult a physician.

Skin - Wash skin with soap and water. If irritation develops, consult a physician.

Ingestion - Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates. Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician immediately.

Inhalation - If overcome by vapor move victim to fresh air. Provide artificial respiration if necessary. Consult a physician if injury develops.

5. Fire Fighting Measures

Flash Point: <20 °F

Flash Point Method: estimated

Lower Explosive Limit: Not available

Upper Explosive Limit: Not available

Fire And Explosion Hazards - This product is an aerosol product for which **Flame Projection is 18 in, with flashback.** Temperatures above 120 F may cause cans to burst.

Extinguishing Media - Use CO2 (Carbon Dioxide), dry chemical, or water fog.

Fire Fighting Instructions - Water spray may be used to cool cans in the vicinity of fire or excessive heat.

6. Accidental Release Measures

Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

Handling & Storage (Pictograms)



7. Handling And Storage

Handling And Storage Precautions - Handle as an extremely flammable material. Store in a cool, dry place away from heat and open flame.

Handling Precautions - Avoid getting spray into eyes. Avoid prolonged contact with skin. Keep out of reach of children.

Storage Precautions - Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

AEROSOL STORAGE LEVEL III (NFPA-30B)

Work/Hygienic Practices - Wash hands thoroughly after using this product.

MATERIAL SAFETY DATA SHEET

PPG PITTBULL BBQ STOVE BLACK 55-631

Protective Clothing (Pictograms)



8. Exposure Controls/Personal Protection

Engineering Controls - Use with adequate general and local exhaust ventilation.

Eye/Face Protection - Conventional eyeglasses to guard against splashing.

Skin Protection - Rubber, vinyl or household type gloves.

Respiratory Protection - Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or use an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully.

Ingredient(s) - Exposure Limits

ACETONE

ACGIH TLV-STEL 750 ppm ; ACGIH TLV-TWA 500 ppm ; OSHA PEL-TWA 1,000 ppm

BONE BLACK

OSHA PEL NA ; ACGIH TLV NA

BUTANE

ACGIH TLV-TWA 800 ppm

PROPANE

ACGIH TLV-TWA 2500 ppm ; OSHA PEL-TWA 1,000 ppm

MINERAL SPIRITS

ACGIH TLV-TWA 100 ppm ; OSHA PEL-TWA 500 ppm

TOLUENE

ACGIH TLV-TWA 50 ppm (Skin) ; OSHA PEL-CEILING 300 ppm ; OSHA PEL-PEAK 500 ppm

OSHA PEL-TWA 200 ppm

9. Physical And Chemical Properties

Appearance - Appearance of paint.

Odor - Paint odor.

Chemical Type: Mixture

Physical State: Liquid

Melting Point: Not applicable °F Not applicable °C

Boiling Point: Acetone 113 °F Acetone 56 °C

Specific Gravity: 0.874

Percent VOCs: 53.33

Solubility: Insoluble

Evaporation Rate: Faster than butyl acetate

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability) - Temperatures above 120 F

Incompatible Materials - Avoid heat, open flame and contact with strong oxidizers.

Hazardous Decomposition Products - Thermal decomposition may yield gases like carbon monoxide and carbon

MATERIAL SAFETY DATA SHEET

PPG PITTBULL BBQ STOVE BLACK 55-631

10. Stability And Reactivity - Continued

dioxide.

Conditions To Avoid (Polymerization) - Temperatures above 120 F

11. Toxicological Information

Chronic/Carcinogenicity - This product contains a small amount of carbon black (from bone black). Carbon black's carcinogenicity in animals and humans is inconclusive.

12. Ecological Information

No Data Available...

13. Disposal Considerations

Wrap empty container in newspaper and dispose of it in non-incinerated trash only.

14. Transport Information

Proper Shipping Name - ORM-D Consumer Commodity

DOT Identification Number

UN1950

DOT Shipping Label

Aerosol Consumer Commodity

15. Regulatory Information

U.S. Regulatory Information - All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard; Chronic Health Hazard; Fire Hazard

SARA Section 313 Notification - This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material. Toluene. See section 2 for % amounts in the product.

Ingredient(s) - U.S. Regulatory Information

TOLUENE

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

Ingredient(s) - State Regulations

ACETONE

New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

BUTANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

PROPANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

MATERIAL SAFETY DATA SHEET

PPG PITTBULL BBQ STOVE BLACK 55-631

15. Regulatory Information - Continued

Ingredient(s) - State Regulations - Continued


MINERAL SPIRITS

New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

TOLUENE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; California - Proposition 65; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

NFPA



HMIS

HEALTH	*2
FLAMMABILITY	4
REACTIVITY	1
PERSONAL PROTECTION	B

16. Other Information

Revision/Preparer Information

MSDS Preparer: Laura E. Radevski

MSDS Preparer Phone Number: 708-865-1000

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

PPG Architectural Finishes, Inc

Printed Using MSDS Generator™ 2000