

Architectural Coatings

WallHide® Interior Eggshell Acrylic Latex Paint

GENERAL DESCRIPTION

Our quality interior eggshell latex formulated to serve as our workhorse eggshell product to meet high-end commercial, residential repaint and consumer needs. WallHide Interior Eggshell is formulated to provide great hiding, resistance to stains and has good application properties. Effective application down to 50°F (10°C). Recommended for use on properly prepared on wallboard, wood, metal, cured plaster, and masonry surfaces.

RECOMMENDED SUBSTRATES

| | |
|---|--------------------------|
| Concrete/Masonry Block (block fillers) | Ferrous Metal |
| Concrete/Masonry Block (primers/sealers) | Gypsum Wallboard-Drywall |
| | Wood |

CONFORMANCE STANDARDS

- VOC compliant in all regulated areas
- Can help earn LEED 2009 credits

APPLICATION INFORMATION

Stir thoroughly before and occasionally during use. When using more than one can of the same color, intermix to ensure color uniformity. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Material Safety Data Sheet (MSDS) information prior to use. MSDS are available through our website or by calling 1-800-441-9695.

Application Equipment: Apply with a high quality brush, roller, paint pad, or by spray equipment. Where necessary, apply a second coat.

Airless Spray: Pressure 2000 psi, tip 0.015" - 0.021"
Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

Brush: Polyester/Nylon Brush
Roller: 3/8" - 3/4" nap roller cover.

Thinning: No thinning is usually required. If necessary add up to 1/4 pint (118 mL) of water per gallon (3.78 L) of paint.

Permissible temperatures during application:

| | | |
|------------|-------------|------------|
| Material: | 50 to 90°F | 10 to 32°C |
| Ambient: | 50 to 100°F | 10 to 38°C |
| Substrate: | 50 to 100°F | 10 to 38°C |

FEATURES AND BENEFITS

Features

Less than 50 g/L VOC
Good hiding power and coverage
Good stain resistance
Low spatter
Good adhesion
Good coalescence at 50°F(10°C)
Good scrubability
Good burnish resistance
Can help earn LEED 2009 credits

Benefits

Meets the most stringent environmental regulations nationwide
Hides surface imperfections
More resistant to spillage or soiling from common household products than flats
Less clean-up needed
Sticks to difficult substrates
More robust at application providing a smooth application
Withstands repeated cleaning
Shine free finish at the site of washing
Contributes to sustainable design

TINTING AND BASE INFORMATION

Refer to the appropriate color formula book, automatic tinting equipment and or computer color matching system for color formulas and tinting instructions.

| | |
|--------|---------------------|
| 80-310 | White & Pastel Base |
| 80-320 | Midtone Base* |
| 80-340 | Ultra Deep Base* |

*Must be tinted before use.

Some colors, drastic color changes, or porous substrates may require more than one coat to achieve a uniform finish.

PRODUCT DATA

| | |
|------------------------|-------------------------|
| PRODUCT TYPE: | Vinyl Acrylic Latex |
| SHEEN: | Eggshell |
| VOLUME SOLIDS*: | 35% +/- 2% |
| WEIGHT SOLIDS*: | 48% +/- 2% |
| VOC*: | <50 g/L (0.4 lbs./gal.) |

WEIGHT/GALLON*: 10.5 lbs. (4.8 kg) +/- 0.2 lbs. (91 g)

*Product data calculated on product 80-310.

COVERAGE*: Approximately 400 sq. ft./gal. (37.2 sq. m/3.78L)

| | |
|---------------------|----------|
| Wet Film Thickness: | 4.0 mils |
| Wet Microns: | 102 |
| Dry Film Thickness: | 1.4 mils |
| Dry Microns: | 36 |

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Dry time @ 77°F (25°C); 50% relative humidity.

| | |
|------------|---------|
| To Touch: | 1 hour |
| To Recoat: | 4 hours |

Drying times listed may vary depending on temperature, humidity, film build, color and air movement.

CLEANUP: Soap and Water

WASHING INSTRUCTIONS: Wait at least 14 days after painting before cleaning the surface with a non-abrasive mild cleaner.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

GENERAL SURFACE PREPARATION

Surfaces to be coated must be dry, clean, sound, and free from all contamination including loose and peeling paint, dirt, grease, oil, wax, concrete curing agents and bond breakers, chalk, efflorescence, mildew, rust, product fines, and dust. Remove loose paint, chalk, and efflorescence by wire brushing, scraping, sanding, and/or pressure washing. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces. Feather back all rough edges to sound surface by sanding. Prime all bare and porous substrates with an appropriate primer.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

CONCRETE/MASONRY BLOCK: Mortar should cure for at least 30 days and preferably 90 days prior to priming. Fill block with an appropriate block filler. Surfaces previously coated with water thinned cement-based paint must be prepared with extra care. If the material appears to be adhering tightly, a masonry sealer may be applied to seal the surface. Check adhesion by applying a piece of masking tape. If the sealer peels off and has loose particles, remove all chalking or crumbling material, re-seal and re-check adhesion.

FERROUS METAL: The surface must be cleaned thoroughly to remove any dust, rust, and surface contaminants, and then primed.

GYPSUM WALLBOARD-DRYWALL: Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust, then prime prior to painting the substrate.

WOOD: Unpainted wood or wood in poor condition should be sanded smooth, wiped clean, then primed. Any knots or resinous areas must be primed before painting. Countersink all nails, putty flush with surface, then prime.

RECOMMENDED PRIMERS

| | |
|---|----------------------------|
| Concrete/Masonry Block (block fillers) | 6-7, 6-15 |
| Concrete/Masonry Block (primers/sealers) | 4-603, 17-921 |
| Ferrous Metal | 90-712, 90-912 |
| Gypsum Wallboard-Drywall | 6-2, 6-4, 9-900, 12-900 |
| Wood | 6-2, 9-900, 12-900, 17-921 |

LIMITATIONS OF USE

FOR INTERIOR USE ONLY. Apply when air, surface and product temperatures are between 50°F (10°C).

PROTECT FROM FREEZING.

Not recommended for use on floors or in high humidity areas.

PACKAGING

1-Gallon (3.78 L)
5-Gallon (18.9 L)
1 Quart (946 mL)

Not all products are available in all sizes.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-441-9695.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.ppgpittsburghpaints.com
www.ppgporterpaints.com

Technical Services
1-800-441-9695
1-888-807-5123 fax

Architect/Specifier
1-888-PPG-IDEA

PPG Canada, Inc.
Architectural Coatings
4 Kenview Blvd
Brampton, ON L6T 5E4

A3.43 5/2013
(Supersedes 1/2012)

Made in the
USA