

**ULTRA ADVANCED Deck, Fence & Siding Solid Color Stain**

**GENERAL DESCRIPTION**

Guaranteed to be our best stain, PITTSBURGH PAINTS® ULTRA ADVANCED Solid Color stain and sealant in one is exceptionally durable and easy to apply, and is available in an extraordinary range of rich, attractive colors. Best in quality, Ultra Advanced will safeguard and enhance the natural beauty of exterior wood surfaces in the harshest conditions, with excellent durability and waterproofing protection, Ultra SunBlock® UV and Scuff Guard® protection while providing a mildew resistant coating. Simply our best – guaranteed!

**RECOMMENDED SUBSTRATES**

Exterior wood surfaces	New wood
Decks	Pressure-treated wood
Siding	Weathered wood
Fences	Outdoor furniture
Previously stained or painted wood	

**FEATURES / BENEFITS**

- Stain and sealant in one - protect and beautify in one step
- Excellent durability & waterproofing protection
  - Ultra *SunBlock* UV and *Scuff Guard* protection
  - Provides a mildew-resistant coating
  - 100% Acrylic formula
  - Ready for immediate use on new, dry, pressure-treated wood
  - Application down to 35°F

**APPLICATION INFORMATION**

**FOR EXTERIOR USE ONLY.** Stir thoroughly and often during use. When using more than one can of the same color, intermix to ensure color uniformity.

**Pretest:** Test a small hidden area prior to application to ensure acceptable appearance and penetration.

**Application Equipment:** Apply with a high quality polyester brush, roller, paint pad, or by spray equipment.

Apply two coats. When spraying or rolling, always backbrush for best results. To help avoid lap marks, apply to only a few boards at a time keeping a wet edge.

**Thinning:** Do not thin.

**Permissible temperatures during application:**

Material:	35 to 90°F	2 to 32°C
Ambient:	35 to 90°F	2 to 32°C
Substrate:	35 to 90°F	2 to 32°C

**PRODUCT INFORMATION**

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

41-2701	White & Pastel Base
41-2702	Clear Base*
41-2703	Outside White
41-2704	Oxford Brown
41-2705	Navajo Red
41-2706	Cedar

\*Must be tinted before use.

Some colors, drastic color changes, or porous substrates may require more than one coat to achieve a uniform finish.

**PRODUCT DATA**

<b>PRODUCT TYPE:</b>	100% Acrylic Latex
<b>VOLUME SOLIDS*:</b>	33% +/- 2%
<b>WEIGHT SOLIDS*:</b>	45% +/- 2%
<b>VOC*:</b>	169 g/L (1.4 lbs./gal.)
<b>WEIGHT/GALLON*:</b>	10.3 lbs. (4.7 kg) +/- 0.2 lbs. (91 g)

\*Product data calculated on 41-2701.

**COVERAGE:** Approximately 350 to 500 sq. ft. (32.5 to 46.5 sq. meters) per gallon (3.78 Liters) depending upon wood texture.

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

**DRYING TIME:** Normally dries in 30 minutes when applied in temperatures of 50°F (10°C) to 85°F (29°C). Allow 2 to 4 hours between coats or before recoating. High humidity, low temperature, or color may prolong drying and recoating times. It is not recommended to apply product if rain is expected within 24 hours. Allow 24-48 hours drying time for light foot traffic or furniture placement. Newly stained surfaces should be allowed to cure 30 days before washing.

**CLEANUP:** Clean brushes and tools with warm soapy water.

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**FLASH POINT\*:** Over 200°F (93°C)

## ULTRA ADVANCED Deck, Fence &amp; Siding Solid Color Stain

## GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the *PITTSBURGH PAINTS* limited warranty to apply. All surfaces must be clean and free of dirt, dust, oil, mildew, loose wood fibers and other contaminants. Remove loose, peeling stain or paint by sanding, scraping or wire brushing. Use an exterior wood cleaner to prepare new wood prior to coating, and to clean and restore weathered, dirty surfaces and remove mildew stains. After rinsing, allow wood to dry.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**DECKS, FENCES OR SIDING:** Clean weathered, dirty or mildewed surfaces prior to applying product.

**PRETEST:** Test a small hidden area prior to application to ensure acceptable appearance and penetration.

**PRIME:** This product is self-priming over most substrates.

**EXTRACTIVE BLEEDING:** Some woods, such as redwood and cedar contain high amounts of tannin, a colored wood extract. The first coat of stain may show some color discoloration, but the tannins will be trapped in the first coat of stain. A second coat will result in a uniform appearance.

## LIMITATIONS OF USE

Apply when air and surface temperatures are 35°F (2°C) or above and when the air and surface temperatures will remain above 35°F (2°C) for the next 24 hours. Avoid staining in direct sunlight or on hot surfaces. **FOR EXTERIOR USE ONLY.** Do not use on metallic, masonry, or interior surfaces.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

PROTECT FROM FREEZING.

## PACKAGING

Quart (945 mL)  
1-Gallon (3.78 L)  
5-Gallon (18.9 L)

## SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. High pressure injection of coatings into the skin by airless equipment may cause serious injury.

**USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.**

The PPG logo is a registered trademark of PPG Industries Ohio, Inc. *PITTSBURGH PAINTS*, *SunBlock*, and *Scuff Guard* are registered trademarks of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



PPG Industries, Inc.  
Architectural Coatings  
One PPG Place  
Pittsburgh, PA 15272  
[www.pittsburghpaints.com/menards](http://www.pittsburghpaints.com/menards)

Technical Services  
1-800-441-9695

Architect/Specifier  
1-888-PPG-IDEA

PPG Canada, Inc.  
Architectural Coatings  
4 Kenview Blvd  
Brampton, ON L6T 5E4

T.D. 41-2701 8/2012  
(Supersedes 8/2010)