

**Product Description**

Sico® Cleaner, Brightener and Conditioner is an all-purpose formula which will clean, brighten and refresh all coated, uncoated and weathered wood surfaces. Use outdoor on decks, siding, shakes, shingles, and fences. Also recommended for use on concrete, brick, stucco, ceramic tiles, and vinyl.

Advantages

- Cleans and refreshes stained and weathered wood.
- Removes dirt and grime and brightens greyed or weathered wood.
- Ready to use.

Available Colour

771-333A Transparent

Projects**Environment**

Exterior only.

Use

New and maintenance work.

Residential and commercial sites.

Surfaces

- Use outdoor on decks, siding, shakes, shingles, and fences.
- Also recommended for use on concrete, brick, stucco, ceramic tiles, and vinyl.

Notes

- For exterior use only.
- Read and carefully follow all safety instructions.
- Use of this product may return the original green colour to pressure-treated wood.
- Application of this product may cause a fuzzy appearance to wood previously damaged by pressure washing or excessive weathering.
- Application to new wood or newly sealed wood may cause spotting and discolouration.
- Surfaces are slippery when wet; use caution when walking on wet surfaces.
- Thoroughly rinse these surfaces to remove all traces of cleaner before applying a finish.
- **KEEP IN AN UPRIGHT POSITION**
- **PROTECT FROM FREEZING.**

Technical Specifications (21°C (70°F))**Appearance**

Transparent

Gloss Level

Not applicable

- Gloss at 60°:

Not applicable

- Gloss at 85°:

Not applicable

Composition

- Diluent: Water
- Binder: None
- Active agent: Oxalic acid

Drying Time*

• Let surface dry at least 24 hours in warm dry weather, before applying any exterior wood stain, protector or finish coating.

Spreading Rate per Coat3.78 L: Approximately 23 to 28 m² (250 to 300 ft²).

Coverage figures do not include loss due to surface irregularities and porosity or material losses due to application method or mixing.

Weight/Gallon* 3.9 kg (8.6 lbs.) ± 91 g (0.2 lbs)**Flammability** Non flammable and Non combustible

*Technical data source: 771-333A

Limited Warranty: PPG Architectural Coatings Canada, Inc. warrants performance of its products to its intended use if properly applied in accordance with the label directions and the specifications of the technical data sheet. Having no control over the application methods and conditions or the circumstances related to its use, no other warranty, expressed or implied, statutory or otherwise is given. This limited warranty extends only to the original purchaser of the product and is not transferable or assignable. If the product fails to conform to this limited warranty, we will, at your option, furnish replacement product or refund the purchase price. This limited warranty excludes (1) labour or costs of labour for the application or removal of any product and (2) all other direct, indirect, incidental, special or consequential damages.

Area Preparation

SAFETY PRECAUTIONS: Wear chemical resistant gloves, safety goggles, and protective clothing. Do not mix with any other chemicals or other household cleaning products as hazardous fumes may result. Surfaces are slippery when wet; use caution when walking on wet surfaces.

Spray all plants and vegetation liberally with water before and after application. Cover delicate vegetation to avoid damage. Prevent contact with metal, fabric, floor coverings, or lawn furniture.

Application

Test a hidden area, rinse and let dry before using this product. This product is Ready-To-Use. DO NOT THIN. Shake well before using. Sweep clean then wet surface with water before applying product. For vertical surfaces, work from bottom to top. Apply product evenly with brush, roller or garden sprayer. Product may damage metal components of spray equipment. Allow product to stand for 20–30 minutes then scrub surface with nylon brush. Make sure to keep surface wet and do not use a wire brush. Rinse surface and adjacent areas using highest pressure from hose. Allow surface to dry 24–48 hours before staining or painting. **FOR PERIODIC CLEANING OF COMPOSITE DECKING:** Apply only when air, surface, and product temperatures are between 10°C (50°F) and 32°C (90°F). Apply the cleaner liberally and work into the surface with a stiff broom (slight foaming should be seen, if not apply more cleaner). Thoroughly rinse, let dry, and apply a second application if needed. **RECOMMENDED SPRAY EQUIPMENT:** Apply cleaner at full strength with a plastic, pump-style garden sprayer and hose.

Recommendations

Application Conditions

Temperature: 10 to 32°C (50 to 90°F)
(ideal 20°C ± 5°C [68°F ± 9°F])

Relative humidity: Ideal between 15 and 55%, maximum 85%.

Tools

- **Wear chemical resistant gloves, safety goggles, and protective clothing.**

Cleanup

Rinse spray equipment thoroughly with water.

Storage and Transportation

KEEP IN AN UPRIGHT POSITION. Store in a cool dry location in tightly closed plastic container. Avoid exposure to sunlight. Rinse container thoroughly before disposal. Do not reuse container.

Disposal

Consult your municipality about proper disposal procedure of residue in accordance with the laws and respect the environment. Do not pour down a drain or storm sewer.

For more information, visit the website at www.sico.ca or call our customer service: 1-800-463-7426.

Safety Measures

CAUTION. IRRITANT. DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS. MAY IRRITATE EYES. MAY IRRITATE

SKIN. Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children. Wear protective gloves and eye/face protection: Chemical splash goggles. Use chemical-resistant, impervious gloves. Keep container tightly closed and sealed until ready for use. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information.** **FIRST AID TREATMENT:** Contains: ethanedioic acid, hydrate (1:2); phosphoric acid, sodium salt, hydrate (1:3:12). If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. For workplace use, an SDS is available from your retailer or by calling 1-800-463-7426. **EMERGENCY SPILL INFORMATION:** 514-645-1320.

Surface Maintenance

Apply a protective coating on dry surfaces.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-866-660-2220.



PPG Architectural Coatings Canada, Inc.
1550 rue Ampère, Suite 500
Boucherville (Quebec), J4B 7L4

The *PPG* logo is a registered trademark of PPG Industries Ohio, Inc. *Sico* is a registered trademark of PPG Architectural Finishes, Inc.