

REVITALIZE Wood & Concrete Resurfacer

GENERAL DESCRIPTION

Pittsburgh Paints & Stains REVITALIZE Wood and Concrete Resurfacer is the ultimate remedy for severely weathered or damaged wood and concrete. This high performance, 100% acrylic formula fills in cracks up to 1/4", locks down splinters and provides a safe, extremely durable surface that resists fading and creates a mildew resistant coating. REVITALIZE gives new life to time-worn wood and concrete.

RECOMMENDED SUBSTRATES

Wood Concrete

Recommended for use on horizontal and vertical concrete and wood surfaces: aged rough, broom-swept concrete; new concrete surfaces cured for 30 days; retaining walls, structurally sound old, gray weathered wood (decks, stairs, docks, posts and railings, and more); new wood when a non-slip, textured surface is desired. REVITALIZE is **not recommended for whole-house vertical surfaces** such as stucco or wood siding.

APPLICATION INFORMATION

Stir thoroughly. When using more than one can of the same color, intermix to ensure color uniformity.

Application Equipment: Apply two coats with a high quality brush or 1/2" nap roller.

Application Method: Ideal temperature for application is between 50° (10°C) and 90°F (32°C). Before applying the first coat, dab a heavily loaded brush into any deep cracks, gaps, nail/screw holes and knots until filled. For cupped, cracked or warped boards, drive product into cracks by rolling across the narrow width as well as the length of the board. Lightly brush any product that drips between the boards. Cut in around the edges of the deck or concrete surface with a brush using a short dabbing stroke. To apply the first coat, fully saturate the roller by rolling back and forth in the tray. A full-loaded roller will cover an area of approximately 5- 7 sq. ft. Using light and even pressure, apply product to a few boards or a few square feet at a time, keeping a wet edge to avoid lap marks. Lightly backbrush after rolling if you desire a smoother appearance.

Thinning: Do not thin.

Permissible temperatures during application:

Material:	50 to 90°F	10 to 32°C
Ambient:	50 to 90°F	10 to 32°C
Substrate:	50 to 90°F	10 to 32°C

FEATURES / BENEFITS

Features

- High-performance coating based on elastomeric technology
- Locks down splinters, fills cracks up to 1/4"
- Great on wood and concrete decks, docks, porches, sidewalks and more
- Finely textured finish
- Resists cracking and peeling and provides a mildew resistant coating
- Waterproofing protection
- Premium latex formula

Benefits

- Bridges cracks with high tensile strength. Moves with substrate to keep cracks from re-opening.
- Gives new life to time-worn wood and concrete
- Versatile coating suitable for multiple projects
- Barefoot friendly and slip-resistant
- Long-lasting finish
- Protects the substrate
- Great adhesion and easy soap and water cleanup

PRODUCT INFORMATION

41-2902 Base 2 (Must be tinted)

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

PRODUCT DATA

PRODUCT TYPE: 100% acrylic
VOLUME SOLIDS*: 57% +/- 2%
WEIGHT SOLIDS*: 72% +/- 2%
VOC*: 50 g/L (0.4 lbs./gal.)
WEIGHT/GALLON*: 13 lbs. (4.8 kg) +/- 0.2 lbs. (91 g)

COVERAGE: Approximately 50 sq. ft. in 2 coats (4.6 sq. meters) per U.S. gallon (3.78 Liters).

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Allow 6 hours for the first coat to dry. To apply the second coat, cut in around the edges of the entire surface again and roll out as for the first coat.

Allow the final coat to dry at least 12 hours before foot traffic and 48 hours before replacing furniture or heavy objects.

To Recoat: 6 hours
 For Pedestrian Service: 12 hours

Drying times listed may vary depending on temperature, humidity, film build, color and air movement.

CLEANUP: Clean brushes and tools with warm soapy water.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

REVITALIZE Wood & Concrete Resurfacer

GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the *Pittsburgh Paints & Stains* limited warranty to apply. All surfaces must be dry, clean and free of dirt, grease, mildew, algae, and other contaminants to ensure proper adhesion. Sand or scrape any loose stain or paint. Clean the surface with PITTSBURGH Paints® Ultra Deck Cleaner (follow product label instructions). Do not apply this product to any surface that has been recently coated with paint, stain, sealer or water repellent.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

WOOD: Cleaning with a pressure washer is not recommended. Pressure washing the wood surface can drive contaminants into the wood, eventually leading to coating failure. Sand any loose wood fibers. Loose deck screws, raised nail heads or loose decking boards should be secured. Remove loose splinters and replace rotting or severely damaged boards. Wood cracks and depressions deeper than 1/4" should be filled with an exterior paintable sealant caulk.

CONCRETE: PITTSBURGH Paints Ultra Premium Deck Cleaner or a pressure washer may be used. Patch cracks and depressions larger than 1/4" with a polymeric concrete patching compound (follow manufacturer's instructions). **Do not use caulks or other non-concrete patching compounds.**

Both wood and concrete surfaces must be thoroughly dry before application and there should be no threat of rain for 24 hours. **Please use caution when applying around aquatic habitats to avoid spills.**

LIMITATIONS OF USE

Apply when air temperatures are between 50°F (10°C) and 90°F (32°C). Do not apply if rain is expected within 24 hours of application. Both wood and concrete surfaces must be thoroughly dry before application.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

Do not apply on garage floors, driveways, or any other areas with vehicular traffic. Do not use on submerged surfaces such as ponds, fountains, swimming pools or interior concrete surfaces.

FOR EXTERIOR USE ONLY. PROTECT FROM FREEZING.

SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

Please use caution when applying around aquatic habitats to avoid spills.

PACKAGING

1-Gallon (3.78 L)
5-Gallon (18.9 L)

The PPG logo is a registered trademark of PPG Industries Ohio, Inc. *PITTSBURGH Paints* is a registered trademark and *PITTSBURGH Paints & Stains* is a trademark of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate: however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



PPG Industries, Inc.
PPG Architectural Finishes, Inc.
One PPG Place
Pittsburgh, PA 15272
www.pittsburghpaints.com/menards

Technical Services
1-800-441-9695

Architect/Specifier
1-888-PPG-IDEA

PPG Canada, Inc.
Architectural Finishes, Inc.
4 Kenview Blvd
Brampton, ON L6T 5E4

T.D. 41-2902 3/2013