

DULUX X-PERT HIGH-BUILD INTERIOR LATEX PRIMER/SEALER 11020

Water based product

Technical Data Sheet



Technical Specifications (21°C (70°F))

Solids by Volume – 43% (+/- 1%)

Solids by Weight – 61% (+/- 1%)

Volatile Organic Compounds (VOCs)*

According to ASTM D3960-05: < 50 g/L

Canadian regulation: < 200 g/L

Colour

White (can be tinted to light pastel colours,
max 1 oz. of colourant per litre)

Gloss Level

• N/A

Practical Coverage

250 - 290 sq. ft. per 3.78 litres

6 - 7 sq. metres per litre

(Actual coverage will vary depending on substrate
and application method.)

Resin Type

• Vinyl Acrylic

Viscosity* Ready to use (92 - 100 Krebs Units)

Flammability Non Flammable

Flash Point* N/A

Recommended Film Thickness*

• Wet: 5.5 mils

• Dry: 2.4 mils

Drying Time* @ 77°F/25°C - 50% Relative Humidity

**Drying & recoat times are dependent on temperature,
humidity, ventilation and film thickness*

Touch dry: 1 hour

To recoat: 2 hours

*Technical Data Source: 11020

Product Description

Dulux X-pert High-Build Interior Latex Primer/Sealer 11020 is a premium product formulated to provide a high-build coating to hide minor imperfections prior to painting.

Dulux X-pert High-Build Interior Latex Primer/Sealer 11020:

- Helps to assist in achieving a Class 4 or 5 drywall finish system
- Easy application
- Excellent sealing properties
- Easy sanding

Intended Uses

- New and maintenance work
- Residential and Commercial sites
- Walls and ceilings of any room
- Painted and unpainted plaster, drywall, stucco, masonry, concrete and wood

Certifications - As of October 2011

Complies with:

LEED® Canada – CI (2006) and NC & CS (2009)

PPG Architectural Coatings Canada, Inc. warrants performance of its products to its intended use if properly applied in accordance with the label directions and the specifications of the technical data sheet. Having no control over the application methods and conditions or the circumstances related to its use, no other warranty, expressed or implied, statutory or otherwise is given. This limited warranty extends only to the original purchaser of the product and is not transferable or assignable. If the product fails to conform to this limited warranty, we will, at your option, furnish replacement product or refund the purchase price. This limited warranty excludes (1) labor or costs of labour for the application or removal of any product and (2) all other direct, indirect, incidental, special or consequential damages. Dulux is a registered trademark of AkzoNobel and is licensed to PPG Architectural Coatings Canada, Inc. for use in Canada only. The *Multi-Colored Swatches Design* is a trademark of PPG Architectural Finishes, Inc.

July 2014



Available at Dulux Paints Stores across Canada and Betonel-Dulux Stores in Québec

SURFACE PREPARATION

All surfaces must be clean, dry and free of dirt, chalk, grease, wax, rust and loose or peeling paint before painting.

- Mildew must be removed by washing affected area with a solution of 30% household bleach and 70% water. Rinse well.
- Remove all loose and peeling paint and sand to smooth edges.
- Repair holes and cracks with filler suitable for the surface to be repaired.
- Sand all surfaces smooth and lightly sand glossy areas. Vacuum sanding residue.
Precaution: Dry sanding, flame cutting and/or welding of dry paint film will give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Previously Painted Surfaces: spot prime repairs or any bare areas or total surface where necessary. Do not use over aged alkyd finishes.

New concrete, masonry or plaster: must age at least 30 days and be thoroughly dry before painting.

Bare Wood: sand smooth.

Application

Ready-to-use product, do not thin.

Mix thoroughly before use.

Apply using brushes, rollers or spray equipment.

Suitable under latex or alkyd topcoats.

Application Conditions

Apply only when air and surface temperatures are above 50°F (10°C)

Tools

- Brush – synthetic bristles (nylon, polyester)
- Roller – 10-15 mm
- Spray (Airless equipment) – tip size: 0.017 to 0.019 in - Pressure: 2300 – 2700 psi

*Spray recommendations may vary from figures listed depending on equipment manufacturer

SYSTEM RECOMMENDATIONS

All recommended surfaces:

- Dulux X-pert High-Build Latex Primer/Sealer 11020 – one coat to total surface.
- Appropriate Glidden or Dulux topcoat – 2 coats for better durability and appearance.

Clean-up

Clean hands and tools immediately with warm, soapy water. Clean spills right away with a damp cloth.

Storage and Transportation

Keep product cool and dry.

DO NOT FREEZE

Disposal

Consult your municipality about proper disposal procedures in accordance with the laws and respect the environment or give leftover paint to someone who could use it: a neighbor or friend, a recreational service or a non-profit organization. Do not pour leftover paint down the drain.

Safety Measures

Read the Material Safety Data Sheet. Avoid contact with eyes. Keep out of reach of children. Use only in well ventilated areas.

FIRST AID TREATMENT: If in contact with eyes, rinse thoroughly with clear water. If swallowed, do not induce vomiting. Call poison centre or physician immediately.

For product information call: 1-(800)-387-3663
www.dulux.ca