

# MATERIAL SAFETY DATA SHEET

Manufacturer's Code: MKMS-81078

Monarch Paint Company

Page: 1

Product Description: MOPAKO FLAT CRISP KHAKI

Date: 03/04/2003

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Description: MOPAKO FLAT CRISP KHAKI

Manufacturer's Code: MKMS-81078

Manufacturer: Monarch Paint Company

3530 Lang Road

Houston, TX 77092

Information 8am - 5pm EST: 713-681-1868

Emergency Telephone Number: 800-854-6813

CHEMTREC #: 800-424-9300

## 2. OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200)

Component	Wt %	CAS Registry #
Titanium Dioxide	01-10	013463-67-7
Crystalline Silica - Cristobalite	01-10	014464-46-1
Crystalline Silica - Quartz	01-10	014808-60-7
Calcined Kaolin Clay	01-10	066402-68-4

### EXPOSURE LIMITS (ppm)

Component	ACGIH TLVs		OSHA PELs	
	TWA	STEL	TWA	STEL
Titanium Dioxide	10mg/m3	N/E	15mg/m3*	N/E S
Crystalline Silica - Cristobalite	0.05mg/m3*	N/E	0.05mg/m3*	N/E S
Crystalline Silica - Quartz	0.1mg/m3*	N/E	0.1mg/m3*	N/E S
Calcined Kaolin Clay	2mg/m3*	N/E	5mg/m3*	N/E S

(M) Maximum Exposure Limit

(S) Occupational Exposure Standard

(R) Supplier's Recommended Limit

(+) There is a risk of absorption through unbroken skin.

(\* ) Respirable fraction.

(C) Ceiling

## 3. HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE:

INHALATION: May cause nose and throat irritation.

EYE CONTACT: Causes eye irritation.

SKIN CONTACT: May cause skin irritation.

INGESTION:

Can result in irritation of the mouth, stomach tissue and digestive tract.

CHRONIC OVEREXPOSURE:

This product contains titanium dioxide. Animals inhaling massive quantities of titanium dioxide in a long-term study developed lung tumors. Studies with humans involved in manufacture of this pigment indicate no increased risk of cancer from exposure. Potential for inhalation of titanium dioxide dusts from coatings is very limited.

Since overexposures are not expected, there is no significant hazard for man.

Cancer hazard. Contains Crystalline silica which can cause cancer.

Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. Overexposure may cause lung and kidney damage.

Contains an ingredient listed as known or suspected carcinogen?

NTP: Yes

OSHA: Yes

IARC: Yes

## 4. FIRST AID MEASURES

General: In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

INHALATION:

If affected by inhalation of vapor or spray mist, remove to fresh air.

EYE CONTACT:

Flush immediately with plenty of water for 15 minutes until irritation subsides. If irritation persists, get medical attention.

SKIN CONTACT:

Flush with large amounts of water. Use soap if available. Remove severely contaminated clothing (including shoes) and wash before reuse. If irritation persists, get medical attention.

INGESTION:

If swallowed, gently wipe out inside mouth to remove any residual material. Do not induce vomiting. Get medical attention immediately.

## 5. FIRE AND EXPLOSION DATA

Flashpoint: NA

OSHA Classification: Not Applicable

FIRE AND EXPLOSION HAZARDS:

Closed containers may explode when exposed to extreme heat. In the absence of electricity, a water spray (a fog nozzle is preferred) may be used to cool containers. Decomposition and combustion products may be toxic.

EXTINGUISHING MEDIA: Foam, Carbon Dioxide, Dry Chemical

## 6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Absorb spill with an inert material (e.g., dry sand or earth), then place in a chemical waste container.

## 7. HANDLING AND STORAGE

GENERAL: Keep container closed when not in use. Wash thoroughly after handling. Use with adequate ventilation.

PRECAUTIONS: This product may contain materials classified as nuisance particulates which may be present at hazardous levels during sanding or abrading of the dried film. Occupational exposure values are as follows: ACGIH TLV TWA-10mg/m3 (total dust), 3mg/m3 (respirable fraction), OSHA PEL TWA-15mg/m3 (total dust), 5mg/m3 (respirable fraction). Refer to section 2 for compound specific exposure limits.

If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component(s) prior to use. Any mixture of components will have hazards of all components.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

Provide sufficient ventilation, in volume and pattern, to:

a) keep the TLV of the hazardous ingredients below the limits specified in Section Two.

b) remove volatiles produced during cure and decomposition products produced during welding or cutting on surfaces coated with this product.

RESPIRATOR:

If personal exposure cannot be controlled below exposure limits listed in Section 2 of this MSDS, use a respirator approved by the National Institute for Occupational Safety and Health (NIOSH) of the Department of Health and Human Services and in accordance with 29CFR 1910.134 to remove particulates (and vapors if there is overexposure to vapors generated during use or following the application of this product).

PROTECTIVE EQUIPMENT:

CLOTHING: As needed, use body protection to avoid contact with product.

EYE: Safety glasses, chemical goggles and/or a face shield should be worn to prevent eye contact.

GLOVES: Wear chemical resistant gloves.

SPECIAL PRECAUTIONS:

This product contains Crystalline Silica which can cause adverse health effects when respired. Recommended use of this product is not expected to create such an exposure risk. If sanding of dried coating is performed, engineering and administrative controls must be used to maintain an exposure level below the applicable PEL, or an appropriate NIOSH approved respirator must be used for protection. Crystalline Silica may aggravate existing respiratory conditions. Smoking aggravates the effects of exposure.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Weight per Gallon: 10.959

Physical State: liquid

Percent Volatile by Volume: 70.08

Evaporation Rate: Slower than ether

Vapor Density: Heavier than air

## 10. STABILITY AND REACTIVITY

GENERAL:

This product is stable and hazardous polymerization will not occur.

INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:

Strong oxidizing agents.

HAZARDOUS DECOMPOSITION:

May produce hazardous fumes when heated to decomposition as in welding. Carbon Dioxide and Carbon Monoxide fumes may be produced.

## 11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself.

## 12. ECOLOGICAL INFORMATION

There is no data available on the product itself.

Monarch Paint Company

3530 Lang Road Houston, TX 77092

# MATERIAL SAFETY DATA SHEET

**Manufacturer's Code:** MKMS-81078

**Monarch Paint Company**

**Page:** 2

**Product Description:** MOPAKO FLAT CRISP KHAKI

**Date:** 03/04/2003

## 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state and federal regulations.  
Do not incinerate unopened containers.

## 14. TRANSPORT INFORMATION (GROUND SHIPMENTS)

Proper Shipping Name: Paint  
Hazard Class: Not Regulated  
UN Number: Not Regulated  
Packing Group: Not Regulated

## 15. REGULATORY INFORMATION

TSCA (Toxic Substance Control Act):

All components of this product are either listed or are exempt from listing on the TSCA Inventory.

SARA TITLE III (Superfund Amendments and Reauthorization Act):

313 Reportable Chemicals:

None Known unless specified below.

CALIFORNIA PROPOSITION 65: None Known unless specified below.

Warning: This product contains a chemical(s) known to the State of California to cause cancer.

## 16. OTHER INFORMATION

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

**Monarch Paint Company**

**3530 Lang Road Houston, TX 77092**