



HOUSTON
713-680-2799 FAX 713-681-1020

DALLAS
972-258-6040 FAX 972-570-5583

6060 LATEX ENAMEL UNDERCOATER
PRIMER FOR INTERIOR WOOD SURFACES

FEATURES

Excellent sealing and enamel holdout
Provides surface foundation for latex or alkyd
paints
Ease of application
Very low odor
Easy sanding
Good film build

RECOMMENDED USES

A premium quality white pigmented acrylic primer and
sealer for interior surfaces of new or previously
painted wood, drywall, masonite, paneling, wallboard,
brick and cured plaster, concrete, and masonry. Not
intended as a rust inhibitive primer. Do not use on
floors.

SPECIFICATION DATA

Color: White

Finish: Flat, 2.5 units @ 60 deg.

Density: 11.88 lbs/gal.

Cleanup Solvent: Soap and water

Recommended film thickness:
1.2 mils dry
3.6 mils wet

Solids:

Weight: 53.6%

Volume: 33.6%

Flash Point: Non-flammable

Drying Time at 77°F and 50% RH:

To touch - 30 minutes

To recoat - 1 to 2 hours

Coverage:

250 to 450 square feet per gallon,
depending on method of application,
texture, and porosity of surface.

V.O.C. Content: 1.21 lbs/gal.

All surfaces must be clean, dry and free of dust, dirt, chalking and peeling paint, wax, grease or any other contamination. Repair any surface defects before painting.

New Surfaces: Use Monarch 6060 Premier Latex Enamel Undercoat as a prime coat. Unpainted wood must be dry.

Plaster and Masonry: All plaster must cure for at least 30 days before painting or priming.

Previously Painted Surfaces: Remove all loose and peeling paint. Properly patch all holes and cracks with appropriate patching compound. Glossy areas must be dulled by light sanding. Porous, flat surfaces should be sealed with this product.

MIXING AND THINNING

Tinting - May be shaded toward finish coat 2 ounces per gallon maximum with Monarch's universal colorant.

Thinning- Thinning is not normally needed, if necessary use only a small amount of water (up to 1/2 pint per gallon). Clean up with soap and water. Do not mix with solvents or solvent based paint.

APPLICATION

Method-May be applied with a nylon polyester brush, roller, or spray. For airless spray, use .015" or larger tip. Adjust pressure as necessary.

Cleanup- Clean equipment promptly with soap and warm water. Wipe up spatters and drips immediately with damp cloth or sponge.

Dry Time- Under normal conditions to touch - 30 minutes, to recoat 2 hours. Provide adequate ventilation. Adverse conditions may affect drying time.

PRECAUTIONS

PROTECT FROM FREEZING!

Do not apply if air or surface temperature is below 50° F (10°C).

KEEP OUT OF THE REACH OF CHILDREN

Do not take internally.

Close container after each use.

Prior to using this product, the user is specifically directed to obtain and read the current Material Safety Data Sheet and Label for this product. If, after reading these documents, you do not understand them, do not use this product.

The statements made in this brochure on product labels, or by the agents of Monarch Paint Company are for information only and are believed to be true and accurate. These statements are intended as a guide to approved construction practices and materials. Many variables that affect results (including workmanship, construction equipment, weather, and quality of other materials) are beyond our control. Consequently Monarch Paint Company does not make nor authorize any agent to make any warranty of merchantability or fitness for any purpose or for any other warranty, representation or guarantee, expressed or implied, concerning this material except that it conforms to Monarch Paint Company's quality control standards. Monarch Paint Company's only liability whatsoever to the buyer or user of this product is limited to the purchaser's cost of the product itself.