



HOUSTON
713-680-2799 FAX 713-681-1020

DALLAS
972-258-6040 FAX 972-570-5583

6600 MOPAKO FLAT WALL PAINT
WALL FINISH FOR INTERIOR GYPSUM WALLBOARD,
PLASTER, WOOD AND MASONRY SURFACES

FEATURES

Uniform flat finish
Excellent touch up
Good hide properties
Ease of application
Low odor
Wide range of colors

RECOMMENDED USES

A high quality latex wall paint designed to produce an even, flat finish for walls and ceilings. Mopako is recommended for use in residences, offices, apartments, hotels, schools, hospitals and manufacturing facilities. May be used on gypsum wallboard, interior plaster, masonry, concrete block and primed metal or wood surfaces. Monarch performance alternate to Federal Specification TT-P-29j.

SPECIFICATION DATA

Color: White, standard off whites and custom mixed colors

Finish: Flat, 2.0-2.3 units @60°

Density: 11.31 lbs/gal.

Cleanup Solvent: Soap and water

Recommended film thickness:
1.5 mils dry
4.9 mils wet

Solids:

Weight: 48.3%
Volume: 30.6%

Flash Point: Non-flammable

Drying Time at 77°F and 50% RH:
To touch - 30 minutes
To recoat - 2 hours

Coverage:

250 to 400 square feet per gallon,
depending on method of application
and texture and porosity of surface.

V.O.C. Content: 1.06 lbs/gal

All surfaces must be clean, dry and free of dust, dirt, chalking and peeling paint, wax, grease or any other contamination. Repair any surface defects before painting.

New Surfaces:

Drywall - Apply a prime coat of this product or use Monarch 6217 Paramount Latex Primer-Sealer.

Plaster or Masonry - All surfaces must cure for at least 30 days before painting.

Bare Wood - Prime with Monarch 4690 M-Prime Interior/Exterior Primer or, for faster dry, Monarch 7704 Lacquer Undercoat or Monarch 6060 Latex Enamel Undercoat. Lightly sand and dust clean.

Block Wall - Fill with Monarch 5501 Block filler, apply prime and finish coats as suggested.

Metal - Apply coat of appropriate Monarch primer for surface involved.

Previously Painted Surfaces:

Remove all loose and peeling paint, spot prime bare areas with Monarch 6217 Paramount Latex-Sealer or appropriate Monarch primer.

MIXING AND THINNING

Tinting - May be tinted with Monarch's universal colorants from pastel to ultra deep shades.

Thinning - Thinning is not normally needed. If necessary, use only a small amount of water (up to 1/2 pint per gallon). Do not mix with solvents or solvent thinned paints. It is important to thin this product with 1/2 pint to 1 pint of water per gallon prior to attempting touch-up.

APPLICATION

Method - Apply with a nylon brush, 1/2" roller, or spray. For airless spray, use .017" or larger tip, adjust pressure as necessary. **Do not apply when air or surface temperature is below 50°F (10°C).**

Dry Time - Under normal conditions to touch in 30 minutes and to recoat 2 hours. Provide adequate ventilation. Adverse conditions may affect drying time.

Cleanup - Clean equipment promptly with soap and water. Wipe up spatters and drips immediately with damp cloth or sponge.

Washing - Use sponge and mild liquid detergent in water. Do not use abrasive cleaners. Do not wash before paint has cured a minimum of 21 days.

PRECAUTIONS

PROTECT FROM FREEZING!

Do not apply if air or surface temperature is below 50°F (10°C).

Prior to using this product, the user is specifically directed to obtain and read the current Material Safety Data Sheet and Label for this product. If, after reading these documents, you do not understand them, do not use this product.

KEEP OUT OF THE REACH OF CHILDREN

Do not take internally.

Close container after each use.

The statements made in this brochure on product labels, or by the agents of Monarch Paint Company are for information only and are believed to be true and accurate. These statements are intended as a guide to approved construction practices and materials. Many variables that affect results (including workmanship, construction equipment, weather, and quality of other materials) are beyond our control. Consequently Monarch Paint Company does not make nor authorize any agent to make any warranty of merchantability or fitness for any purpose or for any other warranty, representation or guarantee, expressed or implied, concerning this material except that it conforms to Monarch Paint Company's quality control standards. Monarch Paint Company's only liability whatsoever to the buyer or user of this product is limited to the purchaser's cost of the product itself.