



Architectural Coatings

PPG Accent Color Base

GENERAL DESCRIPTION

PPG Accent Color Base offers an enriched formulation that provides exceptional hiding and maximum color richness, delivering the deep, dark shades that other paints can't match. With guaranteed two coat coverage Accent Color Base provides ultra hiding power for all colors.

RECOMMENDED SUBSTRATES

Concrete/Masonry Block
 Ferrous Metal
 Gypsum Wallboard-Drywall
 Plaster
 Wood

APPLICATION INFORMATION

Stir thoroughly before using and frequently during use. When using more than one container of the same color, intermix to ensure color uniformity. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Material Safety Data Sheet (MSDS) information prior to use. MSDS are available through our website or by calling 1-800-441-9695.

Application Equipment: Apply with a high quality brush, roller, paint pad or by spray equipment.

Airless Spray: Pressure 2000 psi, tip 0.015" - 0.021"

Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

Brush: Polyester/Nylon Brush

Roller: 3/8" - 3/4" nap roller cover

Thinning: No thinning is required.

Permissible temperatures during application:

Material:	50 to 90°F	10 to 32°C
Ambient:	50 to 90°F	10 to 32°C
Substrate:	50 to 90°F	10 to 32°C

TINTING AND BASE INFORMATION

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

25-250 Accent Tint Base*

*Must be tinted.

Some colors, drastic color changes, or porous substrates may require more than one coat to achieve a uniform finish.

PRODUCT DATA

PRODUCT TYPE: 100% Acrylic Latex

SHEEN: Matte

VOLUME SOLIDS: 37% +/- 2%

WEIGHT SOLIDS: 46% +/- 2%

VOC: 90 g/L (0.8 lbs./gal)

Colorants added to this product may contain VOCs.

WEIGHT/GALLON: 9.7 lbs. (4.4 kg) +/- 0.2 lbs. (91 g)

COVERAGE*: Approximately 400 sq. ft./gal. (37.2 sq. m/3.78L)

Wet Film Thickness: 4.0 mils

Wet Microns: 102

Dry Film Thickness: 1.5 mils

Dry Microns: 38

Coverage does not include variation due to application methods, surface porosity, and/or mixing.

DRYING TIME: Dry time @77°F (25°C); 50% relative humidity.

To Touch: 2 hours

To Recoat: 8 hours

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement.

WASHING INSTRUCTIONS: Wait at least 14 days after painting before cleaning the surface with a non-abrasive mild cleaner.

CLEANUP: Warm soap and water

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

FEATURES / BENEFITS**Features**

100% acrylic
 Exceptional hiding power, formulated for vivid and dark colors
 Good burnish resistance for accent colors

Benefits

Excellent adhesion, easy water clean up
 Guaranteed two coat coverage
 Minimizes shiny spots

GENERAL SURFACE PREPARATION

Surfaces to be coated must be dry, clean, sound, and free from all contamination including loose and peeling paint, dirt, grease, oil, wax, concrete curing agents and bond breakers, chalk, efflorescence, mildew, rust, product fines, and dust. Remove loose paint, chalk, and efflorescence by wire brushing, scraping, sanding, and/or pressure washing. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces. Feather back all rough edges to sound surface by sanding. Prime all bare and porous substrates with an appropriate primer.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

CONCRETE/MASONRY BLOCK: Mortar should cure for at least 30 days and preferably 90 days prior to priming. Fill block with an appropriate block filler. Surfaces previously coated with water thinned cement-based paint must be prepared with extra care. If the material appears to be adhering tightly, a masonry sealer may be applied to seal the surface. Check adhesion by applying a piece of masking tape. If the sealer peels off and has loose particles, remove all chalking or crumbling material, re-seal and re-check adhesion.

FERROUS METAL: The surface must be cleaned thoroughly to remove any dust, rust, and surface contaminants, and then primed.

GYPSUM WALLBOARD-DRYWALL: Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust, then prime prior to painting the substrate.

PLASTER: Plaster, hardcoat, skim coat, or other alkaline surfaces should be allowed to cure for at least 30 days prior to priming with an alkali resistant primer.

WOOD: Unpainted wood or wood in poor condition should be sanded smooth, wiped clean, then primed. Any knots or resinous areas must be primed before painting. Countersink all nails, putty flush with surface, then prime.

RECOMMENDED PRIMERS

Concrete/Masonry Block (Block Fillers)	6-7, 6-15
Concrete/Masonry Block (Primer/Sealers)	4-603, 17-921
Gypsum Wallboard-Drywall	6-2, 6-4, 9-900, 12-900
Ferrous Metal	90-712, 90-912
Plaster	4-603, 17-921
Wood	6-2, 9-900, 12-900, 17-921

LIMITATIONS OF USE

Apply when air, surface and product temperatures are between 50°F (10°C) and 90°F (32°C).

PROTECT FROM FREEZING.

Product should not be used in bathrooms or other high humidity areas.

PACKAGING

1-Gallon (3.78 L)
Quart (946 mL)

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-800-441-9695.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.ppgpittsburghpaints.com

Technical Services
1-800-441-9695
1-888-807-5123 fax

Architect/Specifier
1-888-PPG-IDEA

PPG Canada, Inc.
Architectural Coatings
4 Kenview Blvd
Brampton, ON L6T 5E4

A2.25 10/2011
(Supersedes 4/2009)

Made in the
USA