



OLYMPIC® Premium Interior & Exterior Oil Based Gel Stain

GENERAL DESCRIPTION

OLYMPIC® Premium Oil Based Gel Stain Tint Base is an easy-to-use, no drip formula, which is ideal for vertical surfaces. This unique formula provides uniformity in stain application, which is perfect for use on wood, composite, fiberglass doors, and metal surfaces. For interior applications, topcoat with OLYMPIC Premium Oil or Water Based Polyurethanes or Fast Dry Varnish. For exterior applications, topcoat with OLYMPIC Premium Interior & Exterior Spar Finish. No wood conditioner is required for use on soft or hard woods.

PRODUCT INFORMATION

41600	Tinting Base*
41601	Aged Maple
41602	Antique Cherry
41603	Colonial Oak
41607	Traditional Mahogany

*Must be tinted prior to use.

Ready-Mixed colors can be intermixed to create custom colors.

Do not tint Ready-Mixed colors.

RECOMMENDED USES

Wood
Composite
Fiberglass Doors
Metal

FEATURES / BENEFITS

Easy to Use
No Drip Formula
Ideal for Vertical Surfaces

DIRECTIONS FOR USE

Test the stain on a piece of scrap wood for determination of final color and appearance.

APPLICATION INFORMATION

Application: OLYMPIC Premium Gel Stain can be applied with a rag or brush. For wood or textured surfaces, the stain is wiped or brushed on and gently rubbed into the grain. The excess should be wiped off with a rag. For metal or other substrates, a graining tool can be used. To increase color intensity, allow the stain to dry for 5 hours, then apply a second coat. OLYMPIC Premium Oil Based Gel Stain must be topcoated for exterior applications and may be topcoated for interior applications.

PRODUCT DATA

PRODUCT TYPE:	Alkyd/Oil Resin
VOLUME SOLIDS:	33% +/- 2%
WEIGHT SOLIDS:	43% to 48% +/- 2%
VOC:	<550 g/L (4.58 lbs./gal.)
WEIGHT/GALLON:	8.0 to 8.5 lbs. (3.6 to 3.9 kg) +/- 0.2 lbs. (91 g)
FLASH POINT:	109°F (42.8°C)

COVERAGE: Approximately 200 to 400 sq. ft. (18.6 to 37.2 sq. meters) per quart (945 mL). Coverage will vary with wood type, porosity, preparation and application.

DRYING TIME: Dry times are affected by humidity, temperature, film build, and moisture content of the wood. To test for dryness, lightly rub with a white cloth. If the cloth picks up color, wait for at least one hour and retest. Allow the stain to dry for 5 hours when applying a second coat.

CLEAN UP: Clean up with mineral spirits or paint thinner.

Danger - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.

OLYMPIC® Premium Interior & Exterior Oil Based Gel Stain

GENERAL SURFACE PREPARATION

Proper surface preparation is essential for the OLYMPIC limited warranty to apply. OLYMPIC Premium Oil Based Gel Stain is simple and easy to apply. The key to an excellent final appearance is good surface preparation.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

BARE WOOD: Sand with the grain of the wood.

REFINISHING OLD WOOD: Remove all old finishes.

FINAL SURFACE PREPARATION: All wood must be free of dust, dirt, grease or oils. Use a tack cloth or vacuum cleaner to remove any dust or dirt from the wood. Surfaces must be dry before staining.

LIMITATIONS OF USE

Always sand with the grain of the wood. Test with stain on a piece of scrap wood for determination of final color and appearance. Do not apply when the air, coating, or surface temperature is below 50°F (10°C). For exterior applications, do not apply late in the day when dew or condensation are likely to form or if rain is threatening.

These products are not intended for immersion service, resistance to chemicals or other extreme conditions. Not recommended in situations characterized by high heat or presence of corrosive chemicals nor for use on floors.

PACKAGING

Available in 1-Quart (945 mL) containers.

SAFETY PRECAUTIONS

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

Keep containers closed and away from heat, sparks, and flame when not in use.

USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.pittsburghpaints.com

Technical Services
1-800-441-9695

Architect/Specifier:
1-888-PPG-IDEA

PPG Canada, Inc.
Architectural Coatings
4 Kenview Blvd
Brampton, ON L6T 5E4

T.D. 4011 5/2008
(Supersedes 6/2005)