

PORTER®

P A I N T S

VINYL FLAT™ Interior Latex Wall Paint

979

VINYL FLAT Interior Latex Wall Paint No. 979 Series is a superior professional quality flat interior latex wall paint used for new and previously painted commercial, institutional and residential walls and ceilings where exceptional durability in a flat wall paint is required. This product outperforms most premium and super-premium residential flat paints in stain resistance and scrubability. It is perfect for high traffic and rough duty areas where low sheen is required. Also excellent for homeowner application.

USED FOR	FEATURES
<ul style="list-style-type: none">• Drywall• Acoustical tile• Plaster• Primed metal• Masonry• Wallboard	<ul style="list-style-type: none">• Excellent uniformity• Excellent touch-up• Stain resistant & Washable• Easy to apply; low odor• Non-yellowing• Easy soap & water clean-up

RECOMMENDED SYSTEMS

VINYL FLAT Interior Latex Wall Paint No. 979 series can be applied to a wide variety of primed substrates. Finish the following primed surfaces with one or two coats of **VINYL FLAT Interior Latex Wall Paint No. 979 series**:

SUBSTRATE	TYPICAL PRIMERS
Acoustical Tile:	867, 1129
Aluminum:	272/276, 286, 296
Drywall*:	426, 867, 1129
Masonry	
Brick:	867, 1129
Concrete:	867, 1129
Concrete Block (CMU):	896, 6223, 9203
Plaster:	135, 867, 1129
Repaint:	135, 1129, self-prime**
Steel, iron:	212/215, 272/276, 286, 290, 296, 299
Steel, Galvanized:	212/215, 290, 1129
Wood:	135, 335, 1129, 6064

*NOTE: Although flat finish paint is often used as a primer for new drywall, drywall primers are better designed to seal the surface providing better appearance with a two coat system.

**NOTE: For best appearance, repaint over very porous, low resin flat wall paints requires a suitable primer designed to seal the surface rather than self priming with this finish paint.

LIMITATIONS

Do not apply when air or surface temperature is below 50°F or above 110°F. Surface temperature must be at least 5°F above dew point. For optimum application properties, bring material to 65-85°F (18-29°C) temperature range prior to mixing or application. Use for service below 150°F. Do not use on floors. **Protect from freezing.**

TECHNICAL DATA

Data below is based on Pastel base.

Product Type:	Vinyl acrylic
Bases/Colors:	975 Pastel base 979 Light base 978 Deep base 984 Ultra Deep base
Sheen, 85°:	Flat (Typical range: 1 - 5)
Reflectance:	96 ± 1%
Percent Solids:	
Weight:	48 ± 2%
Volume:	31 ± 2%
PVC:	49 ± 2%
Weight/Gallon:	11.4 lb
Viscosity (Initial):	90 - 95 Krebs Units
Thinner:	

Brush/Roller: If necessary, thin sparingly with clean water up to ½ pint per gallon.

Spray: Thin with clean water up to ½ pint per gallon.

Clean-up: Warm, soapy water.

Recommended Film Thickness:

Wet: 3.4 mils

Dry: 1.1 mils

Spread Rate (Theoretical):

Smooth Surfaces: Up to 470 sq. ft./gal.

Rough Surfaces: 250-300 sq. ft./gal.

Dry time (70°F @ 50% R.H.):

To Touch: <1 hour

To Recoat: 4 hours

Full Service: 15-30 days

(Expect longer dry times at lower temperatures and higher relative humidity.)

Flash Point: >200°F (>93°C)

Flame Spread Rating: Class A (0-25)

(See Porter Technical Bulletin No. 9: Flame Spread Rating.)

Federal Specification Crossover: TT-P-29J

(See Porter Technical Bulletin No. 6: Federal Specification Performance Crossover.)

Note: This product is not formulated with lead or mercury containing materials.

REGULATORY DATA

VOC based on light base. See labels for other bases.

VOC (theoretical):

As supplied (untinted): 0.74 lb/gal (89 g/l)

SURFACE PREPARATION

Paint only clean, dry, deglossed and profiled surfaces. Remove dirt, oils, grease, wax, crayon and ink marks (or seal with STA-KIL™ Primer/Sealer No. 164 or shellac), sanding dust, paint remover, etc. with PORTERPREP™ Heavy Duty Cleaner No. 571, Soilax and water, Porter Paint Thinner No. 5132 or other appropriate cleaners, or by vacuuming as necessary. Remove loose paint by hand scraping or power tool cleaning and sand smooth. Fill cracks and gouges in drywall and plaster with ready mix spackling paste. Fill holes and gouges in wood and other substrates with wood patch or filler, etc. as appropriate. Sand smooth as necessary before painting.

Let new plaster or masonry cure 28 days before painting. Fill cracks and holes in masonry with Bondex Concrete Patch or other appropriate filler. Test plaster for water absorption prior to painting (paint will not adhere if water does not wet out the surface and absorb into the plaster). If necessary, sand or acid etch the surface with Metalprep® 79 diluted with five parts clean water to one part Metalprep 79. Retest for surface wetting before painting. (Note: If GLYPTEX™ Pigmented Sealer No. 135 will be used to prime the plaster, conduct the surface wetting test with mineral spirits instead of water.)

INSTRUCTIONS FOR USE

Tinting: Tint with Porter DESIGN SPECTRUM® Colorants per label directions. For XD base colors, use the Ultra Deep base and add 2 ounces/gallon of VV colorant to the XD base formula.

Mixing: Stir or shake thoroughly before application.

Thinning: Thin sparingly with clean water as necessary for proper application. Do not exceed ½ pint per gallon.

Clean-up: Clean tools and spray equipment with warm, soapy water immediately after use.

Application:

Conditions:	Temperature Range:	50°F to 110°F (air, surface, paint) (Optimum paint temperature 65-85°F)
	Dew Point:	Surface temperature must be at least 5°F above the dew point.
	Relative Humidity:	Maximum 85%
Equipment:	Brushes:	Use nylon or polyester brushes.
	Rollers:	Use 3/8" to 3/4" synthetic roller covers.
	Airless Spray:	Minimum 28:1 Pump Ratio; .015"-.018" tip; 1800-2400 psi; 1/4" high pressure material hose.
Directions:	New Work:	Apply a uniform prime coat per primer data sheet instructions (SEE RECOMMENDED SYSTEMS) at the millage specified for the application. <i>NOTE: Specified drywall sealers are specially designed to seal the surface better than finish paints, and to help reduce the appearance of tape joints and other surface imperfections.</i> Finish with one or more coats of VINYL FLAT Interior Latex Wall Paint No. 979 series.
	Repaint:	Spot prime bare areas as required with an appropriate primer (SEE RECOMMENDED SYSTEMS), then apply one or more coats of VINYL FLAT Interior Latex Wall Paint No. 979 series.

Washing Instructions: Protect the finish from abuse and contamination until well cured, at least 4-6 weeks. Try to avoid washing the finish for 30 days. For large areas, wash with a soft sponge and a solution of Soilax or TSP. For marks, pencil, etc., clean with a damp sponge and powdered cleanser. (See Porter Technical Bulletin #5: "How to Wash Flat Wall Paint.")

PRECAUTIONS

Prior to using this product, the user is specifically directed to obtain and read the current Material Safety Data Sheet and Label for this product. If, after reading these documents, you do not understand them, do not use this product. KEEP OUT OF REACH OF CHILDREN.

SHIPPING

Freight Classification: PAINT OR PAINT RELATED MATERIAL

Packaging: 6 Quarts per carton; 4 Gallons per carton; 5-Gallon Pail

Shipping Weights: 3.1 lb/qt (19.3 lb/carton); 12.2 lb/gal (49.8 lb/carton); 59.9 lb/5-gal



The technical data furnished is true and accurate to the best of our knowledge. However, no guarantee of accuracy is given or implied. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of products. Technical data are theoretical values and subject to change without prior notice.

Porter Paints 400 South 13th Street, Louisville, Kentucky 40203 1-800-332-6270
www.porterpaints.com. For Internet Ordering: www.getpaint.com

A PPG Brand