# SAFETY DATA SHEET

The information in this Safety Data Sheet is required pursuant to GHS UN rev. 7



Date of issue/Date of revision 19 July 2023

**Version 7** 

### **Section 1. Identification**

Product code : 10130DSC12X88

Product name : GORI 88
Product type : Liquid.

#### Other means of identification

\$\overline{\text{00309172}}\$; \$\overline{00309173}\$; \$\overline{00309174}\$; \$\overline{00309175}\$; \$\overline{00331606}\$; \$\overline{00360009}\$; \$\overline{00360000}\$; \$\overline{00360006}\$; \$\overline{00360007}\$; \$\overline{00360008}\$; \$\overline{00360009}\$; \$\overline{00360001}\$; \$\overline{00360001}\$; \$\overline{00360017}\$; \$\overline{00360019}\$; \$\overline{00360020}\$; \$\overline{00360025}\$; \$\overline{00360025}\$; \$\overline{00360025}\$; \$\overline{00360025}\$; \$\overline{00360025}\$; \$\overline{00360026}\$; \$\overline{00360026}\$; \$\overline{00360029}\$; \$\overline{00360031}\$; \$\overline{00360034}\$; \$\overline{00360037}\$; \$\overline{00360039}\$; \$\overline{00360039}\$; \$\overline{00360036}\$; \$\overline{00360037}\$; \$\overline{00360039}\$; \$\overline{00360039}\$; \$\overline{00360036}\$; \$\overline{00360037}\$; \$\overline{00360036}\$; \$\overline{00360110}\$; \$\overline{00360111}\$; \$\overline{00360145}\$; \$\overline{00360145}\$; \$\overline{00360145}\$; \$\overline{00360145}\$; \$\overline{00360145}\$; \$\overline{00360156}\$; \$\overline{00360151}\$; \$\overline{00360152}\$; \$\overline{00360153}\$; \$\overline{00360154}\$; \$\overline{00360155}\$; \$\overline{00360157}\$; \$\overline{00360152}\$; \$\overline{00360153}\$; \$\overline{00360155}\$; \$\overline{00360155}\$; \$\overline{00360157}\$; \$\overline{00360155}\$; \$\overline{00360155}\$; \$\overline{00360156}\$; \$\overline{00360152}\$; \$\overline{00360152}\$; \$\overline{00360154}\$; \$\overline{00360155}\$; \$\overline{00360157}\$; \$\overline{00360152}\$; \$\overline{00360155}\$; \$\overline{0036

#### Relevant identified uses of the substance or mixture and uses advised against

Product use : Coating.

Consumer applications, Professional applications, Application by non spray methods.

.

**Supplier's information**: PPG Asian Paints Private Limited

6A Shanti Nagar Santa Cruz (East) Mumbai - 400055

India

**Emergency telephone** 

number:

: +91 22 6815 8700

### Section 2. Hazards identification

Classification of the substance or mixture

: FLAMMABLE LIQUIDS - Category 4

SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

aquatic environment: 75.3%

**GHS label elements** 

Signal word : Warning

Hazard statements : Combustible liquid.

Harmful to aquatic life.

**Precautionary statements** 

General : Read carefully and follow all instructions. Keep out of reach of children. If medical

advice is needed, have product container or label at hand.

**Prevention**: Wear protective gloves, protective clothing and eye or face protection. Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Avoid release to the environment.

Response : Not applicable.

India Page: 1/11

**Product name GORI 88** 

### Section 2. Hazards identification

: Not applicable. **Storage** 

: Dispose of contents and container in accordance with all local, regional, national **Disposal** 

and international regulations.

result in classification

Other hazards which do not : Prolonged or repeated contact may dry skin and cause irritation.

## Section 3. Composition/information on ingredients

Substance/mixture : Mixture

#### **CAS** number/other identifiers

**CAS** number : Not applicable.

Ingredient name	%	CAS number
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	25 - <50	64742-48-9
2-methylpentane-2,4-diol	0.1 - <0.3	107-41-5
3-iodo-2-propynyl butylcarbamate	0.1 - < 0.3	55406-53-6

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is Inhalation

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show the container or label.

Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.

: No known significant effects or critical hazards. Inhalation

**Skin contact** : Defatting to the skin. May cause skin dryness and irritation.

: No known significant effects or critical hazards. Ingestion

#### Over-exposure signs/symptoms

**Eve contact** : No specific data. Inhalation : No specific data.

Adverse symptoms may include the following: Skin contact

irritation dryness cracking

: No specific data. Ingestion

#### Indication of immediate medical attention and special treatment needed, if necessary

India Page: 2/11

**Product name GORI 88** 

### Section 4. First aid measures

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** 

: No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Firefighting measures

#### **Extinguishing media**

Suitable extinguishing

media

Unsuitable extinguishing

media

: Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

: Do not use water jet.

Specific hazards arising from the chemical

: Combustible liquid. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon oxides

metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

India Page: 3/11

**Product name GORI 88** 

### Section 6. Accidental release measures

#### Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### **Precautions for safe handling**

#### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

#### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits
2-methylpentane-2,4-diol	ACGIH TLV (United States, 1/2022).  STEL: 10 mg/m³ 15 minutes. Form: Inhalable fraction. Aerosol only.  STEL: 50 ppm 15 minutes. Form: Vapor fraction  TWA: 25 ppm 8 hours. Form: Vapor fraction

India Page: 4/11

**Product name GORI 88** 

# Section 8. Exposure controls/personal protection

# Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

# Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

# **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

# Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

#### **Gloves**

: For prolonged or repeated handling, use the following type of gloves:

Recommended: nitrile rubber

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### **Respiratory protection**

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

India Page: 5/11

**Product name GORI 88** 

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**Appearance** 

**Physical state** : Liquid. Colour : Various

Odour : Hydrocarbon. [Slight]

: Not available. **Odour threshold** : Not available. **Melting point/freezing point Boiling point, initial boiling** point, and boiling range

: >37.78°C (>100°F)

**Flammability** Lower and upper explosive

(flammable) limits

: Not available. : Not available.

Flash point : Closed cup: 65°C (149°F)

**Auto-ignition temperature** 

°C °F **Method** Ingredient name Hydrocarbons, C10-C13, n-alkanes, >230 >446 isoalkanes, cyclics, < 2% aromatics

**Decomposition temperature** 

pН

: Not available. : Not applicable.

**Viscosity** 

Kinematic (40°C): >21 mm<sup>2</sup>/s

**Viscosity** 

> 100 s (ISO 6mm)

Solubility(ies)

Media Result cold water Not soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Vapour pressure

	Vapour Pressure at 20°C		Vapour pressure at 50°		re at 50°C	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				

**Relative density** 0.94

Relative vapour density

**Particle characteristics** 

: Not available.

Median particle size

**Evaporation rate** 

: Not applicable. : Not available.

## Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition

products.

India Page: 6/11

**Product name GORI 88** 

## Section 10. Stability and reactivity

**Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

Oxidising agents, strong alkalis, strong acids

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

Hazardous polymerisation : Under normal conditions of storage and use, hazardous polymerisation will not

occur.

## **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>6 g/kg	-
2-methylpentane-2,4-diol	LD50 Dermal	Rat - Male,	>2000 mg/kg	-
		Female		
	LD50 Oral	Rat	3700 mg/kg	-
3-iodo-2-propynyl butylcarbamate	LC50 Inhalation Dusts and mists	Rat	0.67 mg/l	4 hours
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	1470 mg/kg	-

**Conclusion/Summary** 

: There are no data available on the mixture itself.

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
3-iodo-2-propynyl butylcarbamate	Eyes - Severe irritant	Rabbit	-	-	-

#### Conclusion/Summary

**Skin** : There are no data available on the mixture itself.

**Eyes** : There are no data available on the mixture itself.

**Respiratory**: There are no data available on the mixture itself.

**Sensitisation** 

**Conclusion/Summary** 

**Skin**: There are no data available on the mixture itself.

**Respiratory**: There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Reproductive toxicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

India Page: 7/11

**Product name GORI 88** 

## **Section 11. Toxicological information**

#### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
3-iodo-2-propynyl butylcarbamate	Category 1	-	trachea

#### **Aspiration hazard**

Name	Result
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	ASPIRATION HAZARD - Category 1

Information on likely routes

of exposure

: Not available.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: Defatting to the skin. May cause skin dryness and irritation.

**Ingestion** : No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data. **Inhalation** : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation dryness cracking

**Ingestion**: No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects: Not available.

Potential chronic health effects

Not available.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

**Acute toxicity estimates** 

	India	Page: 8/11
--	-------	------------

**Product name GORI 88** 

# Section 11. Toxicological information

Not available.

#### Other information

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
2-methylpentane-2,4-diol	EC50 >429 mg/l EC50 5.41 mg/l LC50 8.51 mg/l NOEC 429 mg/l	Algae - Raphidocelis subcapitata Daphnia - Daphnia magna Fish - Gambusia affinis Algae - Raphidocelis subcapitata	48 hours 96 hours
3-iodo-2-propynyl butylcarbamate	Acute EC50 0.186 mg/l Fresh water  Acute LC50 0.067 mg/l  Chronic NOEC 0.049 mg/l	Daphnia - Daphnia magna Fish Fish	48 hours 96 hours 96 hours

#### Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2-methylpentane-2,4-diol	OECD 301F Ready Biodegradability - Manometric Respirometry Test	81 % - 28 days	-	-
3-iodo-2-propynyl butylcarbamate	-	25 % - Inherent - 28 da	ays -	-
Product/ingredient name	Aquatic half-life	Photolysi	 S	Biodegradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-methylpentane-2,4-diol 3-iodo-2-propynyl butylcarbamate	-	-	Readily Inherent

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
2-methylpentane-2,4-diol	0.58	-	Low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

	India	Page: 9/11
--	-------	------------

**Product name GORI 88** 

## Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## **Section 14. Transport information**

	UN	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### Additional information

UN : None identified. **IMDG** : None identified. **IATA** : None identified.

Special precautions for user :Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

## Section 15. Regulatory information

International regulations

**Montreal Protocol** 

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

India Page: 10/11

**Product name GORI 88** 

### Section 16. Other information

**History** 

Date of issue/Date of : 19 July 2023

revision

Date of previous issue : 6/18/2023

Version : 7
Prepared by : EHS

**yey to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

#### Procedure used to derive the classification

Classification	Justification
9 ,	On basis of test data Calculation method

#### ▼ Indicates information that has changed from previously issued version.

#### **Notice to reader**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

India Page: 11/11