

# SAFETY DATA SHEET



Date of issue/Date of revision

: 22 February 2024

Version

: 4.24

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : BONDEX TEAK OIL

Product code : 10140DSC44X90

#### Other means of identification

00361710; 00361728; 00361729; 00361767; 00361769; 00361914; 00361915; 00361960; 00361961; 00363366; 00385406; 00385421; 00439020; 00473971; 00473972

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

| Identified uses                             |
|---|
| Professional painting, outdoor brush/roller |

Product use : Consumer applications, Professional applications, Application by non spray methods..

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Danmark A/S  
Gladsaxevej 300  
DK-2860 Søborg  
Tlf.: +45 39 57 94 00

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

### 1.4 Emergency telephone number

#### Supplier

+45 (0)56 64 50 00

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Asp. Tox. 1, H304

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.


See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

|                 |                 |                                |                    |
|-----------------|-----------------|--------------------------------|--------------------|
| Code            | : 10140DSC44X90 | Date of issue/Date of revision | : 22 February 2024 |
| BONDEX TEAK OIL |                 |                                |                    |

SECTION 2: Hazards identification

|  |   |  |
|--|---|--|
| Hazard pictograms  | : |   |
| Signal word  | : | Danger   |
| Hazard statements  | : | May be fatal if swallowed and enters airways.  |
| <u>Precautionary statements</u>  |   |  |
| General  | : | Keep out of reach of children. If medical advice is needed, have product container or label at hand.   |
| Prevention   | : | Not applicable.  |
| Response   | : | IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.  |
| Storage  | : | Store locked up.   |
| Disposal   | : | Dispose of contents and container in accordance with all local, regional, national and international regulations.<br>P102, P101, P301 + P310, P331, P405, P501 |
| Hazardous ingredients  | : | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics  |
| Supplemental label elements  | : | <input checked="" type="checkbox"/> Repeated exposure may cause skin dryness or cracking.  |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : | Not applicable.  |
| <u>Special packaging requirements</u>  |   |  |
| Containers to be fitted with child-resistant fastenings  | : | Yes, applicable.   |
| Tactile warning of danger  | : | Yes, applicable.   |

2.3 Other hazards

|   |   |   |
|---|---|---|
| Product meets the criteria for PBT or vPvB          | : | This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do not result in classification | : | Prolonged or repeated contact may dry skin and cause irritation.                      |

SECTION 3: Composition/information on ingredients

|              |   |         |
|--------------|---|---------|
| 3.2 Mixtures | : | Mixture |
|--------------|---|---------|

|                 |                 |                                |                    |
|-----------------|-----------------|--------------------------------|--------------------|
| Code            | : 10140DSC44X90 | Date of issue/Date of revision | : 22 February 2024 |
| BONDEX TEAK OIL |                 |                                |                    |

SECTION 3: Composition/information on ingredients

| Product/ingredient name   | Identifiers  | % by weight | Classification   | Specific Conc. Limits, M-factors and ATEs | Type    |
|---|--|-------------|--|---|---------|
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | REACH #:<br>01-2119457273-39<br>EC: 918-481-9<br>CAS: 64742-48-9 | ≥25 - ≤50   | Asp. Tox. 1, H304<br>EUH066  | EUH066: C ≥ 20%                           | [1]     |
| 2-methylpentane-2,4-diol  | EC: 203-489-0<br>CAS: 107-41-5                                   | ≤0.30       | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Repr. 2, H361d<br><b>See Section 16 for the full text of the H statements declared above.</b> | -   | [1] [2] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type  
[1] Substance classified with a health or environmental hazard  
[2] Substance with a workplace exposure limit  
Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact : No known significant effects or critical hazards.
- Inhalation : No known significant effects or critical hazards.
- Skin contact : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion : May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact : No specific data.
- Inhalation : No specific data.

|                 |                 |                                |                    |
|-----------------|-----------------|--------------------------------|--------------------|
| Code            | : 10140DSC44X90 | Date of issue/Date of revision | : 22 February 2024 |
| BONDEX TEAK OIL |                 |                                |                    |

SECTION 4: First aid measures

|              |  |
|--------------|--|
| Skin contact | : Adverse symptoms may include the following:<br>irritation<br>dryness<br>cracking |
| Ingestion    | : Adverse symptoms may include the following:<br>nausea or vomiting                |

4.3 Indication of any immediate medical attention and special treatment needed

|                     |   |
|---------------------|---|
| Notes to physician  | : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : No specific treatment.  |

SECTION 5: Firefighting measures

5.1 Extinguishing media

|                                |   |
|--------------------------------|---|
| Suitable extinguishing media   | : Use an extinguishing agent suitable for the surrounding fire. |
| Unsuitable extinguishing media | : None known.   |

5.2 Special hazards arising from the substance or mixture

|                                       |  |
|---------------------------------------|--|
| Hazards from the substance or mixture | : In a fire or if heated, a pressure increase will occur and the container may burst.                |
| Hazardous combustion products         | : Decomposition products may include the following materials:<br>carbon oxides<br>metal oxide/oxides |

5.3 Advice for firefighters

|  |   |
|--|---|
| Special precautions for fire-fighters          | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.   |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents. |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

|                             |   |
|-----------------------------|---|
| For non-emergency personnel | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| For emergency responders    | : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".   |

6.2 Environmental precautions

|  |   |
|--|---|
|  | : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). |
|--|---|

|                 |                 |                                |                    |
|-----------------|-----------------|--------------------------------|--------------------|
| Code            | : 10140DSC44X90 | Date of issue/Date of revision | : 22 February 2024 |
| BONDEX TEAK OIL |                 |                                |                    |

SECTION 6: Accidental release measures

6.3 Methods and material for containment and cleaning up

- Small spill
- : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill
- : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

- 6.4 Reference to other sections
- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures
- : Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.
- Advice on general occupational hygiene
- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- 7.2 Conditions for safe storage, including any incompatibilities
- : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

|                 |                 |                                |                    |
|-----------------|-----------------|--------------------------------|--------------------|
| Code            | : 10140DSC44X90 | Date of issue/Date of revision | : 22 February 2024 |
| BONDEX TEAK OIL |                 |                                |                    |

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name  | Exposure limit values  |
|--------------------------|--|
| 2-methylpentane-2,4-diol | ACGIH TLV (United States, 1/2023).<br>STEL: 10 mg/m³ 15 minutes. Form: Inhalable fraction. Aerosol only.<br>STEL: 50 ppm 15 minutes. Form: Vapor fraction<br>TWA: 25 ppm 8 hours. Form: Vapor fraction |

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

| Product/ingredient name  | Type | Exposure              | Value             | Population         | Effects  |
|--------------------------|------|-----------------------|-------------------|--------------------|----------|
| 2-methylpentane-2,4-diol | DNEL | Long term Inhalation  | 25 mg/m³          | General population | Local    |
|                          | DNEL | Long term Inhalation  | 49 mg/m³          | Workers            | Local    |
|                          | DNEL | Short term Inhalation | 98 mg/m³          | Workers            | Local    |
|                          | DNEL | Long term Oral        | 2.25 mg/kg bw/day | General population | Systemic |
|                          | DNEL | Long term Inhalation  | 7.83 mg/m³        | General population | Systemic |
|                          | DNEL | Long term Dermal      | 22.5 mg/kg bw/day | General population | Systemic |
|                          | DNEL | Long term Inhalation  | 44.43 mg/m³       | Workers            | Systemic |
|                          | DNEL | Short term Inhalation | 49 mg/m³          | General population | Local    |
|                          | DNEL | Long term Dermal      | 63 mg/kg bw/day   | Workers            | Systemic |

PNECs

PNECs - Not available.

8.2 Exposure controls

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety glasses with side shields. Use eye protection according to EN 166.
- Skin protection**
- Hand protection** :

|                 |                 |                                |                    |
|-----------------|-----------------|--------------------------------|--------------------|
| Code            | : 10140DSC44X90 | Date of issue/Date of revision | : 22 February 2024 |
| BONDEX TEAK OIL |                 |                                |                    |

SECTION 8: Exposure controls/personal protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

|                                 |  |
|---------------------------------|--|
| Gloves                          | : For prolonged or repeated handling, use the following type of gloves:<br><br>Recommended: nitrile rubber   |
| Body protection                 | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.  |
| Other skin protection           | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.  |
| Respiratory protection          | : Use with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Wear a respirator conforming to EN140. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Mask type: full-face mask half-face mask Filter type: organic vapour filter (Type A) particulate filter P3 Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. |
| Environmental exposure controls | : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.   |

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

|   |   |
|---|---|
| Appearance                              |   |
| Physical state                          | : Liquid.   |
| Colour                                  | : Various   |
| Odour                                   | : Hydrocarbon.  |
| Odour threshold                         | : Not available.  |
| Melting point/freezing point            | : May start to solidify at the following temperature: -54°C (-65.2°F) This is based on data for the following ingredient: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics . |
| Initial boiling point and boiling range | : >37.78°C  |
| Flammability                            | : Not available.  |



|                 |                 |                                |                    |
|-----------------|-----------------|--------------------------------|--------------------|
| Code            | : 10140DSC44X90 | Date of issue/Date of revision | : 22 February 2024 |
| BONDEX TEAK OIL |                 |                                |                    |

SECTION 9: Physical and chemical properties

| Upper/lower flammability or explosive limits   | : Greatest known range: Lower: 0.6% Upper: 7% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics )    |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
|--|---|-----------------|-------------------------|-------------------------|-------------|---|------|------|-------|-----|--------|-------|-----|--------|---|-------|------|--|--|--|--|
| Flash point  | : Closed cup: 63°C  |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| Auto-ignition temperature  | :   |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| <table><tr><th>Ingredient name</th><th>°C</th><th>°F</th><th>Method</th></tr><tr><td>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics</td><td>&gt;230</td><td>&gt;446</td><td></td></tr></table>   |   | Ingredient name | °C                      | °F                      | Method      | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | >230 | >446 |       |     |        |       |     |        |   |       |      |  |  |  |  |
| Ingredient name  | °C  | °F              | Method                  |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics  | >230  | >446            |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| Decomposition temperature  | : Stable under recommended storage and handling conditions (see Section 7).   |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| pH   | : Not applicable. insoluble in water.   |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| Viscosity  | : Kinematic (40°C): <20 mm²/s   |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| Viscosity  | : 30 - <40 s (ISO 6mm)  |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| Solubility(ies)  | :   |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| <table><tr><th>Media</th><th>Result</th></tr><tr><td>cold water</td><td>Not soluble</td></tr></table>  |   | Media           | Result                  | cold water              | Not soluble |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| Media  | Result  |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| cold water   | Not soluble   |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| Partition coefficient: n-octanol/ water  | : 3   |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| Vapour pressure  | :   |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| <table><tr><th rowspan="2">Ingredient name</th><th colspan="3">Vapour Pressure at 20°C</th><th colspan="3">Vapour pressure at 50°C</th></tr><tr><th>mm Hg</th><th>kPa</th><th>Method</th><th>mm Hg</th><th>kPa</th><th>Method</th></tr><tr><td>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics</td><td>0.375</td><td>0.05</td><td></td><td></td><td></td><td></td></tr></table> |   | Ingredient name | Vapour Pressure at 20°C |                         |             | Vapour pressure at 50°C   |      |      | mm Hg | kPa | Method | mm Hg | kPa | Method | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | 0.375 | 0.05 |  |  |  |  |
| Ingredient name  | Vapour Pressure at 20°C   |                 |                         | Vapour pressure at 50°C |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
|  | mm Hg   | kPa             | Method                  | mm Hg                   | kPa         | Method  |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics  | 0.375   | 0.05            |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| Evaporation rate   | : 0.04 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics ) compared with butyl acetate               |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| Relative density   | : 0.9   |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| Explosive properties   | : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible. |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| Oxidising properties   | : Product does not present an oxidizing hazard.   |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| <u>Particle characteristics</u>  |   |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| Median particle size   | : Not applicable.   |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| 9.2 Other information  |   |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |
| No additional information.   |   |                 |                         |                         |             |   |      |      |       |     |        |       |     |        |   |       |      |  |  |  |  |

SECTION 10: Stability and reactivity

|   |  |
|---|--|
| 10.1 Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients.   |
| 10.2 Chemical stability                 | : The product is stable.   |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.  |
| 10.4 Conditions to avoid                | : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8. |
| 10.5 Incompatible materials             | : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.           |



|                 |                 |                                |                    |
|-----------------|-----------------|--------------------------------|--------------------|
| Code            | : 10140DSC44X90 | Date of issue/Date of revision | : 22 February 2024 |
| BONDEX TEAK OIL |                 |                                |                    |

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials:  
carbon oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Product/ingredient name   | Result      | Species            | Dose        | Exposure |
|---|-------------|--------------------|-------------|----------|
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics<br><br>2-methylpentane-2,4-diol | LD50 Dermal | Rabbit             | >5000 mg/kg | -        |
|   | LD50 Oral   | Rat                | >6 g/kg     | -        |
|   | LD50 Dermal | Rat - Male, Female | >2000 mg/kg | -        |
|   | LD50 Oral   | Rat                | 3700 mg/kg  | -        |

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitisation

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Aspiration hazard

| Product/ingredient name   | Result                         |
|---|--------------------------------|
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | ASPIRATION HAZARD - Category 1 |

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.

Ingestion : May be fatal if swallowed and enters airways.

Skin contact : Defatting to the skin. May cause skin dryness and irritation.

Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : No specific data.

|                 |                 |                                |                    |
|-----------------|-----------------|--------------------------------|--------------------|
| Code            | : 10140DSC44X90 | Date of issue/Date of revision | : 22 February 2024 |
| BONDEX TEAK OIL |                 |                                |                    |

SECTION 11: Toxicological information

|   |  |
|---|--|
| Ingestion   | : Adverse symptoms may include the following:<br>nausea or vomiting                                    |
| Skin contact  | : Adverse symptoms may include the following:<br>irritation<br>dryness<br>cracking                     |
| Eye contact   | : No specific data.  |
| <u>Delayed and immediate effects as well as chronic effects from short and long-term exposure</u> |  |
| <u>Short term exposure</u>  |  |
| Potential immediate effects   | : Not available.   |
| Potential delayed effects   | : Not available.   |
| <u>Long term exposure</u>   |  |
| Potential immediate effects   | : Not available.   |
| Potential delayed effects   | : Not available.   |
| <u>Potential chronic health effects</u>   |  |
| Not available.  |  |
| Conclusion/Summary  | : Not available.   |
| General   | : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. |
| Carcinogenicity   | : No known significant effects or critical hazards.  |
| Mutagenicity  | : No known significant effects or critical hazards.  |
| Reproductive toxicity   | : No known significant effects or critical hazards.  |
| Other information   | : Not available.   |

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name  | Result         | Species                                 | Exposure |
|--------------------------|----------------|---|----------|
| 2-methylpentane-2,4-diol | EC50 >429 mg/l | Algae - <i>Raphidocelis subcapitata</i> | 72 hours |
|                          | EC50 5.41 mg/l | Daphnia - <i>Daphnia magna</i>          | 48 hours |
|                          | LC50 8.51 mg/l | Fish - <i>Gambusia affinis</i>          | 96 hours |
|                          | NOEC 429 mg/l  | Algae - <i>Raphidocelis subcapitata</i> | 72 hours |

|                    |  |
|--------------------|--|
| Conclusion/Summary | : There are no data available on the mixture itself. |
|--------------------|--|

|                 |                 |                                |                    |
|-----------------|-----------------|--------------------------------|--------------------|
| Code            | : 10140DSC44X90 | Date of issue/Date of revision | : 22 February 2024 |
| BONDEX TEAK OIL |                 |                                |                    |

SECTION 12: Ecological information

12.2 Persistence and degradability

| Product/ingredient name  | Test  | Result         | Dose | Inoculum |
|--------------------------|---|----------------|------|----------|
| 2-methylpentane-2,4-diol | OECD 301F Ready Biodegradability - Manometric Respirometry Test | 81 % - 28 days | -    | -        |

Conclusion/Summary : There are no data available on the mixture itself.

| Product/ingredient name  | Aquatic half-life | Photolysis | Biodegradability |
|--------------------------|-------------------|------------|------------------|
| 2-methylpentane-2,4-diol | -                 | -          | Readily          |

12.3 Bioaccumulative potential

| Product/ingredient name  | LogP <sub>ow</sub> | BCF | Potential |
|--------------------------|--------------------|-----|-----------|
| BONDEX TEAK OIL          | 3                  | -   | Low       |
| 2-methylpentane-2,4-diol | 0.58               | -   | Low       |

12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

|                 |                 |                                |                    |
|-----------------|-----------------|--------------------------------|--------------------|
| Code            | : 10140DSC44X90 | Date of issue/Date of revision | : 22 February 2024 |
| BONDEX TEAK OIL |                 |                                |                    |

SECTION 13: Disposal considerations

| Waste code | Waste designation   |
|------------|---|
| 08 01 11*  | waste paint and varnish containing organic solvents or other hazardous substances |

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container         | 15 01 06 mixed packaging       |

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

|                                 | ADR/RID         | ADN  | IMDG            | IATA            |
|---------------------------------|-----------------|--|-----------------|-----------------|
| 14.1 UN number or ID number     | Not regulated.  | 9003   | Not regulated.  | Not regulated.  |
| 14.2 UN proper shipping name    | -               | SUBSTANCES WITH A FLASH-POINT ABOVE 60 °C AND NOT MORE THAN 100 °C<br><br>(Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics ) | -               | -               |
| 14.3 Transport hazard class(es) | -               | 9  | -               | -               |
| 14.4 Packing group              | -               | -  | -               | -               |
| 14.5 Environmental hazards      | No.             | No.  | No.             | No.             |
| Marine pollutant substances     | Not applicable. | Not applicable.  | Not applicable. | Not applicable. |

Additional information

ADR/RID : None identified.  
ADN : The product is only regulated as a dangerous good when transported in tank vessels.  
IMDG : None identified.  
IATA : None identified.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

|                 |                 |                                |                    |
|-----------------|-----------------|--------------------------------|--------------------|
| Code            | : 10140DSC44X90 | Date of issue/Date of revision | : 22 February 2024 |
| BONDEX TEAK OIL |                 |                                |                    |

14. Transport information

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture  
EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions** : Not applicable.  
on the manufacture,  
placing on the market  
and use of certain  
dangerous substances,  
mixtures and articles

**Explosive precursors** : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

**VOC for Ready-for-Use Mixture** : IIA/f. Interior and exterior minimal build woodstains. EU limit values: 700 g/l (2010.)  
This product contains a maximum of 500 g/l VOC.

Seveso Directive

This product is not controlled under the Seveso Directive.

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms**

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- PBT = Persistent, Bioaccumulative and Toxic
- vPvB = Very Persistent and Very Bioaccumulative
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- IMDG = International Maritime Dangerous Goods
- IATA = International Air Transport Association

Full text of abbreviated H statements

|                 |                 |                                |                    |
|-----------------|-----------------|--------------------------------|--------------------|
| Code            | : 10140DSC44X90 | Date of issue/Date of revision | : 22 February 2024 |
| BONDEX TEAK OIL |                 |                                |                    |

SECTION 16: Other information

|   |  |
|---|--|
| H304<br>H315<br>H319<br>H361d<br>EUH066 | May be fatal if swallowed and enters airways.<br>Causes skin irritation.<br>Causes serious eye irritation.<br>Suspected of damaging the unborn child.<br>Repeated exposure may cause skin dryness or cracking. |
|---|--|

Full text of classifications [CLP/GHS]

|   |  |
|---|--|
| Asp. Tox. 1<br>Eye Irrit. 2<br>Repr. 2<br>Skin Irrit. 2 | ASPIRATION HAZARD - Category 1<br>SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2<br>REPRODUCTIVE TOXICITY - Category 2<br>SKIN CORROSION/IRRITATION - Category 2 |
|---|--|

History

|                                 |                    |
|---------------------------------|--------------------|
| Date of issue/ Date of revision | : 22 February 2024 |
| Date of previous issue          | : 9 January 2024   |
| Prepared by                     | : EHS              |
| Version                         | : 4.24             |

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

# Safe Use of Mixtures Information for end-users

**Title** : Professional painting, outdoor brush/roller

*This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.*

## General description of the process covered

Outdoor painting by professionals with brush or roller

**This safe use information is linked to SWED no.** : CEPE\_PW\_06

**Product category(ies)** : Coatings and paints, thinners, paint removers

## Operational conditions

**Place of use** : Outdoor use

## Risk management measures (RMM)

| Contributing activity   | Maximum duration  | Ventilation |                            | Respiratory   | Eye                                     | Hands                                 |
|---|-------------------|-------------|----------------------------|---|---|---------------------------------------|
|   |                   | Type        | ach (air changes per hour) |   |   |                                       |
| Preparation of material for application                                     | More than 4 hours | Outdoors    | 3 - 5                      | See chapter 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Loading of application equipment and handling of coated parts before curing | More than 4 hours | Outdoors    | 3 - 5                      | See chapter 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Professional application of coatings and inks by brush or roller            | More than 4 hours | Outdoors    | 3 - 5                      | See chapter 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Film formation - force drying, stoving and other technologies               | More than 4 hours | Outdoors    | 3 - 5                      | See chapter 8 of this Safety Data Sheet for specifications. | None                                    | None                                  |
| Cleaning  | More than 4 hours | Outdoors    | 3 - 5                      | See chapter 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Waste management  | More than 4 hours | Outdoors    | 3 - 5                      | See chapter 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |

See chapter 8 of this Safety Data Sheet for specifications.



## Disclaimer

The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.