

SAFETY DATA SHEET

Date of issue/Date of revision

: 15 May 2020

Version

: 2



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : JOHNSTONES WOODWORKS Opaque Wood Finish

Product code : 17000DUW002

Other means of identification

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Consumer applications, Professional applications.

**Use of the substance/
mixture** : Coating.

1.3 Details of the supplier of the safety data sheet

PPG Architectural Coatings UK Ltd
Huddersfield Road
Birstall, West Yorkshire WF179XA
United Kingdom
Tel: +44 (0) 1924 354000
Fax: +44 (0) 1924 354533

**e-mail address of person
responsible for this SDS** : ps.acemea-north@ppg.com

1.4 Emergency telephone number

Supplier

+44 (0) 1924 354000

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Code : 17000DUW002 Date of issue/Date of revision : 15 May 2020
 JOHNSTONES WOODWORKS Opaque Wood Finish

SECTION 2: Hazards identification

Hazard pictograms :



Signal word : Warning

Hazard statements : Flammable liquid and vapour.

Precautionary statements

- General** : Keep out of reach of children. If medical advice is needed, have product container or label at hand.
- Prevention** : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Response** : Not applicable.
- Storage** : Not applicable.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
 P102, P101, P210, P501

Hazardous ingredients : Not applicable.

Supplemental label elements : Contains 2-butanone oxime. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % by weight | Classification Regulation (EC) No. 1272/2008 [CLP] | Type |
|-------------------------|-------------|-------------|--|------|
| | | | | |

| | |
|--|---|
| Code : 17000DUW002 | Date of issue/Date of revision : 15 May 2020 |
| JOHNSTONES WOODWORKS Opaque Wood Finish | |

SECTION 3: Composition/information on ingredients

| | | | | |
|--|---|-------------|---|---------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | REACH #: 01-2119463258-33 EC: 919-857-5 CAS: 64742-48-9 | ≥10 - <20 | Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066 | [1] |
| Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics | REACH #: 01-2119456620-43 EC: 926-141-6 CAS: 64742-47-8 | ≥1.0 - ≤5.0 | Asp. Tox. 1, H304 EUH066 | [1] [2] |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | REACH #: 01-2119457273-39 EC: 918-481-9 CAS: 64742-48-9 (EC 918-481-9) | ≥1.0 - ≤5.0 | Asp. Tox. 1, H304 EUH066 | [1] |
| Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics | REACH #: 01-2119457736-27 EC: 927-632-8 CAS: 64742-47-8 | ≥1.0 - ≤5.0 | Asp. Tox. 1, H304 EUH066 | [1] |
| 2-butanone oxime | REACH #: 01-2119539477-28 EC: 202-496-6 CAS: 96-29-7 Index: 616-014-00-0 | <1.0 | Acute Tox. 4, H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351 | [1] |
| 2-ethylhexanoic acid, zirconium salt | REACH #: 01-2119979088-21 EC: 245-018-1 CAS: 22464-99-9 | ≤0.30 | Repr. 2, H361 (oral) | [1] [2] |
| | | | See Section 16 for the full text of the H statements declared above. | |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

- Type
- [1] Substance classified with a health or environmental hazard
 - [2] Substance with a workplace exposure limit
 - [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
 - [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
 - [5] Substance of equivalent concern
 - [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Code : 17000DUW002 Date of issue/Date of revision : 15 May 2020
 JOHNSTONES WOODWORKS Opaque Wood Finish

SECTION 4: First aid measures

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon oxides
metal oxide/oxides

5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Code : 17000DUW002 Date of issue/Date of revision : 15 May 2020

JOHNSTONES WOODWORKS Opaque Wood Finish

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Code : 17000DUW002 Date of issue/Date of revision : 15 May 2020
 JOHNSTONES WOODWORKS Opaque Wood Finish

SECTION 7: Handling and storage

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 5 to 25°C (41 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|--|---|
| Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics 2-ethylhexanoic acid, zirconium salt | EU OEL (Europe). TWA: 1200 mg/m ³ EH40/2005 WELs (United Kingdom (UK), 8/2018). STEL: 10 mg/m ³ , (as Zr) 15 minutes. TWA: 5 mg/m ³ , (as Zr) 8 hours. |

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

| | |
|--|---|
| Code : 17000DUW002 | Date of issue/Date of revision : 15 May 2020 |
| JOHNSTONES WOODWORKS Opaque Wood Finish | |

SECTION 8: Exposure controls/personal protection

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|---|------|----------------------|------------------------|--------------------------------|----------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | DNEL | Long term Dermal | 208 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 871 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 125 mg/kg bw/day | General population [Consumers] | Systemic |
| | DNEL | Long term Inhalation | 185 mg/m ³ | General population [Consumers] | Systemic |
| 2-butanone oxime | DNEL | Long term Oral | 125 mg/kg bw/day | General population [Consumers] | Systemic |
| | DNEL | Long term Dermal | 0.78 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 1.3 mg/kg bw/day | Workers | Systemic |
| | DNEL | Short term Dermal | 1.5 mg/kg bw/day | General population | Systemic |
| 2-ethylhexanoic acid, zirconium salt | DNEL | Long term Inhalation | 2 mg/m ³ | General population | Local |
| | DNEL | Short term Dermal | 2.5 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 2.7 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 3.33 mg/m ³ | Workers | Local |
| | DNEL | Long term Inhalation | 9 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Oral | 2.5 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Inhalation | 2.5 mg/m ³ | General population | Systemic |
| | DNEL | Long term Dermal | 3.25 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Inhalation | 5 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 6.49 mg/kg bw/day | Workers | Systemic |

PNECs

| Product/ingredient name | Type | Compartment Detail | Value | Method Detail |
|-------------------------|------|------------------------|------------|--------------------|
| 2-butanone oxime | - | Fresh water | 0.256 mg/l | Assessment Factors |
| | - | Sewage Treatment Plant | 177 mg/l | Assessment Factors |

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles. Use eye protection according to EN 166.

Skin protection

Code : 17000DUW002 Date of issue/Date of revision : 15 May 2020

JOHNSTONES WOODWORKS Opaque Wood Finish

SECTION 8: Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Gloves** : For prolonged or repeated handling, use the following type of gloves:
Recommended: nitrile rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Wear a respirator conforming to EN140. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Mask type: full-face mask half-face mask Filter type: organic vapour filter (Type A) particulate filter P3 Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Various
- Odour** : Hydrocarbon. [Slight]
- Odour threshold** : Not available.
- pH** : insoluble in water.
- Melting point/freezing point** : May start to solidify at the following temperature: -15°C (5°F) This is based on data for the following ingredient: Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics. Weighted average: -60.69°C (-77.2°F)
- Initial boiling point and boiling range** : 145°C

Code : 17000DUW002 **Date of issue/Date of revision** : 15 May 2020
JOHNSTONES WOODWORKS Opaque Wood Finish

SECTION 9: Physical and chemical properties

| | |
|---|--|
| Flash point | : Closed cup: 43°C |
| Evaporation rate | : Highest known value: 0.04 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics) Weighted average: 0.03 compared with butyl acetate |
| Flammability (solid, gas) | : liquid |
| Upper/lower flammability or explosive limits | : Greatest known range: Lower: 0.6% Upper: 7% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics) |
| Vapour pressure | : Highest known value: 0.1 to 0.3 kPa (0.8 to 2.3 mm Hg) (at 20°C) (Naphtha (petroleum), hydrotreated heavy). Weighted average: 0.16 kPa (1.2 mm Hg) (at 20°C) |
| Vapour density | : Highest known value: 4.5 (Air = 1) (Distillates (petroleum), hydrotreated light). Weighted average: 4.5 (Air = 1) |
| Relative density | : 1.3 |
| Solubility(ies) | : Insoluble in the following materials: cold water. |
| Partition coefficient: n-octanol/ water | : Not applicable. |
| Auto-ignition temperature | : Lowest known value: >220°C (>428°F) (Distillates (petroleum), hydrotreated light). |
| Decomposition temperature | : Stable under recommended storage and handling conditions (see Section 7). |
| Viscosity | : Kinematic (room temperature): >4 cm ² /s Kinematic (40°C): >0.21 cm ² /s |
| Viscosity | : > 100 s (ISO 6mm) |
| Explosive properties | : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible. |
| Oxidising properties | : Product does not present an oxidizing hazard. |

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

| | |
|--|---|
| 10.1 Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| 10.2 Chemical stability | : The product is stable. |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| 10.4 Conditions to avoid | : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8. |
| 10.5 Incompatible materials | : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids. |
| 10.6 Hazardous decomposition products | : Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides |

Code : 17000DUW002 Date of issue/Date of revision : 15 May 2020
 JOHNSTONES WOODWORKS Opaque Wood Finish

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|-------------|---------|-------------|----------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | LD50 Dermal | Rat | >5000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics | LD50 Dermal | Rat | >5000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | LD50 Dermal | Rabbit | >5000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| 2-butanone oxime | LD50 Oral | Rat | >6 g/kg | - |
| 2-ethylhexanoic acid, zirconium salt | LD50 Oral | Rat | 930 mg/kg | - |
| | LD50 Dermal | Rabbit | >5 g/kg | - |
| | LD50 Oral | Rat | >5 g/kg | - |

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

| Route | ATE value |
|----------------|-----------|
| Not available. | |

Irritation/Corrosion

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitisation

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|---|------------|-------------------|------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | Category 3 | - | Narcotic effects |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Code : 17000DUW002 **Date of issue/Date of revision** : 15 May 2020
JOHNSTONES WOODWORKS Opaque Wood Finish

SECTION 11: Toxicological information

| Product/ingredient name | Result |
|---|--------------------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | ASPIRATION HAZARD - Category 1 |
| Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics | ASPIRATION HAZARD - Category 1 |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | ASPIRATION HAZARD - Category 1 |
| Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics | ASPIRATION HAZARD - Category 1 |

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.
Skin contact : Defatting to the skin. May cause skin dryness and irritation.
Eye contact : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : No specific data.
Ingestion : No specific data.
Skin contact : Adverse symptoms may include the following:
 irritation
 dryness
 cracking
Eye contact : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.
General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Teratogenicity : No known significant effects or critical hazards.
Developmental effects : No known significant effects or critical hazards.
Fertility effects : No known significant effects or critical hazards.
Other information : Not available.

⚠ Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

Code : 17000DUW002 **Date of issue/Date of revision** : 15 May 2020
JOHNSTONES WOODWORKS Opaque Wood Finish

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|---|----------------------|---------|----------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | LC50 >1000 mg/l | Algae | 72 hours |
| 2-ethylhexanoic acid, zirconium salt | Acute LC50 >100 mg/l | Fish | 96 hours |

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

| Product/ingredient name | Test | Result | Dose | Inoculum |
|--|---|--------------------------|------|----------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | - | 80 % - Readily - 28 days | - | - |
| Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics | OECD 301F Ready Biodegradability - Manometric Respirometry Test | 69 % - Readily - 28 days | - | - |

Conclusion/Summary : There are no data available on the mixture itself.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | - | - | Readily |
| Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics | - | - | Readily |
| Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics | - | - | Readily |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|---|--------------------|------------|-----------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | - | 10 to 2500 | high |
| Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics | - | 159 | low |
| 2-butanone oxime | 0.63 | 5.01 | low |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

Code : 17000DUW002 **Date of issue/Date of revision** : 15 May 2020
JOHNSTONES WOODWORKS Opaque Wood Finish

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

| Waste code | Waste designation |
|------------|---|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances |

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | European waste catalogue (EWC) |
|-------------------|--------------------------------|
| Container | 15 01 04 metallic packaging |

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

| | ADR/RID | ADN | IMDG | IATA |
|--|-----------------|-----------------|-----------------|-----------------|
| 14.1 UN number | UN1263 | UN1263 | UN1263 | UN1263 |
| 14.2 UN proper shipping name | PAINT | PAINT | PAINT | PAINT |
| 14.3 Transport hazard class(es) | 3 | 3 | 3 | 3 |
| 14.4 Packing group | III | III | III | III |
| 14.5 Environmental hazards | No. | Yes. | No. | No. |
| Marine pollutant substances | Not applicable. | Not applicable. | Not applicable. | Not applicable. |

Additional information

ADR/RID : This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.

Code : 17000DUW002 **Date of issue/Date of revision** : 15 May 2020
JOHNSTONES WOODWORKS Opaque Wood Finish

14. Transport information

Tunnel code : (D/E)
ADN : The product is only regulated as an environmentally hazardous substance when transported in tank vessels. This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.
IMDG : This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.
IATA : None identified.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

VOC for Ready-for-Use Mixture : IIA/e. Interior/exterior trim varnishes and woodstains, including opaque woodstains. EU limit values: 400g/l (2010.)
 This product contains a maximum of 400 g/l VOC.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

| Category |
|----------|
| P5c |

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

Code : 17000DUW002 **Date of issue/Date of revision** : 15 May 2020
JOHNSTONES WOODWORKS Opaque Wood Finish

SECTION 16: Other information

✓ Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number
 PBT = Persistent, Bioaccumulative and Toxic
 vPvB = Very Persistent and Very Bioaccumulative
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 IMDG = International Maritime Dangerous Goods
 IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|----------------------|-----------------------|
| ✓ Flam. Liq. 3, H226 | On basis of test data |

Full text of abbreviated H statements

| | |
|--|---|
| ✓ H226 H304 H312 H317 H318 H336 H351 H361 EUH066 | Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful in contact with skin. May cause an allergic skin reaction. Causes serious eye damage. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Repeated exposure may cause skin dryness or cracking. |
|--|---|

Full text of classifications [CLP/GHS]

| | |
|--|---|
| ✓ Acute Tox. 4 Asp. Tox. 1 Carc. 2 Eye Dam. 1 Flam. Liq. 3 Repr. 2 Skin Sens. 1 STOT SE 3 | ACUTE TOXICITY - Category 4 ASPIRATION HAZARD - Category 1 CARCINOGENICITY - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 FLAMMABLE LIQUIDS - Category 3 REPRODUCTIVE TOXICITY - Category 2 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |
|--|---|

History

Date of issue/ Date of revision : 15 May 2020
Date of previous issue : 11 February 2020
Prepared by : EHS
Version : 2

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.