# **SAFETY DATA SHEET**



Date of issue/Date of revision 5 May 2023 Version 14

| Section 1. Identification        |   |  |
|----------------------------------|---|--|
| Product name                     | : 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE  |  |
| Product code                     | : 00410952  |  |
| Other means of<br>identification | : Not available.  |  |
| Product type                     | : Liquid.   |  |
| Relevant identified uses of      | the substance or mixture and uses advised against   |  |
| Product use                      | : Consumer applications, Professional applications, Used by spraying.   |  |
| Use of the substance/<br>mixture | : Coating.  |  |
| Uses advised against             | : Not applicable.   |  |
| Manufacturer                     | : PPG Industries, Inc.<br>One PPG Place<br>Pittsburgh, PA 15272   |  |
| Emergency telephone<br>number    | : (412) 434-4515 (U.S.)<br>(514) 645-1320 (Canada)<br>SETIQ Interior de la República: 800-00-214-00 (México)<br>SETIQ Ciudad de México: (55) 5559-1588 (México) |  |
| Technical Phone Number           | : 1-800-441-9695 (8:00 am to 5:00 pm EST)   |  |

# Section 2. Hazards identification

| OSHA/HCS status                            | <ul> <li>This material is considered hazardous by the OSHA Hazard Communication Standard<br/>(29 CFR 1910.1200).</li> </ul>  |
|--|--|
| Classification of the substance or mixture | : SKIN SENSITIZATION - Category 1<br>CARCINOGENICITY - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2   |
|  | Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 23.4% (oral), 23.4% (dermal), 26.7% (inhalation)  |
|  | This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). |
| GHS label elements                         |  |

#### <u>label elements</u>

Version 14

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

### Section 2. Hazards identification

| Hazard pictograms                   |   |
|-------------------------------------|---|
| Signal word                         | : Warning   |
| Hazard statements                   | : May cause an allergic skin reaction.<br>Suspected of causing cancer.<br>May cause damage to organs through prolonged or repeated exposure. (kidneys)  |
| Precautionary statements            |   |
| Prevention                          | : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Do not breathe vapor.   |
| Response                            | <ul> <li>IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.</li> <li>Photosensitive agents : In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact. In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact. In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact.</li> </ul> |
| Storage                             | : Store locked up.  |
| Disposal                            | : Dispose of contents and container in accordance with all local, regional, national and international regulations.   |
| Supplemental label elements         | : Contains isothiazolinones. May cause allergic reaction. Avoid contact with skin and<br>clothing. Wash thoroughly after handling. Emits toxic fumes when heated.   |
| Hazards not otherwise<br>classified | : Prolonged or repeated contact may dry skin and cause irritation.  |

### Section 3. Composition/information on ingredients

: Mixture

Substance/mixture
Product name

: 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

| Ingredient name       | %           | CAS number     |
|-----------------------|-------------|----------------|
| titanium dioxide      | ≥10 - ≤20   | 13463-67-7     |
| ethanediol            | ≥1.0 - ≤5.0 | 107-21-1       |
| Diatomaceous earth    | ≥1.0 - ≤5.0 | 61790-53-2     |
| Petroleum Derivatives | ≥1.0 - ≤5.0 | Not available. |
| octhilinone (ISO)     | <1.0        | 26530-20-1     |

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

| United States | Page: 2/14 |
|---------------|------------|
|---------------|------------|

Version 14

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

### Section 3. Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

#### Description of necessary first aid measures

| Eye contact  | <ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids<br/>apart for at least 10 minutes and seek immediate medical advice.<br/>In case of accidental eye contact, avoid direct exposure to the sun or other sources of<br/>UV light as severe irritation including burns may result. These reactions can be delayed<br/>– get medical attention if pain, irritation or blistering occurs after contact.</li> </ul> |
|--------------|--|
| Inhalation   | <ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is<br/>irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained<br/>personnel.</li> </ul>   |
| Skin contact | <ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> <li>In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact.</li> </ul>      |
| Ingestion    | <ul> <li>If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>  |

#### Most important symptoms/effects, acute and delayed

| Potential acute health effect   | <u>cts</u>  |
|---------------------------------|---|
| Eye contact                     | : No known significant effects or critical hazards.   |
| Inhalation                      | : No known significant effects or critical hazards.   |
| Skin contact                    | : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.  |
| Ingestion                       | : No known significant effects or critical hazards.   |
| <u>Over-exposure signs/symp</u> | <u>otoms</u>  |
| Eye contact                     | : No specific data.   |
| Inhalation                      | : No specific data.   |
| Skin contact                    | : Adverse symptoms may include the following:<br>irritation<br>redness<br>dryness<br>cracking   |
| Ingestion                       | : No specific data.   |
| Notes to physician              | : Treat symptomatically. Contact poison treatment specialist immediately if large   |
| Specific treatments             | <ul><li>quantities have been ingested or inhaled.</li><li>No specific treatment.</li></ul>  |
| Protection of first-aiders      | : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

Version 14

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

### Section 4. First aid measures

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

| Extinguishing media                            |   |
|--|---|
| Suitable extinguishing media                   | : Use an extinguishing agent suitable for the surrounding fire.   |
| Unsuitable extinguishing media                 | : None known.   |
| Specific hazards arising from the chemical     | : In a fire or if heated, a pressure increase will occur and the container may burst.   |
| Hazardous thermal decomposition products       | : Decomposition products may include the following materials:<br>carbon oxides<br>metal oxide/oxides  |
| Special protective actions for fire-fighters   | <ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if<br/>there is a fire. No action shall be taken involving any personal risk or without suitable<br/>training.</li> </ul> |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.   |

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

| For non-emergency<br>personnel<br>For emergency responders | <ul> <li>No action shall be taken involving any personal risk or without suitable training.<br/>Evacuate surrounding areas. Keep unnecessary and unprotected personnel from<br/>entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist.<br/>Provide adequate ventilation. Wear appropriate respirator when ventilation is<br/>inadequate. Put on appropriate personal protective equipment.</li> <li>If specialized clothing is required to deal with the spillage, take note of any information in<br/>Section 8 on suitable and unsuitable materials. See also the information in "For non-<br/>emergency personnel".</li> </ul> |
|--|--|
| Environmental precautions                                  | : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).  |
| Methods and materials for c                                | ontainment and cleaning up   |
| Small spill  | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.  |
| Large spill  | <ul> <li>Stop leak if without risk. Move containers from spill area. Approach release from<br/>upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash<br/>spillages into an effluent treatment plant or proceed as follows. Contain and collect<br/>spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or<br/>diatomaceous earth and place in container for disposal according to local regulations<br/>(see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated<br/>absorbent material may pose the same hazard as the spilled product. Note: see</li> </ul>                 |

#### Date of issue 5 May 2023

Version 14

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

### Section 6. Accidental release measures

Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

| Precautions for safe handling                                      | <u>a</u>  |
|--|---|
| Protective measures  | : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
| Special precautions  | : If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.   |
| Advice on general<br>occupational hygiene                          | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.   |
| Conditions for safe storage,<br>including any<br>incompatibilities | : Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.   |

## Section 8. Exposure controls/personal protection

#### **Control parameters**

**Occupational exposure limits** 

| Ingredient name    | Exposure limits  |
|--------------------|--|
| titanium dioxide   | OSHA PEL (United States, 5/2018).                      |
|                    | TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust    |
|                    | ACGIH TLV (United States, 1/2022).                     |
|                    | TWA: 2.5 mg/m <sup>3</sup> 8 hours. Form: respirable   |
|                    | fraction, finescale particles                          |
| ethanediol         | ACGIH TLV (United States, 1/2022).                     |
|                    | STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Inhalable |
|                    | fraction. Aerosol only.                                |
|                    | STEL: 50 ppm 15 minutes. Form: Vapor                   |
|                    | fraction   |
|                    | TWA: 25 ppm 8 hours. Form: Vapor fraction              |
| Diatomaceous earth | OSHA PEL Z3 (United States, 6/2016).                   |
|                    | TWA: 20 mppcf 8 hours.                                 |
|                    | TWA: 80 mg/m³ / (%SiO2) 8 hours.                       |
|                    | United States Page: 5/14                               |

Version 14

### Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

# Section 8. Exposure controls/personal protection

|                 | leum Derivatives<br>none (ISO)   | OSHA PEL (United States).<br>TWA: 5 mg/m <sup>3</sup><br>STEL: 10 mg/m <sup>3</sup><br>None.      |
|-----------------|--|---|
| ł               | Key to abbreviations   |   |
| А               | = Acceptable Maximum Peak  | S = Potential skin absorption   |
| ACGIH           | <ul> <li>American Conference of Governmental Industrial Hygienists.</li> </ul>   | SR = Respiratory sensitization  |
| С               | = Ceiling Limit  | SS = Skin sensitization   |
| F               | = Fume   | STEL = Short term Exposure limit values   |
| IPEL            | <ul> <li>Internal Permissible Exposure Limit</li> </ul>  | TD = Total dust   |
| OSHA            | <ul> <li>Occupational Safety and Health Administration.</li> </ul>   | TLV = Threshold Limit Value   |
| R               | = Respirable   | TWA = Time Weighted Average   |
| Z               | = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances   |   |
| ;onsult         | local authorities for acceptable exposure limits.  |   |
| Recom<br>procec | <b>International Sector Reference</b> should be made to appropriate guidance documents for methods for also be required. | priate monitoring standards. Reference to national the determination of hazardous substances will |

| Appropriate engineering | : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, |
|-------------------------|--|
| controls                | local exhaust ventilation or other engineering controls to keep worker exposure to     |
|                         | airborne contaminants below any recommended or statutory limits.                       |
| Environmental exposure  | : Emissions from ventilation or work process equipment should be checked to ensure     |

| Environmental exposure | ÷. | Emissions from ventilation or work process equipment should be checked to ensure     |
|------------------------|----|--|
| controls               |    | they comply with the requirements of environmental protection legislation. In some   |
|                        |    | cases, fume scrubbers, filters or engineering modifications to the process equipment |
|                        |    | will be necessary to reduce emissions to acceptable levels.                          |

Individual protection measures

| Hygiene measures      | : | Wash hands, forearms and face thoroughly after handling chemical products, before<br>eating, smoking and using the lavatory and at the end of the working period.<br>Appropriate techniques should be used to remove potentially contaminated clothing.<br>Contaminated work clothing should not be allowed out of the workplace. Wash<br>contaminated clothing before reusing. Ensure that eyewash stations and safety<br>showers are close to the workstation location.  |
|-----------------------|---|--|
| Eye/face protection   | : | Safety glasses with side shields.  |
| Skin protection       |   |  |
| Hand protection       | : | Chemical-resistant, impervious gloves complying with an approved standard should be<br>worn at all times when handling chemical products if a risk assessment indicates this is<br>necessary. Considering the parameters specified by the glove manufacturer, check<br>during use that the gloves are still retaining their protective properties. It should be<br>noted that the time to breakthrough for any glove material may be different for different<br>glove manufacturers. In the case of mixtures, consisting of several substances, the<br>protection time of the gloves cannot be accurately estimated. |
| Gloves                | : | polyethylene butyl rubber  |
| Body protection       | : | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.  |
| Other skin protection | : | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.  |

Date of issue 5 May 2023

Version 14

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

### Section 8. Exposure controls/personal protection

| hazaro<br>are ex<br>certifie<br>with ar | ator selection must be based on known or anticipated exposure levels, the<br>ls of the product and the safe working limits of the selected respirator. If workers<br>posed to concentrations above the exposure limit, they must use appropriate,<br>ad respirators. Use a properly fitted, air-purifying or air-fed respirator complying<br>approved standard if a risk assessment indicates this is necessary.<br>espiratory protection shall be in accordance to 29 CFR 1910.134. |
|---|--|
|---|--|

# Section 9. Physical and chemical properties

| <u>Appearance</u>                            |    |   |
|--|----|---|
| Physical state                               | 1  | Liquid.   |
| Color  | 1  | Not available.  |
| Odor   | 1  | Characteristic.   |
| Odor threshold                               | 1  | Not available.  |
| рН   | 4  | Not available.  |
| Melting point                                | 4  | Not available.  |
| Boiling point                                | 4  | >37.78°C (>100°F)   |
| Flash point                                  | 4  | Closed cup: 113.33°C (236°F) [Product does not sustain combustion.] |
| Auto-ignition temperature                    | 1  | Not available.  |
| Decomposition temperature                    | 1  | Not available.  |
| Flammability                                 | 1  | Not available.  |
| Lower and upper explosive (flammable) limits | 1  | Not available.  |
| Evaporation rate                             | 1  | Not available.  |
| Vapor pressure                               | 1  | Not available.  |
| Vapor density                                | 1  | Not available.  |
| Relative density                             | 1  | 1.14  |
| Density(lbs / gal)                           | 1  | 9.51  |
|  |    | Media Result  |
| Solubility(ies)                              | 1  | cold water Soluble  |
| Partition coefficient: n-<br>octanol/water   | :  | Not applicable.   |
| Viscosity                                    | 1  | Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)                       |
| Volatility                                   | 1  | 67% (v/v), 58.711% (w/w)  |
| % Solid. (w/w)                               | :  | 41.289  |
| Section 10 Stabili                           | 4. | and reactivity  |

### Section 10. Stability and reactivity

| Reactivity                         | 1 | No specific test data related to reactivity available for this product or its ingredients. |
|------------------------------------|---|--|
| Chemical stability                 | : | The product is stable.   |
| Possibility of hazardous reactions | : | Under normal conditions of storage and use, hazardous reactions will not occur.            |

**United States** 

Page: 7/14

Version 14

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

## Section 10. Stability and reactivity

| Conditions to avoid              | : | When exposed to high temperatures may produce hazardous decomposition products.<br>Refer to protective measures listed in sections 7 and 8. |
|----------------------------------|---|---|
| Incompatible materials           | : | Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.              |
| Hazardous decomposition products | : | Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides                       |

# Section 11. Toxicological information

#### Information on toxicological effects

### Acute toxicity

| Product/ingredient name                | Result   |           |                 | Species              | Dose                                   | Exposure          |
|--|--|-----------|-----------------|----------------------|--|-------------------|
| titanium dioxide                       | LD50 Derm  |           | ts and mists    | Rat<br>Rabbit        | >6.82 mg/l<br>>5000 mg/kg              | 4 hours<br>-      |
| ethanediol                             | LD50 Oral<br>LD50 Derm<br>LD50 Oral                  | nal       |                 | Rat<br>Rabbit<br>Rat | >5000 mg/kg<br>9.53 g/kg<br>4700 mg/kg | -                 |
| octhilinone (ISO)                      |  |           | ts and mists    | Rat<br>Rabbit<br>Rat | 0.27 mg/l<br>311 mg/kg<br>125 mg/kg    | 4 hours<br>-<br>- |
| Conclusion/Summary                     | : There are  | no data a | available on th | ne mixture itself.   | 5 5                                    |                   |
| Irritation/Corrosion                   |  |           |                 |                      |  |                   |
| Conclusion/Summary                     |  |           |                 |                      |  |                   |
| Skin                                   | : There are  | no data a | available on th | ne mixture itself.   |  |                   |
| Eyes                                   | : There are  | no data a | available on th | ne mixture itself.   |  |                   |
| Respiratory                            | : There are  | no data a | available on th | ne mixture itself.   |  |                   |
| <u>Sensitization</u>                   |  |           |                 |                      |  |                   |
| Product/ingredient name                | Route of exposure                                    |           | Species         |                      | Result                                 |                   |
| octhilinone (ISO)                      | skin   | N         | Mouse           |                      | Sensitizing                            |                   |
| Conclusion/Summary                     | •  |           |                 |                      |  |                   |
| Skin                                   | : There are  | no data a | available on th | ne mixture itself.   |  |                   |
| Respiratory                            | : There are  | no data a | available on th | ne mixture itself.   |  |                   |
| <u>Mutagenicity</u>                    |  |           |                 |                      |  |                   |
| Conclusion/Summary                     | : There are no data available on the mixture itself. |           |                 |                      |  |                   |
| <u>Carcinogenicity</u>                 |  |           |                 |                      |  |                   |
| Conclusion/Summary                     | : There are  | no data a | available on th | ne mixture itself.   |  |                   |
| <b>Classification</b>                  |  |           |                 |                      |  |                   |
| Product/ingredient name                | OSHA   | IARC      | NTP             |                      |  |                   |
| titanium dioxide<br>Diatomaceous earth | -  | 2B<br>3   | -               |                      |  |                   |
|  |  |           | •               |                      | United States                          | S Page: 8/14      |

Version 14

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

### Section 11. Toxicological information

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

#### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

#### **Teratogenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Specific target organ toxicity (single exposure)

| Name                  |            | Route of exposure | Target organs                   |
|-----------------------|------------|-------------------|---------------------------------|
| Petroleum Derivatives | Category 3 |                   | Respiratory tract<br>irritation |

#### Specific target organ toxicity (repeated exposure)

| Name       |            | Route of<br>exposure | Target organs |
|------------|------------|----------------------|---------------|
| ethanediol | Category 2 | oral                 | kidneys       |

#### Target organs

: Contains material which may cause damage to the following organs: blood, kidneys, lungs, upper respiratory tract, skin, eyes, central nervous system (CNS).

#### Aspiration hazard

Not available.

#### Information on the likely routes of exposure

#### Potential acute health effects

| Eye contact :                 | No known significant effects or critical hazards.  |
|-------------------------------|--|
| Inhalation :                  | No known significant effects or critical hazards.  |
| Skin contact :                | Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction. |
| Ingestion :                   | No known significant effects or critical hazards.  |
| Over-exposure signs/sympton   | ns   |
| Eye contact :                 | No specific data.  |
| Inhalation :                  | No specific data.  |
| Skin contact :                | Adverse symptoms may include the following:  |
|                               | irritation   |
|                               | redness  |
|                               | dryness  |
|                               | cracking   |
| Ingestion :                   | No specific data.  |
| Delayed and immediate effects | and also chronic effects from short and long term exposure   |

Version 14

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

# Section 11. Toxicological information

| Conclusion/Summary             | :   | There are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/ or engineering controls (see Section 8). Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. |
|--------------------------------|-----|---|
| Short term exposure            |     |   |
| Potential immediate effects    | :   | There are no data available on the mixture itself.  |
| Potential delayed effects      | 1   | There are no data available on the mixture itself.  |
| Long term exposure             |     |   |
| Potential immediate<br>effects | :   | There are no data available on the mixture itself.  |
| Potential delayed effects      | ÷   | There are no data available on the mixture itself.  |
| Potential chronic health effe  | ect | <u>s</u>  |
| General                        | :   | May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.   |
| Carcinogenicity                | :   | Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.  |
| Mutagenicity                   | :   | No known significant effects or critical hazards.   |
| Reproductive toxicity          | :   | No known significant effects or critical hazards.   |
| Numerical measures of toxic    | itv |   |

#### Acute toxicity estimates

| Product/ingredient name   | Oral (mg/<br>kg) | Dermal<br>(mg/kg) | Inhalation<br>(gases)<br>(ppm) | (vapors)   | Inhalation<br>(dusts and<br>mists) (mg/<br>I) |
|---|------------------|-------------------|--------------------------------|------------|---|
| 76-110 SUN PROOF HOUSE/TRIM PAINT<br>EXTERIOR SATIN-WHITE/PASTEL BASE | 19097.4          | N/A               | N/A                            | N/A        | N/A   |
| ethanediol<br>octhilinone (ISO)                                       | 500<br>500       | 9530<br>311       | N/A<br>N/A                     | N/A<br>0.5 | N/A<br>0.5                                    |

|  | United States | Page: 10/14 |
|--|---------------|-------------|
|  |               |             |

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

### Section 12. Ecological information

#### **Toxicity**

| Product/ingredient name | Result                           | Species                 | Exposure |
|-------------------------|----------------------------------|-------------------------|----------|
| titanium dioxide        | Acute LC50 >100 mg/l Fresh water | Daphnia - Daphnia magna | 48 hours |

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| ethanediol              | -1.36  | -   | low       |
| octhilinone (ISO)       | 2.45   |     | low       |

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

### Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

### **14. Transport information**

|                            | DOT   | IMDG   | IATA   |
|----------------------------|---|--------|--|
| UN number                  | Not regulated.  | UN3082 | UN3082   |
| UN proper shipping<br>name | - ENVIRONMENTALLY<br>HAZARDOUS SUBSTANCE,<br>LIQUID, N.O.S.<br>(Poly(oxy-1,2-ethanediyl), α-[ (Poly(oxy-1,2-ethaned |        | (Poly(oxy-1,2-ethanediyl), α-[<br>(1,1,3,3-tetramethylbutyl) |
|                            |   | Ur     | ited States Page: 11/14                                      |

Date of issue 5 May 2023

Version 14

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

### 14. Transport information

| Transport hazard class<br>(es) | -               | 9   | 9               |
|--------------------------------|-----------------|---|-----------------|
| Packing group                  | -               | III   |                 |
| Environmental hazards          | No.             | Yes.  | Yes.            |
| Marine pollutant<br>substances | Not applicable. | (Poly(oxy-1,2-ethanediyl), α-[<br>(1,1,3,3-tetramethylbutyl)<br>phenyl]-ω-hydroxy-) | Not applicable. |

#### Additional information

| DOT  | : None identified.  |
|------|---|
| IMDG | This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. |
| ΙΑΤΑ | : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.    |

# Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

### Section 15. Regulatory information

#### United States

United States inventory (TSCA 8b) : All components are active or exempted.

| United States - TSCA 5(a)2 - Proposed significant new use rules: |        |           |
|--|--------|-----------|
| S-chloro-2-methyl-2H-isothiazol-3-one                            | Listed | P-96-1251 |
| 3(2H)-Isothiazolone, 2-methyl-                                   | Listed | P-96-1250 |
|  |        |           |

#### <u>SARA 302/304</u>

SARA 304 RQ : Not applicable.

#### Composition/information on ingredients

No products were found.

#### SARA 311/312

Classification

: SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 HNOC - Defatting irritant

**Composition/information on ingredients** 

Date of issue 5 May 2023

Version 14

#### Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

### Section 15. Regulatory information

| Name                  | %           | Classification                                   |
|-----------------------|-------------|--|
| titanium dioxide      | ≥10 - ≤20   | CARCINOGENICITY - Category 2                     |
| ethanediol            | ≥1.0 - ≤5.0 | ACUTE TOXICITY (oral) - Category 4               |
|                       |             | SPECIFIC TARGET ORGAN TOXICITY (REPEATED         |
|                       |             | EXPOSURE) - Category 2                           |
|                       |             | HNOC - Defatting irritant                        |
| Petroleum Derivatives | ≥1.0 - ≤5.0 | SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) |
|                       |             | (Respiratory tract irritation) - Category 3      |
| octhilinone (ISO)     | <1.0        | ACUTE TOXICITY (oral) - Category 4               |
|                       |             | ACUTE TOXICITY (dermal) - Category 3             |
|                       |             | ACUTE TOXICITY (inhalation) - Category 2         |
|                       |             | SKIN CORROSION - Category 1                      |
|                       |             | SERIOUS EYE DAMAGE - Category 1                  |
|                       |             | SKIN SENSITIZATION - Category 1A                 |

#### SARA 313

**Supplier notification** 

|   | Chemical name |  |
|---|---------------|--|
| 1 | ethanediol    |  |

CAS numberConcentration107-21-11 - 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

### Section 16. Other information

#### Hazardous Material Information System (U.S.A.)

```
Health : 2 * Flammability : 1 Physical hazards : 0 (*) - Chronic effects
```

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

| National Fire Protection Ass       | ociation (U.S.A.)   |
|------------------------------------|---|
| Health : 2 Flamma                  | bility : 1 Instability : 0  |
| Date of previous issue             | : 10/3/2022   |
| Organization that prepared the SDS | : EHS   |
| Key to abbreviations               | <ul> <li>ATE = Acute Toxicity Estimate<br/>BCF = Bioconcentration Factor<br/>GHS = Globally Harmonized System of Classification and Labelling of Chemicals<br/>IATA = International Air Transport Association<br/>IBC = Internediate Bulk Container<br/>IMDG = International Maritime Dangerous Goods<br/>LogPow = logarithm of the octanol/water partition coefficient<br/>MARPOL = International Convention for the Prevention of Pollution From Ships, 1973</li> </ul> |
|                                    | United States Page: 13/14   |

United States Page: 13/14

Date of issue 5 May 2023

Version 14

Product name 76-110 SUN PROOF HOUSE/TRIM PAINT EXTERIOR SATIN-WHITE/PASTEL BASE

### Section 16. Other information

as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

#### Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.