Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

SAFETY DATA SHEET

Date of issue/Date of revision

: 6 January 2019 Version



: 1

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: SIGMALINE 855 REPAIR BASE REDBROWN
Product code	: 00421471
Product type	: Liquid.
Other means of identification	: Not available.
1.2 Relevant identified us	es of the substance or mixture and uses advised against
Productuse	Professional applications lsed by spraving

Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.

1.3 Details of the supplier of the safety data sheet

Sigma Paint Saudi Arabia Ltd. PO Box 7509 Dammam 31472 Saudi Arabia Tel: 00966 138 47 31 00 Fax: 00966 138 47 17 34	
e-mail address of person responsible for this SDS	: ndpic@sfda.gov.sa
1.4 Emergency telephone number	: 00966 138473100 extn 1001

SECTION 2: Hazards identification

2.1 Classification of the subst	ance or mixture
Product definition	: Mixture
Classification according to R Skin Sens. 1, H317	egulation (EC) No. 1272/2008 [CLP/GHS]

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements **Hazard pictograms**



Signal word **Hazard statements Precautionary statements**

- : Warning
- : May cause an allergic skin reaction.

English (GB) **United Arab Emirates**

Code : 00421471	Date of issue/Date of revision : 6 January 2019
SIGMALINE 855 REPAIR BASE	REDBROWN
SECTION 2: Hazards	identification
Prevention	: Wear protective gloves. Avoid breathing vapour. Contaminated work clothing should not be allowed out of the workplace.
Response	: IF ON SKIN: Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical attention.
Storage	: Not applicable.
Disposal	: Not applicable.
Hazardous ingredients	: Phenol, methylstyrenated
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirem	ents
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Product/ingredient name	Identifiers	% by weight	<u>Classification</u> Regulation (EC) No. 1272/2008 [CLP]	Туре
Phenol, methylstyrenated	REACH #: 01-2119555274-38 EC: 270-966-8 CAS: 68512-30-1	≥5.0 - <10	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

4.1 Description of first aid measures		
Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. 	
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. 	
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. 	
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.	
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	

4.2 Most important symptoms and effects, both acute and delayed	
Potential acute health effects	

Eye contact	. No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sympt	oms
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
	•

SECTION 5: Firefighting measures

5.4 Eastin main him a succedia	
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising	from the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	: Decomposition products may include the following materials: sulfur oxides metal oxide/oxides

5.3 Advice for firefighters

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	otec	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	соі	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

 Protective measures Put on appropriate personal protective equipment (see Section 8 and smoking should be prohibited in areas where this material is processed. Workers should wash hands and face before eating smoking. Remove contaminated clothing and protective equipmeating areas. Persons with a history of skin sensitization problem employed in any process in which this product is used. Do not get or clothing. Do not ingest. Avoid breathing vapour or mist. Keep container or an approved alternative made from a compatible matclosed when not in use. Empty containers retain product residue hazardous. Do not reuse container. 	g, drinking and ment before entering ems should not be get in eyes or on skin ep in the original material, kept tightly
--	--

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II			
Code : 00421471		Date of issue/Date of revision : 6 January 2019	
SIGMALINE 855 REPAIR B	ASE REDBROWN		
SECTION 7: Handl	ing and storage		
Advice on general occupational hygiene	handled, stored an drinking and smoki	d smoking should be prohibited in areas where this material is d processed. Workers should wash hands and face before eatin ng. Remove contaminated clothing and protective equipment ing areas. See also Section 8 for additional information on	ng,
7.2 Conditions for safe storage, including any incompatibilities	accordance with lo sunlight in a dry, co (see Section 10) ar ready for use. Con kept upright to prev appropriate contair	following temperatures: 0 to 35°C (32 to 95°F). Store in cal regulations. Store in original container protected from direct ol and well-ventilated area, away from incompatible materials id food and drink. Keep container tightly closed and sealed until tainers that have been opened must be carefully resealed and ent leakage. Do not store in unlabelled containers. Use ment to avoid environmental contamination. See Section 10 for ials before handling or use.	il
7.3 Specific end use(s)			

See Section 1.2 for Identified uses.

Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Code : 00421471 Date of issue/Date of revision : 6 January 2019 SIGMALINE 855 REPAIR BASE REDBROWN SECTION 8: Exposure controls/personal protection Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. Gloves : butyl rubber Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Other skin protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to	Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II					
SECTION 8: Exposure controls/personal protection Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. Gloves : butyl rubber Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Other skin protection : Respiratory protection Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, a	Code : 00421471	Date of issue/Date of revision : 6 January 2019				
Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.Gloves:butyl rubberBody protection:Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.Other skin protection:Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is	SIGMALINE 855 REPAIR BASE REDBROWN					
be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.Gloves:butyl rubberBody protection:Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.Respiratory protection:Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the sak being performed and the risks involved and should be approved by a specialist before handling this product.Respiratory protection:Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified	SECTION 8: Exposure controls/personal protection					
 Body protection Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Other skin protection Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Respiratory protection Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is 		be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular				
Other skin protectionbeing performed and the risks involved and should be approved by a specialist before handling this product.Other skin protectionAppropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.Respiratory protectionRespirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is		-				
 Respiratory protection Respiratory protection Respiratory protection Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is 	Body protection	being performed and the risks involved and should be approved by a specialist				
hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is	Other skin protection	selected based on the task being performed and the risks involved and should be				
necessary.	Respiratory protection	hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed				
Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment				

SECTION 9: Physical and chemical properties

9.1 Information on basic physica	and chemical properties
<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Brownish-red.
Odour	: Aromatic.
Odour threshold	: Not available.
рН	: insoluble in water.
Melting point/freezing point	: May start to solidify at the following temperature: -14°C (6.8°F) This is based on data for the following ingredient: Phenol, methylstyrenated.
Initial boiling point and boiling range	: >37.78°C
Flash point	: Closed cup: 210°C
Evaporation rate	: Not available.
Material supports combustion.	: Yes.
Flammability (solid, gas)	: liquid
Upper/lower flammability or explosive limits	: Not available.
Vapour pressure	: Highest known value: <0.3 kPa (<2.3 mm Hg) (at 20°C) (Branched Polyalcohol with Ester and Ether Groups). Weighted average: 0.18 kPa (1.35 mm Hg) (at 20°C)
	English (GB) United Arab Emirates 6/11

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II				
Code	: 00421471	Date of issue/Date of revision	: 6 January 2019	
SIGMALINE 8	855 REPAIR BASE REDBROWN			

SECTION 9: Physical and chemical properties

Relative density	: 1.86
Solubility(ies)	: Insoluble in the following materials: cold water.
Partition coefficient: n-octanol/ water	: Not applicable.
Auto-ignition temperature	: Lowest known value: >385°C (>725°F) (Phenol, methylstyrenated).
Decomposition temperature	: Stable under recommended storage and handling conditions (see Section 7).
Viscosity	: Kinematic (40°C): >0.21 cm ² /s
Explosive properties	: Product does not present an explosion hazard.
Oxidising properties	: Product does not present an oxidizing hazard.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	 When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: sulfur oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient	name	Result	Species	Dose	Exposure
Phenol, methylstyrenated		LD50 Dermal LD50 Oral	Rabbit Rat	>2000 mg/kg >2000 mg/kg	-
Conclusion/Summary Acute toxicity estimates Not available.	: There	are no data available on the mi	ixture itself.		
<u>Irritation/Corrosion</u> Conclusion/Summary Skin	: There a	are no data available on the mix	xture itself.		
Eyes	: There a	are no data available on the mix	xture itself.		
Respiratory <u>Sensitisation</u>	: There a	are no data available on the mix	xture itself.		
Conclusion/Summary					
Skin	: There	are no data available on the mi	ixture itself.		
		English (GB)	United Arab	o Emirates	7/1

Conforms to Regulation (EC)	No. 1907/2006 (REACH), Annex II
Code : 00421471	Date of issue/Date of revision : 6 January 2019
SIGMALINE 855 REPAIR BASE	EREDBROWN
SECTION 11: Toxico	logical information
Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
<u>Teratogenicity</u>	
Conclusion/Summary	: There are no data available on the mixture itself.
Specific target organ toxicit Not available.	<u>y (single exposure)</u>
Not avallable.	
Specific target organ toxicit	<u>y (repeated exposure)</u>
Not available.	
Aspiration hazard	
Not available.	
Information on likely	: Not available.
routes of exposure	
Potential acute health effect	<u>IS</u>
Inhalation	No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Eye contact	: No known significant effects or critical hazards.
Symptoms related to the ph	ysical, chemical and toxicological characteristics
Inhalation	: No specific data.
Ingestion	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Eye contact	: No specific data.
	cts as well as chronic effects from short and long-term exposure
Short term exposure	
Potential immediate	: Not available.
effects	
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate	: Not available.
effects	
Potential delayed effects	
Potential chronic health effe	<u>icts</u>
Not available.	
Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
	English (GB) United Arab Emirates 8/11

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II				
Code : 00421471		Date of issue/Date of revision	: 6 January 2019	
SIGMALINE 855 REPAIR BASE REDBROWN				

SECTION 11: Toxicological information

Fertility effects

: No known significant effects or critical hazards.

Other information : Not available.

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains Phenol, methylstyrenated. May produce an allergic reaction.

SECTION 12: Ecological information

12.1 Toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
12.2 Persistence and degrad	dability
Conclusion/Summary	: There are no data available on the mixture itself.
12.3 Bioaccumulative poten Not available.	tial
12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.
12.5 Results of PBT and vPv	/B assessment
PBT	: Not applicable.
vPvB	: Not applicable.
12.6 Other adverse effects	: No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods <u>Product</u>

	C) No. 1907/2006 (REACH)		
ode : 00421471		Date of issue/Date of revision : 6 January 2019)
GMALINE 855 REPAIR B	ASE REDBROWN		
ECTION 13: Disp	osal consideration	5	
Methods of disposal	Disposal of this produ with the requirements any regional local au products via a license	ste should be avoided or minimised wherever possible. Ict, solutions and any by-products should at all times comply of environmental protection and waste disposal legislation hority requirements. Dispose of surplus and non-recyclable d waste disposal contractor. Waste should not be disposed or unless fully compliant with the requirements of all authorit	and e I of
Hazardous waste	: Yes.		
European waste catalog	gue (EWC)		
Waste code		Waste designation	
08 01 11*	waste paint and varnish co	ntaining organic solvents or other hazardous substances	
ackaging			
Methods of disposal		ste should be avoided or minimised wherever possible. Wa recycled. Incineration or landfill should only be considered feasible.	ste
Type of packaging		European waste catalogue (EWC)	
Container	15 01 06	mixed packaging	
Special precautions	taken when handling Empty containers or	container must be disposed of in a safe way. Care should b emptied containers that have not been cleaned or rinsed ou iners may retain some product residues. Avoid dispersal of off and contact with soil, waterways, drains and sewers.	ıt.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID	: None identified.
IMDG	: None identified.
IATA	: None identified.

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk: Not applicable.according to Annex II of
Marpol and the IBC Code:

Conforms to Regulation (EC) No. 1907/2006 (REACH), A	Annex II	
Code : 00421471	Date of issue/Date of revision : 6	6 January 2019
SIGMALINE 855 REPAIR BASE REDBROWN		
SECTION 15: Regulatory information		
15.1 Safety, health and environmental regulations/legi	slation specific for the substance or mixt	ture
EU Regulation (EC) No. 1907/2006 (REACH)		
Annex XIV - List of substances subject to authorisa	<u>tion</u>	
Annex XIV		
None of the components are listed.		
Substances of very high concern		
None of the components are listed.		
Annex XVII - Restrictions : Not applicable.		
on the manufacture,		
placing on the market and use of certain dangerous		
substances, mixtures and		
articles		
Other national and international regulations.		
Ozone depleting substances (1005/2009/EU)		
Not listed.		

15.2 Chemical safety : No Chemical Safety Assessment has been carried out. **assessment**

SECTION 16: Other information

Indicates information that has changed from previously issued version.						
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) N 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number 	IO.				
Full text of abbreviated H statements	 H315 Causes skin irritation. H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects. 					
Full text of classifications [CLP/GHS]	 Aquatic Chronic 3, H412 Skin Irrit. 2, H315 Skin Sens. 1, H317 LONG-TERM (CHRONIC) AQUATIC HAZARD - C 3 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 	Category				
<u>History</u>						
Date of issue/ Date of revision	6 January 2019					
Date of previous issue	: No previous validation					
Prepared by	: EHS					
Version	: 1					
<u>Disclaimer</u>						

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.