SAFETY DATA SHEET



Date of issue 1/15/2020 (month/day/year)

Version 5.03

mixture

Section 1. Chemical product and company identification

Α.	Product name	1	PSX 700 RESIN RAL 7005
	Product code	1	00328794

B. Relevant identified uses of the substance or mixture and uses advised against Product use : Professional applications, Used by spraying. Use of the substance/ : Coating. Paint. Painting-related materials.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

C.	Supplier's information	:	PPG SSC (680-090) 19, Yeocheon-ro 217beon-gil, Nam-gu, Ulsan, Korea Tel: +82-52-210-8222 Korea.MSDS@PPG.COM
	Emergency telephone number:	:	+82-52-210-8222

Section 2. Hazards identification

 A. Hazard classification
 : SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 3
 This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. GHS label elements, including precautionary statements

Symbol

Signal word



: Warning

Hazard statements

- : H317 May cause an allergic skin reaction. H351 - Suspected of causing cancer.
 - H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Product code 00328794 Product name PSX 700 RESIN RAL 7005 Date of issue 1/15/2020 (month/day/year)

Section 2. Hazards identification

Prevention	: P201 - Obtain special instructions before use.
	P202 - Do not handle until all safety precautions have been read and understood.
	P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing
	P273 - Avoid release to the environment.
	P261 - Avoid breathing vapor.
	P272 - Contaminated work clothing should not be allowed out of the workplace.
Response	: P308 + P313 - IF exposed or concerned: Get medical attention.
	P302 + P352 + P362 + P364 - IF ON SKIN: Wash with plenty of soap and water.
	Take off contaminated clothing and wash it before reuse.
	P333 + P313 - If skin irritation or rash occurs: Get medical attention.
Storage	: P405 - Store locked up.
Disposal	 P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

C. Other hazards which do : None known. not result in classification

Section 3. Composition/information on ingredients

CAS number/other identifiers

CAS number

: Not applicable.

Chemical name	Common name	Identifiers	%
4-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	cyclohexanol, 4,4'-(1-methylethylidene) bis-, polymer with (chloromethyl)oxirane	CAS: 30583-72-3	20 - <30
titanium dioxide bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	TITANIUM DIOXIDE BIS(PENTAMETHYLPIPERIDYL) SEBACATE	CAS: 13463-67-7 CAS: 41556-26-7	5 - <10 1 - <5
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	METHYL-(1,2,2,6,6-PENTAMETHYL- 4-PIPERDIYL) SEBACATE	CAS: 82919-37-7	0.1 - <1
carbon black, respirable powder	CARBON BLÁCK	CAS: 1333-86-4	0.1 - <1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

A. Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
B. Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
C. Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Section 4. First aid measures				
D. Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.			
E. Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delay			

 E. Notes to physician
 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
 Specific treatments
 No specific treatment.
 No action shall be taken involving any personal risk or without suitable training. It

> may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Α.	Extinguishing media		
	Suitable extinguishing media	1	Use an extinguishing agent suitable for the surrounding fire.
	Unsuitable extinguishing media	:	None known.
В.	Specific hazards arising from the chemical	:	A fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
	Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides
C.	Special equipment for fire-fighting	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
	Fire-fighting procedures	-	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Section 6. Accidental release measures

A. Personal precautions, protective equipment and emergency procedures	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
B. Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Section 6. Accidental release measures

C. Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Α.	Precautions for safe handling	:	Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
В.	Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10

for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

A. Occupational exposure limits

Ingredient name	Exposure limits	
ji ranium dioxide	Ministry of Employment and Labor (Republic of Korea, 7/2018). TWA: 10 mg/m ³ 8 hours. Form: total dust	
carbon black, respirable powder	with less than 1% of free SiO2 Ministry of Employment and Labor (Republic of Korea, 7/2018). TWA: 3.5 mg/m ³ 8 hours. Form: inhalable fraction	

Section 8. Exposure controls/personal protection

	_		
	Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
в.	Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
	Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
с.	Personal protective equip	me	nt
	Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
	Eye protection	:	Safety glasses with side shields.
	Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer,

this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
butyl rubber

Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Section 9. Physical and chemical properties

A .	Appearance		
	Physical state	:	Liquid.
	Color	:	Gray.
В.	Odor	:	Aromatic.
C .	Odor threshold	1	Not available.
D.	рН	:	Not available.
Ε.	Melting/freezing point	:	Not available.

Gloves

Korea (GHS) Page: 5/12

Product code 00328794

Section 9. Physical and chemical properties F. Boiling point/boiling : >37.78°C (>100°F) range : Closed cup: Not applicable. G. Flash point H. Evaporation rate : Not available. Flammability (solid, gas) : Not available. I. – J. Lower and upper : Not available. explosive (flammable) limits K. Vapor pressure : Not available. L. Solubility : Insoluble in the following materials: cold water. M. Vapor density : Not available. N. Relative density : 1.51 O. Partition coefficient: n-: Not available. octanol/water P. Auto-ignition : Not available. temperature Q. Decomposition : Not available. temperature

- **R. Viscosity** : Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)
- S. Molecular weight : Not applicable.

Section 10. Stability and reactivity

Α.	Chemical stability	The product is stable.	
	Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.	
В.	Conditions to avoid	When exposed to high temperatures may produce hazardous decomposition products.	
C.	Incompatible materials	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.	
D.	Hazardous decomposition products	Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides	

Section 11. Toxicological information

A. Information on the likely routes of exposure	: Not available.
Potential acute health effect	uts
Inhalation :	No known significant effects or critical hazards.
Ingestion :	No known significant effects or critical hazards.
Skin contact :	May cause an allergic skin reaction.
Eye contact :	No known significant effects or critical hazards.
<u>Over-exposure signs/symp</u>	<u>toms</u>

Section 11. Toxicological information

Inhalation	: No specific data.
Ingestion	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Eye contact	: No specific data.

B. Health hazards

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	LD50 Oral	Rat	3.125 g/kg	-
methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	LD50 Oral	Rat	3.125 g/kg	-
carbon black, respirable powder	LD50 Dermal LD50 Oral	Rabbit Rat	>3 g/kg >15400 mg/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.

Sensitization

Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Teratogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Korea (GHS) Page: 7/12

Section 11. Toxicological information

Not available.

Aspiration hazard

Not available.

Potential chronic health effects

General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Additional information

Sanding and grinding dusts may be harmful if inhaled. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Emits toxic fumes when heated.

Chemical name	Common name	CAS #	GHS Classification
4,4'- Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane	cyclohexanol, 4,4'- (1-methylethylidene)bis-, polymer with (chloromethyl) oxirane	30583-72-3	SKIN SENSITIZATION - Category 1
2,0 000,0000			AQUATIC HAZARD (LONG-TERM) -
titanium dioxide	TITANIUM DIOXIDE	13463-67-7	Category 3 CARCINOGENICITY - Category 2
bis(1,2,2,6,6-pentamethyl-	BIS	41556-26-7	SKIN SENSITIZATION - Category 1
4-piperidyl) sebacate	(PENTAMETHYLPIPERIDYL) SEBACATE		
			AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1
methyl	METHYL-	82919-37-7	SKIN SENSITIZATION - Category 1
1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	(1,2,2,6,6-PENTAMETHYL- 4-PIPERDIYL) SEBACATE		
	,		AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1
carbon black, respirable powder	CARBON BLACK	1333-86-4	CARCINOGENICITY - Category 2

Product name PSX 700 RESIN RAL 7005

Section 12. Ecological information

A. Ecotoxicity

Product/ingredient name	Result	Species	Exposure
4,4'-	LC50 11.5 mg/l	Fish	96 hours
Isopropylidenedicyclohexanol,			
oligomeric reaction			
products with 1-chloro-			
2,3-epoxypropane			
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

B. Persistence and degradability

Not available.

C. Bioaccumulative potential

Not available.

- D. <u>Mobility in soil</u> Soil/water partition : Not available. coefficient (K_{oc})
- E. <u>Other adverse effects</u> : No known significant effects or critical hazards.

Section 13. Disposal considerations

 A. Disposal methods
 The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

B. Disposal precautions
 This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	IATA
A. UN number	Not regulated.	Not regulated.	Not regulated.
B. UN proper shipping name	-	-	-
C. Transport hazard class(es)	-	-	-
D. Packing group	-	-	-
			Korea (GHS) Page: 9/12

Product name PSX 700 RESIN RAL 7005

Section 14. Transport information

Environmental hazards	No.	No.	No.
E. Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

UN	: None identified.
IMDG	: None identified.
IATA	: None identified.

F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

Α.	Regulation according to IS	H	<u>A</u>
	ISHA article 37 (Harmful substances prohibited from manufacture)	:	None of the components are listed.
	ISHA article 38 (Harmful substances requiring permission)	:	None of the components are listed.
	Article 2 of Youth Protection Act on Substances Hazardous to Youth	:	It is not allowed to sell to persons under the age of 19.
	Exposure Limits of Chemi	ca	Substances and Physical Factors
	The following components Manium dioxide carbon black, respirable po		
	ISHA Enforcement Regs Annex 11-3 (Exposure standards established for harmful factors)	:	None of the components are listed.
	ISHA Enforcement Regs Annex 11-5 (Harmful factors subject to Work Environment Measurement)	:	The following components are listed: Titanium dioxide Preparations containing material at weight ratio more than 1%
	ISHA Enforcement Regs Annex 12-2 (Harmful Factors Subject to Special Health Check-up)	:	None of the components are listed.
	Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to control)	:	The following components are listed: titanium dioxide

Korea (GHS)

Page: 10/12

Product code 00328794

Product name PSX 700 RESIN RAL 7005

Date of issue 1/15/2020 (month/day/year)

Version 5.03

Section 15. Regulatory information

В.	Regulation according to Chemicals Control Act		
	CCA Article 20 Toxic Chemicals (K-Reach Article 20)	:	Not applicable
	CCA Article 18 Prohibited (K-Reach Article 27)	:	None of the components are listed.
	CCA Article 20 Restricted (K-Reach Article 27)	:	The following components are listed: Nonylphenolethoxylates
	CCA Article 11 (TRI)	:	The following components are listed: Barium and its compounds
	Korea inventory	:	All components are listed or exempted.
	CCA Article 39 (Accident Precaution Chemicals)	:	None of the components are listed.
C.	<u>Dangerous Materials</u> <u>Safety Management Act</u>	:	Not applicable.
D.	Wastes regulation	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Е.	Regulation according to o	the	er foreign laws
	Safety, health and environmental regulations specific for the product	:	No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

Α.	References	: Korean Ministry of Environment; Chemical Control Act Korean Ministry of Labor; Industrial Safety and Health Act NIER Notice Registry of Toxic Effects of Chemical Substances (RTECS) U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information Retrieval) ECOTOX Database System.	
В.	Date of issue/Date of revision	: 1/15/2020	
С.	Version	: 5.03	
	Prepared by	: EHS	

Prepared by D. Other

Procedure used to derive the classification

Classification	Justification
Carc. 2, H351	Calculation method Calculation method Calculation method

${\ensuremath{\overline{/}}}$ Indicates information that has changed from previously issued version.

Disclaimer

Product code 00328794

Product name PSX 700 RESIN RAL 7005

Section 16. Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.