SAFETY DATA SHEET



Date of issue 5 October 2021

Version 3

Section 1. Product and company identification

Product name
Product code
Other means of identification
Product type

: MEGASEAL HSPC Comp B

: 00333469

: Not available.

: Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Coating. Paints. Painting-related materials.

Uses advised against	Reason
Not applicable.	

Supplier's details:	
Supplier	: PPG Industries Uruguay SA Av. Italia 5846 esq. Ancona – Montevideo Uruguay Tel. +598 26000514 Fax. +598 26003032
Email address:	: HazComLatam@ppg.com
Emergency telephone number	: Hospital de Clinicas- CIAT- 1722

Section 2. Hazards identification

Classification of the	: CUTE TOXICITY (oral) - Category 4
substance or mixture	ACUTE TOXICITY (dermal) - Category 5
	ACUTE TOXICITY (inhalation) - Category 4
	SKIN CORROSION - Category 1
	SERIOUS EYE DAMAGE - Category 1
	SKIN SENSITIZATION - Category 1
	TOXIC TO REPRODUCTION - Category 2
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	AQUATIC HAZARD (ACUTE) - Category 1
	AQUATIC HAZARD (LONG-TERM) - Category 1
Target organs	: Contains material which causes damage to the following organs: blood, liver, heart, brain, skin, central nervous system (CNS).
	Contains material which may cause damage to the following organs: kidneys, lungs, the reproductive system, gastrointestinal tract, upper respiratory tract, eye, lens or
	cornea, muscle tissue, ovary, testes.

English (US) Uruguay 1/

	Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity 16.7%
	Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 35.5%
	Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 84.3%
	Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 28.4%
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	: ⊮ armful if swallowed or if inhaled.
	May be harmful in contact with skin.
	Causes severe skin burns and eye damage. May cause an allergic skin reaction.
	Suspected of damaging fertility or the unborn child.
	May cause damage to organs through prolonged or repeated exposure. (kidneys) Very toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Øbtain special instructions before use. Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapo Do not eat, drink or smoke when using this product. Wash thoroughly after handlin
Response	: Collect spillage. IF exposed or concerned: Get medical advice or attention. IF INHALED: Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs Get medical advice or attention. IF IN EYES: Rinse cautiously with water for severa minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	: Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation.

Date of issue

3

Section 3. Composition/information on ingredients

Substance/mixture Other means of identification

CAS number

: Mixture

: Not available.

CAS number/other identifiers

:	Not applicable.

Ingredient name	%	CAS number
-nonylphenol, branched	20 - <30	84852-15-3
Polyaminoamide	15 - <20	68082-29-1
Poly[oxy(methyl-1,2-ethanediyl)], α-	12.5 - <15	9046-10-0 (n = 2-6)
(2-aminomethylethyl)-ω-(2-aminomethylethoxy)-		
benzyl alcohol	10 - <12.5	100-51-6
Formaldehyde, polymer with benzenamine, hydrogenated	10 - <12.5	135108-88-2
4-tert-butylphenol	3 - <5	98-54-4
m-phenylenebis(methylamine)	3 - <5	1477-55-0
trimethylhexane-1,6-diamine	3 - <5	25620-58-0
Phenol, 2-nonyl-, branched	2 - <3	91672-41-2
2,4,6-tris(dimethylaminomethyl)phenol	2 - <3	90-72-2
3,6-diazaoctanethylenediamin	1 - <2	112-24-3
salicylic acid	1 - <2	69-72-7
4,4'-methylenebis(cyclohexylamine)	1 - <2	1761-71-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary	<u>/ first aid measures</u>
Eye contact	 Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Indication of immediate	medical attention and special treatment needed, if necessary
Notes to physician Specific treatments	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. No specific treatment.

Code	00333469		Date of issue	5 October 2021	Version	3
Product nam	e	MEGASEAL HSPC Comp B				

Section 4. First aid measures

Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Potential acute health effects		
Eye contact	:	Causes serious eye damage.
Inhalation	1	Harmful if inhaled.
Skin contact	:	\mathbf{c} auses severe burns. May be harmful in contact with skin. Defatting to the skin. May cause an allergic skin reaction.
Ingestion	:	Harmful if swallowed. Corrosive to the digestive tract. Causes burns.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	If a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures : No action shall be taken involving any personal risk or without suitable training. For non-emergency Evacuate surrounding areas. Keep unnecessary and unprotected personnel from personnel entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any For emergency responders : information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". **Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage. English (US) Uruguay

Section 6. Accidental release measures

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	E Vut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage, including any incompatibilities	Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
-phenylenebis(methylamine)	ACGIH TLV (United States, 3/2020). Absorbed through skin. C: 0.018 ppm

-			
	English (US)	Uruguay	5/14

Section 8. Exposure controls/personal protection

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls		Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	res	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye protection Skin protection	:	Chemical splash goggles and face shield.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	:	butyl rubber
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Not available.
Odor	: Characteristic.
рН	: Not applicable.
Melting point	: Not available.
Boiling point	: >37.78°C (>100°F)
Flash point	: Closed cup: 93.33°C (200°F)
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 0.98
Solubility	: Insoluble in the following materials: cold water.
Water Solubility at room temperature	: 0.1 g/l
Partition coefficient: n- octanol/water	: Not applicable.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: K inematic (40°C (104°F)): >21 mm²/s (>21 cSt)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides

Section 11. Toxicological information

Information on toxicological effects

-				
	ITO	tov	ICIT	\
AU		tox	ICIL	. v

Product/ingredient name	Result	Species	Dose	Exposure
섉-nonylphenol, branched	LD50 Dermal	Rabbit	2.14 g/kg	-
	LD50 Oral	Rat	1300 mg/kg	-
Poly[oxy(methyl-1,2-ethanediyl)],	LD50 Dermal	Rat	2980 mg/kg	-
α-				
(2-aminomethylethyl)-ω-(2-aminomethylethoxy)-				
	LD50 Oral	Rat	2885 mg/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>4178 mg/m ³	4 hours
,	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
4-tert-butylphenol	LD50 Dermal	Rabbit	2.29 g/kg	-
51	LD50 Oral	Rat	2.95 g/kg	-
m-phenylenebis	LC50 Inhalation Gas.	Rat	700 ppm	1 hours
(methylamine)				
	LD50 Dermal	Rat - Male,	>3100 mg/kg	-
		Female		
	LD50 Oral	Rat	930 mg/kg	-
2,4,6-tris	LD50 Dermal	Rabbit	1.28 g/kg	-
(dimethylaminomethyl)				
phenol				
	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
3,6-diazaoctanethylenediamin	LD50 Dermal	Rabbit	1465 mg/kg	-
	LD50 Oral	Rat	1716 mg/kg	-
salicylic acid	LD50 Oral	Rat	0.891 g/kg	-
4,4'-methylenebis	LD50 Dermal	Rabbit	2.11 g/kg	-
(cyclohexylamine)				
	LD50 Oral	Rat	0.625 g/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
nonylphenol, branched m-phenylenebis (methylamine)	Skin - Erythema/Eschar Skin - Severe irritant	Rabbit Rat	4 -	- 4 hours	- 4 hours
2,4,6-tris (dimethylaminomethyl) phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days

Conclusion/Summary

- : There are no data available on the mixture itself.
- : There are no data available on the mixture itself.: There are no data available on the mixture itself.
- Respiratory

Skin

Eyes

Sensitization

- - English (US) Uruguay

Code 00333469 Product name MEGASEAL	- HSPC Comp B	Date of issue	5 October 202	1 Version	3
Section 11. Toxico	ological inf	ormation			
Product/ingredient name	Route of exposure	Species	Resu	lit	
Formaldehyde, polymer with benzenamine, hydrogenated	skin	Guinea pig	Sens	sitizing	
m-phenylenebis (methylamine)	skin	Mouse	Sens	sitizing	
2,4,6-tris (dimethylaminomethyl)	skin	Guinea pig	Sens	sitizing	
phenol 3,6-diazaoctanethylenediamin	skin	Guinea pig	Sens	sitizing	
Skin Respiratory <u>Mutagenicity</u> Not available. Conclusion/Summary <u>Carcinogenicity</u>	 There are no data available on the mixture itself. There are no data available on the mixture itself. There are no data available on the mixture itself. 				
Not available. Conclusion/Summary Reproductive toxicity Not available.	: There are no d	ata available on the	mixture itself.		
Conclusion/Summary Teratogenicity Not available.	: There are no d	ata available on the	mixture itself.		
Conclusion/Summary		ata available on the	mixture itself.		
Specific target organ toxicit	<u>y (single exposur</u>	<u>e)</u>			

Not available.

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Formaldehyde, polymer with benzenamine, hydrogenated 4,4'-methylenebis(cyclohexylamine)	Category 2	oral	kidneys
	Category 2	oral	-

Target organs

: Contains material which causes damage to the following organs: blood, liver, heart, brain, skin, central nervous system (CNS). Contains material which may cause damage to the following organs: kidneys, lungs, the reproductive system, gastrointestinal tract, upper respiratory tract, eye, lens or

cornea, muscle tissue, ovary, testes.

Aspiration hazard

Name	Result
benzyl alcohol	ASPIRATION HAZARD - Category 2

English (US) Urugu	y 9/14
--------------------	--------

Date of issue

3

Section 11. Toxicological information

Information on the likely	: Not available.
routes of exposure	
Potential acute health effe	
Eye contact	: Causes serious eye damage.
Inhalation	: Harmful if inhaled.
Skin contact	: Causes severe burns. May be harmful in contact with skin. Defatting to the skin. May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed. Corrosive to the digestive tract. Causes burns.
Symptoms related to the p	hysical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	 Adverse symptoms may include the following: pain or irritation redness dryness cracking blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate eff	ects and also chronic effects from short and long term exposure
Conclusion/Summary	: There are no data available on the mixture itself. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause

drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Exposure to amine vapor has been reported to cause transient corneal edema described as blue haze, halo effect, foggy or blurred vision for several hours. This condition is typically temporary and does not cause permanent visual effects. When the proper eye protection specified in Section 8 is

English (US)	Uruguay	10 /1

Date of issue

3

Section 11. Toxicological information

worn, exposure is significantly reduced and the condition has not been observed.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
MEGASEAL HSPC Comp B	1039.9	2219.2	20022.9	N/A	2
4-nonylphenol, branched	1300	2140	N/A	N/A	N/A
Poly[oxy(methyl-1,2-ethanediyl)], α- (2-aminomethylethyl)-ω-(2-aminomethylethoxy)-	2885	2980	N/A	N/A	N/A
benzyl alcohol	1230	2000	N/A	N/A	1.5
Formaldehyde, polymer with benzenamine, hydrogenated	500	N/A	N/A	N/A	N/A
4-tert-butylphenol	2950	2290	N/A	N/A	N/A
m-phenylenebis(methylamine)	930	2500	4500	N/A	N/A
trimethylhexane-1,6-diamine	500	N/A	N/A	N/A	N/A
Phenol, 2-nonyl-, branched	500	N/A	N/A	N/A	N/A
2,4,6-tris(dimethylaminomethyl)phenol	1200	1280	N/A	N/A	N/A
3,6-diazaoctanethylenediamin	1716	1465	N/A	N/A	N/A
salicylic acid	891	N/A	N/A	N/A	N/A
4,4'-methylenebis(cyclohexylamine)	625	2110	N/A	N/A	N/A

Other information

: Not available.

5 October 2021

3

Section 12. Ecological information

Ecotoxicity

Product/ingredient name	Result	Species	Exposure
-nonylphenol, branched	Acute EC50 0.04 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 0.044 mg/l	Crustaceans - Moina macrocopa	48 hours
	Acute LC50 0.221 mg/l	Fish	96 hours
Poly[oxy(methyl-1,2-ethanediyl)], α- (2-aminomethylethyl)-ω-(2-aminomethylethoxy)-	EC50 15 mg/l	Algae	72 hours
Formaldehyde, polymer with benzenamine, hydrogenated	Acute EC50 63 mg/l	Fish	96 hours
Phenol, 2-nonyl-, branched	Acute LC50 0.017 mg/l	Fish - Pleuronectes americanus	96 hours
2,4,6-tris (dimethylaminomethyl)phenol	Acute LC50 175 mg/l	Fish	96 hours
salicylic acid	Acute EC50 1147.57 mg/l Fresh water	Daphnia - Daphnia longispina - Neonate	48 hours
	Chronic NOEC 5.6 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days

Date of issue

Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Poly[oxy(methyl-1,2-ethanediyl)], α- (2-aminomethylethyl)-ω-(2-aminomethylethoxy)-		-	Not readily
benzyl alcohol	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
-nonylphenol, branched	5.4	251.19	low
benzyl alcohol	0.87	-	low
Formaldehyde, polymer with	-	209 to 219	low
benzenamine, hydrogenated			
4-tert-butylphenol	3	67.61	low
m-phenylenebis	0.18	2.69	low
(methylamine)			
2,4,6-tris	0.219	-	low
(dimethylaminomethyl)phenol			
3,6-diazaoctanethylenediamin	-1.66 to -1.4	-	low
salicylic acid	2.21 to 2.26	-	low
4,4'-methylenebis	2.03	-	low
(cyclohexylamine)			

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	Brazil (ANTT)	IMDG	ΙΑΤΑ
UN number	UN3066	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	8	8	8	8
Packing group	II	II	II	II
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	(4-nonylphenol, branched, 4-tert- butylphenol)	Not applicable.

Additional inform	mation
UN	: None identified.
Brazil	: None identified.
Risk number	: 80
IMDG	: The marine pollutant mark is not required when transported in sizes of \leq 5 L or \leq 5 kg.
ΙΑΤΑ	: The environmentally hazardous substance mark may appear if required by other transportation regulations.
Special precauti	ons for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

History

Date of previous issue	5/9/2018	
Version	3	
	EHS	
Key to abbreviations	ADN = European Provisions concerning the International Carriage of Dan Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Che IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous by Rail	f emicals Ships,
References	UN = United Nations ABNT NBR 14725-4: 2014 ANTT - National Land Transportation Agency	

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.